LINDER

L. O. C.

INC. OIL

COMPANY

LUBE OIL 68

CAUTION: Avoid contact with eyes. Wash with soap and water after handling. Launder contaminated clothing before re-use.

FIRST AID In case of eye contact, flush with large amounts of water. If irritation occurs, get medical attention.
If swallowed, do no induce vomiting. In general, no treatment is necessary unless large quantities of product are swallowed. However, get medical advice.
If skin contact, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

SPILL: In case of large spill, dike and pump into containers for recycle or salvage. For small spills and residue from large spill, soak up with absorbent material such as clay, sand or other suitable material. Dispose of according to local, State and Federal regulations.

STORAGE: Avoid heat, open flames and strong oxidizing agents. Combustion will produce carbon monoxide.

HEALTH	1	For Transportation Emergency Call CHEMTREC 1-800-424-9300. For Health Emergency Information Call 260-622-4680.	Batch Number C0410209F
FLAMMABILITY	1		
REACTIVITY	0		Product Code
PERSONAL PROTECTION	C		Net Wt / Volume

CAUTION: "Empty" containers retain residue and can be hazardous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL OR EXPOSE TO HEAT OR FLAME- It may cause fire, explode or produce toxic fumes and cause injury or death. Keep container closed and drum bungs in place. All label warnings and precautions must be observed until container has been reconditioned or destroyed.
Return "Empty" to a qualified reconditioner. For further information refer to MSDS.

Don't Pollute Return to Collection Site

Manufactured in USA - LINDER OIL COMPANY, Inc. 820 Industrial Pathway, Ossian, IN 46777

LINDER OIL COMPANY

LUBE OIL 68

CAUTION: Avoid contact with eyes. Wash with soap and water after handling. Launder contaminated clothing before re-use.

FIRST AID In case of eye contact, flush with large amounts of water. If irritation occurs, get medical attention.
If swallowed, do no induce vomiting. In general, no treatment is necessary unless large quantities of product are swallowed. However, get medical advice.
If skin contact, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

SPILL In case of large spill, dike and pump into containers for recycle or salvage. For small spills and residue from large spill, soak up with absorbent material such as clay, sand or other suitable material. Dispose of according to local, State and Federal regulations.

STORAGE Avoid heat, open flames and strong oxidizing agents. Combustion will produce carbon monoxide.

HEALTH	1	For Transportation Emergency Call CHEMTREC 1-800-424-9300. For Health Emergency Information Call 260-622-4680.	Batch Number C0402 09F
FLAMMABILITY	1		
REACTIVITY	0		Product Code
PERSONAL PROTECTION	C		Net Wt / Volume

CAUTION: "Empty" containers retain residue and can be hazardous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL OR EXPOSE TO HEAT OR FLAME- It may cause fire, explode or produce toxic fumes and cause injury or death. Keep container closed and drum bungs in place. All label warnings and precautions must be observed until container has been reconditioned or destroyed.
Return "Empty" to a qualified reconditioner. For further information refer to MSDS.

Don't Pollute Return to Collection Site

Manufactured in USA - LINDER OIL COMPANY, Inc. 820 Industrial Parkway, Ossian, IN 46777

MILLER

ENVIRONMENTAL

Additive C-12

Caution

FOR INDUSTRIAL USE ONLY

ATTENTION:

THIS CONTAINER HAZARDOUS WHEN EMPT

KEEP OUT OF REACH OF CHILDREN

MILLER

ENVIRONMENTAL

1402 S. MILLER ST. • SHELBYVILLE IN 46176 • 317.398.2700

Caution:

OMNOVA

SOLUTIONS INC

Performance Chemicals

1495 South Cleveland Avenue
Mogadore, Ohio USA 44260

OMNOVA
FLAMMABLE LIQUID
3
GENGLAZE®
COATING
EC-2447
2447AM
77756
Manufacture Date
11-Feb-09
Emergency Telephone Number: CHEMTREC 1-800-424-9300
G- 248.6 kg
T- 21.8 kg
N- 226.8 kg
G – 548.0 lb
T - 48.0 lb
N - 500.0 lb
NON-WARRANTY OF RESULTS

E67BR1906 05/22/2009

GLAS CLAD® MOLDED COATING

BLACK

R00808866E09

DRUM #8

DANGER!

HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE! HARMFUL IF INHALED - MAY AFFECT THE BRAIN OR NERVOUS SYSTEM. CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY CAUSE EYE, BURNS AND SEVERE SKIN AND RESPIRATORY TRACT IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. EFFECTS MAY BE DELAYED. CAN BE ABSORBED THROUGH THE SKIN.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY. SEE MATERIAL SAFETY DATA SHEET FOR DETAILS ON ABOVE HAZARDS.

CAS No. Ingredients

PHOTOCHEMICALLY REACTIVE

440 Lbs 199 Kg

SHERWIN WILLIAMS.
Automotive Finishes

DANGER

142 SOLVENT LA

CAS# 64742 - 47 - 8 LIGHT HYDROTREATED DISTILLATE

WARNING!

COMBUSTIBLE LIQUID AND VAPOR.
MAY CAUSE MILD TO MODERATE EYE IRRITATION.
MAY CAUSE MODERATE TO SEVERE SKIN IRRITATION.
MAY BE HARMFUL IF INHALED
ASPIRATION MAY CAUSE LUNG DAMAGE.
MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION

BEFORE USING THIS PRODUCT, READ THE MATERIAL SAFETY DATA SHEET

KEEP AWAY FROM HEAT, SPARKS AND FLAME.
AVOID CONTACT WITH EYES, SKIN AND CLOTHING.
AVOID BREATHING VAPOR.
DO NOT TASTE OR SWALLOW.
KEEP CONTAINER CLOSED.
USE WITH ADEQUATE VENTILATION.
WASH THOROUGHLY AFTER HANDLING.
DO NOT TRANSFER TO UNLABELED CONTAINERS.

SPILLS OR LEAKS:
ELIMINATE ALL SOURCES OF IGNITION.
SMALL SPILL – SOAK UP WITH ABSORBENT MATERIAL AND SCOOP INTO DRUMS.
LARGE SPILL – DIKE AND PUMP INTO DRUMS. PREVENT MATERIAL FROM ENTERING DRAINS, SEWERS, OR WATERWAYS.
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.
FOR HELP IN A CHEMICAL EMERGENCY, CALL CHEMTREC (800) 424-9300.

FIRST AID

IN CASE OF EYE CONTACT FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES, HOLDING LIDS APART TO ENSURE FLUSHING OF THE ENTIRE SURFACE. SEEK MEDICAL ATTENTION IMMEDIATELY.

IN CASE OF CONTACT: FOR SKIN WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE AND [illegible] CONTAMINATED CLOTHING BEFORE REUSE. IF IRRITATION DEVELOPS, CONSULT A PHYSICIAN.

IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN.

IF SWALLOWED, DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONCIOUS PERSON. ASPIRATION HAZARD IF SWALLOWED – CAN ENTER LUNGS AND CAUSE DAMAGE. GET MEDICAL ASSISTANCE IMMEDIATELY.

IN CASE OF FIRE:
USE FOAM, CARBON DIOXIDE, DRY CHEMICAL OR WATER FOG OR SPRAY.

FOR INDUSTRIAL USE ONLY

CHEMCENTRAL INDIANAPOLIS

MAY 2002

PLIOGRIP® 9115 ADHESIVE

WARNING!
MAY CAUSE EYE IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF INHALED OR SWALLOWED.

ATTENTION:
CONTAINS CRYSTALLINE SILICA (QUARTZ) WHICH CAN CAUSE CANCER.

FIRST AID:

PRECAUTIONARY MEASURES:

FIRE PROCEDURE:

SPILL PROCEDURE:

ASHLAND

ASHLAND

P. O. Box 3219
Columbus, OH 43216
United States of America
1-800-ASHLAND (1-800-274-5263)

UNISEAL
Innovative Chemistries for Better Solutions.
1800 W. MARYLAND ST.
EVANSVILLE, INDIANA 47712
PLEASE ROTATE STOCK
DO NOT DENT
OR DROP
Do Not Store
Near Heat Source
or In Sunlight
MADE IN U.S.A.
Apply material at temperature
in accordance with engineering
guidelines for optimum performance
Customer Part No
80709900AA

DISTRIBUTED
ULRICH CHEMICAL, INC.
PA RATING
Health : 3
Flammability : 0
Reactivity : 0
CORROSIVE
8
MATERIAL SAFETY
DATA SHEET
AVAILABLE

NITRIC ACID 42°
DANGER!
NITRIC ACID
(55 – 68%)
UN 2031
C.A.S. NUMBER
7697 – 37 – 2
CORROSIVE
8
600
600

DISTRIBUTED BY:

ULRICH CHEMICAL, INC.

INDIANAPOLIS, IN 46226
FORT WAYNE, IN 46803

EVANSVILLE, IN 47711
LOUISVILLE, KY 40208

TERRE HAUTE, IN 47802
BARTONVILLE, IL 61607

DOT SHIPPING NAME
OXIDIZING SUBSTANCE
LIQUID N.O.S.

UN 3139

C.A.S. NUMBER

DANGER

MATERIAL SAFETY
DATA SHEET
AVAILABLE

DOT SHIPPING NAME:
HYDROGEN PEROXIDE,
AQUEOUS SOLUTION / CONTAINS
50% HYDROGEN PEROXIDE
UN 2014
C.A.S. NUMBER
7722 — 84 — 1
CORROSIVE
8
NR
500
HYDROGEN PEROXIDE 50%
DANGER! WARNING! WARNING!
REVISION DATE 11 — 01 — 96

DISTRIBUTED BY
ULRICH CHEMICAL, INC.
PA RATING
Health : 2
Flammability : 0
Reactivity : 2
OXIDIZER
5.1
SAFETY
SHEET
AVAILABLE

XYLENE

XYLENES
*, UN 1307, PG II RQ (XYLENE)

WARNING!

FLAMMABLE LIQUID AND VAPOR.
HARMFUL IF INHALED.
CAUSES EYE AND SKIN IRRITATION.
MAY CAUSE RESPIRATORY TRACT IRRITATION.
MAY BE HARMFUL IF SWALLOWED.

BEFORE USING THIS PRODUCT, READ THE MATERIAL SAFETY DATA SHEET

KEEP AWAY FROM HEAT, SPARKS AND FLAME.
AVOID BREATHING VAPOR.
AVOID CONTACT WITH EYES, SKIN AND CLOTHING.
KEEP CONTAINER CLOSED.
USE WITH ADEQUATE VENTILATION.
VAPORS MAY SPREAD LONG DISTANCES AND IGNITE.
WASH THOROUGHLY AFTER HANDLING.
DO NOT TRANSFER TO UNLABELED CONTAINERS.
CONTAINER MUST BE GROUNDED TO RECEIVING CONTAINER WHEN BEING EMPTIED.

IN CASE OF FIRE:

USE CO2, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG OR FOAM.

SPILLS OR LEAKS:

ELIMINATE ALL IGNITION SOURCES. ABSORB WITH ABSORBENT MATERIAL. SHOVEL OR SWEEP UP AND PUMP INTO DRUMS. DO NOT ALLOW MATERIAL ENTERING DRAINS. IF MATERIAL ENTERS DRAINS, NOTIFY LOCAL AUTHORITIES. IN EMERGENCY, CALL

FIRST AID

IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN.

IN CASE OF CONTACT: FOR EYES, IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. CALL A PHYSICIAN. FOR SKIN, FLUSH WITH WATER. WASH CLOTHING BEFORE REUSE.

IF SWALLOWED CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

395 | 05

FLAMMABLE LIQUID

3

DANGER

FOR INDUSTRIAL USE ONLY

CHEMCENTRAL INDIANAPOLIS

MARCH 2001

768515
CLEAR URETHANE
HARDENER(PART B)
THEORETICAL VOC
002.185 LBS/GA
261.820 GR/LIT
PROCESS
08/26/02
2 H
3 F
1 R
H PP
STORAGE & HANDLING
CHRONIC HAZARDS
FLAMMABLE LIQUID
3
RESIN SOLUTION, 3, UN1866, PG II
55.00 U. S. GAL
208.18 LITERS
WARNING!
FLAMMABLE
INDUSTRIAL COATING
MADE IN THE U. S. A.
CHEMTREC
EMERGENCY HELP
RED SPOT PAINTS
1-812-428-9100
REFER TO MATERIAL SAFETY DATA SHEET
RED SPOT

3

55.00 U. S. GAL

208.18 LITERS

RED SPOT

BLEND 3100

Net Contents: 124.7 KG (275 LBS.)

CAUTION:

MAY BE HARMFUL IF INHALED. MAY IRRITATE SKIN.

* AVOID BREATHING MIST OR VAPORS * DO NOT GET IN EYES, ON SKIN OR CLOTHING * DO NOT HANDLE NEAR HEAT, SPARKS OR OPEN FLAME * DO NOT TAKE INTERNALLY * KEEP CONTAINER CLOSED WHEN NOT IN USE * USE WITH ADEQUATE VENTILATION * WASH THOROUGHLY AFTER HANDLING

FIRST AID

INHALATION: MOVE VICTIM TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. GET MEDICAL ATTENTION.

EYE CONTACT: FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.

SKIN CONTACT: FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING (CLEAN CLOTHING BEFORE RE-USE). GET MEDICAL ATTENTION.

IF SWALLOWED: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION. CALL THE POISON CONTROL CENTER.

BEFORE USING, READ AND UNDERSTAND CURRENT MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT AND EVALUATE THE NEED FOR PERSONAL PROTECTIVE EQUIPMENT.

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN

HEALTH 1
FLAMMABILITY 0
REACTIVITY 0

Lot Number:49778298238

PC NUMBER: 449778

BERNTAG MID-SOUTH, INC. 3111 NORTH POST ROAD, INDIANAPOLIS, IN 46226

STOF
102-2357906

LUBE-LINE
Sales • Service • Leasing

LUBE-LINE® LT-450

INDUSTRIAL LUBRICANT

LUBE-LINE® LT-450 lubricant is a heavy anti-wear lubricant, which protects against corrosion over a temperature range of -50° F to 450° F.

EMERGENCY AID PROCEDURES:

Eye Contact: Flush with water for 15 minutes

Skin Contact: Wash with soap and water thouroughly. Remove contaminated clothing. See physician if necessary.

Ingestion: Do not induce vomiting. Drink plenty of water. Do not give anything to unconscience victim. See physician immediately.

PRECAUTIONS FOR SAFE HANDLING AND USE:

Steps to be taken in case material is released or spilled:

Dike and contain spill. Apply absorbent. Put in container. Close container.

PERSONAL PROTECTION: Ventilate use area, or use approved hydrocarbon vapor respirator.

CAUTION: COMBUSTIBLE

COMBUSTIBLE

LUBE-LINE® CORPORATION
906 Carroll Rd. Ft. Wayne, IN 46845
Phone: (260) 637-3779 FAX: (260) 637-8171
Box 38, Herod, IL 62947
Phone: (618) 264-5811 FAX: (618) 264-5831

PACKING LIST

BLEND 3005 - T

NOTICE
AFTER USE, IN ORDER TO COMPLY WITH THE RESOURCES CONSERVATION AND RECOVERY ACT REGULATIONS, THIS CONTAINER MUST BE COMPLETELY EMPTY WITH CLOSURES SECURELY TIGHTENED PRIOR TO BEING TRANSPORTED

Net Contents: 290.75 KG (641 LBS.)

DANGER!

MAY BE HARMFUL IF SWALLOWED. MAY CAUSE BURNS TO EYES AND SKIN.

* DO NOT GET IN EYES, ON SKIN OR CLOTHING * DO NOT TAKE INTERNALLY * KEEP CONTAINER CLOSED WHEN NOT IN USE * WASH THOROUGHLY AFTER HANDLING

FIRST AID

INHALATION: MOVE VICTIM TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. GET MEDICAL ATTENTION.
EYE CONTACT: FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.
SKIN CONTACT: FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING (CLEAN CLOTHING BEFORE RE-USE). GET MEDICAL ATTENTION.
IF SWALLOWED: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

READ AND UNDERSTAND CURRENT MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT AND EVALUATE THE NEED FOR PERSONAL PROTECTIVE EQUIPMENT.

D.O.T. SHIPPING NAME

PROPER SHIPPING NAME: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (POTASSIUM HYDROXIDE)
HAZARD CLASS: 8 (CORROSIVE)
ID NUMBER: UN 3266
PG II

HEALTH	3
FLAMMABILITY	0
REACTIVITY	1

Lot Number: 250400298329

PC NUMBER: 250400

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN

BRENNTAG MID-SOUTH, INC. 3111 NORTH POST ROAD, INDIANAPOLIS, IN 46226

SODIUM HYPOCHLORITE SOLUTION 12.5%

BLEACHES AND DISINFECTS

Active Ingredient - Sodium Hypochlorite	12.5%
Other Ingredients	87.5%
Total	100%

Available Chlorine 11.9%

KEEP OUT OF REACH OF CHILDREN

DANGER

FIRST AID

Call a poison control center or doctor immediately for treatment advice.

"If in Eyes", Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. **"If on Skin or Clothing"**, Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. **"If Inhaled"**, Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth – to mouth, if possible. **"If Swallowed"**, Call poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. May cause severe skin irritation or chemical burns to broken skin. Causes eye damage. Do not get in eyes, on skin and clothing. Wear goggles or safety glasses and rubber gloves when handling this product. Wash after handling. Avoid breathing vapors. Remove and wash contaminated clothing before reuse. Vacate poorly ventilated areas as soon as possible. Do not reenter until strong odors have dissipated.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge.
Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your state board or regional office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

STRONG OXIDIZING AGENT: Mix only with water according to label directions. Mixing this product with chemicals (e.g. ammonia, acids, detergents, etc.) or organic matter (e.g. urine, feces, etc.) will release chlorine gas which is irritating to eyes, lungs and mucous membranes.

BRENNTAG MID-SOUTH, INC.

P.O. BOX 20
HENDERSON, KY 42419-0020

FOR EMERGENCIES PHONE 270-830-1222

EPA Reg. No. 6785-4
NET CONTENTS ____5____ GALLONS

EPA EST. # 6785-IN-2

For the following supplemental uses, contact your supplier for descriptive information.

1. Sanitization of nonporous food contact surfaces.
2. Sanitization of porous food contact surfaces.
3. Sanitization of nonporous non-food contact surfaces.
4. Disinfection of nonporous non-food contact surfaces.
5. Sanitization of porous non-food contact surfaces.
6. Emergency disinfection after main breaks.
7. Cooling tower/evaporative condenser water.
8. Pulp and paper mill process water systems.
9. Sanitizing dairy, meat, poultry, shell egg product processing equipment.
10. Shell egg sanitizing compounds.
11. Disinfection of individual drinking water systems.
12. Sanitizer for components of paper and paperboard for aqueous and fatty foods.
13. Sewage & wastewater effluent treatment.
14. Laundry Sanitizers/Household Laundry Sanitizers.
15. Commercial laundry sanitizers.
16. Farm premises
17. Agricultural uses.

Amount of Water	Available Chlorine	12.5%
1000 Gallons	3 ppm	1pt
1000 Gallons	5 ppm	1qt

SPAS AND HOT TUBS

Apply 5 oz. of product per 1000 gallons of water to obtain a free available chlorine concentration of 3 ppm, as determined by a suitable chlorine test kit. Adjust and maintain water pH to between 7.2 and 7.6. Some oils, debris, fragrances, cleaners, etc. may cause foaming or cloudy water as well as reduce the efficiency of the product.

To maintain the water, apply 3 oz. of product per 1000 gallons of water over the surface to maintain a chlorine concentration of 3 ppm.

After each use, shock treat with 5 oz. of this product per 500 gallons of water to control odor and algae.

During extended periods of disuse, add 3 oz. of product daily per 500 gallons of water to maintain a 3 ppm chlorine concentration.

Re-entry into treated pools is prohibited at levels above 3 ppm due to risk of bodily harm.

NSF

CERTIFIED TO ANSI/NSF 60 MAXIMUM USE FOR POTABLE WATER 84 mg/L

...USDA FOR USE IN FEDERALLY
...MEAT AND POULTRY PLANTS

...water of meat and poultry plants at concentrations ...calculated as available chlorine. Also chlorine may be ...water, and in carcass wash water at concentrations up to ...available chlorine. Chlorine must be dispensed at a con... ...method or system must be such that a controlled rate is ...of this product in 200 gallons of water to make a sanitiz... ...chlorine, or 10 oz. in 200 gallons of water for 50 ppm avail...

...NG POOL WATER DISINFECTION

...up, superchlorinate with 52 to 104 oz. of product for each ...5 to 10 ppm available chlorine by weight. Check the level ...kit. Adjust and maintain pool water pH to between 7.2 to ...alkalinity of the pool to between 50 to 100 ppm.

...usually or by a feeder device 11 oz. of this product for each ...an available chlorine residual between 0.8 to 1.0 ppm by ...maintain a residual of 1.0 to 1.5 ppm available chlorine. ...residual and alkalinity of the water frequently with appropri... ...water treatment will depend upon temperature and number of

...ary, superchlorinate the pool with 52 to 104 oz. of product for ...to yield 5 to 10 ppm available chlorine by weight. Check the ...with a test kit. Do not reenter pool until the chlorine residual is

...is prohibited at levels above 4 ppm due to risk of bodily harm.

...ing pool season or when water is to be drained from the pool, ...to dissipate from treated pool water before discharge. Do not ...24 hours prior to discharge.

...while water is still clear and clean, apply 3 oz. of product per 1000 ...ing, to obtain a 3 ppm available chlorine residual, as determined ...ver pool, prepare heater, filter and heater components for winter by ...instructions.

...use maintain dosage 5 oz. of product per 1000 gallons of water to ...chlorine. Shock treat dosage 6 oz. of product per 500 gallons of ...duct 3 oz. per 1000 gallons of water.

...ing 911 or an ambulance, then give artificial respiration, preferably by mouth – to mouth, if possible. "If Swallowed" Call poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. May cause severe skin irritation or chemical burns to broken skin. Causes eye damage. Do not get in eyes, on skin and clothing. Wear goggles or safety glasses and rubber gloves when handling this product. Wash after handling. Avoid breathing vapors. Remove and wash contaminated clothing before reuse. Vacate poorly ventilated areas as soon as possible. Do not reenter until strong odors have dissipated.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge.
Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your state board or regional office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

STRONG OXIDIZING AGENT: Mix only with water according to label directions. Mixing this product with chemicals (e.g. ammonia, acids, detergents, etc.) or organic matter (e.g. urine, feces, etc.) will release chlorine gas which is irritating to eyes, lungs and mucous membranes.

BRENNTAG MID-SOUTH, INC.

P.O. BOX 20
HENDERSON, KY 42419-0020

FOR EMERGENCIES PHONE 270-830-1222

EPA EST. # 6785-IN-2

EPA Reg. No. 6785-4

NET CONTENTS 5 GALLONS

For the following supplemental uses, contact your supplier for descriptive information.

1. Sanitization of nonporous food contact surfaces.
2. Sanitization of porous food contact surfaces.
3. Sanitization of nonporous non-food contact surfaces.
4. Disinfection of nonporous non-food contact surfaces.
5. Sanitization of porous non-food contact surfaces.
6. Emergency disinfection after main breaks.
7. Cooling tower/evaporate condenser water.
8. Pulp and paper mill process water systems.
9. Sanitizing dairy, meat, poultry, shell egg product processing equipment.
10. Shell egg sanitizing compounds.
11. Disinfection of individual drinking water systems.
12. Sanitizer for components of paper and paperboard for aqueous and fatty foods.
13. Sewage & wastewater effluent treatment.
14. Laundry Sanitizers/Household Laundry Sanitizers.
15. Commercial laundry sanitizers.
16. Farm premises.
17. Agricultural uses.

NSF

2-ETHYL HEXANOL

CASN 104-76-7 2-ETHYL HEXANOL

WARNING!

HARMFUL IF SWALLOWED.
CAUSES EYE AND SKIN IRRITATION.
COMBUSTIBLE LIQUID AND VAPOR.

MAY CAUSE LIVER AND KIDNEY DAMAGE

FIR T AID:

IF SWALL D, GIVE TWO GLASSES OF WATER AND INDUCE VOMITING
DO NOT A AN UNCONSCIOUS PERSON
MOUTH A PHYSICIAN

IN CASE O E CONTACT FLUSH EYES WITH ER AND CONTINUE
WASHING F SEVERAL MINUTES. REMOVE CONTACT LENSES IF
WORN. OBTAIN MEDICAL ATTENTION

IN CASE IN CONTACT WASH SKIN WITH SOAP AND WATER
OBTAIN AL ATTENTION IF SYMPTOMS PERSIST. WASH CLOTHING
BEFORE DISCARD CONTAMINATED LEATHER ARTICLES SUCH AS
ES AND T

BEFORE USING THIS PRODUCT, READ
THE MATERIAL SAFETY DATA SHEET

DO NOT TASTE OR SWALLOW
AVOID CONTACT WITH EYES, SKIN AND CLOTHING
KEEP AWAY FROM HEAT AND FLAME
KEEP CONTAINERS CLOSED
USE WITH ADEQUATE VENTILATION
WASH THOROUGHLY AFTER HANDLING
DO NOT TRANSFER TO UNLABELLED CONTAINERS

IN CASE OF FIRE:

USE FOAM, CARBON DIOXIDE, DRY CHEMICAL
OR WATER FOG OR SPRAY

DANGER

SPILLS OR LEAKS:

ELIMINATE ALL SOURCES OF IGNITION.
SMALL SPILL – SOAK UP WITH ABSORBENT MATERIAL AND SCOOP INTO DRUMS.
LARGE SPILL – DIKE AND PUMP INTO DRUMS. PREVENT MATERIAL FROM ENTERING DRAINS, SEWERS, OR WATERWAYS.
DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.
FOR HELP IN A CHEMICAL EMERGENCY, CALL CHEMTREC-(800) 424-9300.

FOR INDUSTRIAL USE ONLY

CHEMCENTRAL CLEVELAND
21600 DRAKE RD.
STRONGSVILLE, OH. 44136
440 - 378 - 5000

AUGUST 2000

BLEND 1105

Net Contents: 145.1 KG (320 LBS.)

CAUTION:

MAY BE HARMFUL IF INHALED. MAY IRRITATE SKIN.

* AVOID BREATHING MIST OR VAPORS * DO NOT GET IN EYES, ON SKIN OR CLOTHING * DO NOT HANDLE NEAR HEAT, SPARKS OR OPEN FLAME * DO NOT TAKE INTERNALLY * KEEP CONTAINER CLOSED WHEN NOT IN USE * USE WITH ADEQUATE VENTILATION * WASH THOROUGHLY AFTER HANDLING

FIRST AID

INHALATION: MOVE VICTIM TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. GET MEDICAL ATTENTION.

EYE CONTACT: FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.

SKIN CONTACT: FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING (CLEAN CLOTHING BEFORE RE-USE). GET MEDICAL ATTENTION.

DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION. CALL THE POSION CONTROL CENTER.

BEFORE USING: READ AND UNDERSTAND CURRENT MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT AND EVALUATE THE NEED FOR PERSONAL PROTECTIVE EQUIPMENT.

HEALTH	0
FLAMMABILITY	0
REACTIVITY	0

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN

Lot Number 618684298238

PC NUMBER: 618684

BRENNTAG MID-SOUTH, INC. 3111 NORTH POST ROAD, INDIANAPOLIS, IN 46226

ACTION
"A COMPANY ON THE MOVE"

MADE IN USA

FIRE	0
HEALTH	1
REACTIVITY	0
PERSONAL PROTECTION	D

ACTA SOLV MF

LOW FOAMING BIODEGRADABLE CLEANER

DESCRIPTION/USES

DIRECTIONS

For very soiled floors use at 1/2 to 2 oz./gal.

CAUTION/FIRST AID

SKIN: Flush with plenty of water. EYES: Flush with plenty of water for at least 15 minutes and seek medical attention. INHALED: Remove immediately from area of exposure and get plenty of fresh air. INGESTED: Drink large amounts of water and seek prompt medical attention. DO NOT induce vomiting.

PART NUMBER

ACT MF

CHEMICAL EMERGENCY RESPONSE NUMBER

CORROSIVE LIQUIDS, N.O.S., (CONTAINS POTASSIUM HYDROXIDE) 8, UN1760, II

PRESSURE WAVES

PART NUMBER

ACT MF

CHEMICAL EMERGENCY RESPONSE NUMBER

1-800-535-5053

ACTION EQUIPMENT SALES CO., INC.

Indianapolis

Evansville

Louisville

877-754-6565

1099
NITROGEN,
COMPRESSED
NON-FLAMMABLE
GAS
2
UN1066
Airgas

OXYGEN
2

SED