ORMET
PRIMARY ALUMINUM CORPORATION

November 9, 2001

Mr. Bernie Schorle SR-6J
USEPA Remedial Project Manager
U.S. Environmental Protection Agency
77 West Jackson Boulevard
Chicago, IL 60604-3590

Dear Mr. Schorle:

Re: Consent Decree between the United States of America and Ormet Primary Aluminum Corporation (S.D. Ohio) Civil Action No. C2-95-947 – Remedial Action Ground-Water Monitoring Plan (April 28, 1998)

As required in the Monitoring Plan mentioned above, Ormet is to submit two copies of the enclosed ground-water analytical results. The ground-water monitoring program was initiated in May 1998; this monitoring event is the second conducted during 2001. Sampling was conducted on the respective list of wells as described in the plan for the two types of sampling events. If you have any questions regarding this transmittal or require any additional information, please contact me.

Respectfully,

John Reggi

John Reggi Director,
Corporate Environmental Services

cc: T. Temple, Ormet Corporation
J. Smith, OEPA

US EPA RECORDS CENTER REGION 5
473483

Hannibal Reduction Division
P.O. Box 176 / State Route 7
Hannibal, Ohio 43931
(740) 483-1381
(740) 483-2622 FAX

TABLE 1
WATER-LEVEL ELEVATION DATA
ORMET CORPORATION
HANNIBAL, OHIO
DATE: SEPTEMBER 10, 2001

WATER-LEVEL MEASURING POINT	MEASURING POINT ELEVATION (ft. MSL)	DEPTH TO WATER (feet)	GROUND-WATER ELEVATION (ft. MSL)
MW-1	668.07	55.29	612.78
MW-2	668.12	58.20	609.92
MW-3	645.17	30.19	614.98
MW-4	661.07	60.23	600.84
MW-5	668.16	65.98	602.18
MW-7	667.94	60.75	607.19
MW-8	667.71	72.75	594.96
MW-9	666.59	70.83	595.76
MW-10	667.16	72.64	594.52
MW-11	667.31	65.86	601.45
MW-12	636.73	23.33	613.40
MW-13	661.44	41.78	619.66
MW-14	653.59	37.96	615.63
MW-15	657.31	37.55	619.76
MW-16	662.72	49.10	613.62
MW-17	655.03	37.27	617.76
MW-18	660.91	39.96	620.95
MW-19	662.03	41.53	620.50
MW-20	632.33	12.04	620.29
MW-21s	664.02	67.71	596.31
MW-21d	663.60	67.31	596.29
MW-22s	667.47	71.57	595.90
MW-22d	667.21	71.35	595.86
MW-23s	663.18	66.67	596.51
MW-23d	663.41	67.01	596.40
MW-24s	667.88	72.76	595.12
MW-24d	667.75	72.66	595.09
MW-25	667.73	65.83	601.90
MW-26s	665.54	70.03	595.51
MW-26d	665.59	70.16	595.43
MW-27	667.86	67.52	600.34
MW-28	663.27	20.40	642.87
MW-29s	653.40	40.15	613.25
MW-29d	653.07	39.74	613.33
MW-30	667.58	48.78	618.80
MW-31	661.59	46.83	614.76
MW-32	656.66	39.48	617.18
MW-34s	655.67	37.39	618.28
MW-34d	654.67	35.48	619.19
MW-35	661.90	35.93	625.97
MW-36	655.14	37.76	617.38
MW-37	661.14	19.71	641.43
MW-38	666.64	20.21	646.43
MW-39s	657.30	40.93	616.37
MW-39d	657.18	40.62	616.56
MW-40s	662.22	52.13	610.09
MW-40d	661.95	51.96	609.99
MW-41	637.67	13.13	624.54
MW-42s	654.37	40.00	614.37
MW-42d	654.34	39.89	614.45
MW-44s	662.01	52.32	609.69
MW-44d	661.76	52.84	608.92

TABLE 1 (CONT.)
WATER-LEVEL ELEVATION DATA
ORMET CORPORATION
HANNIBAL, OHIO
DATE: SEPTEMBER 10, 2001

WATER-LEVEL MEASURING POINT	MEASURING POINT ELEVATION (ft. MSL)	DEPTH TO WATER (feet)	GROUND-WATER ELEVATION (ft. MSL)
PPB-01*	663.24	20.74	642.50
PPB-02s*	663.14	18.12	645.02
PPB-02d+	662.78	43.16	619.62
PPB-04+	661.57	45.31	616.26
PPB-05*	661.62	20.32	641.30
PPB-06+	663.04	47.41	615.63
PPB-07*	661.71	NM	--
PPB-09+	664.30	43.37	620.93
PPB-10*	663.45	15.34	648.11
PPB-14*	660.64	NM	--
TH-3	667.81	59.34	608.47
TH-10	658.17	37.74	620.43
TH-11	659.08	36.67	622.41
TH-15	663.62	68.33	595.29
TH-16	664.62	68.42	596.20
TH-17	663.93	67.54	596.39
RP-1	643.17	18.86	624.31
RP-2	643.05	18.58	624.47

NOTE:

All MW-series wells are measured from the top of the PVC casing.

All TH-series wells are measured from the top of steel casing.

River pool measuring point RP-2 is located on the walkway below the dry scrubbers and RP-1 is located on the walkway at the barge unloading dock.

* - Designates a perched zone piezometer

+ - Designates an alluvial aquifer piezometer.

WLE91001.123

TABLE 1
WATER-LEVEL ELEVATION DATA
ORMET CORPORATION
HANNIBAL, OHIO
DATE: SEPTEMBER 10, 2001

WATER-LEVEL MEASURING POINT	MEASURING POINT ELEVATION (ft. MSL)	DEPTH TO WATER (feet)	GROUND-WATER ELEVATION (ft. MSL)
MW-1	668.07	55.29	612.78
MW-2	668.12	58.20	609.92
MW-3	645.17	30.19	614.98
MW-4	661.07	60.23	600.84
MW-5	668.16	65.98	602.18
MW-7	667.94	60.75	607.19
MW-8	667.71	72.75	594.96
MW-9	666.59	70.83	595.76
MW-10	667.16	72.64	594.52
MW-11	667.31	65.86	601.45
MW-12	636.73	23.33	613.40
MW-13	661.44	41.78	619.66
MW-14	653.59	37.96	615.63
MW-15	657.31	37.55	619.76
MW-16	662.72	49.10	613.62
MW-17	655.03	37.27	617.76
MW-18	660.91	39.96	620.95
MW-19	662.03	41.53	620.50
MW-20	632.33	12.04	620.29
MW-21s	664.02	67.71	596.31
MW-21d	663.60	67.31	596.29
MW-22s	667.47	71.57	595.90
MW-22d	667.21	71.35	595.86
MW-23s	663.18	66.67	596.51
MW-23d	663.41	67.01	596.40
MW-24s	667.88	72.76	595.12
MW-24d	667.75	72.66	595.09
MW-25	667.73	65.83	601.90
MW-26s	665.54	70.03	595.51
MW-26d	665.59	70.16	595.43
MW-27	667.86	67.52	600.34
MW-28	663.27	20.40	642.87
MW-29s	653.40	40.15	613.25
MW-29d	653.07	39.74	613.33
MW-30	667.58	48.78	618.80
MW-31	661.59	46.83	614.76
MW-32	656.66	39.48	617.18
MW-34s	655.67	37.39	618.28
MW-34d	654.67	35.48	619.19
MW-35	661.90	35.93	625.97
MW-36	655.14	37.76	617.38
MW-37	661.14	19.71	641.43
MW-38	666.64	20.21	646.43
MW-39s	657.30	40.93	616.37
MW-39d	657.18	40.62	616.56
MW-40s	662.22	52.13	610.09
MW-40d	661.95	51.96	609.99
MW-41	637.67	13.13	624.54
MW-42s	654.37	40.00	614.37
MW-42d	654.34	39.89	614.45
MW-44s	662.01	52.32	609.69
MW-44d	661.76	52.84	608.92

TABLE 1 (CONT.)
WATER-LEVEL ELEVATION DATA
ORMET CORPORATION
HANNIBAL, OHIO
DATE: SEPTEMBER 10, 2001

WATER-LEVEL MEASURING POINT	MEASURING POINT ELEVATION (ft. MSL)	DEPTH TO WATER (feet)	GROUND-WATER ELEVATION (ft. MSL)
PPB-01*	663.24	20.74	642.50
PPB-02s*	663.14	18.12	645.02
PPB-02d+	662.78	43.16	619.62
PPB-04+	661.57	45.31	616.26
PPB-05*	661.62	20.32	641.30
PPB-06+	663.04	47.41	615.63
PPB-07*	661.71	NM	--
PPB-09+	664.30	43.37	620.93
PPB-10*	663.45	15.34	648.11
PPB-14*	660.64	NM	--
TH-3	667.81	59.34	608.47
TH-10	658.17	37.74	620.43
TH-11	659.08	36.67	622.41
TH-15	663.62	68.33	595.29
TH-16	664.62	68.42	596.20
TH-17	663.93	67.54	596.39
RP-1	643.17	18.86	624.31
RP-2	643.05	18.58	624.47

NOTE:

All MW-series wells are measured from the top of the PVC casing.

All TH-series wells are measured from the top of steel casing.

River pool measuring point RP-2 is located on the walkway below the dry scrubbers and RP-1 is located on the walkway at the barge unloading dock.

* - Designates a perched zone piezometer

+ - Designates an alluvial aquifer piezometer.

WLE91001.123

TABLE 4
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-1															
12/83	6.4	6.0	270	210	0.018	0.014		0.1			0.04	0.65	14.2		
2/84	6.1	6.1	270	215	0.04			0.1			0.01	0.54	14.9		
9/84	6.1	5.7	195	210	<0.01	<0.01		<0.2			0.02	0.33	13.8		
5/85	6.4	6.0	200	210	0.13	0.13		<0.2			0.04	0.15	16.2		
6/88	6.2	6.4	670	540	<0.01		<0.01	0.2	0.0024	<0.0015	6.21	0.379	20.3	0.006	
1/95	6.2	4.7	370	550	0.02		<0.01	0.1	<0.004	<0.01	<0.04	0.39	21	<0.01	
5/97	5.9	6.32	470	365	<0.01			0.1	<0.004	<0.0005		0.13	19	<0.01	
5/98	6.01	5.65	480	505	<0.01			0.20	<0.004	<0.0005		0.10	20	<0.01	
5/01	5.95	6.35	450	392	<0.01			0.13	<0.004	<0.0005		0.098	19	<0.01	
MW-2															
12/83	10.3	10.3	6,000	6,000	56.0	0.27		400			55.2	1.98	1,950		
2/84	10.3	10.3	7,752	2,750	48.0			420			58	2.46	2,290		
9/84	10.5	9.9	6,308	6,900	40.8	0.095		480			59.3	2.1	2,460		
5/85	10.4	10.4	13,200	5,800	95	0.10		400			54.0	1.74	2150		
10/85	10.5		7,100		140	12		390		<0.01	54.0	1.82	2,060		
7/88	10.4	10.4	6,200	6,000	22		12	330	0.394	<0.0015	34.2	1.00	1,450	0.251	0.011
2/90	10.34	10.2	4,800	3,900	36.2		29.6	200			31.0		1,200		
1/95	10.0	9.6	2,400	>2,000	7.1		<0.01	93	0.085	<0.01	8.6	0.82	520	0.09	
5/97	10.1	10.07	2,100	1,865	17		<1.0	63	0.092	0.001		1	470	0.06	0.008
5/98	9.98	10.24	1,900	1,880	13		<0.01	68	0.082	0.001		0.93	450	0.06	0.0053
9/98	9.96	9.96	1,900	1,991	21		0.30	69	0.086	0.00089		0.90	440	0.051	<0.005
1/99	9.98	10.27	2,000	2,000	21		5.3	65	0.085	0.00064		1.1	440	0.054	<0.005
1/99 (DUP)	9.98	10.27	1,900	2,000	22		<0.1	66	0.087	0.00064		1.0	440	0.053	<0.005
5/99	10.1	9.94	1,900	1,940	25		3.5	67	0.095	0.00088		0.96	400	0.046	<0.005
9/99	9.88	10.60	1,600	1,830	22		2.6	59	0.077	<0.0005		0.85	430	0.032	<0.005
9/99 (DUP)	9.88	10.60	1,900	1,830	22		2.5	60	0.079	<0.0005		0.95	460	0.039	<0.005
1/00	9.88	9.65	2,000	1,825	23		2.4	66	0.086	0.0006		0.99	360	0.041	<0.005
5/00	9.92	9.84	2,000	1,863	18		<0.5	66	0.0809	0.00075	13	1.0	430	0.045	<0.005
5/00 (DUP)	9.97	9.84	1,900	1,863	18		11	67	0.081	0.00076	13	1.1	410	0.045	<0.005
10/00	9.92	9.95	1,800	1,518	17		0.73	61	0.077	0.00051		1.0	270	0.039	<0.005
1/01	9.91	11.34	1,900	1,708	18		3.4	68	0.082	0.00073		1.1	450	0.045	<0.005
5/01	9.88	10.66	1,900	1,621	15		13	67	0.087	0.00078		0.96	360	0.048	<0.005
5/01 (Dup.)	9.87	10.66	1,800	1,621	15		15	68	0.076	0.00071		0.89	360	0.045	<0.005
9/01	9.80	10.14	1,800	1,635	17		2.5	63	0.089	0.00088		1.1	400	0.056	<0.005
MW-5															
12/83	9.7	9.5	3,058	2,825	18.8	0.064		130			17.5	1.61	880		
2/84	9.6	9.6	3,636	2,700	14.5			120			18.0	1.39	1,030		
9/84	9.8	9.3	2,278	3,100	4.94	0.032		140			19.4	1.7	850		
5/85	9.8	9.9	4,800	2,400	25.0	0.037		91			15.8	1.01	710		
10/85	9.8		2,550		22.0	2.0		70		<0.01	13.0	0.93	650		
7/88	9.5	9.6	2,000	2,050	5.5		0.10	90	0.076	<0.0015	7.05	0.514	449	0.025	0.012
1/95	8.6	8.5	1,500	1,250	3.1		<0.01	32	0.008	<0.01	1.3	0.27	270	<0.01	
5/97	9.0	9.2	1,500	1,318	3.5		<0.25	16	0.015	<0.0005		0.4	310	<0.01	<0.005
5/98	8.83	8.84	1,400	1,340	2.1		<0.01	18	0.007	<0.0005		0.17	300	<0.01	<0.005
5/98 (DUP)	8.83	8.84	1,400	1,340	1.3		<0.01	18	0.007	<0.0005		0.18	300	<0.01	<0.005
9/98	8.92	8.66	1,200	1,219	2.0		0.02	18	0.0089	<0.0005		0.16	240	<0.01	<0.005
1/99	8.95	8.93	1,100	1,175	1.8		0.14	17	0.0086	<0.0005		0.16	240	<0.01	<0.005
5/99	8.97	8.60	1,200	1,260	1.9		<0.01	16	0.0094	<0.0005		0.27	250	<0.01	<0.005
5/99 (DUP)	8.97	8.60	1,200	1,260	2.2		2.2	16	0.0097	<0.0005		0.25	240	<0.01	<0.005
9/99	8.78	9.10	1,100	1,030	2.4		0.10	17	0.0074	<0.0005		0.23	230	<0.01	<0.005
1/00	8.76	8.30	1,200	1,040	2.0		2.0	15	0.0063	<0.0005		0.24	180	<0.01	<0.005
1/00 (DUP)	8.77	8.30	1,100	1,040	1.9		1.9	16	0.006	<0.005		0.23	180	<0.01	<0.005
5/00	8.81	8.59	1,100	1,020	2.3		2.3	16	0.0082	<0.0005	1.8	0.37	110	<0.01	<0.005
10/00	8.71	8.59	1,000	817	2.6		2.6	11	0.006	<0.0005		0.35	120	<0.01	<0.005
10/00 (DUP)	8.71	9	1,000	817	2.5		2.5	11	0.0061	<0.0005		0.35	110	<0.01	<0.005
1/01	8.65	9.27	1,000	863	2.7		0.13	13	<0.004	<0.0005		0.72	190	<0.01	<0.005
1/01 (DUP)	8.65	9.27	1,000	863	2.8		0.33	14	<0.004	<0.0005		0.58	210	<0.01	<0.005
5/01	8.51	8.99	960	791	2.9		2.9	13	<0.004	<0.0005		0.66	170	<0.01	<0.005
9/01	8.42	8.69	708	970	3.6		0.34	11	<0.004	<0.0005		0.80	160	<0.01	<0.005
9/01 (DUP)	8.46	8.69	708	950	3.6		0.22	13	<0.004	<0.0005		0.80	170	<0.01	<0.005

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-7															
12/83	6.8	6.2	613	700	0.019	0.020		0.1			1.01	7.88	49.0		
2/84	5.9	5.9	581	750	<0.01			0.1			9.0	4.72	49.2		
9/84	5.8	5.7	410	680	<0.01	<0.01		<0.2			11.6	4.65	58.0		
5/85	6.1	5.6	720	890	0.023	0.021		<0.2			24.7	3.70	61.0		
6/88	5.7	5.8	740	760	0.02		0.01	0.2	0.012	<0.0015	17.6	3.05	64.2	0.0032	
1/95	5.5	5.3	850	1,500	<0.01		<0.01	0.2	0.040	<0.01	22	2.3	72	<0.01	
5/97	5.6	6.04	790	670	<0.01			0.10	0.038	<0.0005		2.2	89	<0.01	
5/97 (DUP)	5.7		800	670	<0.01			0.20	0.038	<0.0005		2.2	84	<0.01	
5/98	5.71	5.69	770	900	<0.01			0.20	0.051	<0.0005		2.2	78	<0.01	
5/99	5.81	6.00	780	700	<0.01			0.16	0.042	<0.0005		2.0	78	<0.01	
5/00	5.74	5.96	810	777	<0.01			0.14	0.041	<0.0005	18	2.0	93	<0.01	
5/01	5.69	5.27	770	771	<0.01			0.13	0.033	<0.0005		2.0	75	<0.01	
MW-8															
12/83	9.5	9.2	820	700	0.32	0.017		18			0.20	0.01	202		
2/84	9.5	9.5	820	700	0.14			18			0.23	0.04	199		
9/84	9.5	9.0	661	800	0.35	0.013		22			1.00	0.04	216		
5/85	9.2	9.2	830	550	0.11	0.024		7.9			0.21	0.01	151		
5/86	8.8		550		0.04						<0.01	<0.01	111		
6/88	8.4	8.3	560	550	0.06		<0.01	2.8	0.0018	<0.0015	0.044	0.023	67.8	<0.0026	<0.005
1/95	7.8	7.8	610	930	0.09		<0.01	3.1	<0.004	<0.01	<0.04	0.08	50	<0.01	
5/97	7.8	8.02	560	442	0.040		<0.01	2.2	<0.004	<0.0005		0.12	44	<0.01	
5/98	7.81	7.60	490	514	0.02		<0.01	2.3	<0.004	<0.0005		0.14	30	<0.01	
5/99	8.00	8.10	530	455	0.028		0.028	2.4	<0.004	<0.0005		0.15	34	<0.01	
5/00	7.91	8.01	600	533	0.026		0.026	2.2	<0.004	<0.0005	0.054	0.24	36	<0.01	
5/01	8.24	7.48	560	482	0.024		0.024	1.9	<0.004	<0.0005		0.26	34	<0.01	
MW-10															
12/83	7.7	7.6	1,205	1,280	1.36	0.083		6.9			0.60	0.26	195		
2/84	7.6	7.5	820	800	0.79			5.5			0.30	0.26	106		
9/84	7.6	6.5	547	675	0.22	0.14		4.3			0.13	0.34	88		
5/85	7.7	7.0	800	710	0.33	0.060		2.9			0.07	0.05	53		
6/88	7.3	7.2	770	750	<0.01		<0.01	2.1	0.0038	<0.0015	0.081	<0.001	28.7	<0.0026	
1/95	7.0	6.8	800	560	0.02		0.02	0.5	<0.004	<0.01	<0.04	<0.01	26	<0.01	
5/97	7.2	7.4	670	510	<0.01			0.70	<0.004	<0.0005		<0.01	25	<0.01	
5/98	7.22	7.23	970	1,110	0.15		0.01	0.60	<0.008	<0.0005		<0.01	120	<0.01	
5/99	7.40	7.32	750	545	<0.01			0.41	<0.004	<0.0005		0.012	30	<0.01	
5/00	7.45	7.51	650	549	<0.01			0.48	<0.004	<0.0005	0.079	<0.01	21	<0.01	
5/01	8.19	7.21	610	502	0.013		0.013	0.47	<0.004	<0.0005		<0.01	27	<0.01	
MW-11															
12/83	9.6	9.4	980	825	0.52	0.021		33			0.48	0.06	238		
2/84	9.6	9.5	962	775	0.25			27			7.9	0.37	232		
9/84	9.7	9.1	656	800	0.20	0.015		22			4.90	0.21	213		
5/85	9.4	9.5	750	650	0.30	0.026		13			2.68	0.13	181		
6/88	8.5	8.4	570	565	0.12		<0.01	4.9	0.0043	<0.0015	0.071	0.227	78.5	<0.0026	<0.005
1/95	7.6	7.9	540	680	0.02		<0.01	2.3	<0.004	<0.01	<0.04	0.40	30	<0.01	
5/97	7.8	7.64	530	404	0.09		<0.01	1.8	<0.004	<0.0005		0.42	33	<0.01	
5/98	7.84	7.57	490	507	0.02		<0.01	1.7	<0.004	<0.0005		0.45	31	<0.01	
5/98 (DUP)	7.85	7.57	500	507	0.02		<0.01	1.7	<0.004	<0.0005		0.43	29	<0.01	
5/99	8.07	8.39	490	425	0.024		0.011	1.7	<0.004	<0.0005		0.45	28	<0.01	
5/00	7.96	7.58	580	500	0.013		0.013	1.4	<0.004	<0.0005	0.046	0.54	32	<0.01	
5/01	7.84	7.26	550	458	<0.01			1.6	<0.004	<0.0005		0.52	35	<0.01	

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-12															
12/83	7.5	7.3	476	400	0.074	0.021		2.1			<0.01	0.94	24.3		
2/84	7.5	7.2	476	385	0.02			2.0			0.02	0.71	23.8		
9/84	7.7	6.3	366	375	<0.01	<0.01		2.2			<0.01	0.61	29.0		
5/85	7.7	7.4	540	390	0.024	0.022		1.6			<0.01	1.00	27.7		
5/86	7.5		494		<0.01						<0.01	1.23	27		
6/88	7.2	7.5	510	515	<0.01		<0.01	1.3	<0.0015	<0.0015	0.066	1.09	24.4	<0.0026	<0.005
1/95	7.4	7.6	530	350	<0.01		<0.01	1.1	<0.004	<0.01	<0.04	1.5	23	<0.01	
5/97	7.5	7.7	540	422	<0.01			0.90	<0.004	<0.0005		1.7	19	<0.01	
5/98	7.43	7.43	470	550	<0.01			0.80	<0.008	<0.0005		1.9	23	<0.01	
9/98	7.57	7.38	470	481	<0.01			0.92	<0.004	<0.0005		1.6	20	<0.01	
1/99	7.53	7.04	470	440	<0.01			0.89	<0.004	<0.0005		1.8	22	<0.01	
5/99	7.42	7.39	630	515	0.026		0.026	0.73	<0.004	<0.0005		2.5	29	<0.01	
9/99	7.54	7.25	530	565	0.017		0.012	0.68	<0.004	<0.0005		1.9	27	<0.01	
1/00	7.44	6.65	570	495	<0.01			0.74	<0.004	<0.0005		1.8	22	<0.01	
5/00	7.53	7.57	600	558	<0.01			0.73	<0.004	<0.0005	0.043	2.0	29	<0.01	
10/00	7.64	7.33	530	429	<0.01			0.83	<0.004	<0.0005		1.6	22	<0.01	
1/01	7.56	7.69	530	484	<0.01			0.92	<0.004	<0.0005		1.8	1.2	<0.01	
5/01	7.48	7.13	530	442	<0.01			0.82	<0.004	<0.0005		1.6	23	<0.01	
9/01	7.46	7.96	520	460	<0.01			0.83	<0.004	<0.0005		1.8	28	<0.01	
MW-15															
12/83	6.9	6.7	568	435	0.44	0.018		0.1			0.14	0.03	28.8		
2/84	6.9	6.7	550	435	0.51			0.1			0.13	<0.01	29.4		
5/85	7.4	6.8	590	445	0.44	0.034		0.3			0.18	<0.01	32.5		
5/86	7.1		550		0.39						0.15	<0.01	34		
7/88	7.0/7.1	7.1/7.1	610/630	600/600	0.43/0.32		0.10/<0.01	0.2/0.2	0.0045	0.0025	10.8	0.117	34.4	0.0059	<0.005
1/95	7.0	7.1	720	420	0.49		0.12	1.4	<0.004	<0.01	0.26	<0.01	45	<0.01	
7/96	6.8	7.07	570	613	1.0	<0.020		2.1	<0.004	<0.0005		<0.01		<0.01	
5/97	7.4	7.44	800	731	2.8		0.20	11	<0.004	<0.0005		0.02	140	<0.01	
5/97 (DUP)	7.4	7.44	800	731	3.3		0.40	8.9	<0.004	<0.0005		0.05	140	<0.01	
5/98	6.99	6.78	610	625	0.49		0.02	0.40	<0.004	<0.0005		<0.01	40	<0.01	
5/99	7.49	7.70	980	785	8.5		<0.01	15	<0.004	<0.0005		0.017	150	<0.01	
5/00	7.53	7.56	1,200	1,169	12		<0.01	25	<0.004	<0.0005	10	0.17	120	<0.01	
5/01	7.03	6.83	600	501	0.49		0.32	2.0	<0.004	<0.0005		0.017	51	<0.01	
MW-16															
12/83	9.8	9.9	2,092	1,800	7.35	0.034		110			12.4	0.91	530		
2/84	9.7	9.7	2,049	1,550	5.5			98			13.9	1.41	570		
9/84	9.8	9.2	1,390	10,500	2.11	<0.01		80			9.5	0.5	475		
5/85	9.4	9.0	2,300	1,400	10.0	0.11		72			10.3	1.09	443		
10/85	8.4		1,540		3.9	0.0		30		<0.01	2.10	0.41	186		
7/88	9.4	9.7	1,400	1,410	4.6		<0.01	61	0.063	<0.0015	6.57	0.22	300	0.018	0.006
1/95	7.7	9.0	850	930	1.4		0.13	7.9	<0.004	<0.01	0.52	1.1	81	<0.01	
7/96	7.3	7.75	990	941	1.6	<0.020		7.9	<0.004	<0.0005		1		<0.01	
5/97	7.6	7.6	980	801	1.3		0.3	11	<0.004	<0.0005		0.43	130	<0.01	
5/98	7.72	7.70	750	760	2.0		0.40	11	<0.004	<0.0005		1.2	80	<0.01	
9/98	7.70	7.50	860	790	1.4		1.4	9.5	<0.004	<0.0005		1.3	75	<0.01	
1/99	7.70	7.12	740	665	1.4		<0.04	9.8	<0.004	<0.0005		1.5	85	<0.01	
5/99	7.88	7.90	750	600	2.8		0.16	9.0	<0.004	<0.0005		1.5	82	<0.01	
9/99	7.62	8.15	730	745	2.9		0.88	8.2	<0.004	<0.0005		1.7	78	<0.01	
1/00	7.76	6.95	950	810	5.5		5.5	7.6	<0.004	<0.0005		2.2	68	<0.01	
1/00 (DUP)	7.77	6.95	940	810	5.8		5.8	7.8	<0.004	<0.005		2.2	70	<0.01	
5/00	7.69	7.53	1,100	945	12		12	7.9	<0.004	<0.0005	4.3	2.3	91	<0.01	
5/00 (DUP)	7.72	7.53	1,000	945	12		12	8.1	<0.004	<0.0005	4.4	2.4	91	<0.01	
10/00	7.74	7.67	1,000	774	16		<0.01	13	<0.004	<0.0005		1.6	130	<0.01	
10/00 (DUP)	7.77	7.67	1,000	774	15		<0.01	13	<0.004	<0.0005		1.7	130	<0.01	
1/01	7.84	7.42	1,200	939	16		3.2	24	<0.004	<0.0005		1.6	250	<0.01	
1/01 (DUP)	7.85	7.42	1,200	939	17		2.5	24	<0.004	<0.0005		1.6	250	<0.01	
5/01	7.89	8.04	1,100	920	12		12	39	<0.004	<0.0005		1.2	200	<0.01	
5/01 (DUP)	7.90	8.04	1,100	920	11		11	40	<0.004	<0.0005		1.2	210	<0.01	
9/01	7.91	7.86	1,300	754	9.7		0.85	43	<0.004	0.00058		0.89	270	0.013	
9/01 (DUP)	7.90	7.86	1,200	754	9.0		0.65	43	0.019	0.00096		1.1	260	0.021	

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-17															
12/83	7.9	7.6	613	475	0.99	0.021		5.6			0.44	1.38	78		
2/84	7.6	7.4	581	470	1.03			4.4			0.39	1.77	52		
9/84	8.0	6.7	485	550	0.17	<0.01		9.1			0.28	1.27	99		
5/85	7.9	7.9	610	470	0.76	0:045		4.1			0.28	1.80	45.3		
10/85	7.9		564		0.56	0.43		4.2		<0.01	6.80	1 93	43.4		
6/88	7.7	7.5	590	475	1.3		0.46	5.2	0.0054	<0.0015	0.973	1.72	39.7	<0.0026	<0.005
2/90	7.7	7.55	680	640	0.582		<0.005	4.1			18		40		
1/95	7.5	7.7	710	420	0.64		<0.01	3.9	<0.004	<0.01	0.26	1.9	36	<0.01	
5/97	7.5	7.67	870	488	0.54		<0.01	3.1	<0.004	<0.0005		1.9	30	<0.01	
5/98	7.6	7.40	570	580	0.72		0.09	3.4	<0.004	<0.0005		1.8	34	<0.01	
5/99	7.50	7.40	550	470	0.46		0.46	3.2	<0.004	<0.0005		1.8	31	<0.01	
5/99 (DUP)	7.37	7.40	550	470	0.49		0.49	3.2	<0.004	<0.0005		1.8	30	<0.01	
5/00	7.57	7.61	610	523	0.53		0.31	2.9	<0.004	<0.0005	0.34	1.8	24	<0.01	
5/01	7.87	7.36	570	460	0.50		0.50	3.0	<0.004	<0.0005		1.7	28	<0.01	
MW-18															
12/83	9.9	10.0	10,526	8,750	110.0	0.45		460			58.7	0.26	3,150		
2/84	9.8	9.8	9,615	7,500	52.0			350			61	0.50	2,750		
9/84	10.1	9.5	9,111	10,000	194	0.19		690			103	0.3	4,130		
5/85	9.8	9.9		7,000	35.2	0.091		410			64.2	0.35	2,540		
10/85	9.9		6,300		120	12		350		<0.01	71.4	1.06	1,940		
7/88	10.0	10.1	9,700	10,000	29		25	820	0.159	0.0071	144	1.75	2,640	0.191	0.022
2/90	10.0	10.1	8,000	11,400	67.0		10.5	710			110		3,500		
1/95	9.6	11.1	5,900	>2,000	15		6.6	290	0.062	<0.01	56	0.22	1,500	0.02	
7/96	9.1	8.67	4,300	4,200	7.2	<0.020		180	0.065	0.0006	56	0.19	1,500	0.01	0.006
5/97	9.7	9.58	4,000	4,110	8.7		<0.50	200	0.078	0.0009		0.29	1,100	0.02	
5/98	9.76	10.06	4200	4,300	9.8		0.40	260	0.094	0.0014		0.49	1100	0.05	0.024
9/98	9.70	9.88	3,600	3,590	5.9		<0.01	210	0.085	0.00084		0.29	800	0.022	0.014
1/99	9.67	10.04	3,600	3,450	79		3.0	210	0.088	0.00063		0.29	830	0.028	0.0219
5/99	9.72	9.80	3,000	3,000	95		81	370	0.088	0.0014		0.92	650	0.045	0.017
9/99	9.62	10.26	3,000	2,870	90		14	170	0.074	<0.0005		0.24	700	0.011	0.016
1/00	9.56	9.15	3,000	2,700	27		19	180	0.078	0.00059		0.26	680	0.017	0.020
5/00	9.59	9.73	2,800	2,270	84		75	160	0.075	0.00089	25	0.56	620	0.035	0.019
5/00 (DUP)	9.60	9.73	2,800	2,270	64		50	160	0.073	0.00062	20	0.33	620	0.023	0.016
10/00	9.54	9.67	2,400	1,948	29		<0.01	130	0.074	0.0024		2.1	400	0.08	0.012
1/01	9.62	10.82	2,500	1,980	53		9.2	170	0.067	0.0006		0.3	580	0.019	0.043
5/01	9.52	10.36	2,100	1,780	15		<0.50	100	0.065	0.0014		0.97	380	0.042	0.040
5/01 (Dup.)	9.52	10.36	2,000	1,780	49		49	110	0.079	0.0037		3.1	380	0.140	0.046
9/01	9.61	9.75	2,100	1,668	91		11	180	0.12	0.00099		0.3	520	0.024	0.027
MW-19															
12/83	7.2	7.1	581	435	0.068	0.013		0.3			<0.01	0.54	22.9		
2/84	7.1	6.8	575	405	0.04			0.5			0.05	0.26	20.2		
9/84	7.2	6.3	451	460	0.01	<0.01		0.4			0.02	0.04	23.5		
5/85	7.6	7.0	640	460	0.019	0.014		0.5			0.12	0.02	23.6		
7/88	7.3	7.3	630	600	<0.01		<0.01	0.5	0.0067	<0.0015	17.6	0.23	32.2	0.015	<0.005
2/90	7.3	7.27	520	560	0.2		<0.005	0.7					21.0		
1/95	7.3	7.2	630	410	<0.01		<0.01	1.0	<0.004	<0.01	0.09	<0.01	24	<0.01	
5/97	7.4	7.5	520	431	<0.01		<0.01	2.0	<0.004	<0.0005		<0.01	18	<0.01	
5/98	7.23	6.95	560	575	<0.01			1.4	<0.008	<0.0005		<0.01	23	<0.01	
5/99	7.47	7.40	570	460	<0.01			1.3	<0.004	<0.0005		<0.01	22	<0.01	
5/00	7.33	7.20	580	538	<0.01			1.2	<0.004	<0.0005	0.13	<0.01	16	<0.01	
5/01	7.18	6.96	580	494	<0.01			1.1	<0.004	<0.0005		<0.01	20	<0.01	

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-28															
5/86	5.5		382		0.89	0.08		<0.1			0.36	0.02	41		
6/88	5.7	5.8	640	665	7.4		0.6	<0.1	<0.0015	<0.0015	2.41	0.035	83.3	<0.0026	<0.005
1/95	6.2	7.4	500	700	0.74		0.26	2.7	<0.004	<0.01	0.38	0.02	79	<0.01	
7/96	5.7	5.92	440	429	0.26	<0.020		0.50	<0.004	<0.0005		0.01		<0.01	
5/97	5.6	6.4	590	453	0.11		<0.02	0.2	<0.004	<0.0005		0.01	62	<0.01	
5/98	5.74	5.32	500	550	0.12		<0.01	0.20	<0.004	<0.0005		0.01	65	<0.01	
9/98	5.81	5.28	540	527	0.11		0.11	0.27	<0.004	<0.0005		0.011	64	<0.01	
9/98 (DUP)	5.83	5.28	540	527	0.11		0.11	0.24	<0.004	<0.0005		0.01	65	<0.01	
1/99	5.72	5.17	470	450	0.087		0.027	0.38	<0.004	<0.0005		0.013	67	<0.01	
5/99	5.72	5.43	460	405	0.13		0.13	0.35	<0.004	<0.0005		0.011	70	<0.01	
9/99	5.95	6.15	480	480	0.12		0.016	0.26	<0.004	<0.0005		<0.01	57	<0.01	
1/00	6.04	5.25	460	410	0.23		0.22	0.35	<0.004	<0.0005		<0.01	58	<0.01	
5/00	5.89	5.90	470	464	1.0		1.0	0.30	<0.004	<0.0005	0.69	0.014	77	<0.01	
10/00	5.85	5.47	460	384	0.96		0.28	0.27	<0.004	<0.0005		0.014	52	<0.01	
1/01	5.75	5.45	480	412	0.9		0.9	0.32	<0.004	<0.0005		0.015	64	<0.01	
5/01	5.65	5.20	420	391	1.1		0.36	0.22	<0.004	<0.0005		0.014	54	<0.01	
9/01	5.70	6.01	430	415	1.3		<0.1	0.56	<0.004	<0.0005		0.015	64	<0.01	
MW-29S															
5/86	8.4		2,350		1.5	0.02		28			0.64	0.08	590		
6/88	9.0	9.0	1,100	1,090	0.99		0.37	44	0.0052	<0.0015	1.52	0.094	224	0.0044	<0.005
1/95	8.3	10.0	2,900	1,750	0.79		0.07	56	<0.004	<0.01	0.37	0.12	590	<0.01	
5/97	8.3	8.43	2,200	1,735	0.6		<0.1	44	<0.004	<0.0005		0.14	410	<0.01	
5/98	8.64	8.70	1,700	1,665	0.18		<0.01	26	<0.004	<0.0005		0.09	370	<0.01	
5/99	8.35	8.37	1,300	1,090	0.22		0.021	16	<0.004	<0.0005		0.30	230	<0.01	
5/00	8.11	8.11	1,200	1,023	0.17		0.17	16	0.0057	<0.0005	0.14	0.41	130	<0.01	
5/01	7.89	7.54	1,000	828	0.16		0.16	16	<0.004	<0.0005		0.42	160	<0.01	
MW-29D															
5/86	8.6		648		0.31	0.01		9.7			0.18	0.26	139		
6/88	8.1	8.0	590	570	0.25		<0.01	4.2	0.002	<0.0015	0.082	1.16	60.4	<0.0026	<0.005
1/95	7.5	8.9	650	770	0.22		0.03	3.7	<0.004	<0.01	0.09	2.0	33	<0.01	
5/97	7.7	7.9	600	479	0.18		<0.02	3.3	<0.004	<0.0005		2	31	<0.01	
5/98	7.65	7.53	550	560	0.17		<0.01	3.5	<0.004	<0.0005		1.8	28	<0.01	
5/99	7.82	7.60	550	465	0.19		0.19	3.4	<0.004	<0.0005		1.8	28	<0.01	
5/00	7.75	7.66	590	503	0.15		0.15	3.1	<0.004	<0.0005	0.12	1.9	24	<0.01	
5/01	7.55	6.82	570	489	0.15		0.15	3.1	<0.004	<0.0005		1.8	27	<0.01	
MW-30															
5/86	6.6		342		0.01	<0.01		0.5			<0.01	2.10	20		
6/88	6.3	6.3	340	400	0.01		<0.01	<0.1	0.0018	<0.0015	4.42	0.753	18.7	0.0044	0.005
1/95	6.2	6.0	430	570	0.01		<0.01	<0.1	<0.004	<0.01	0.78	0.60	19	<0.01	
5/97	6.2	6.47	420	334	<0.01			<0.1	<0.004	<0.005		0.6	18	<0.01	0.012
5/98	6.19	5.70	390	418	<0.01			0.10	<0.004	<0.0005		0.68	21	<0.01	0.013
5/99	6.43	6.10	400	390	0.016		0.013	0.19	<0.004	<0.0005		0.71	21	<0.01	0.02
5/00	6.34	5.91	430	380	0.026		0.026	0.12	<0.004	<0.0005	1.5	0.70	21	<0.01	0.017
5/01	6.14	6.21	420	409	0.79		0.79	0.17	<0.004	<0.0005		0.54	19	<0.01	0.015
MW-31															
5/86	9.1		1,250		12	1.5		46			84.5	3.67	380		
6/88	10.2	10.5	3,400	3,500	39		<0.01	140	0.046	<0.0015	20.3	1.93	703	0.184	0.040
2/90	10.0	9.95	2,300	2,700	4.80		3.94	110			49		660		
1/95	9.6	10.4	1,900	1,600	7.1		<0.01	89	0.027	<0.01	4.6	0.66	420	<0.02	
7/96	9.5	9.52	2,300	2,100	12	<0.020		91	0.042	0.0007		0.62		0.04	0.041
5/97	9.9	9.69	2,500	2,100	12		<0.50	110	0.04	0.0007		0.68	480	0.05	0.028
5/97 (DUP)	9.9	9.69	2,500	2,100	6.2			93	0.038	0.0008		0.74	480	0.05	0.029
5/98	9.63	9.80	2,400	2,350	9.3		<0.01	100	0.036	0.0013		1.1	490	0.04	0.022
9/98	9.67	9.86	2,600	2,520	9.8		<0.01	120	0.044	0.0014		1.1	620	0.045	0.017
9/98 (DUP)	9.67	9.86	2,700	2,520	9.5		<0.01	130	0.045	0.0013		1.1	600	0.043	0.020
1/99	9.72	9.97	2,500	2,240	22		0.63	120	0.047	0.0012		1.3	620	0.065	0.019
5/99	9.91	10.02	2,600	2,510	29		6.5	130	0.06	0.0014		1.2	600	0.07	0.034
9/99	9.83	10.03	2,600	2,810	30		4.3	150	0.063	0.0011		1.6	750	0.088	<0.005
1/00	9.98	9.80	2,900	2,600	24		6.3	150	0.072	0.001		1.4	650	0.120	0.028
5/00	10.1	10.10	2,900	2,400	21		1.7	140	0.096	0.0011	13	1.6	820	0.12	0.020
10/00	9.99	10.18	2,800	2,550	20		0.54	140	0.056	0.00076		1.1	480	0.079	0.043
1/01	10.1	11.21	2,100	1,900	13		1.5	110	0.056	0.001		1.3	560	0.11	0.020
5/01	9.93	10.85	2,100	1,866	12		12	77	0.046	0.0012		1.4	430	0.081	0.027
9/01	9.95	9.98	2,300	1,877	16		1.2	110	0.054	0.0014		1.4	590	0.09	0.032

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-32															
5/86	10.5		6430		97	18		369			27.4	0.69	2120		
7/88	9.2	9.3	890	1,040	7.2		0.30	39	0 014	<0.0015	4.05	0 513	234	0.024	<0.005
1/95	9.4	9.4	1,300	630	12		3.6	47	0.014	<0.01	2.7	0.37	230	0.03	
7/96	8.6	8.89	1,000	1,038	6.9	<0.020		29	0.011	<0.0005		0.84		0.01	
5/97	8.7	8.71	930	697	4.4		1 3	19	0.008	<0.0005		1.1	110	<0.01	
5/98	8.03	8.10	630	697	2.5		0.34	7.7	<0.004	<0.0005		1.9	61	<0.01	
5/98 (DUP)	8.05	8.10	690	697	2.5		0.09	8.0	<0.004	<0.0005		2.0	68	<0.01	
9/98	8.30	8.26	760	760	4.5		1.0	13	<0.004	<0.0005		1.8	78	<0.01	
1/99	8.39	8.00	710	650	3.1		<0.02	13	<0.004	<0.0005		1.7	77	<0.01	
1/99 (DUP)	8.39	8.00	720	650	3.7		<0.02	13	<0.004	<0.0005		1.7	76	<0.01	
5/99	8.38	8.50	690	555	4.4		0.59	12	<0.004	<0.0005		2.0	78	<0.01	
9/99	9.84	10.01	2,200	2,300	18		1.8	120	0.057	0.0014		2.2	520	0.093	
1/00	8.93	8.28	950	770	4.8		0.57	27	0.017	<0.0005		1.9	97	0.024	
5/00	8.80	8.95	830	858	3.9		<0.01	19	0.013	<0.0005	3.1	1.6	70	<0.01	
10/00	9.75	9.98	1,500	1,227	8.3		0.76	70	0.051	0.00099		1.6	290	0.058	
1/01	8.46	9.24	740	675	4.3		0.82	13	0.004	<0.0005		2.0	95	<0.01	
5/01	8.51	8.84	790	624	4.9		4.9	17	0.0054	<0.0005		2.1	94	0.012	
9/01	8.69	8.74	720	606	4.9		0.53	99	0 0088	<0.0005		1.9	110	0.011	
MW-34S															
5/86	7.4		668		0.13	<0.01		9.4			0.07	0.42	64		
7/88	7.2	7.2	690	670	40		38	7.3	0.0087	<0.0015	14.6	0.416	33.1	0.018	<0.005
2/90	7.4	6.93	690	740	0.113		0.26	6.5			21		49		
1/95	7.2	7.1	700	430	0.03		<0.01	7.3	<0.004	<0.01	0.18	0.01	35	<0.01	
5/97	7.4	7.43	710	579	0.18		0.04	8.1	<0.004	<0.0005		0.04	69	<0.01	
5/98	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
5/99	7.34	7.55	650	505	0.19		<0.01	6.8	<0.004	<0.0005		0.014	46	<0.01	
5/00	7.60	7.46	740	607	1.1		1.1	11	<0.004	<0.0005	1.2	0.044	83	<0.01	
5/01	7.71	7.34	670	537	0.12		0.12	8.6	0.025	0.0019		2.9	50	0.054	
MW-34D															
5/86	7.3		602		0.05	<0.01		10.2			0.02	0.55	42		
7/88	7.4	7.4	560	580	0.07		<0.01	4.4	0.0031	<0.0015	0.538	0.762	32.4	<0.0026	<0.005
1/95	7.3	7.4	640	400	0.07		0.07	4.2	<0.004	<0.01	<0.04	0.82	34	<0.01	
5/97	7.4	7.43	630	492	0.05		<0.01	3.6	<0.004	<0.0005		0.79	31	<0.01	
5/98	7.37	7.23	590	595	0.09		0.01	3.9	<0.004	<0.0005		0.68	35	<0.01	
5/99	7.40	7.52	470	475	0.062		<0.01	3.6	<0.004	<0.0005		0.72	29	<0.01	
5/00	7.55	7.37	620	519	0.063		0.063	4.2	<0.004	<0.0005	0.14	0.76	28	<0.01	
5/01	8.00	7.16	600	453	0.13		0.13	3.9	<0.004	<0.0005		0.70	30	<0.01	
MW-35															
5/86	10.2		6,430		240	38		358			125	1.76	2,070		
7/88	10.2	10.4	6,100	6,150	43		41	400	0.147	0.002	56.5	0.337	1,630	0.053	<0.005
2/90	9.6	9.7	1,500	1,540	8.0		<0.005	71			20		350		
1/95	9.5	9.7	1,200	562	16		<0.01	35	0.018	<0.01	11	0.43	220	<0.01	
7/96	9.5	9.5	1,700	1,851	6.0	0.040		71	0.028	0.0006		0.5		0.03	
5/97	9.4	9.47	1,000	900	16		<1.0	40	0.02	0.0006		0.68	220	0.02	
5/98	8.93	9.10	710	766	15		2.9	27	0.012	<0.0005		0.92	140	0.01	
9/98	8.97	8.90	550	778	16		0.99	26	0.01	<0.0005		0.88	130	<0.01	
1/99	9.28	9.15	820	925	23		2.9	40	0.019	<0.0005		0.81	190	0.016	
5/99	9.35	9.70	830	870	28		10	38	0.013	<0.0005		0.86	160	0.015	
9/99	9.18	9.60	790	930	18		2.0	34	0.012	<0.0005		0.53	170	0.05	
1/00	8.91	8.15	610	500	13		3.3	21	0.0077	<0.0005		0.47	94	0.068	
5/00	9.07	9.24	690	693	27		20	28	0.081	<0.0005	5.2	0.48	69	0.077	
10/00	8.76	8.84	520	470	7.3		0.59	17	0.0076	<0.0005		0.57	81	0.11	
1/01	8.86	9.59	530	549	10		3.1	19	0.008	<0.0005		0.50	89	0.075	
5/01	9.17	9.43	800	790	17		2.6	35	0.013	<0.0005		0.48	130	0.04	
9/01	9.26	9.03	820	749	15		<0.5	41	0.0097	<0.0005		0.46	120	0.062	

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-36															
5/86	9.7		2,700		25	1.4		97			39.5	1.13	760		
7/88	8.9	9.6	940	1,255	8.6		1.3	18	0.0078	<0.0015	3.52	0.332	161	0.0063	<0.005
1/95	9.8	9.7	3,500	1,350	18		<0.01	160	0.034	<0.01	8.7	0.83	770	0.07	
7/96	9.6	9.55	3,300	3,280	8.1	<0.020		160	0.058	0.0021		0.67		0.07	
5/97	9.8	9.64	3,600	3,290	9.2		3.5	180	0.084	0.0035		1.7	850	0.1	
5/98	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
9/98	9.90	10.10	4,500	4,380	6.5		0.03	230	0.11	0.0036		1.4	990	0.074	
1/99	9.76	10.20	3,500	3,300	41		1.2	190	0.076	0.0036		1.5	820	0.072	
5/99	10.10	10.40	2,500	2,260	19		4.4	150	0.12	0.0019		1.3	600	0.12	
9/99	10.10	10.10	1,800	1,790	6.2		0.69	93	0.059	0.00055		1.2	420	0.067	
9/99 (DUP)	10.10	10.10	1,800	1,790	6.3		<0.5	96	0.061	0.00062		1.2	450	0.07	
1/00	10.2	9.80	1,600	1,450	3.9		0.51	80	0.072	<0.0005		0.70	290	0.082	
5/00	10.2	10.42	1,200	1,272	1.6		<0.01	50	0.03	<0.0005	4.0	0.54	150	0.03	
10/00	9.84	10.05	1,200	1,043	4.9		<0.01	41	0.024	0.00061		1.6	210	0.033	
1/01	9.79	11.00	1,700	1,567	12		2.0	89	0.027	0.0018		1.4	450	0.049	
5/01	9.87	10.28	1,100	1,109	3.0		3.0	49	0.029	0.00054		0.68	220	0.045	
9/01	9.80	9.75	1,100	960	2.7		<0.25	44	0.018	0.00053		0.59	210	0.026	
MW-37															
5/86	10.1		7,340		97	8.2		890			498	46.3	1,800		
7/88	9.9	9.8	5,600	5,500	0.30		<0.01	1000	0.169	0.035	115	15.4	1,470	0.369	<0.005
2/90	9.6	9.65	2,700	3,100	4.6		22.7	360			1000		970		
1/95	9.1	9.2	1,200	970	18		<0.01	87	0.033	<0.01	8.5	0.58	280	0.01	
7/96	9.1	8.89	570	832	14	<0.020		45	0.042	0.0005		0.51		0.03	
5/97	9.2	9.07	1,100	846	13		1.7	53	0.027	<0.0005		0.56	210	0.02	
5/98	8.57	8.30	530	505	6.4		<0.01	6.8	0.018	<0.0005		0.28	120	0.02	
9/98	8.90	8.26	670	682	15		5.5	52	0.020	<0.0005		0.53	140	0.017	
1/99	9.02	9.25	660	750	19		<0.10	25	0.02	<0.0005		0.68	140	0.029	
5/99	9.39	9.45	610	540	11		3.6	22	0.023	<0.0005		0.23	130	0.016	
9/99	8.78	8.91	760	753	7.9		0.91	31	0.01	<0.0005		0.33	170	<0.01	
1/00	8.83	8.40	880	822	10		2.2	32	0.011	<0.0005		0.49	110	<0.01	
5/00	8.51	8.89	770	765	5.2		0.93	32	0.015	<0.0005	9.0	0.72	92	<0.01	
10/00	8.39	8.46	750	630	6.6		<0.01	17	0.0089	<0.0005		0.61	79	<0.01	
1/01	8.42	8.99	780	678	8.8		2.7	29	0.02	0.00088		1.5	160	0.035	
5/01	7.89	7.97	650	528	7.9		<0.01	10	0.018	0.00075		2.0	110	0.026	
9/01	7.84	7.54	680	590	5.6		<0.5	21	0.0042	<0.0005		3.0	110	0.011	
MW-39S															
5/86	9.5		8,360		11	2.9		244			25.0	1.35	2780		
6/88	9.3	9.1	3,500	2,550	3.8		0.10	110	0.016	<0.0015	36.6	1.63	826	0.053	<0.005
1/95	8.9	8.7	2,700	900	0.64		<0.01	59	<0.004	<0.01	0.36	0.22	520	<0.01	
5/97	8.9	9.2	5,500	5,500	3.6		<0.2	150	0.009	<0.0005		0.15	1300	<0.01	
5/98	9.04	9.09	4,000	4,000	2.3		<0.01	98	0.009	<0.0005		0.11	700	<0.01	
5/99	9.05	9.30	4,300	3,620	3.4		0.24	120	0.0096	<0.0005		0.12	950	<0.01	
5/99 (DUP)	9.05	9.30	4,200	3,620	3.6		0.89	120	0.009	<0.0005		0.11	1,100	<0.01	
5/00	9.18	9.19	4,500	3,870	3.5		3.5	110	0.013	<0.0005	2.3	0.097	1,100	<0.01	
5/01	8.91	9.38	3,700	2,820	2.0		0.86	97	0.011	<0.005		0.22	880	0.015	
MW-39D															
5/86	8.1		627		0.21	0.02		7.4			0.14	0.54	103		
6/88	7.9	7.8	590	595	0.17		0.03	6.1	0.0021	<0.0015	0.36	0.681	53.9	<0.0026	<0.005
1/95	7.5	7.6	630	410	0.07		<0.01	3.9	<0.004	<0.01	0.06	0.87	36	<0.01	
5/97	7.5	7.66	630	457	0.06		0.06	3.8	<0.004	<0.0005		0.87	32	<0.01	
5/98	7.52	7.35	590	560	0.04		<0.01	3.6	<0.004	<0.0005		0.77	34	<0.01	
5/99	7.59	7.64	540	447	0.037		<0.01	3.4	<0.004	<0.0005		0.87	33	<0.01	
5/00	7.68	7.60	580	503	0.027		0.027	3.2	<0.004	<0.0005	0.13	0.90	29	<0.01	
5/01	7.50	7.83	550	423	0.024		0.024	3.1	<0.004	<0.0005		0.78	32	<0.01	
MW-40S															
5/86	8.9		2,550		1.7	0.03		28			12.8	0.49	650		
6/88	9.2	9.2	2,100	2,200	1.5		<0.01	5.9	0.018	<0.0015	1.89	0.139	445	0.0056	<0.005
1/95	7.9	7.9	2,500	1,600	0.87		<0.01	40	<0.004	<0.01	0.36	0.33	470	<0.01	
5/97	7.9	8.07	1,900	1,417	0.72		0.40	21	<0.004	<0.0005		0.66	380	<0.01	
5/98	8.2	8.18	1,400	1,335	0.36		<0.01	39	<0.004	<0.0005		0.13	270	<0.01	
5/99	8.50	8.83	1,300	1,100	0.32		<0.01	30	<0.004	<0.0005		0.11	250	<0.01	
5/00	8.08	8.04	1,100	900	0.25		0.25	14	<0.004	<0.0005	0.19	0.42	110	<0.01	
5/01	8.10	7.61	950	693	0.25		0.25	13	<0.004	<0.0005		0.57	140	<0.01	

Note: All results in mg/L unless otherwise noted.

NS = Not sampled. Well damaged during remedial construction.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-40D															
5/86	9.4		1,120		7.4	0.06		20			11.7	0.62	280		
6/88	9.4	9.4	1,200	1,290	7.0		<0.01	36	0.018	<0.0015	7.81	0.454	258	0.012	<0.005
1/95	7.6	7.7	2,000	1,375	0.70		<0.01	16	<0.004	<0.01	0.29	0.74	340	<0.01	
5/97	7.6	7.9	1,800	1,350	0.59		<0.1	7.6	<0.004	<0.0005		1.3	340	<0.01	
5/98	7.85	7.73	1,300	1,250	0.49		0.47	19	<0.004	<0.0005		0.36	250	<0.01	
5/99	7.99	8.25	920	745	0.16		0.16	12	<0.004	<0.0005		0.42	150	<0.01	
5/00	7.88	7.84	960	810	0.25		0.25	11	<0.004	<0.0005	0.16	0.69	97	<0.01	
5/01	8.01	7.45	790	611	0.15		0.15	8.6	<0.004	<0.0005		0.90	78	<0.01	
MW-41															
1/95	6.6	8.2	490	600	0.04		0.02	0.2	0.017	<0.01	8.9	1.3	22	<0.01	
5/97	6.8	6.98	490	357	<0.01			0.20	0.022	<0.0005		1.6	21	<0.01	
5/98	6.67	6.74	420	449	<0.01			0.30	0.016	<0.0005		1.3	21	<0.01	
5/99	6.79	6.80	420	370	<0.01			0.33	0.014	<0.0005		1.1	20	<0.01	
5/00	6.79	6.96	430	424	<0.01			0.25	0.016	<0.0005	9.2	1.1	17	<0.01	
5/01	6.70	7.00	450	421	<0.01			0.34	0.015	<0.0005		1.0	19	<0.01	
MW-42S															
6/88	8.0	8.4	930	870	0.70		0.25	14.0	0.002	<0.0015	0.232	0.237	143	0.0027	<0.005
2/90	8.4	8.25	2,100	2,400	0.266		0.079	35.0			0.88		520		
1/95	8.2	8.4	1,600	765	0.45		<0.01	22	<0.004	<0.01	0.2	0.35	280	<0.01	
5/97	8.2	8.57	1,700	1,350	0.56		<0.02	29	<0.004	<0.0005		0.33	300	<0.01	
5/98	8.26	8.46	1,400	1,460	0.52		<0.01	27	<0.004	<0.0005		0.37	270	<0.01	
5/99	8.19	8.54	1,500	1,100	0.54		0.033	26	<0.004	<0.0005		0.49	260	<0.01	
5/00	8.19	8.18	1,900	1,530	0.66		0.66	28	<0.004	<0.0005	0.39	0.65	280	<0.01	
5/01	8.03	8.03	1,700	1,208	0.51		0.062	23	<0.004	<0.0005		0.84	300	<0.01	
MW-42D															
6/88	7.9	8.1	550	600	0.16		<0.01	6.0	0.0028	<0.0015	1.11	0.636	68.6	0.0028	<0.005
1/95	7.5	7.7	640	410	0.04		<0.01	3.6	<0.004	<0.01	0.08	1.5	31	<0.01	
5/97	7.6	7.99	580	468	0.04		<0.01	3.2	<0.004	<0.0005		1.3	27	<0.01	
5/98	7.54	7.64	550	535	0.07		0.01	3.3	<0.008	<0.0005		1.2	26	<0.01	
5/99	7.56	7.83	530	435	0.03		<0.01	3.4	<0.004	<0.0005		1.3	26	<0.01	
5/00	7.73	7.74	580	490	0.027		0.027	3.0	<0.004	<0.0005	0.053	1.3	24	<0.01	
5/01	7.53	7.68	550	462	0.023		0.023	3.1	<0.004	<0.0005		1.3	32	<0.01	

Note: All results in mg/L unless otherwise noted.

HM03-01/DATA-SUM.123

TABLE 4
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-1															
12/83	6.4	6.0	270	210	0.018	0.014		0.1			0.04	0.65	14.2		
2/84	6.1	6.1	270	215	0.04			0.1			0.01	0.54	14.9		
9/84	6.1	5.7	195	210	<0.01	<0.01		<0.2			0.02	0.33	13.8		
5/85	6.4	6.0	200	210	0.13	0.13		<0.2			0.04	0.15	16.2		
6/88	6.2	6.4	670	540	<0.01		<0.01	0.2	0.0024	<0.0015	6.21	0.379	20.3	0.006	
1/95	6.2	4.7	370	550	0.02		<0.01	0.1	<0.004	<0.01	<0.04	0.39	21	<0.01	
5/97	5.9	6.32	470	365	<0.01			0.1	<0.004	<0.0005		0.13	19	<0.01	
5/98	6.01	5.65	480	505	<0.01			0.20	<0.004	<0.0005		0.10	20	<0.01	
5/01	5.95	6.35	450	392	<0.01			0.13	<0.004	<0.0005		0.098	19	<0.01	
MW-2															
12/83	10.3	10.3	6,000	6,000	56.0	0.27		400			55.2	1.98	1,950		
2/84	10.3	10.3	7,752	2,750	48.0			420			58	2.46	2,290		
9/84	10.5	9.9	6,308	6,900	40.8	0.095		480			59.3	2.1	2,460		
5/85	10.4	10.4	13,200	5,800	95	0.10		400			54.0	1.74	2150		
10/85	10.5		7,100		140	12		390		<0.01	54.0	1.82	2,060		
7/88	10.4	10.4	6,200	6,000	22		12	330	0.394	<0.0015	34.2	1.00	1,450	0.251	0.011
2/90	10.34	10.2	4,800	3,900	36.2		29.6	200			31.0		1,200		
1/95	10.0	9.6	2,400	>2,000	7.1		<0.01	93	0.085	<0.01	8.6	0.82	520	0.09	
5/97	10.1	10.07	2,100	1,865	17		<1.0	63	0.092	0.001		1	470	0.06	0.008
5/98	9.98	10.24	1,900	1,880	13		<0.01	68	0.082	0.001		0.93	450	0.06	0.0053
9/98	9.96	9.96	1,900	1,991	21		0.30	69	0.086	0.00089		0.90	440	0.051	<0.005
1/99	9.98	10.27	2,000	2,000	21		5.3	65	0.085	0.00064		1.1	440	0.054	<0.005
1/99 (DUP)	9.98	10.27	1,900	2,000	22		<0.1	66	0.087	0.00064		1.0	440	0.053	<0.005
5/99	10.1	9.94	1,900	1,940	25		3.5	67	0.095	0.00088		0.96	400	0.046	<0.005
9/99	9.88	10.60	1,600	1,830	22		2.6	59	0.077	<0.0005		0.85	430	0.032	<0.005
9/99 (DUP)	9.88	10.60	1,900	1,830	22		2.5	60	0.079	<0.0005		0.95	460	0.039	<0.005
1/00	9.88	9.65	2,000	1,825	23		2.4	66	0.086	0.0006		0.99	360	0.041	<0.005
5/00	9.92	9.84	2,000	1,863	18		<0.5	66	0.0809	0.00075	13	1.0	430	0.045	<0.005
5/00 (DUP)	9.97	9.84	1,900	1,863	18		11	67	0.081	0.00076	13	1.1	410	0.045	<0.005
10/00	9.92	9.95	1,800	1,518	17		0.73	61	0.077	0.00051		1.0	270	0.039	<0.005
1/01	9.91	11.34	1,900	1,708	18		3.4	68	0.082	0.00073		1.1	450	0.045	<0.005
5/01	9.88	10.66	1,900	1,621	15		13	67	0.087	0.00078		0.96	360	0.048	<0.005
5/01 (Dup.)	9.87	10.66	1,800	1,621	15		15	68	0.076	0.00071		0.89	360	0.045	<0.005
9/01	9.80	10.14	1,800	1,635	17		2.5	63	0.089	0.00088		1.1	400	0.056	<0.005
MW-5															
12/83	9.7	9.5	3,058	2,825	18.8	0.064		130			17.5	1.61	880		
2/84	9.6	9.6	3,636	2,700	14.5			120			18.0	1.39	1,030		
9/84	9.8	9.3	2,278	3,100	4.94	0.032		140			19.4	1.7	850		
5/85	9.8	9.9	4,800	2,400	25.0	0.037		91			15.8	1.01	710		
10/85	9.8		2,550		22.0	2.0		70		<0.01	13.0	0.93	650		
7/88	9.5	9.6	2,000	2,050	5.5		0.10	90	0.076	<0.0015	7.05	0.514	449	0.025	0.012
1/95	8.6	8.5	1,500	1,250	3.1		<0.01	32	0.008	<0.01	1.3	0.27	270	<0.01	
5/97	9.0	9.2	1,500	1,318	3.5		<0.25	16	0.015	<0.0005		0.4	310	<0.01	<0.005
5/98	8.83	8.84	1,400	1,340	2.1		<0.01	18	0.007	<0.0005		0.17	300	<0.01	<0.005
5/98 (DUP)	8.83	8.84	1,400	1,340	1.3		<0.01	18	0.007	<0.0005		0.18	300	<0.01	<0.005
9/98	8.92	8.66	1,200	1,219	2.0		0.02	18	0.0089	<0.0005		0.16	240	<0.01	<0.005
1/99	8.95	8.93	1,100	1,175	1.8		0.14	17	0.0086	<0.0005		0.16	240	<0.01	<0.005
5/99	8.97	8.60	1,200	1,260	1.9		<0.01	16	0.0094	<0.0005		0.27	250	<0.01	<0.005
5/99 (DUP)	8.97	8.60	1,200	1,260	2.2		2.2	16	0.0097	<0.0005		0.25	240	<0.01	<0.005
9/99	8.78	9.10	1,100	1,030	2.4		0.10	17	0.0074	<0.0005		0.23	230	<0.01	<0.005
1/00	8.76	8.30	1,200	1,040	2.0		2.0	15	0.0063	<0.0005		0.24	180	<0.01	<0.005
1/00 (DUP)	8.77	8.30	1,100	1,040	1.9		1.9	16	0.006	<0.005		0.23	180	<0.01	<0.005
5/00	8.81	8.59	1,100	1,020	2.3		2.3	16	0.0082	<0.0005	1.8	0.37	110	<0.01	<0.005
10/00	8.71	8.59	1,000	817	2.6		2.6	11	0.006	<0.0005		0.35	120	<0.01	<0.005
10/00 (DUP)	8.71	9	1,000	817	2.5		2.5	11	0.0061	<0.0005		0.35	110	<0.01	<0.005
1/01	8.65	9.27	1,000	863	2.7		0.13	13	<0.004	<0.0005		0.72	190	<0.01	<0.005
1/01 (DUP)	8.65	9.27	1,000	863	2.8		0.33	14	<0.004	<0.0005		0.58	210	<0.01	<0.005
5/01	8.51	8.99	960	791	2.9		2.9	13	<0.004	<0.0005		0.66	170	<0.01	<0.005
9/01	8.42	8.69	708	970	3.6		0.34	11	<0.004	<0.0005		0.80	160	<0.01	<0.005
9/01 (DUP)	8.46	8.69	708	950	3.6		0.22	13	<0.004	<0.0005		0.80	170	<0.01	<0.005

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-7															
12/83	6.8	6.2	613	700	0.019	0.020		0.1			1.01	7.88	49.0		
2/84	5.9	5.9	581	750	<0.01			0.1			9.0	4.72	49.2		
9/84	5.8	5.7	410	680	<0.01	<0.01		<0.2			11.6	4.65	58.0		
5/85	6.1	5.6	720	890	0.023	0.021		<0.2			24.7	3.70	61.0		
6/88	5.7	5.8	740	760	0.02		0.01	0.2	0.012	<0.0015	17.6	3.05	64.2	0.0032	
1/95	5.5	5.3	850	1,500	<0.01		<0.01	0.2	0.040	<0.01	22	2.3	72	<0.01	
5/97	5.6	6.04	790	670	<0.01			0.10	0.038	<0.0005		2.2	89	<0.01	
5/97 (DUP)	5.7		800	670	<0.01			0.20	0.038	<0.0005		2.2	84	<0.01	
5/98	5.71	5.69	770	900	<0.01			0.20	0.051	<0.0005		2.2	78	<0.01	
5/99	5.81	6.00	780	700	<0.01			0.16	0.042	<0.0005		2.0	78	<0.01	
5/00	5.74	5.96	810	777	<0.01			0.14	0.041	<0.0005	18	2.0	93	<0.01	
5/01	5.69	5.27	770	771	<0.01			0.13	0.033	<0.0005		2.0	75	<0.01	
MW-8															
12/83	9.5	9.2	820	700	0.32	0.017		18			0.20	0.01	202		
2/84	9.5	9.5	820	700	0.14			18			0.23	0.04	199		
9/84	9.5	9.0	661	800	0.35	0.013		22			1.00	0.04	216		
5/85	9.2	9.2	830	550	0.11	0.024		7.9			0.21	0.01	151		
5/86	8.8		550		0.04						<0.01	<0.01	111		
6/88	8.4	8.3	560	550	0.06		<0.01	2.8	0.0018	<0.0015	0.044	0.023	67.8	<0.0026	<0.005
1/95	7.8	7.8	610	930	0.09		<0.01	3.1	<0.004	<0.01	<0.04	0.08	50	<0.01	
5/97	7.8	8.02	560	442	0.040		<0.01	2.2	<0.004	<0.0005		0.12	44	<0.01	
5/98	7.81	7.60	490	514	0.02		<0.01	2.3	<0.004	<0.0005		0.14	30	<0.01	
5/99	8.00	8.10	530	455	0.028		0.028	2.4	<0.004	<0.0005		0.15	34	<0.01	
5/00	7.91	8.01	600	533	0.026		0.026	2.2	<0.004	<0.0005	0.054	0.24	36	<0.01	
5/01	8.24	7.48	560	482	0.024		0.024	1.9	<0.004	<0.0005		0.26	34	<0.01	
MW-10															
12/83	7.7	7.6	1,205	1,280	1.36	0.083		6.9			0.60	0.26	195		
2/84	7.6	7.5	820	800	0.79			5.5			0.30	0.26	106		
9/84	7.6	6.5	547	675	0.22	0.14		4.3			0.13	0.34	88		
5/85	7.7	7.0	800	710	0.33	0.060		2.9			0.07	0.05	53		
6/88	7.3	7.2	770	750	<0.01		<0.01	2.1	0.0038	<0.0015	0.081	<0.001	28.7	<0.0026	
1/95	7.0	6.8	800	560	0.02		0.02	0.5	<0.004	<0.01	<0.04	<0.01	26	<0.01	
5/97	7.2	7.4	670	510	<0.01			0.70	<0.004	<0.0005		<0.01	25	<0.01	
5/98	7.22	7.23	970	1,110	0.15		0.01	0.60	<0.008	<0.0005		<0.01	120	<0.01	
5/99	7.40	7.32	750	545	<0.01			0.41	<0.004	<0.0005		0.012	30	<0.01	
5/00	7.45	7.51	650	549	<0.01			0.48	<0.004	<0.0005	0.079	<0.01	21	<0.01	
5/01	8.19	7.21	610	502	0.013		0.013	0.47	<0.004	<0.0005		<0.01	27	<0.01	
MW-11															
12/83	9.6	9.4	980	825	0.52	0.021		33			0.48	0.06	238		
2/84	9.6	9.5	962	775	0.25			27			7.9	0.37	232		
9/84	9.7	9.1	656	800	0.20	0.015		22			4.90	0.21	213		
5/85	9.4	9.5	750	650	0.30	0.026		13			2.68	0.13	181		
6/88	8.5	8.4	570	565	0.12		<0.01	4.9	0.0043	<0.0015	0.071	0.227	78.5	<0.0026	<0.005
1/95	7.6	7.9	540	680	0.02		<0.01	2.3	<0.004	<0.01	<0.04	0.40	30	<0.01	
5/97	7.8	7.64	530	404	0.09		<0.01	1.8	<0.004	<0.0005		0.42	33	<0.01	
5/98	7.84	7.57	490	507	0.02		<0.01	1.7	<0.004	<0.0005		0.45	31	<0.01	
5/98 (DUP)	7.85	7.57	500	507	0.02		<0.01	1.7	<0.004	<0.0005		0.43	29	<0.01	
5/99	8.07	8.39	490	425	0.024		0.011	1.7	<0.004	<0.0005		0.45	28	<0.01	
5/00	7.96	7.58	580	500	0.013		0.013	1.4	<0.004	<0.0005	0.046	0.54	32	<0.01	
5/01	7.84	7.26	550	458	<0.01			1.6	<0.004	<0.0005		0.52	35	<0.01	

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-12															
12/83	7.5	7.3	476	400	0.074	0.021		2.1			<0.01	0.94	24.3		
2/84	7.5	7.2	476	385	0.02			2.0			0.02	0.71	23.8		
9/84	7.7	6.3	366	375	<0.01	<0.01		2.2			<0.01	0.61	29.0		
5/85	7.7	7.4	540	390	0.024	0.022		1.6			<0.01	1.00	27.7		
5/86	7.5		494		<0.01						<0.01	1.23	27		
6/88	7.2	7.5	510	515	<0.01		<0.01	1.3	<0.0015	<0.0015	0.066	1.09	24.4	<0.0026	<0.005
1/95	7.4	7.6	530	350	<0.01		<0.01	1.1	<0.004	<0.01	<0.04	1.5	23	<0.01	
5/97	7.5	7.7	540	422	<0.01			0.90	<0.004	<0.0005		1.7	19	<0.01	
5/98	7.43	7.43	470	550	<0.01			0.80	<0.008	<0.0005		1.9	23	<0.01	
9/98	7.57	7.38	470	481	<0.01			0.92	<0.004	<0.0005		1.6	20	<0.01	
1/99	7.53	7.04	470	440	<0.01			0.89	<0.004	<0.0005		1.8	22	<0.01	
5/99	7.42	7.39	630	515	0.026		0.026	0.73	<0.004	<0.0005		2.5	29	<0.01	
9/99	7.54	7.25	530	565	0.017		0.012	0.68	<0.004	<0.0005		1.9	27	<0.01	
1/00	7.44	6.65	570	495	<0.01			0.74	<0.004	<0.0005		1.8	22	<0.01	
5/00	7.53	7.57	600	558	<0.01			0.73	<0.004	<0.0005	0.043	2.0	29	<0.01	
10/00	7.64	7.33	530	429	<0.01			0.83	<0.004	<0.0005		1.6	22	<0.01	
1/01	7.56	7.69	530	484	<0.01			0.92	<0.004	<0.0005		1.8	1.2	<0.01	
5/01	7.48	7.13	530	442	<0.01			0.82	<0.004	<0.0005		1.6	23	<0.01	
9/01	7.46	7.96	520	460	<0.01			0.83	<0.004	<0.0005		1.8	28	<0.01	
MW-15															
12/83	6.9	6.7	568	435	0.44	0.018		0.1			0.14	0.03	28.8		
2/84	6.9	6.7	550	435	0.51			0.1			0.13	<0.01	29.4		
5/85	7.4	6.8	590	445	0.44	0.034		0.3			0.18	<0.01	32.5		
5/86	7.1		550		0.39						0.15	<0.01	34		
7/88	7.0/7.1	7.1/7.1	610/630	600/600	0.43/0.32		0.10/<0.01	0.2/0.2	0.0045	0.0025	10.8	0.117	34.4	0.0059	<0.005
1/95	7.0	7.1	720	420	0.49		0.12	1.4	<0.004	<0.01	0.26	<0.01	45	<0.01	
7/96	6.8	7.07	570	613	1.0	<0.020		2.1	<0.004	<0.0005		<0.01		<0.01	
5/97	7.4	7.44	800	731	2.8		0.20	11	<0.004	<0.0005		0.02	140	<0.01	
5/97 (DUP)	7.4	7.44	800	731	3.3		0.40	8.9	<0.004	<0.0005		0.05	140	<0.01	
5/98	6.99	6.78	610	625	0.49		0.02	0.40	<0.004	<0.0005		<0.01	40	<0.01	
5/99	7.49	7.70	980	785	8.5		<0.01	15	<0.004	<0.0005		0.017	150	<0.01	
5/00	7.53	7.56	1,200	1,169	12		<0.01	25	<0.004	<0.0005	10	0.17	120	<0.01	
5/01	7.03	6.83	600	501	0.49		0.32	2.0	<0.004	<0.0005		0.017	51	<0.01	
MW-16															
12/83	9.8	9.9	2,092	1,800	7.35	0.034		110			12.4	0.91	530		
2/84	9.7	9.7	2,049	1,550	5.5			98			13.9	1.41	570		
9/84	9.8	9.2	1,390	10,500	2.11	<0.01		80			9.5	0.5	475		
5/85	9.4	9.0	2,300	1,400	10.0	0.11		72			10.3	1.09	443		
10/85	8.4		1,540		3.9	0.0		30		<0.01	2.10	0.41	186		
7/88	9.4	9.7	1,400	1,410	4.6		<0.01	61	0.063	<0.0015	6.57	0.22	300	0.018	0.006
1/95	7.7	9.0	850	930	1.4		0.13	7.9	<0.004	<0.01	0.52	1.1	81	<0.01	
7/96	7.3	7.75	990	941	1.6	<0.020		7.9	<0.004	<0.0005		1		<0.01	
5/97	7.6	7.6	980	801	1.3		0.3	11	<0.004	<0.0005		0.43	130	<0.01	
5/98	7.72	7.70	750	760	2.0		0.40	11	<0.004	<0.0005		1.2	80	<0.01	
9/98	7.70	7.50	860	790	1.4		1.4	9.5	<0.004	<0.0005		1.3	75	<0.01	
1/99	7.70	7.12	740	665	1.4		<0.04	9.8	<0.004	<0.0005		1.5	85	<0.01	
5/99	7.88	7.90	750	600	2.8		0.16	9.0	<0.004	<0.0005		1.5	82	<0.01	
9/99	7.62	8.15	730	745	2.9		0.88	8.2	<0.004	<0.0005		1.7	78	<0.01	
1/00	7.76	6.95	950	810	5.5		5.5	7.6	<0.004	<0.0005		2.2	68	<0.01	
1/00 (DUP)	7.77	6.95	940	810	5.8		5.8	7.8	<0.004	<0.005		2.2	70	<0.01	
5/00	7.69	7.53	1,100	945	12		12	7.9	<0.004	<0.0005	4.3	2.3	91	<0.01	
5/00 (DUP)	7.72	7.53	1,000	945	12		12	8.1	<0.004	<0.0005	4.4	2.4	91	<0.01	
10/00	7.74	7.67	1,000	774	16		<0.01	13	<0.004	<0.0005		1.6	130	<0.01	
10/00 (DUP)	7.77	7.67	1,000	774	15		<0.01	13	<0.004	<0.0005		1.7	130	<0.01	
1/01	7.84	7.42	1,200	939	16		3.2	24	<0.004	<0.0005		1.6	250	<0.01	
1/01 (DUP)	7.85	7.42	1,200	939	17		2.5	24	<0.004	<0.0005		1.6	250	<0.01	
5/01	7.89	8.04	1,100	920	12		12	39	<0.004	<0.0005		1.2	200	<0.01	
5/01 (DUP)	7.90	8.04	1,100	920	11		11	40	<0.004	<0.0005		1.2	210	<0.01	
9/01	7.91	7.86	1,300	754	9.7		0.85	43	<0.004	0.00058		0.89	270	0.013	
9/01 (DUP)	7.90	7.86	1,200	754	9.0		0.65	43	0.019	0.00096		1.1	260	0.021	

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-17															
12/83	7.9	7.6	613	475	0.99	0.021		5.6			0.44	1.38	78		
2/84	7.6	7.4	581	470	1.03			4.4			0.39	1.77	52		
9/84	8.0	6.7	485	550	0.17	<0.01		9.1			0.28	1.27	99		
5/85	7.9	7 9	610	470	0.76	0.045		4.1			0.28	1.80	45.3		
10/85	7.9		564		0.56	0.43		4.2		<0.01	6.80	1.93	43.4		
6/88	7.7	7.5	590	475	1.3		0.46	5.2	0.0054	<0.0015	0.973	1.72	39.7	<0.0026	<0.005
2/90	7.7	7.55	680	640	0.582		<0.005	4.1			18		40		
1/95	7.5	7.7	710	420	0.64		<0 01	3.9	<0.004	<0.01	0.26	1.9	36	<0.01	
5/97	7.5	7.67	870	488	0.54		<0.01	3.1	<0.004	<0.0005		1.9	30	<0.01	
5/98	7.6	7.40	570	580	0.72		0.09	3.4	<0.004	<0.0005		1.8	34	<0.01	
5/99	7.50	7.40	550	470	0.46		0.46	3.2	<0.004	<0.0005		1.8	31	<0.01	
5/99 (DUP)	7.37	7.40	550	470	0.49		0.49	3.2	<0.004	<0.0005		1.8	30	<0.01	
5/00	7.57	7.61	610	523	0.53		0.31	2.9	<0.004	<0.0005	0.34	1.8	24	<0.01	
5/01	7.87	7.36	570	460	0.50		0.50	3.0	<0.004	<0.0005		1.7	28	<0.01	
MW-18															
12/83	9.9	10.0	10,526	8,750	110.0	0.45		460			58.7	0.26	3,150		
2/84	9.8	9.8	9,615	7,500	52.0			350			61	0.50	2,750		
9/84	10.1	9.5	9,111	10,000	194	0.19		690			103	0.3	4,130		
5/85	9.8	9.9		7,000	35.2	0.091		410			64.2	0.35	2,540		
10/85	9.9		6,300		120	12		350		<0.01	71.4	1.06	1,940		
7/88	10.0	10.1	9,700	10,000	29		25	820	0.159	0.0071	144	1.75	2,640	0.191	0.022
2/90	10.0	10.1	8,000	11,400	67.0		10.5	710			110		3,500		
1/95	9.6	11.1	5,900	>2,000	15		6.6	290	0.062	<0.01	56	0.22	1,500	0.02	
7/96	9.1	8.67	4,300	4,200	7.2	<0.020		180	0.065	0.0006	56	0.19	1,500	0.01	0.006
5/97	9.7	9.58	4,000	4,110	8.7		<0.50	200	0.078	0.0009		0.29	1,100	0.02	
5/98	9.76	10.06	4200	4,300	9.8		0.40	260	0.094	0.0014		0.49	1100	0.05	0.024
9/98	9.70	9.88	3,600	3,590	5.9		<0.01	210	0.085	0.00084		0.29	800	0.022	0.014
1/99	9.67	10.04	3,600	3,450	79		3.0	210	0.088	0.00063		0.29	830	0.028	0.0219
5/99	9.72	9.80	3,000	3,000	95		81	370	0.088	0.0014		0.92	650	0.045	0.017
9/99	9.62	10.26	3,000	2,870	90		14	170	0.074	<0.0005		0.24	700	0.011	0.016
1/00	9.56	9.15	3,000	2,700	27		19	180	0.078	0.00059		0.26	680	0.017	0.020
5/00	9.59	9.73	2,800	2,270	84		75	160	0.075	0.00089	25	0.56	620	0.035	0.019
5/00 (DUP)	9.60	9.73	2,800	2,270	64		50	160	0.073	0.00062	20	0.33	620	0.023	0.016
10/00	9.54	9.67	2,400	1,948	29		<0.01	130	0.074	0.0024		2.1	400	0.08	0.012
1/01	9.62	10.82	2,500	1,980	53		9.2	170	0.067	0.0006		0.3	580	0.019	0.043
5/01	9.52	10.36	2,100	1,780	15		<0.50	100	0.065	0.0014		0.97	380	0.042	0.040
5/01 (Dup.)	9.52	10.36	2,000	1,780	49		49	110	0.079	0.0037		3.1	380	0.140	0.046
9/01	9.61	9.75	2,100	1,668	91		11	180	0.12	0.00099		0.3	520	0.024	0.027
MW-19															
12/83	7.2	7.1	581	435	0.068	0.013		0.3			<0.01	0.54	22.9		
2/84	7.1	6.8	575	405	0.04			0.5			0.05	0.26	20.2		
9/84	7.2	6.3	451	460	0.01	<0.01		0.4			0.02	0.04	23.5		
5/85	7.6	7.0	640	460	0.019	0.014		0.5			0.12	0.02	23.6		
7/88	7.3	7.3	630	600	<0.01		<0.01	0.5	0.0067	<0.0015	17.6	0.23	32.2	0.015	<0.005
2/90	7.3	7.27	520	560	0.2		<0.005	0.7					21.0		
1/95	7.3	7.2	630	410	<0.01		<0.01	1.0	<0.004	<0.01	0.09	<0.01	24	<0.01	
5/97	7.4	7.5	520	431	<0.01		<0.01	2.0	<0.004	<0.0005		<0.01	18	<0.01	
5/98	7.23	6.95	560	575	<0.01			1.4	<0.008	<0.0005		<0.01	23	<0.01	
5/99	7.47	7.40	570	460	<0.01			1.3	<0.004	<0.0005		<0.01	22	<0.01	
5/00	7.33	7.20	580	538	<0.01			1.2	<0.004	<0.0005	0.13	<0.01	16	<0.01	
5/01	7.18	6.96	580	494	<0.01			1.1	<0.004	<0.0005		<0.01	20	<0.01	

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-28															
5/86	5.5		382		0.89	0.08		<0.1			0.36	0.02	41		
6/88	5.7	5.8	640	665	7.4		0.6	<0.1	<0.0015	<0.0015	2.41	0.035	83.3	<0.0026	<0.005
1/95	6.2	7.4	500	700	0.74		0.26	2.7	<0.004	<0.01	0.38	0.02	79	<0.01	
7/96	5.7	5.92	440	429	0.26	<0.020		0.50	<0.004	<0.0005		0.01		<0.01	
5/97	5.6	6.4	590	453	0.11		<0.02	0.2	<0.004	<0.0005		0.01	62	<0.01	
5/98	5.74	5.32	500	550	0.12		<0.01	0.20	<0.004	<0.0005		0.01	65	<0.01	
9/98	5.81	5.28	540	527	0.11		0.11	0.27	<0.004	<0.0005		0.011	64	<0.01	
9/98 (DUP)	5.83	5.28	540	527	0.11		0.11	0.24	<0.004	<0.0005		0.01	65	<0.01	
1/99	5.72	5.17	470	450	0.087		0.027	0.38	<0.004	<0.0005		0.013	67	<0.01	
5/99	5.72	5.43	460	405	0.13		0.13	0.35	<0.004	<0.0005		0.011	70	<0.01	
9/99	5.95	6.15	480	480	0.12		0.016	0.26	<0.004	<0.0005		<0.01	57	<0.01	
1/00	6.04	5.25	460	410	0.23		0.22	0.35	<0.004	<0.0005		<0.01	58	<0.01	
5/00	5.89	5.90	470	464	1.0		1.0	0.30	<0.004	<0.0005	0.69	0.014	77	<0.01	
10/00	5.85	5.47	460	384	0.96		0.28	0.27	<0.004	<0.0005		0.014	52	<0.01	
1/01	5.75	5.45	460	412	0.9		0.9	0.32	<0.004	<0.0005		0.015	64	<0.01	
5/01	5.65	5.20	420	391	1.1		0.36	0.22	<0.004	<0.0005		0.014	54	<0.01	
9/01	5.70	6.01	430	415	1.3		<0.1	0.56	<0.004	<0.0005		0.015	64	<0.01	
MW-29S															
5/86	8.4		2,350		1.5	0.02		28			0.64	0.08	590		
6/88	9.0	9.0	1,100	1,090	0.99		0.37	44	0.0052	<0.0015	1.52	0.094	224	0.0044	<0.005
1/95	8.3	10.0	2,900	1,750	0.79		0.07	56	<0.004	<0.01	0.37	0.12	590	<0.01	
5/97	8.3	8.43	2,200	1,735	0.6		<0.1	44	<0.004	<0.0005		0.14	410	<0.01	
5/98	8.64	8.70	1,700	1,665	0.18		<0.01	26	<0.004	<0.0005		0.09	370	<0.01	
5/99	8.35	8.37	1,300	1,090	0.22		0 021	16	<0.004	<0.0005		0.30	230	<0.01	
5/00	8.11	8.11	1,200	1,023	0.17		0.17	16	0.0057	<0.0005	0.14	0.41	130	<0.01	
5/01	7.89	7.54	1,000	828	0.16		0.16	16	<0.004	<0.0005		0.42	160	<0.01	
MW-29D															
5/86	8.6		648		0.31	0 01		9.7			0.18	0.26	139		
6/88	8.1	8.0	590	570	0.25		<0.01	4.2	0.002	<0.0015	0.082	1.16	60.4	<0.0026	<0.005
1/95	7.5	8.9	650	770	0.22		0.03	3.7	<0.004	<0.01	0.09	2.0	33	<0.01	
5/97	7.7	7.9	600	479	0.18		<0.02	3.3	<0.004	<0.0005		2	31	<0.01	
5/98	7.65	7.53	550	560	0.17		<0.01	3.5	<0.004	<0.0005		1.8	28	<0.01	
5/99	7.82	7.60	550	465	0.19		0.19	3.4	<0.004	<0.0005		1.8	28	<0.01	
5/00	7.75	7.66	590	503	0.15		0.15	3.1	<0.004	<0.0005	0.12	1.9	24	<0.01	
5/01	7.55	6.82	570	489	0.15		0.15	3.1	<0.004	<0.0005		1.8	27	<0.01	
MW-30															
5/86	6.6		342		0.01	<0.01		0.5			<0.01	2.10	20		
6/88	6.3	6.3	340	400	0.01		<0.01	<0.1	0.0018	<0.0015	4.42	0.753	18.7	0.0044	0.005
1/95	6.2	6.0	430	570	0.01		<0.01	<0.1	<0.004	<0.01	0.78	0.60	19	<0.01	
5/97	6.2	6.47	420	334	<0.01			<0.1	<0.004	<0.005		0.6	18	<0.01	0.012
5/98	6.19	5.70	390	418	<0.01			0.10	<0.004	<0.0005		0.68	21	<0.01	0.013
5/99	6.43	6.10	400	390	0.016		0.013	0.19	<0.004	<0.0005		0.71	21	<0.01	0.02
5/00	6.34	5.91	430	380	0.026		0.026	0.12	<0.004	<0.0005	1.5	0.70	21	<0.01	0.017
5/01	6.14	6.21	420	409	0.79		0.79	0.17	<0.004	<0.0005		0.54	19	<0.01	0.015
MW-31															
5/86	9.1		1,250		12	1.5		46			84.5	3.67	380		
6/88	10.2	10.5	3,400	3,500	39		<0.01	140	0.046	<0.0015	20.3	1.93	703	0.184	0.040
2/90	10.0	9.95	2,300	2,700	4.80		3.94	110			49		660		
1/95	9.6	10.4	1,900	1,600	7.1		<0.01	89	0.027	<0.01	4.6	0.66	420	<0.02	
7/96	9.5	9.52	2,300	2,100	12	<0.020		91	0.042	0.0007		0.62		0.04	0.041
5/97	9.9	9.69	2,500	2,100	12		<0.50	110	0.04	0.0007		0.68	480	0.05	0.028
5/97 (DUP)	9.9	9.69	2,500	2,100	6.2			93	0.038	0.0008		0.74	480	0.05	0.029
5/98	9.63	9.80	2,400	2,350	9.3		<0.01	100	0.036	0.0013		1.1	490	0.04	0.022
9/98	9.67	9.86	2,600	2,520	9.8		<0.01	120	0.044	0.0014		1.1	620	0.045	0.017
9/98 (DUP)	9.67	9.86	2,700	2,520	9.5		<0.01	130	0.045	0.0013		1.1	600	0.043	0.020
1/99	9.72	9.97	2,500	2,240	22		0.63	120	0.047	0.0012		1.3	620	0.065	0.019
5/99	9.91	10.02	2,600	2,510	29		6.5	130	0.06	0.0014		1.2	600	0.07	0.034
9/99	9.83	10.03	2,600	2,810	30		4.3	150	0.063	0.0011		1.6	750	0.088	<0.005
1/00	9.98	9.80	2,900	2,600	24		6.3	150	0.072	0.001		1.4	650	0.120	0.028
5/00	10.1	10.10	2,900	2,400	21		1.7	140	0.096	0.0011	13	1.6	820	0.12	0.020
10/00	9.99	10.18	2,800	2,550	20		0.54	140	0.056	0.00076		1.1	480	0.079	0.043
1/01	10.1	11.21	2,100	1,900	13		1.5	110	0.056	0.001		1.3	560	0.11	0.020
5/01	9.93	10.85	2,100	1,866	12		12	77	0.046	0.0012		1.4	430	0.081	0.027
9/01	9.95	9.98	2,300	1,877	16		1.2	110	0.054	0.0014		1.4	590	0.09	0.032

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-32															
5/86	10.5		6430		97	18		369			27.4	0.69	2120		
7/88	9.2	9.3	890	1,040	7.2		0 30	39	0.014	<0.0015	4.05	0.513	234	0.024	<0.005
1/95	9.4	9.4	1,300	630	12		3.6	47	0.014	<0.01	2.7	0.37	230	0.03	
7/96	8 6	8.89	1,000	1,038	6.9	<0.020		29	0.011	<0.0005		0.84		0.01	
5/97	8.7	8.71	930	697	4.4		1.3	19	0.008	<0.0005		1.1	110	<0.01	
5/98	8.03	8.10	630	697	2.5		0.34	7.7	<0.004	<0.0005		1.9	61	<0.01	
5/98 (DUP)	8.05	8.10	690	697	2.5		0.09	8.0	<0.004	<0.0005		2.0	68	<0.01	
9/98	8.30	8.26	760	760	4.5		1.0	13	<0.004	<0 0005		1.8	78	<0.01	
1/99	8.39	8.00	710	650	3.1		<0.02	13	<0.004	<0.0005		1.7	77	<0.01	
1/99 (DUP)	8.39	8.00	720	650	3.7		<0.02	13	<0.004	<0.0005		1.7	76	<0.01	
5/99	8.38	8.50	690	555	4.4		0.59	12	<0.004	<0.0005		2.0	78	<0.01	
9/99	9.84	10.01	2,200	2,300	18		1.8	120	0.057	0.0014		2.2	520	0.093	
1/00	8.93	8.28	950	770	4.8		0.57	27	0.017	<0.0005		1.9	97	0.024	
5/00	8.80	8.95	830	858	3.9		<0.01	19	0.013	<0.0005	3.1	1.6	70	<0.01	
10/00	9.75	9.98	1,500	1,227	8.3		0.76	70	0.051	0.00099		1.6	290	0.058	
1/01	8.46	9.24	740	675	4.3		0.82	13	0.004	<0.0005		2.0	95	<0.01	
5/01	8.51	8.84	790	624	4.9		4.9	17	0.0054	<0.0005		2.1	94	0.012	
9/01	8.69	8.74	720	606	4.9		0.53	99	0.0088	<0.0005		1.9	110	0.011	
MW-34S															
5/86	7.4		668		0.13	<0.01		9.4			0.07	0.42	64		
7/88	7.2	7.2	690	670	40		38	7.3	0.0087	<0.0015	14.6	0.416	33.1	0.018	<0.005
2/90	7.4	6.93	690	740	0.113		0.26	6.5			21		49		
1/95	7.2	7.1	700	430	0.03		<0.01	7.3	<0.004	<0.01	0.18	0.01	35	<0.01	
5/97	7.4	7.43	710	579	0.18		0.04	8.1	<0.004	<0.0005		0.04	69	<0.01	
5/98	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
5/99	7.34	7.55	650	505	0.19		<0.01	6.8	<0.004	<0.0005		0.014	46	<0.01	
5/00	7.60	7.46	740	607	1.1		1.1	11	<0.004	<0.0005	1.2	0.044	83	<0.01	
5/01	7.71	7.34	670	537	0.12		0.12	8.6	0.025	0.0019		2.9	50	0.054	
MW-34D															
5/86	7.3		602		0.05	<0.01		10.2			0.02	0.55	42		
7/88	7.4	7.4	560	580	0.07		<0.01	4.4	0.0031	<0.0015	0.538	0.762	32.4	<0.0026	<0.005
1/95	7.3	7.4	640	400	0.07		0.07	4.2	<0.004	<0.01	<0.04	0.82	34	<0.01	
5/97	7.4	7.43	630	492	0.05		<0.01	3.6	<0.004	<0.0005		0.79	31	<0.01	
5/98	7.37	7.23	590	595	0.09		0.01	3.9	<0.004	<0.0005		0.68	35	<0.01	
5/99	7.40	7.52	470	475	0.062		<0.01	3.6	<0.004	<0.0005		0.72	29	<0.01	
5/00	7.55	7.37	620	519	0.063		0.063	4.2	<0.004	<0.0005	0.14	0.76	28	<0.01	
5/01	8.00	7.16	600	453	0.13		0.13	3.9	<0.004	<0.0005		0.70	30	<0.01	
MW-35															
5/86	10.2		6,430		240	38		358			125	1.76	2,070		
7/88	10.2	10.4	6,100	6,150	43		41	400	0.147	0.002	56.5	0.337	1,630	0.053	<0.005
2/90	9.6	9.7	1,500	1,540	8.0		<0.005	71			20		350		
1/95	9.5	9.7	1,200	562	16		<0.01	35	0.018	<0.01	11	0.43	220	<0.01	
7/96	9.5	9.5	1,700	1,851	6.0	0.040		71	0.028	0.0006		0.5		0.03	
5/97	9.4	9.47	1,000	900	16		<1.0	40	0.02	0.0006		0.68	220	0.02	
5/98	8.93	9.10	710	766	15		2.9	27	0.012	<0.0005		0.92	140	0.01	
9/98	8.97	8.90	550	778	16		0.99	26	0.01	<0.0005		0.88	130	<0.01	
1/99	9.28	9.15	820	925	23		2.9	40	0.019	<0.0005		0.81	190	0.016	
5/99	9.35	9.70	830	870	28		10	38	0.013	<0.0005		0.86	160	0.015	
9/99	9.18	9.60	790	930	18		2.0	34	0.012	<0.0005		0.53	170	0.05	
1/00	8.91	8.15	610	500	13		3.3	21	0.0077	<0.0005		0.47	94	0.068	
5/00	9.07	9.24	690	693	27		20	28	0.081	<0.0005	5.2	0.48	69	0.077	
10/00	8.76	8.84	520	470	7.3		0.59	17	0.0076	<0.0005		0.57	81	0.11	
1/01	8.86	9.59	530	549	10		3.1	19	0.008	<0.0005		0.50	89	0.075	
5/01	9.17	9.43	800	790	17		2.6	35	0.013	<0.0005		0.48	130	0.04	
9/01	9.26	9.03	820	749	15		<0.5	41	0.0097	<0.0005		0.46	120	0.062	

Note: All results in mg/L unless otherwise noted.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-36															
5/86	9.7		2,700		25	1.4		97			39.5	1.13	760		
7/88	8.9	9.6	940	1,255	8.6		1.3	18	0.0078	<0.0015	3.52	0.332	161	0.0063	<0.005
1/95	9.8	9.7	3,500	1,350	18		<0.01	160	0.034	<0.01	8.7	0.83	770	0.07	
7/96	9.6	9.55	3,300	3,280	8.1	<0.020		160	0.058	0.0021		0.67		0.07	
5/97	9.8	9.64	3,600	3,290	9.2		3.5	180	0.084	0.0035		1.7	850	0.1	
5/98	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS	NS
9/98	9.90	10.10	4,500	4,380	6.5		0.03	230	0.11	0.0036		1.4	990	0.074	
1/99	9.76	10.20	3,500	3,300	41		1.2	190	0.076	0.0036		1.5	820	0.072	
5/99	10.10	10.40	2,500	2,260	19		4.4	150	0.12	0.0019		1.3	600	0.12	
9/99	10.10	10.10	1,800	1,790	6.2		0.69	93	0.059	0.00055		1.2	420	0.067	
9/99 (DUP)	10.10	10.10	1,800	1,790	6.3		<0.5	96	0.061	0.00062		1.2	450	0.07	
1/00	10.2	9.80	1,600	1,450	3.9		0.51	80	0.072	<0.0005		0.70	290	0.082	
5/00	10.2	10.42	1,200	1,272	1.6		<0.01	50	0.03	<0.0005	4.0	0.54	150	0.03	
10/00	9.84	10.05	1,200	1,043	4.9		<0.01	41	0.024	0.00061		1.6	210	0.033	
1/01	9.79	11.00	1,700	1,567	12		2.0	89	0.027	0.0018		1.4	450	0.049	
5/01	9.87	10.28	1,100	1,109	3.0		3.0	49	0.029	0.00054		0.68	220	0.045	
9/01	9.80	9.75	1,100	960	2.7		<0.25	44	0.018	0.00053		0.59	210	0.026	
MW-37															
5/86	10.1		7,340		97	8.2		890			498	46.3	1,800		
7/88	9.9	9.8	5,600	5,500	0.30		<0.01	1000	0.169	0.035	115	15.4	1,470	0.369	<0.005
2/90	9.6	9.65	2,700	3,100	4.6		22.7	360			1000		970		
1/95	9.1	9.2	1,200	970	18		<0.01	87	0.033	<0.01	8.5	0.58	280	0.01	
7/96	9.1	8.89	570	832	14	<0.020		45	0.042	0.0005		0.51		0.03	
5/97	9.2	9.07	1,100	846	13		1.7	53	0.027	<0.0005		0.56	210	0.02	
5/98	8.57	8.30	530	505	6.4		<0.01	6.8	0.018	<0.0005		0.28	120	0.02	
9/98	8.90	8.26	670	682	15		5.5	52	0.020	<0.0005		0.53	140	0.017	
1/99	9.02	9.25	660	750	19		<0.10	25	0.02	<0.0005		0.68	140	0.029	
5/99	9.39	9.45	610	540	11		3.6	22	0.023	<0.0005		0.23	130	0.016	
9/99	8.78	8.91	760	753	7.9		0.91	31	0.01	<0.0005		0.33	170	<0.01	
1/00	8.83	8.40	880	822	10		2.2	32	0.011	<0.0005		0.49	110	<0.01	
5/00	8.51	8.89	770	765	5.2		0.93	32	0.015	<0.0005	9.0	0.72	92	<0.01	
10/00	8.39	8.46	750	630	6.6		<0.01	17	0.0089	<0.0005		0.61	79	<0.01	
1/01	8.42	8.99	780	678	8.8		2.7	29	0.02	0.00088		1.5	160	0.035	
5/01	7.89	7.97	650	528	7.9		<0.01	10	0.018	0.00075		2.0	110	0.026	
9/01	7.84	7.54	680	590	5.6		<0.5	21	0.0042	<0.0005		3.0	110	0.011	
MW-39S															
5/86	9.5		8,360		11	2.9		244			25.0	1.35	2780		
6/88	9.3	9.1	3,500	2,550	3.8		0.10	110	0.016	<0.0015	36.6	1.63	826	0.053	<0.005
1/95	8.9	8.7	2,700	900	0.64		<0.01	59	<0.004	<0.01	0.36	0.22	520	<0.01	
5/97	8.9	9.2	5,500	5,500	3.6		<0.2	150	0.009	<0.0005		0.15	1300	<0.01	
5/98	9.04	9.09	4,000	4,000	2.3		<0.01	98	0.009	<0.0005		0.11	700	<0.01	
5/99	9.05	9.30	4,300	3,620	3.4		0.24	120	0.0096	<0.0005		0.12	950	<0.01	
5/99 (DUP)	9.05	9.30	4,200	3,620	3.6		0.89	120	0.009	<0.0005		0.11	1,100	<0.01	
5/00	9.18	9.19	4,500	3,870	3.5		3.5	110	0.013	<0.0005	2.3	0.097	1,100	<0.01	
5/01	8.91	9.38	3,700	2,820	2.0		0.86	97	0.011	<0.005		0.22	880	0.015	
MW-39D															
5/86	8.1		627		0.21	0.02		7.4			0.14	0.54	103		
6/88	7.9	7.8	590	595	0.17		0.03	6.1	0.0021	<0.0015	0.36	0.681	53.9	<0.0026	<0.005
1/95	7.5	7.6	630	410	0.07		<0.01	3.9	<0.004	<0.01	0.06	0.87	36	<0.01	
5/97	7.5	7.66	630	457	0.06		0.06	3.8	<0.004	<0.0005		0.87	32	<0.01	
5/98	7.52	7.35	590	560	0.04		<0.01	3.6	<0.004	<0.0005		0.77	34	<0.01	
5/99	7.59	7.64	540	447	0.037		<0.01	3.4	<0.004	<0.0005		0.87	33	<0.01	
5/00	7.68	7.60	580	503	0.027		0.027	3.2	<0.004	<0.0005	0.13	0.90	29	<0.01	
5/01	7.50	7.83	550	423	0.024		0.024	3.1	<0.004	<0.0005		0.78	32	<0.01	
MW-40S															
5/86	8.9		2,550		1.7	0.03		28			12.8	0.49	650		
6/88	9.2	9.2	2,100	2,200	1.5		<0.01	5.9	0.018	<0.0015	1.89	0.139	445	0.0056	<0.005
1/95	7.9	7.9	2,500	1,600	0.87		<0.01	40	<0.004	<0.01	0.36	0.33	470	<0.01	
5/97	7.9	8.07	1,900	1,417	0.72		0.40	21	<0.004	<0.0005		0.66	380	<0.01	
5/98	8.2	8.18	1,400	1,335	0.36		<0.01	39	<0.004	<0.0005		0.13	270	<0.01	
5/99	8.50	8.83	1,300	1,100	0.32		<0.01	30	<0.004	<0.0005		0.11	250	<0.01	
5/00	8.08	8.04	1,100	900	0.25		0.25	14	<0.004	<0.0005	0.19	0.42	110	<0.01	
5/01	8.10	7.61	950	693	0.25		0.25	13	<0.004	<0.0005		0.57	140	<0.01	

Note: All results in mg/L unless otherwise noted.

NS = Not sampled. Well damaged during remedial construction.

TABLE 4 (CONT.)
SUMMARY OF ANALYTICAL RESULTS FOR REMEDIAL ACTION
GROUND-WATER MONITORING WELLS AND PARAMETERS

ORMET CORPORATION
HANNIBAL, OHIO

	pH (lab)	pH (field)	Specific Conductance (lab)	Specific Conductance (field)	Cyanide Total	Cyanide Free	Cyanide Amenable	Fluoride	Arsenic	Beryllium	Iron	Manganese	Sodium	Vanadium	Tetrachloroethene
MW-40D															
5/86	9.4		1,120		7.4	0.06		20			11.7	0.62	280		
6/88	9.4	9.4	1,200	1,290	7.0		<0.01	36	0.018	<0.0015	7.81	0.454	258	0.012	<0.005
1/95	7.6	7.7	2,000	1,375	0.70		<0.01	16	<0.004	<0.01	0.29	0.74	340	<0.01	
5/97	7.6	7.9	1,800	1,350	0.59		<0.1	7.6	<0.004	<0.0005		1.3	340	<0.01	
5/98	7.85	7.73	1,300	1,250	0.49		0.47	19	<0.004	<0.0005		0.36	250	<0.01	
5/99	7.99	8.25	920	745	0.16		0.16	12	<0.004	<0.0005		0.42	150	<0.01	
5/00	7.88	7.84	960	810	0.25		0.25	11	<0.004	<0.0005	0.16	0.69	97	<0.01	
5/01	8.01	7.45	790	611	0.15		0.15	8.6	<0.004	<0.0005		0.90	78	<0.01	
MW-41															
1/95	6.6	8.2	490	600	0.04		0.02	0.2	0.017	<0.01	8.9	1.3	22	<0.01	
5/97	6.8	6.98	490	357	<0.01			0.20	0.022	<0.0005		1.6	21	<0.01	
5/98	6.67	6.74	420	449	<0.01			0.30	0.016	<0.0005		1.3	21	<0.01	
5/99	6.79	6.80	420	370	<0.01			0.33	0.014	<0.0005		1.1	20	<0.01	
5/00	6.79	6.96	430	424	<0.01			0.25	0.016	<0.0005	9.2	1.1	17	<0.01	
5/01	6.70	7.00	450	421	<0.01			0.34	0.015	<0.0005		1.0	19	<0.01	
MW-42S															
6/88	8.0	8.4	930	870	0.70		0.25	14.0	0.002	<0.0015	0.232	0.237	143	0.0027	<0.005
2/90	8.4	8.25	2,100	2,400	0.266		0.079	35.0			0.88		520		
1/95	8.2	8.4	1,600	765	0.45		<0.01	22	<0.004	<0.01	0.2	0.35	280	<0.01	
5/97	8.2	8.57	1,700	1,350	0.56		<0.02	29	<0.004	<0.0005		0.33	300	<0.01	
5/98	8.26	8.46	1,400	1,460	0.52		<0.01	27	<0.004	<0.0005		0.37	270	<0.01	
5/99	8.19	8.54	1,500	1,100	0.54		0.033	26	<0.004	<0.0005		0.49	260	<0.01	
5/00	8.19	8.18	1,900	1,530	0.66		0.66	28	<0.004	<0.0005	0.39	0.65	280	<0.01	
5/01	8.03	8.03	1,700	1,208	0.51		0.062	23	<0.004	<0.0005		0.84	300	<0.01	
MW-42D															
6/88	7.9	8.1	550	600	0.16		<0.01	6.0	0.0028	<0.0015	1.11	0.636	68.6	0.0028	<0.005
1/95	7.5	7.7	640	410	0.04		<0.01	3.6	<0.004	<0.01	0.08	1.5	31	<0.01	
5/97	7.6	7.99	580	468	0.04		<0.01	3.2	<0.004	<0.0005		1.3	27	<0.01	
5/98	7.54	7.64	550	535	0.07		0.01	3.3	<0.008	<0.0005		1.2	26	<0.01	
5/99	7.56	7.83	530	435	0.03		<0.01	3.4	<0.004	<0.0005		1.3	26	<0.01	
5/00	7.73	7.74	580	490	0.027		0.027	3.0	<0.004	<0.0005	0.053	1.3	24	<0.01	
5/01	7.53	7.68	550	462	0.023		0.023	3.1	<0.004	<0.0005		1.3	32	<0.01	

Note: All results in mg/L unless otherwise noted.

HM03-01/DATA-SUM.123