NE ¼ SEC. 11 T. 27 R. 11

H

W E

S

SPECIFY OIL, GAS, OR DRY

8-635a

DEPARTMENT OF THE INTERIOR
OFFICE OF INDIAN AFFAIRS
FINAL REPORT OF COMPLETED OR DEEPENED WELL
FOR LANDS COVERED BY DEPARTMENTAL LEASES

MISCELLANEOUS
RECEIVED
APR 10 1925
NO. 9466
OSAGE AGENCY

This report must be filed within Ten Days after well is shot or producing entered. Use this form for Supplemental Report on Wells pumped back.

COMPANY OPERATING Phillips Pet. Co ADDRESS Bartlesville, Oklahoma

LESSEE Phillips Pet. Co LESSOR M. S. Norman (Osage Tribe of Indians)

WELL No. 11 NE ¼ SEC. 11 T. 27 R. 11 OSAGE COUNTY

Well located 981' from north line; 979' from east line Ft. N.-S. of and Ft. E.-W. of Elevation 1132.3 G.R. (Derrick floor, relative to sea level)

Well drilled by Chas Meade, Tulsa, Oklahoma Superintendent A. R. Edmondson

Date commenced drilling 3-16-25 , 19 Finished 4-2-25 , 19

Date commenced deepening , 19 Finished , 19

Casing used in drilling: Length	Size	Wt. per ft.	Thread	Casing left in hole: Length	Landed at	Length	Shoe: Make	Packers: Kind	Length	Set at
12 Ft.	20	90 Lbs.	Per in.	12 Ft.	Ft.	Ft.			Ft.	Ft.
883' 6" Ft.	L.T. 15½	70 Lbs.	Per in.	Ft.	Ft.	Ft.			Ft.	Ft.
1208' 5" Ft.	L.T. 12½	50 Lbs.	Per in.	Ft.	Ft.	Ft.			Ft.	Ft.
1456 Ft.	L.T. 10	40 Lbs.	Per in.	79'2" Ft.	Ft.	Ft.			Ft.	Ft.
2330'11" Ft.	L.T. 8½	25 Lbs.	Per in.	2330'11" Ft.	Ft.	Ft.			Ft.	Ft.
2801'11" Ft.	S.L. 6-5/8	24 Lbs.	Per in.	2801'11" Ft.	Ft.	Ft.			Ft.	Ft.

What was done to protect sands when outside casing was pulled?

Is water completely shut off? Amount water with oil per cent. Is oil cut

Oil—Initial 24-hr. production 0 bbls. Initial 24-hr. production after shot 150 bbls. Shot from 2952-3007, size 6"x4" qts. 140

Tubing

Gas—Initial open flow sand from ft. to ft. Cu. ft. rock pressure lbs. per sq. in.

Initial open flow sand from ft. to ft. Cu. ft. rock pressure lbs. per sq. in.

Dry Hole—State what steps have been taken to plug.

Location fee paid Date Amount, $

Phillips Pet. Co paid $100.00 location bonus to Geo. N. Wise 1/28/25

Remarks

Soft grey sand. Reduced 2941- Sandy shale 2946. Small show of gas at 2946-½ mi. 2953. Show of oil, good at 2968'. Dark gray sand 2946-2952. Dark brown sand 2952-2957. Light brown 2957-2980. Light gray 2980-2988 Light brown 2988-3005. Gray 3002-3005. Dark gray broken 3005-3007. Steel line 3007 total depth.