8-17-95
12.3.8 v.6

Overlake Oil

P.O. Box 506 Kirkland WA 98083-0506
206-822-1776 800-PAC-PRIDE
206-827-5791 FAX 800-722-7743

Shell Oil Fuel and Lubricating Products

PACIFIC PRIDE

An independent franchisee of PACIFIC PRIDE — The Commercial Fueling System

FAX COVER LETTER

DATE: August 17 1995

ATTENTION: Jerry

COMPANY: Ash Grove Cement

FROM: Kathy

FAX NUMBER: 206-623-5355

NUMBER OF COPIES: 5
(Including Cover)

COMMENTS: Hope this will help you!
Have a Great Day!

USEPA SF
1279417

AGC2G000093

The State CHEMICAL MANUFACTURING CO.

MATERIAL SAFETY DATA SHEET

STATE 999

Description:

A formulated water-based all purpose cleaner

I. SHIPPING INFORMATION

D.O.T. Shipping Name: N/A
D.O.T. Hazard Class: N/A
D.O.T. ID No: N/A
D.O.T. Label: N/A

II. HAZARDOUS INGREDIENTS

Material	Weight %	TLV
2-butoxyethanol (CAS #111-76-2)	< 4%	25 ppm (skin)
Trisodium Phosphate (CAS #10101-89-0)	< 5%	N/A
Sodium Metasilicate (CAS #6834-92-0)	< 3%	N/A
Nitrilotriacetic Acid, Trisodium Salt (CAS #18662-53-8)	< 3%	N/A

This product contains 2-butoxyethanol (glycol ether) which is a toxic chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a substance known to the State of California to cause cancer.

All components of this product are listed on the TSCA inventory

III. PHYSICAL DATA

Boiling Point(F°): 216°F
Specific Gravity(Water=1): 1.080 +/- 0.003
Volatile By Weight(%): APPROX. 84
Weight Per Gallon(pounds): 9.04 lbs.
Solubility In Water: Complete.
pH: 12.5
Appearance & Odor: A clear blue liquid with bouquet odor.

IV. FIRE & HAZARD DATA

Flashpoint (Method Used): None to 200°F (C.O.C. & T.C.C.)
Extinguishing Media: N/A
Special Fire Fighting Procedures: None
Unusual Fire & Explosion Hazards: None

V. HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: May be harmful if swallowed. Direct eye contact will cause mild irritation.
CHRONIC EFFECTS: Based on tests with laboratory rats and mice, the National Toxicology Program (NTP) lists nitrilotriacetic acid (NTA) as a suspect carcinogen. There is no evidence that NTA is a human carcinogen. Chronic exposure to 2-butoxyethanol can cause blood abnormalities; lung, liver, kidney or central nervous system damage.

FIRST AID PROCEDURES:

If Swallowed: Contact a physician or poison control center immediately.
If Inhaled: N/A
If In Eyes: Flush eyes immediately with plenty of cool water for at least 15 minutes. If irritation persists, contact a physician.
If on Skin: Flush with water

VI. REACTIVITY DATA

Stability: Stable.
Conditions to avoid: Application through a steam cleaner.
Incompatibility(Materials to avoid): None
Hazardous Decomposition Products: Exposure to high temperatures may produce carbon dioxide, carbon monoxide, water and traces of oxide of phosphorous and aliphatic compounds.

HAZARDOUS POLYMERIZATION WILL NOT OCCUR

VII. SPILL OR LEAK PROCEDURES

Steps To Be Taken If Material Is Released Or Spilled: Flush with plenty of water.
Waste Disposal Method: Do not reuse empty containers for any purpose. Flush thoroughly with water, crush or perforate and discard, or give rinsed drums to a drum reconditioner for recycling. Be sure pH of waste stream is below 12.5. If this is true, dispose of as a nonhazardous waste.
Follow All Federal, State and Local Regulations Regarding Waste Disposal.

VIII. SPECIAL PROTECTION INFORMATION

Eye protection and protective gloves are recommended any time you work wi any concentrated industrial strength products.

Respiratory Protection: No special protection required.
Ventilation: Normal ventilation is adequate.
Protective Gloves: Recommended.
Eye Protection: Recommended.
Other Protective Equipment: An eyewash station or source of clean water should be nearby in case of accidental eye contact.

IX. SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storage: Avoid temperatures below freezing. Keep containers tightly closed when not in use.

OTHER PRECAUTIONS: CAUTION: Avoid contact with eyes. If accidentally splashed in the eyes, immediately flush with plenty o water for at least 15 minutes. If irritation persists, seek medical attention. Do not reuse any empty containers for any purpose. NOTE: A cleaning solution too concentrated can have a dulling e on certain paints and inexpensive-grade varnishes. It is recommended to try the cleaning solution first on a small area b using.
HMIS/NFPA RATINGS: Health 2 Flammability 1
Reactivity 0

Read and follow all label directions and precautions before using the pr These products are intended for industrial and institutional use only.

NOT FOR HOUSEHOLD USE OR RESALE. KEEP OUT OF THE REACH OF CHILDREN

While we believe that the data contained herein is factual and that opin expressed are those of qualified experts, the data are not to be taken warranty or representation for which the company assumes legal responsibility. They are offered solely for your consideration, investi and verification. Any use of these data and information must be deta the user to be in accordance with applicable Federal, State, and Loca and regulations.

HEALTH AND SAFETY INFORMATION
(216) 851-7114

NOVEMBER 1994