MATERIAL SAFETY DATA SHEET

****

SECTION I - COMPANY AND PRODUCT INFORMATION

****

MANUFACTURER:
Tec Laboratories, Inc.
7100 Tec Labs Way SW
Albany, OR 97321

EMERGENCY TELEPHONE NUMBERS:
(541) 926-4577
24 Hour Emergency Assistance
1-800-535-5053

PRODUCT DESCRIPTION:
Cleanser for removal of poison plant oils.

PRODUCT NAME:
Tecnu® Outdoor Skin Cleanser

CHEMICAL FAMILY:
Detergent

CAS NUMBER:
Not available for this mixture

****

SECTION II - HAZARDOUS INGREDIENTS

****

**********NO HAZARDOUS INGREDIENTS**********

HAZARDOUS SUMMARY

Rating		Definitions
Health	0	0 - least
Fire	2	1 - slight
Reactivity	0	2 - moderate
		3 - high
		4 - extreme

****

SECTION III - COMPOSITION

****

CAS NUMBER	CHEMICAL NAME	PERCENT BY WEIGHT
64741-65-7	Odorless mineral spirits	PI*
7732-18-5	Water	"
57-55-6	Propylene glycol	"
61790-12-3	Octylphenoxy-polyethoxyethanol surfactant	"
9036-19-5	Mixed fatty acid soap	"
N/A	Fragrance	"

*PI - Proprietary information

MATERIAL SAFETY DATA SHEET

****

SECTION IV - HEALTH HAZARD AND FIRST AID INFORMATION

****

OCCUPATION EXPOSURE LIMIT: Not established

CARCINOGENICITY: Not listed by NTP, IARC or OSHA

PRIMARY ROUTES OF ENTRY: Skin, eyes

SYMPTOMS AND EFFECTS OF OVEREXPOSURE	ROUTE OF ENTRY	EMERGENCY AND FIRST AID PROCEDURES
Causes moderate to extreme irritation, with possible corneal injury.	EYES	Immediately flush with large amounts of water for 15 minutes. Get medical attention.
Extended use may cause drying of skin. Prolonged contact may cause dermatitis or chemical burns on sensitive skin.	SKIN	Immediately flush skin with running water. If irritation persists, get medical attention.
Not likely.	INHALATION	Remove to fresh air.
Will cause nausea if swallowed. Stomach cramps may also occur.	INGESTION	DO NOT INDUCE VOMITING. Call doctor immediately. Treat for petroleum jelly ingestion.

NOTE TO PHYSICIAN: There is no specific antidote. Treatment of over-exposure should be directed at the control of symptoms and the clinical condition.

MATERIAL SAFETY DATA SHEET

****

SECTION V - PERSONAL PROTECTION INFORMATION

****

--WHEN HANDLING BULK QUANTITIES--

EYE PROTECTION: OSHA approved safety glasses.

PROTECTIVE CLOTHING: Wear rubber gloves. To avoid excessive exposure, wear impervious boots and clothing.

RESPIRATORY PROTECTION: Not necessary.

--WHEN USING PRODUCT ACCORDING TO DIRECTIONS FOR USE--

EYE PROTECTION: Avoid applying product in and around eyes.

PROTECTIVE CLOTHING: None required for normal use.

VENTILATION: Normal room ventilation is satisfactory.

RESPIRATORY PROTECTION: None required for normal use.

****

SECTION VI - STORAGE AND SPECIAL HANDLING INFORMATION

****

Keep away from heat, sparks, and flame. Avoid contact with eyes. Store at room temperature.

****

SECTION VII - SPILL OR LEAK RESPONSE INFORMATION

****

PRECAUTIONS IN CASE OF SPILLS OR LEAKS: Material is not considered toxic. Absorb with dry sand or oil absorbents. All materials are bio-degradable. Clean spill area with detergent solution and flush down sewer with water.

WASTE DISPOSAL METHOD: Waste materials should be dumped or buried in an approved industrial waste landfill. Large quantities may be disposed of by incineration.

RCRA/CERCLA HAZARDOUS WASTE: This product contains no hazardous waste.

MATERIAL SAFETY DATA SHEET

****

SECTION VIII - FIRE AND EXPLOSION HAZARD INFORMATION

****

FLASH POINT (open cup): 158°F

FLAMMABLE LIMITS: Unknown.

EXTINGUISHING MEDIA: Foam for large fires; carbon dioxide or dry chemical for small fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Smoke may be generated when burning.

SPECIAL FIRE FIGHTING PROCEDURES: Keep away from heat or hot surfaces above 150°F, treat vapors as you would odorless spirits. Treat as oil fire.

****

SECTION IX - REACTIVITY INFORMATION

****

STABILITY: Stable.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Waxy mixed alkanes at high temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None.

****

SECTION X - PHYSICAL DATA

****

APPEARANCE: Creamy white, slightly viscous

ODOR: Lavender

SOLUBILITY IN WATER (% by weight): 100%

SPECIFIC GRAVITY: 0.916 @ 25°C

BOILING POINT: 164°F

WEIGHT PER GALLON: 7.65 lbs.

VISCOSITY: 1,200 - 1,700 cps

AUTO IGNITION TEMPERATURE: Unknown