NE ¼ SEC. 11 T. 27 R. 5

N

W E

S

02658

5—428a

MISCELLANEOUS
RECEIVED
DEC 19 1928
No. 47519
OSAGE AGENCY

DEPARTMENT OF THE INTERIOR
OFFICE OF INDIAN AFFAIRS
FINAL REPORT OF COMPLETED OR DEEPENED WELLS
FOR LANDS COVERED BY DEPARTMENTAL LEASES

SPECIFY ~~OIL, GAS, OR DRY~~ Pressure Well.

This report must be filed within Ten Days after well is shut or producing natural. Use this form for Supplemental Report on Wells plugged back.

COMPANY OPERATING Phillips Pet. Co. ADDRESS Bartlesville, Oklahoma.

LESSEE Phillips Petroleum Company, LESSOR Osage Indian Tribe (M.S.Norman)

WELL No. 17 NE ¼ SEC. 11 T. 27 R. 5 OSAGE COUNTY

Well located 1285.8 Ft. N.-S. of N. Line and 1265.8 Ft. E.-W. of E. Line Elevation (Derrick floor, relative to sea level.)

Well drilled by Hays Development Co. Superintendent C. E. Klein

Date commenced drilling 10-22-28 , 19 Finished 12-8-28 , 19

Date commenced deepening , 19 Finished , 19

CASING USED IN DRILLING Length	Size	Wt. per ft.	Thread	CASING LEFT IN HOLE Length	Landed at	SHOE Length	Make	PACKERS Kind	Length	Set at
18'37	20 Ins.	90 Lbs.	Per in.	18'37	Ft.	Ft.			Ft.	Ft.
901 Ft.	15½ Ins.	70 Lbs.	Per in.	Ft.	Ft.	Ft.			Ft.	Ft.
1245 Ft.	12½ Ins.	50 Lbs.	Per in.	1031 Ft.	Ft.	Ft.			Ft.	Ft.
1504 Ft.	10 Ins.	Lbs.	Per in.	Ft.	Ft.	Ft.			Ft.	Ft.
2366 Ft.	8 5/8	28 Lbs.	Per in.	Ft.	Ft.	Ft.			Ft.	Ft.
2985 Ft.	6¼ Ins.	24 Lbs.	Per in.	2985 Ft.	Ft.	Ft.			Ft.	Ft.

What was done to protect sands when outside casing was pulled?

3040

Is water completely shut off? Yes Amount water with oil - per cent. Is oil cut -

Oil—Initial 24-hr. production - bbls. Initial 24-hr. production after shot - bbls. Shot from - to -, size - qts.

Tubing

Gas—Initial open flow sand from ft. to ft. Cu. ft. rock pressure lbs. per sq. in.

Initial open flow sand from ft. to ft. Cu. ft. rock pressure lbs. per sq. in.

Dry Hole—State what steps have been taken to plug.

Location fee paid Phillips Owns Fee Date Amount, $

Top of Sand	2980	
Bottom of Sand	3038	
T. D.	3040	Cable Measurement.
Dark soft sand	2980-	2989
Dark brown sand	2989	3012
Light brown sand	3012	3020
Light grey sand	3020	3028
Dark brown sand	3028	3038
Black shale	3038	3040
T. D.	3040	