MSDS - Material Safety Data Sheet

Product Name: HYDRAULIC JACK OIL

MSDS No.: M3312

I. Basic Information:

Manufacturer: RADIATOR SPECIALTY COMPANY

Address: P.O. BOX 159, 600 RADIATOR ROAD

City, ST Zip: INDIAN TRAIL, NC 28079

Emergency Contact: Rocky Mountain Poision Control Center

Emergency Telephone Number: 303-623-5716

Contact: Robert Geer

Information Telephone Number: 704-688-3430

Last Update: 06/18/2004

Chemical State: [X] Liquid [ ] Gas [ ] Solid

Chemical Type: [ ] Pure [X] Mixture



1	Health
1	Flammability
0	Reactivity
B	Pers. Protection

II. Ingredients:

[ ] **Trade Secret**

CAS No.	Chemical Name	% Range	EHS	NTP	IARC	SUB Z	SARA 313	OSHA PEL	ACGIH TLV	Other Limits
64742525	Naphthenic Petroleum Distillate	45-90						5 mg/m3	5 mg/m3	
Proprietary	Zinc Compounds	<0.3					X	N/E	N/E	

III. Hazardous Identification:

Hazard Category:

[X] Acute [ ] Chronic [ ] Fire [ ] Pressure [ ] Reactive

Hazardous Identification Information:

Harmful or Fatal if Swallowed.

IV. First Aid Measures:

Route(s) of Entry:

Absorption, Inhalation, and Ingestion.

Health Hazards (Acute and Chronic):

See signs and symptoms below

Signs and Symptoms:

Eye Contace: May cause slight iffitation
Skin Contact: May cause slight irritation
Inhalation: If oil mist is inhaled for prolonged periods, may cause irritation.
Ingestion: Can be Harmful or fatal if swallowed.

Medical Conditions Generally Aggravated by Exposure:

None known

Emergency and First Aid Procedures:

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids and get prompt medical attention.
Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.
Inhalation: Remove to fresh air. If breathing becomes difficult get prompt medical attention.
Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

V. Fire Fighting Measures:

Flash Point: 320 F **Lower Explosive Limit:** N/D **Upper Explosive Limit:** N/D

F.P. Method: COC

Fire Extinguishing Media: Water Fog, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Wear self-contained positive pressure breathing apparatus and protective clothes. Cool containers with a water fog. Do not use forced water stream as this could cause the fire to spread.

Unusual Fire and Explosion:

None known.

VI. Accidental Release Measures:

Steps to be Taken in Case Material is Released or Spilled:

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc). Place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occured.

VII. Handling and Storage:

Precautions to be Taken:

Handling: Use with adequate ventilation and proper protective equipment.
Do not use or store near fire, sparks, or flame. Do not puncture or incinerate container. Exposure to temperatures above 120° may cause container to vent, rupture, or burst.

Other Precautions:

Keep container closed tightly when not in use.
Store in a cool place away from oxidizing agents.

VIII. Exposure Controls/Personal Protection:

Ventilation Requirements:

See Section 2 for applicable exposure limits. Maintain adequate ventilation.
Avoid breathing mist. In restricted areas, use approved chemical filters designed to remove mist. In confined areas, use approved air line type respirator or hood. A self-contained breathing apparatus is required for vapor or mist concentrations above TLV limit

Personal Protective Equipment:

See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, and apron.

MSDS - Material Safety Data Sheet
Product Name: HYDRAULIC JACK OIL

MSDS No.: M3312

IX. Physical and Chemical Properties:

Boiling Point: 465 F

Melting Point: N/A

Evaporation Rate (Butyl Acetate = 1): Slow

Vapor Pressure (mm Hg.): 0.008

Specific Gravity (H20 = 1): 0.89500

Vapor Density (AIR = 1): 4.3

Solubility In Water: Insoluble

Appearance and Odor: Clear amber oil with petroleum odor

Other Information: N/D

X. Stability and Reactivity:

Stability:

Stable

Incompatibility (Materials to Avoid):

Avoid contact with strong ozidizing agents

Decomposition/By Products:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, phosphorus, nitrogen and sulfur oxides.

Hazardous Polymerization:

Will not occur

XI. Toxicological Information:

N/D

XII. Ecological Information:

N/D

XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in a recycling centers when empty. Before offering for recycling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations

XIV. Transport Information:

DOT Shipping Name: Not DOT regulated.
DOT Hazard Class: None

XV. Regulatory Information:

See Section 2 for SARA Reportable Chemicals.

USA TSCA: All components of this material are listed on the US TSCA Inventory.

XVI. Other Information:

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye.
KEEP AWAY FROM CHILDREN AND ANIMALS!

N/E: Not Established
N/D: Not Determined
N/A: Not Applicable
N/AV: Not Available

MSDS - Material Safety Data Sheet

Product Name: HYDRAULIC JACK OIL

MSDS No.: M3312

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered soley for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is repsonsible for full compliance.