MATERIAL SAFETY DATA SHEET

PRODUCT NAME: INT ACRYLIC FLAT- DEEP BASE
PRODUCT CODE: 120-01

HMIS CODES: H F R P
1*0 0 B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: CONCO PAINT COMPANY
ADDRESS : 2801 WEST MISSION ROAD
ALHAMBRA, CA 91803

EMERGENCY PHONE : (800) 535-5053
INFORMATION PHONE : (323) 222-7616
SUPERSEDES DATE : March 23, 1998

DATE PRINTED : 05/03/00
NAME OF PREPARER : Gregg Lindblom
REVISION DATE : April 12, 1999

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg	@ TEMP	WEIGHT PERCENT
ISOMORPHIC HYDROUS ALUMINUM POTASSIUM SILICATE	12001 26 2	N/A	N/A	3 2
ACGIH/TWA: 20mmpcf, ACGIH/STEL: 3mg/m3 RESPIRABLE DUST				
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	N/A	N/A	0 16
ACGIH TLV 10mg/m3 OSHA PEL 10mg/m3 (RESPIRABLE DUST)				
* VINYL ACETATE MONOMER	108-05 4	92	68 F	0 13
ACGIH TWA 10 PPM ACGIH STEL: 15 PPM; OSHA TWA: 10 PPM, OSHA STEL 20 PPM				

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 163.4 F
SPECIFIC GRAVITY (H2O=1): 1.32
VAPOR DENSITY: Lighter than air.
EVAPORATION RATE: Slower than ether.
COATING V.O.C.: 42 g/l
MATERIAL V.O.C.: 15 g/l
SOLUBILITY IN WATER: Complete.
APPEARANCE AND ODOR: Typical for water based paints.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Not Applicable.
METHOD USED: Not Applicable.
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 2.6
UPPER: 13.4

EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical, or Water Fog.

SPECIAL FIREFIGHTING PROCEDURES

Cool containers with water spray

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed container exposed to high temperatures may explode or burst due to build up of steam pressure

SECTION V - REACTIVITY DATA

STABILITY: Stable.
CONDITIONS TO AVOID

None

INCOMPATIBILITY (MATERIALS TO AVOID)

Avoid contact with strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

May form toxic materials on thermal decomposition including Carbon Dioxide, Carbon Monoxide, and various Hydrocarbons

HAZARDOUS POLYMERIZATION: Will not occur.

========== SECTION VI - HEALTH HAZARD DATA ==========

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Adverse health effects from vapors or spray mists in poorly ventilated areas may include irritation of the mucous membranes of the nose, throat, and respiratory tract and symptoms of headache and nausea

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYES In direct contact, may cause irritation. SKIN. Prolonged and repeated contact with product may cause skin irritation

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Redness, drying of the skin, or other signs of irritation or contact dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE May cause irritation to skin and eyes, gastrointestinal irritation, nausea, and vomiting. CHRONIC. Contains crystalline silica that IARC has concluded may cause cancer in animals but limited evidence of cancer in humans Risk of cancer depends on duration and level of exposure In coatings products, risk is due primarily to inhalation of sanding dust Prolonged exposure to respirable crystalline silica (quartz) may cause delayed (chronic) lung injury (silicosis)

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: Yes

WARNING! This product contains chemical(s) known to the State of California to cause cancer (California Health and Safety Code Section 25249 5) (Prop 65) WARNING! This product contains chemical(s) known to the State of California to cause birth defects or other reproductive harm (California Health and Safety Code Section 25249 5) (Prop 65)

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

May be aggravating to some skin and respiratory conditions, and to pre-existing liver and/or kidney disorders

EMERGENCY AND FIRST AID PROCEDURES

EYES Flush with large amounts of water for at least 15 minutes Take to a physician SKIN Wash affected areas with soap and water Remove contaminated clothing. If irritation persists, consult physician INHALATION Remove to fresh air Treat symptomatically. Consult physician INGESTION Drink 1 or 2 glasses of water to dilute DO NOT INDUCE VOMITING CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY.

========== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ==========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike contain or absorb with inert materials Transfer to containers for recovery or disposal Prevent runoff into sewers streams or other bodies of water

WASTE DISPOSAL METHOD

Dispose of in accordance with all local, state and federal regulations

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Do not expose to extremes in temperature Avoid exposure to high temperatures DO NOT ALLOW TO FREEZE.

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY Avoid prolonged or repeated exposure to levels above TLV KEEP OUT OF REACH OF CHILDREN

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION

Not normally required If TLV is exceeded, use NIOSH/MSHA approved organic vapor and mist, supplied air, or self contained breathing apparatus Avoid breathing sanding dust PRODUCT CONTAINS CRYSTALLINE SILICA. Long term exposure to Crystalline Silica may cause lung damage and cancer Risk depends upon duration and level of exposure to sanding dust. When sanding, use NIOSH/MSHA approved dust mask

VENTILATION

Use adequate mechanical (general and/or local) ventilation to maintain exposure below TLV

PROTECTIVE GLOVES

Wear resistant gloves such as polyethylene

EYE PROTECTION

Use chemical splash goggles or OSHA permitted safety glasses

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Wear impervious clothing. Eye wash station.

WORK/HYGIENIC PRACTICES

Wash hands before eating or using restrooms. Remove and wash all contaminated clothing before reuse.

SECTION IX - DISCLAIMER

The information contained herein is furnished without warranty of any kind Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees