Shale, gray soft	2340	[illegible]	
Sandy lime, gray med. hard	2365	2365	8½" at 2360' SL
Shale, light soft	[illegible]	[illegible]	
Lime, white hard	2615	2630	
Shale, black soft	2630	2635	
Lime, white hard	2635	2640	Cave
Shale, dark soft	2640	2715	
Lime, white hard	2715	2735	
Shale, black soft	2735	2745	
Lime, white hard	2745	2760	
Shale, black soft	2760	2770	
Lime, white hard	2770	2810	
Shale, black soft	2810	2830	
Lime, white hard	2830	2895	6-5/8" at 2835' SL
Shale, dark soft	2895	2905	
Lime, white hard	2905	2915	
Shale, dark soft	2915	3022	Reduced hole at 2999'
Sandy shale, light soft		3031	
Gas sand, light soft	3031	3051	
Oil sand, brown soft	3051	3085	First oil 3051'
Oil sand, brown soft	3085	3104	Total depth

0278-A

Remarks.

Reduced 2999'. Dark shale 2999' 3022'
Sandy shale 3022' 3031' Gas 5 mi. ft. 3031'
Gas, 6 mi. ft. 3036' First Oil 3051'
Sand, soft 3051' 3085' Med. Hard 3085' 3104'