SECTION 1

PRODUCT IDENTIFIER ZY1820 ACOUSTICAL CEILING OLD WHITE
DATE OF PREPARATION DECEMBER 30, 1999
PRODUCT USE PROTECTIVE COATING

MANUFACTURED BY: ICI PAINTS NORTH AMERICA, 925 EUCLID AVENUE, CLEVELAND , OHIO 44115, U.S.A.
ICI PAINTS (CANADA), 8200 KEELE STREET, CONCORD, ONTARIO L4K 2A5, CANADA.

EMERGENCY AND MSDS TELEPHONE NUMBER:
1-800-345-2643

MSDS PREPARED BY: PRODUCT SAFETY AND TOXICOLOGY DEPARTMENT
ICI PAINTS NORTH AMERICA

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

	INGREDIENT	WT.%:
CHEMICAL NAME	VINYL TOLUENE ALKYD COPOLYMER	1-5
COMMON NAME	ALKYD RESIN	
CAS NUMBER:	CONFIDENTIAL	
CHEMICAL NAME	BENZENE, ETHYL-	1-5
COMMON NAME :	ETHYLBENZENE	
CAS NUMBER:	100-41-4	
CHEMICAL NAME	BENZENE, METHYL-	5-10
COMMON NAME :	TOLUENE	
CAS NUMBER.	108-88-3	
CHEMICAL NAME	BENZENE, DIMETHYL-	1-5
COMMON NAME :	XYLENE	
CAS NUMBER.	1330-20-7	
CHEMICAL NAME	TITANIUM OXIDE	1-5
COMMON NAME :	TITANIUM DIOXIDE	
CAS NUMBER:	13463-67-7	
CHEMICAL NAME	TALC	5-10
COMMON NAME	TALC	
CAS NUMBER.	14807-96-6	
CHEMICAL NAME	QUARTZ	.1-1.0
COMMON NAME .	QUARTZ	
CAS NUMBER:	14808-60-7	
CHEMICAL NAME	SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	5-10
COMMON NAME :	LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM)	
CAS NUMBER:	64742-89-8	
CHEMICAL NAME	2-PROPANONE	20-30
COMMON NAME	ACETONE	
CAS NUMBER:	67-64-1	
CHEMICAL NAME	DISTILLATES (PETROLEUM), STEAM-CRACKED, POLYMERIZED	1-5
COMMON NAME :	PETROLEUM RESINS	
CAS NUMBER	68131-77-1	

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	PETROLEUM GASES, LIQUEFIED, SWEETENED	30-40
COMMON NAME :	LIQUEFIED PETROLEUM GASES, SWEETENED	
CAS NUMBER:	68476-86-8	
CHEMICAL NAME	BENZENE	.01-.1
COMMON NAME :	BENZENE	
CAS NUMBER:	71-43-2	

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTE(S) OF EXPOSURE
INHALATION, SKIN CONTACT, EYE CONTACT, INGESTION.

EFFECTS OF OVEREXPOSURE

INHALATION PROLONGED INHALATION MAY LEAD TO MUCOUS MEMBRANE IRRITATION, FATIGUE, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, ABDOMINAL PAIN, CHEST PAIN, BLURRED VISION, COUGHING, DIFFICULTY WITH SPEECH, CENTRAL NERVOUS SYSTEM DEPRESSION, INTOXICATION, TIGHTNESS OF CHEST, METALLIC TASTE, CONFUSION, ANESTHETIC EFFECT OR NARCOSIS, DIFFICULTY OF BREATHING, BLOOD ABNORMALITIES, TREMORS, LIVER DAMAGE, KIDNEY DAMAGE.
NEUROTOXICITY
CONVULSIONS, LOSS OF CONSCIOUSNESS, RESPIRATORY FAILURE, ASPHYXIATION, DEATH.

SKIN CONTACT IRRITATION OF SKIN. PROLONGED OR REPEATED CONTACT CAN CAUSE DERMATITIS, DEFATTING, BLISTERING.

EYE CONTACT IRRITATION OF EYES. PROLONGED OR REPEATED CONTACT CAN CAUSE CONJUNCTIVITIS, BLURRED VISION, TEARING OF EYES, REDNESS OF EYES SEVERE EYE IRRITATION, CORNEAL INJURY, BLINDNESS.

INGESTION INGESTION MAY CAUSE LUNG INFLAMMATION AND DAMAGE DUE TO ASPIRATION OF MATERIAL INTO LUNGS, MUCOUS MEMBRANE IRRITATION, FATIGUE, DROWSINESS, DIZZINESS AND/OR LIGHTHEADEDNESS, HEADACHE, UNCOORDINATION, NAUSEA, VOMITING, DIARRHEA, GASTRO-INTESTINAL DISTURBANCES, CENTRAL NERVOUS SYSTEM DEPRESSION, LIVER DAMAGE, KIDNEY DAMAGE, PULMONARY EDEMA.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
EYE, SKIN, RESPIRATORY DISORDERS
KIDNEY DISORDERS

SECTION 4: FIRST-AID MEASURES

INHALATION REMOVE TO FRESH AIR. RESTORE AND SUPPORT CONTINUED BREATHING.
GET EMERGENCY MEDICAL ATTENTION.
HAVE TRAINED PERSON GIVE OXYGEN IF NECESSARY. GET MEDICAL HELP FOR ANY BREATHING DIFFICULTY.
REMOVE TO FRESH AIR IF INHALATION CAUSES EYE WATERING, HEADACHES, DIZZINESS, OR OTHER DISCOMFORT.

SECTION 4: FIRST-AID MEASURES

SKIN CONTACT FLUSH FROM SKIN WITH WATER. THEN WASH THORDUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING.
WASH CONTAMINATED CLOTHING BEFORE RE-USE.

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS FOR AT LEAST 15 MINUTES. IF IRRITATION OR OTHER EFFECTS PERSIST, OBTAIN MEDICAL TREATMENT.

INGESTION IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

SECTION 5: FIRE-FIGHTING MEASURES

FLASH POINT (SETA) 1 F./ -17 C. **LOWER EXPLOSIVE LIMIT** 1.8 (%)
UPPER EXPLOSIVE LIMIT 9.5 (%)

FIRE EXTINGUISHING MEDIA
DRY CHEMICAL OR FOAM
WATER FOG.
CARBON DIOXIDE.

UNUSUAL FIRE AND EXPLOSION HAZARDS
CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE.
VAPORS MAY IGNITE EXPLOSIVELY AT AMBIENT TEMPERATURES.
VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL LONG DISTANCES TO A SOURCE OF IGNITION AND FLASH BACK.
VAPORS CAN FORM EXPLOSIVE MIXTURES IN AIR AT ELEVATED TEMPERATURES.
CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE
MAY DECOMPOSE UNDER FIRE CONDITIONS EMITTING IRRITANT AND/OR TOXIC GASES.

FIRE FIGHTING PROCEDURES
WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.
FIREFIGHTERS SHOULD USE FULL PROTECTIVE CLOTHING, EYE PROTECTION, AND SELF-CONTAINED BREATHING APPARATUS.

HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS
CARBON MONOXIDE, CARBON DIOXIDE, OXYGEN.

SECTION 6 ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS.
ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA.
VENTILATE AREA WITH EXPLOSION-PROOF EQUIPMENT. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. USE NON-SPARKING TOOLS. EVACUATE ALL UNNECESSARY PERSONNEL. PLACE COLLECTED MATERIAL IN PROPER CONTAINER.
COMPLETE PERSONAL PROTECTIVE EQUIPMENT MUST BE USED DURING CLEANUP.
LARGE SPILLS - SHUT OFF LEAK IF SAFE TO DO SO. DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP SALVAGEABLE MATERIAL AND RINSE WATER OUT OF SEWERS AND WATER COURSES.

SECTION 6 ACCIDENTAL RELEASE MEASURES

SMALL SPILLS - USE ABSORBENT TO PICK UP RESIDUE AND DISPOSE OF PROPERLY.

SECTION 7 HANDLING AND STORAGE

HANDLING AND STORAGE

STORE BELOW 80F.
STORE IN ORIGINAL CONTAINERS. ISOLATED STORAGE IS DESIRABLE.
KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

OTHER PRECAUTIONS USE ONLY WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS. WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING OR SMOKING.
KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.
EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.
GROUND EQUIPMENT WHEN TRANSFERRING TO PREVENT ACCUMULATION OF STATIC CHARGE.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

COMMON NAME : ETHYLBENZENE
CAS NUMBER: 100-41-4
ACGIH(TWA): 100 PPM OSHA(TWA): 100 PPM
ACGIH(STEL): 125 PPM

COMMON NAME : TOLUENE
CAS NUMBER: 108-88-3
ACGIH(TWA): SKIN 50 PPM OSHA(TWA): 200 PPM
OSHA((SKIN) : CEILING 300 PPM SUPP REC STD.: NOT AVAILABLE

COMMON NAME : XYLENE
CAS NUMBER: 1330-20-7
ACGIH(TWA): 100 PPM OSHA(TWA): 100 PPM
ACGIH(STEL): 150 PPM

COMMON NAME : TITANIUM DIOXIDE
CAS NUMBER: 13463-67-7
ACGIH(TWA) 10 MG/M3 OSHA(TWA) 10 MG/M3

COMMON NAME : TALC
CAS NUMBER 14807-96-6
ACGIH(TWA): 2 MG/M3

COMMON NAME : QUARTZ
CAS NUMBER: 14808-60-7
ACGIH(TWA): 0.1 MG/M3 OSHA(TWA): 0.1 MG/M3

COMMON NAME : LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM)
CAS NUMBER: 64742-89-8
OSHA(TWA): 300 PPM

COMMON NAME : ACETONE
CAS NUMBER: 67-64-1
ACGIH(TWA): 500 PPM OSHA(TWA): 1000 PPM
ACGIH(STEL): 750 PPM

COMMON NAME : PETROLEUM RESINS

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS NUMBER: 68131-77-1
ACGIH(TWA): 5 MG/M3 OSHA(TWA): 5 MG/M3

COMMON NAME : LIQUEFIED PETROLEUM GASES, SWEETENED
CAS NUMBER: 68476-86-8
ACGIH(TWA): 1000 PPM OSHA(TWA) 1000 PPM

COMMON NAME : BENZENE
CAS NUMBER: 71-43-2
ACGIH(TWA): .5 PPM OSHA(TWA): 1 PPM
ACGIH(STEL): 2.5 PPM OSHA(STEL): 5 PPM

SKIN - DENOTES THAT ADDITIONAL EXPOSURE, OVER AND ABOVE AIRBORNE EXPOSURE, MAY RESULT FROM SKIN ABSORPTION.

RESPIRATORY PROTECTION
CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE EXPOSURE STANDARDS WHEN USING THIS MATERIAL. WHEN RESPIRATORY PROTECTION IS DETERMINED TO BE NECESSARY, USE A NIOSH/MSHA (CANADIAN Z94.4) APPROVED ELASTOMERIC SEALING-SURFACE FACEPIECE RESPIRATOR OUTFITTED WITH ORGANIC VAPOR CARTRIDGES AND PAINT SPRAY (DUST/MIST) PREFILTERS. DETERMINE THE PROPER LEVEL OF PROTECTION BY CONDUCTING APPROPRIATE AIR MONITORING. CONSULT 29CFR1910.134 FOR SELECTION OF RESPIRATORS (CANADIAN Z94.4).

VENTILATION
PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.
USE EXPLOSION-PROOF EQUIPMENT. USE NON-SPARKING EQUIPMENT.

PERSONAL PROTECTIVE EQUIPMENT
EYE WASH, SAFETY SHOWER, SAFETY GLASSES OR GOGGLES.
IMPERVIOUS GLOVES, IMPERVIOUS CLOTHING, APRON, BOOTS.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:	NOT AVAILABLE	SPECIFIC GRAVITY:	.779
BOILING RANGE:	137-295F/56-146C	WEIGHT PER GALLON:	6.49/ 7.79IMP
XVOLATILE BY VOLUME:	93.42		
PHYSICAL STATE:	AEROSOL	APPEARANCE	WHITE
SOLUBILITY IN WATER:	NOT AVAILABLE	PH:	NOT AVAILABLE

SECTION 10: STABILITY AND REACTIVITY

UNDER NORMAL CONDITIONS
STABLE
SEE SECTION 5 FIRE FIGHTING MEASURES

MATERIALS TO AVOID
OXIDIZERS, ACIDS, BASES, AMINES, NITRIC ACID, MINERAL ACIDS.

CONDITIONS TO AVOID
ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENT, SPARKS, OPEN FLAME, IGNITION SOURCES.

SECTION 10: STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION
WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME : ALKYD RESIN
CAS NUMBER: CONFIDENTIAL
CARCINOGENICITY LISTED BY NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : ETHYLBENZENE
CAS NUMBER: 100-41-4
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
LD50: 3500.00 MG/KG ORL RAT
LD50: 2272.00 MG/KG IPR MOU
LD50: 17.80 GM/KG SKN RBT

COMMON NAME : TOLUENE
CAS NUMBER: 108-88-3
CARCINOGENICITY LISTED BY NTP NO IARC NO OSHA NO ACGIH NO
LD50: 12.10 GM/KG SKN RBT
LD50: 636.00 MG/KG ORL RAT
LC50 400.00 PPM IHL MOU

COMMON NAME : XYLENE
CAS NUMBER: 1330-20-7
CARCINOGENICITY LISTED BY: NTP NO IARC NO OSHA NO ACGIH NO
LD50:>1700.00 MG/KG SKN RBT
LD50 4300.00 MG/KG ORL RAT
LC50: 5000.00 PPM/4HR IHL RAT

COMMON NAME : TITANIUM DIOXIDE
CAS NUMBER 13463-67-7
CARCINOGENICITY LISTED BY NTP NO IARC NO OSHA NO ACGIH NO
LD50 24.00 GM/KG ORL RAT
LC50: 6820.00 MG/M3/4HR IHL RAT

COMMON NAME : TALC
CAS NUMBER: 14807-96-6
CARCINOGENICITY LISTED BY NTP NO IARC NO OSHA NO ACGIH NO

COMMON NAME : QUARTZ
CAS NUMBER: 14808-60-7
CARCINOGENICITY LISTED BY NTP YES IARC YES 1 OSHA NO ACGIH NO

COMMON NAME : LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM)
CAS NUMBER: 64742-89-8
CARCINOGENICITY LISTED BY NTP NO IARC NO OSHA NO ACGIH NO
LD50:> 3.16 GM/KG SKN RBT
LD50:> 5.00 GM/KG ORL RAT

COMMON NAME : ACETONE
CAS NUMBER 67-64-1
CARCINOGENICITY LISTED BY NTP NO IARC NO OSHA NO ACGIH NO
LD50: 5800.00 MG/KG ORL RAT
LD50:>9400.00 MG/KG SKN GPG

COMMON NAME : PETROLEUM RESINS
CAS NUMBER: 68131-77-1
CARCINOGENICITY LISTED BY NTP NO IARC NO OSHA NO ACGIH NO

SECTION 11: TOXICOLOGICAL INFORMATION

COMMON NAME : LIQUEFIED PETROLEUM GASES, SWEETENED
CAS NUMBER: 68476-86-8
CARCINOGENICITY LISTED BY NTP NO IARC NO OSHA NO ACGIH NO
LD50: 6960.00 MG/KG ORL RAT

COMMON NAME : BENZENE
CAS NUMBER: 71-43-2
CARCINOGENICITY LISTED BY NTP YES A IARC YES 1 OSHA YES ACGIH YES A2
LD50: 930.00 MG/KG ORL RAT
LD50: >9400.00 MG/KG SKN RBT

SUPPLEMENTAL HEALTH INFORMATION

CONTAINS A CHEMICAL THAT IS MODERATELY TOXIC BY INGESTION.
CONTAINS A CHEMICAL THAT IS READILY ABSORBED THROUGH SKIN.
CONTAINS A CHEMICAL THAT MAY BE ABSORBED THROUGH SKIN.
NOTICE - REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.
OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE TOXICITY TO LIVER, KIDNEY, LUNGS, CENTRAL NERVOUS SYSTEM, BLOOD, SPLEEN, HEART, GASTROINTESTINAL TRACT.

CARCINOGENICITY

INHALATION OF NON-ASBESTIFORM COSMETIC GRADE TALC FOR 2 YEARS AT 6 AND 18 MG/M3 PRODUCED CLEAR EVIDENCE OF CARCINOGENICITY IN FEMALE RATS (LUNG AND ADRENAL TUMORS) AND SOME EVIDENCE OF CARCINOGENICITY IN MALE RATS (ADRENAL TUMORS). NO EVIDENCE OF CARCINOGENICITY WAS DEMONSTRATED IN MALE AND FEMALE MICE EXPOSED UNDER THE SAME CONDITIONS. MICROSCOPIC EXAMINATION OF THE LUNGS OF RATS AND MICE EXPOSED TO TALC REVEALED ADDITIONAL EXPOSURE RELATED EFFECTS PRIMARILY ASSOCIATED WITH THE INFLAMMATORY RESPONSE.
CONTAINS CRYSTALLINE SILICA WHICH IS CONSIDERED A HAZARD BY INHALATION. IARC HAS CLASSIFIED CRYSTALLINE SILICA AS CARCINOGENIC TO HUMANS (GROUP 1). CRYSTALLINE SILICA IS ALSO A KNOWN CAUSE OF SILICOSIS, A NONCANCEROUS LUNG DISEASE. NTP HAS CLASSIFIED CRYSTALLINE SILICA A REASONABLY ANTICIPATED CARCINOGEN.
IN A 2 YEAR INHALATION STUDY CONDUCTED BY THE NATIONAL TOXICOLOGY PROGRAM (NTP), ETHYLBENZENE VAPOR AT 750 PPM PRODUCED KIDNEY AND TESTICULAR TUMORS IN RATS AND LUNG AND LIVER TUMORS IN MICE. GENETIC TOXICITY STUDIES SHOWED NO GENOTOXIC EFFECTS. THE RELEVANCE OF THESE RESULTS TO HUMANS IS NOT KNOWN.

REPRODUCTIVE EFFECTS

HIGH EXPOSURES TO XYLENE IN SOME ANIMAL STUDIES, OFTEN AT MATERNALLY TOXIC LEVELS, HAVE AFFECTED EMBRYO/FETAL DEVELOPMENT. THE SIGNIFICANCE OF THIS FINDING TO HUMANS IS NOT KNOWN.

MUTAGENICITY

NO MUTAGENIC EFFECTS ARE ANTICIPATED

TERATOGENICITY

NO TERATOGENIC EFFECTS ARE ANTICIPATED

SECTION 12: ECOLOGICAL INFORMATION

NO ECOLOGICAL TESTING HAS BEEN DONE BY ICI PAINTS ON THIS PRODUCT AS A WHOLE.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

SECTION 14: TRANSPORT INFORMATION

DOT PAINT

IMDG AEROSOLS,CLASS 2,UN1950,LIMITED QUANTITY

IATA NOT AVAILABLE

TDG NOT AVAILABLE

SECTION 15: REGULATORY INFORMATION

		SARA 302	SARA 313	CERCLA 302.4	HAZ AIR POLLUTANT	MARINE POLTNT
CAS NUMBER COMMON NAME :	100-41-4 ETHYLBENZENE	NO	YES	YES	YES	NO
CAS NUMBER. COMMON NAME :	108-88-3 TOLUENE	NO	YES	YES	YES	NO
CAS NUMBER: COMMON NAME :	1330-20-7 XYLENE	NO	YES	YES	YES	NO
CAS NUMBER. COMMON NAME :	67-64-1 ACETONE	NO	NO	YES	NO	NO
CAS NUMBER. COMMON NAME :	71-43-2 BENZENE	NO	YES	YES	YES	NO

AS OF THE DATE OF THIS MSDS, ALL OF THE COMPONENTS IN THIS PRODUCT ARE LISTED (OR ARE OTHERWISE EXEMPT FROM LISTING) ON THE TSCA INVENTORY.
THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR (CONTROLLED PRODUCTS REGULATIONS) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

SECTION 16: OTHER INFORMATION

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE AT THE TIME OF PREPARATION OF THIS DATA SHEET AND WHICH ICI PAINTS BELIEVES TO BE RELIABLE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA. ICI PAINTS SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS INFORMATION, OR OF ANY PRODUCT, METHOD OR APPARATUS MENTIONED AND YOU MUST MAKE YOUR OWN DETERMINATION OF ITS SUITABILITY AND COMPLETENESS FOR YOUR OWN USE, FOR THE PROTECTION OF THE ENVIRONMENT, AND THE HEALTH AND SAFETY OF YOUR EMPLOYEES AND USERS OF THIS MATERIAL.
COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD 29CFR1910.1200.