MATERIAL SAFETY DATA SHEET

PRODUCT NAME: DUREX PASTEL BASE
PRODUCT CODE: DL-732

HMIS CODES:

H	F	R	P
1	0	0	N

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Lanco Mfg.
ADDRESS: URB. APONTE #5 SAN LORENZO PR, 00754
EMERGENCY PHONE: 1-800-424-9300 **INFORMATION PHONE:** (787) 736-4221
DATE REVISED : 02-02-99 **NAME OF PREPARER :** VICTOR M. HERNANDEZ

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS OSHA PEL	ACGIH TLV	OTHER	VAPOR PRESSURE mm Hg @ TEMP		WEIGHT PERCENT
WATER	7732-18-5	N\A	N\A	N\A	N/A		
*ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	25 PPM	25 PPM		0.9	77F	1
AQUA AMMONIA 29%	1336-21-6	35 PPM	25 PPM	35 PPM	1.0	80F	
STYRENE ACRYLIC LATEX	N\A				N/A		
*DIETHYLENE GLYCOL MONOBUTYL ETHER	112-34-5	N/A	N/A	N/A	0.0	68F	2
ALIPHATIC SOLVENT	64742-88-7	500 PPM	100 PPM	N/A	2.0	68F	

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: N/A **SPECIFIC GRAVITY (H2O=1):** 1.2
VAPOR DENSITY: LIGHTER THAN AIR **EVAPORATION RATE:** N/A
COATING V.O.C. : 1.60 LB/GL (192 G/L)
MATERIAL V.O.C. : 0.73 LB/GL (88 G/L)
SOLUBILITY IN WATER: AQUEOUS SYSTEM
APPEARANCE AND ODOR:

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A **METHOD USED:** N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.0% **UPPER:** 10.0%

EXTINGUISHING MEDIA: , CO2, WATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES
SUMMON PROFESSIONAL FIREFIGHTERS. USE FULL PROTECTIVE EQUIPMENT INCLUDING SELFCONTAINED BREATHING APPARATUS. WATER SPRAY MAY BEINEFFECTIVE. IF WATER IS USED,FOGNOZZLES ARE PREFERABLE.

UNUSUAL FIRE AND EXPLOSION HAZARDS
DUE TO PRESSURE BUILD- UP, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODEDURING EMERGENCY CONDITIONS, OVEREXPSURE TO DECOMPOSITION PRODUCT MAY CAUSE A HEALTH HAZARD. SYMTOMS MAY NOT BE INMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

SECTION V - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID

INCOMPATIBILITY (MATERIALS TO AVOID)
NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
MAY CAUSE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION. FUMES MAY CONTAIN CARBONMONOXIDE, CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
IRRITATION OF THE RESPIRATORY TRACT;HEADACHE,NAUSEA,DIZZINESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE
INCASE OF EYE CONTACT, FLUSH WHITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ASSISTANT.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
REMOVE WHITH SOAP AND WATER. REMOVED SOILED CLOTHING.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
DRINK 1 OR 2 GLASSES OF WATER DILUTE. DO NOT INDUCE VOMITING. CONSULT PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMTOMATICALLY.

HEALTH HAZARDS (ACUTE AND CHRONIC)
PROLONGED AND REPEATED BREATHING OF SPRAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE DUST DISEASE OF THE LUNGS.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO
NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE
NONE WHEN USED IN ACORDANCE WHITH SAFE HANDLING AND USE INFORMATION.

EMERGENCY AND FIRST AID PROCEDURES
IF BREATHED: REMOVED TO FRESH AIR. IF IN EYES:IN CASE OF EYE CONTACT,FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. IF OF SKIN:REMOVE WITH SOAP AND WATER. REMOVED SOILED CLOTHING. INGESTION: INDUCE VOMITING PROMTLY ACCORDING TO PHYSICIANS INTRUCTIONS OR BY HAVING PATIENT STICK FINGER DOWN THROAT. AFTER VOMITING HAS BEEN INDUCED, GIVE TWO TEAS POONFULS OF BAKING SODA IN WATER.

========== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ==========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
WASH WITH WATER, BEFORE ATTEMTING CLEAN UP, REFER TO HAZARD CAUTION INFOMATION IN OTHER SECTION OF THIS MATERIAL SAFETY DATA FORM. CONTAIN SPILLED MATERIAL ANDREMOVED WITH INERT ABSORBENT. STORE IN CLOSED CONTAINER.

WASTE DISPOSAL METHOD
DISPOSE OF IN ACORDANCE WITH LOCAL, STATE AND FEDERAL REGULATION.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
STORE BELOW 100 F AND KEEP FROM FREEZING. KEEP CONTAINER CLOUSED WHEN NOT IN USEDO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN.

OTHER PRECAUTIONS
NONE

========== SECTION VIII - CONTROL MEASURES ==========

RESPIRATORY PROTECTION
DO NOT BREATHE VAPORS,SPRAY MIST OR SANDING DUST. WHEN SPRAY APPLIED IN OUTDOOR OR OPEN AREASWITH UNRESTRICTED VENTILATION, AND DURING SANDINGOR GRINDING OPERATION, USE NIOSH/NSHA APROVED MACHANICAL FILTER RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY AND SANDING DUST.

VENTILATION
USE ONLY WITH ADEQUATE VENTILATION. PROVIDE GENARAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP AIR COTAIMINANT CONCETRATION BELOW CURRENT APPLICABLE SAFETY AND HEALTH STANDARS IN THE MIXING.

PROTECTIVE GLOVES
NOT REQUIRED.

EYE PROTECTION
DO NOT IN EYES. SAFETY EYEWEAR WITH SPLASH GUARDS OR RECOMMENDED TO PREVENT CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
NOT REQUIRED.

WORK/HYGIENIC PRACTICES
REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE BASHROOM.

========== SECTION IX - DISCLAIMER ==========

DISCLAIMER
The information contained herein is based on data believed by this company to be accurate, but we do not assume any liability for its accuracy. We neither suggest nor guarantee that any hazards mentioned are the only ones which exist. The manner of that use and whether there is any infringement of patents is the sole responsability of the user.