Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard. 29 CFR 1910. 1200. Standard must be consulted for specific requirements. WATER BASED COATING

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

H.I.M.S. RATING

HEALTH: 2
FLAMMABILITY: 1
REACTIVITY: 1
PERSONAL PROTECTIVE EQUIP.: H

IDENTITY (as Used on Label and List)
COAL TAR DRIVEWAY SEALER

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name MONSEY PRODUCTS CO.	Emergency Telephone Number 215-933-8888
Address (Number, Street, City, State, and ZIP Code) P. O. BOX 368	Telephone Number for Information 215-933-8888
COLD STREAM ROAD	Date Prepared SHEET # 8 2/5/88 SUPERSEDES 7/10/87
KIMBERTON, PA 19442	Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specify Chemical Identity; Common Name(s))		OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
REFINED COAL TAR	CAS 61789-60-4		0.2 mg/cu.m.*		33
EMULSIFIER	CAS 65996-91-0		0.2 mg/cu.m.*		0.3

Benzene solubles

Section III – Physical/Chemical Characteristics

Boiling Point	212°F	Weight Per Gallon	9.7#
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	Heavier	Evaporation Rate (Butyl Acetate = 1)	Slower

Solubility in Water
Readily dispersible in water

Appearance and Odor
Black arromatic

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits	LEL N/A	UEL N/A

Extinguishing Media
N/A

Special Fire Fighting Procedures
N/A

Unusual Fire and Explosion Hazards
N/A

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility *(Materials to Avoid)*

Hazardous Decomposition or Byproducts

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI – Health Hazard Data

Route(s) of Entry:	Inhalation?	Eyes?	Skin?	Ingestion?
	yes	yes	yes	yes

Health Hazards *(Acute and Chronic)* and Signs and Symptoms of Exposure

Do not take internally. Harmful or fatal if swallowed.

May be skin irritant, contains coal tar pitch. Can cause contact dermatitis, sensitization.

Avoid inhalation of spray mist.

Burning of eyes.

Emergency and First Aid Procedures:

ESTION: Do not induce vomiting. Call doctor immediately.

SKIN CONTACT: Flush with water immediately. Minor skin irritation can be treated as a sunburn.

INHALATION: Get into fresh air. Call doctor immediately.

EYE CONTACT: Flush with water immediately. Call doctor immediately.

Section VII – Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

Allow to dry or absorb with inert sorbant and remove to a sanitary landfill location.

Waste Disposal Method

Dispose of in accordance with local regulations.

Precautions to Be Taken in Handling and Storing

Store in a tightly closed, properly labeled container in a well ventilated area.

Other Precautions

Freezable

Section VIII – Control Measures

Respiratory Protection *(Specify Type)*

se a NIOSH approved respirator within the limits of the respirator.

ilation	Local Exhaust	Special Necessary when working in a confined location.
	Mechanical *(General)*	

Protective Gloves Rubber gloves	Eye Protection Goggles

Other Protective Clothing or Equipment

Hand creme

Work Hygienic Practices