[illegible] SEC. 11 T. 27 R. 5

N
W E
S

SPECIFY OIL, GAS, OR DRY

DEPARTMENT OF THE INTERIOR
OFFICE OF INDIAN AFFAIRS
FINAL REPORT OF COMPLETED OR DEEPENED WELLS
FOR LANDS COVERED BY DEPARTMENTAL LEASES

RECEIVED
APR 4 1925
NO. [illegible]
OSAGE AGENCY

This report must be filed within Ten Days after well is shut or producing natural. Use this form for Supplemental Report on Wells plugged back.

COMPANY OPERATING Phillips Pet Co.

LESSEE Phillips Pet. Co

ADDRESS Bartlesville, Okla.

LESSOR [illegible] (Osage Tribe of Indians)

WELL No. 8 [illegible] ¼ SEC. 11 T. 27 R. 5

Well located 983' from south line and 305' from east line

Ft. N.S. of and Ft. E.-W. of

Well drilled by [illegible] Clark

Elevation 1150 [illegible] (Outside [illegible] relative to [illegible])

Date commenced drilling Jan. 31, 1925

Superintendent [illegible] Edmondson

Date commenced deepening , 19 Finished March 17, 1925

, 19 Finished , 19

Length	Size	Wt. per ft.	Thread	Length	Landed at	Length	Make	Kind	Length	Set at
[illegible]	[illegible]	90 Lbs.	Per in.	27'10"	Ft.	Ft.			Ft.	Ft.
[illegible]	[illegible]	70 Lbs.	Per in.	Ft.	Ft.	Ft.			Ft.	Ft.
[illegible]	[illegible]	50 Lbs.	Per in.	Ft.	Ft.	Ft.			Ft.	Ft.
[illegible]	[illegible]	40 Lbs.	Per in.	Ft.	Ft.	Ft.			Ft.	Ft.
[illegible]	[illegible]	28 Lbs.	Per in.	[illegible]	Ft.	Ft.			Ft.	Ft.
[illegible]	[illegible]	24 Lbs.	Per in.	[illegible]	Ft.	Ft.			Ft.	Ft.

What was done to protect sands when outside casing was pulled?

Reduced 2940
Sandy shale 2936-2942
Gray sand 2942-2947
Dark brown 2947-2961
Dark gray 2961-2986
Light gray 2986-2998

Is water completely shut off? Amount water with oil per cent. Is oil cut

Oil—Initial 24-hr. production 150 bbls. Initial 24-hr. production after shot bbls. Shot from to , size qts.

Tubing

Gas—Initial open flow sand from ft. to ft. Cu. ft. rock pressure lbs. per sq. in.
Initial open flow sand from ft. to ft. Cu. ft. rock pressure lbs. per sq. in.

Dry Hole—State what steps have been taken to plug.

Location fee paid

Date Amount, $

January 7, 1925.

Lime, light hard	2795	2806	
Shale, blue soft	2800	2802	
Lime, light hard	2802	2809	
Shale, blue soft	2809	2813	
Lime, light hard	2813	2817	
Shale, black soft	2817	2849	Reduced at 2942'
Lime, light hard	2849	2845	
Shale, blue soft	2845	2940	
Shale, light soft sandy	2940	2938	Gas
Sand, dark soft	2938	2961	Oil sand
Sand, brown soft	2961	2998	Oil sand