Contains Ashland

EPA

Form Approved
OMB No. 2010-0019
Approval Expires 12-31-89

EPA-OTS
000657070P

90-890000102

89 JUN -6 AM 9:59
OTS CONTROL OFFICE

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

Comprehensive Assessment Information Rule

REPORTING FORM

CONTAINS NO CBI

When completed, send this form to:

Document Processing Center
Office of Toxic Substances, TS-790
U.S. Environmental Protection Agency
401 M Street, SW
Washington, DC 20460
Attention: CAIR Reporting Office

For Agency Use Only:

Date of Receipt: _____

Document Control Number: _____

Docket Number: _____

EPA Form 7710-52

SECTION 1 GENERAL MANUFACTURER, IMPORTER, AND PROCESSOR INFORMATION

PART A GENERAL REPORTING INFORMATION

1.01 This Comprehensive Assessment Information Rule (CAIR) Reporting Form has been completed in response to the Federal Register Notice of..... [1][2] [2][2] [8][8]
mo. day year

CBI

[ ] a. If a Chemical Abstracts Service Number (CAS No.) is provided in the Federal Register, list the CAS No. ..... [0][2][6][4][7][1]-[6][2]-[5]

b. If a chemical substance CAS No. is not provided in the Federal Register, list either (i) the chemical name, (ii) the mixture name, or (iii) the trade name of the chemical substance as provided in the Federal Register.

(i) Chemical name as listed in the rule ..... Benzene, 1,3-Diisocyanatomethyl-

(ii) Name of mixture as listed in the rule .... NA

(iii) Trade name as listed in the rule ..... NA

c. If a chemical category is provided in the Federal Register, report the name of the category as listed in the rule, the chemical substance CAS No. you are reporting on which falls under the listed category, and the chemical name of the substance you are reporting on which falls under the listed category.

Name of category as listed in the rule ..... NA

CAS No. of chemical substance ..... [ ][ ][ ][ ][ ][ ]-[ ][ ]-[ ]

Name of chemical substance ..... NA

1.02 Identify your reporting status under CAIR by circling the appropriate response(s).

CBI

[ ]

Manufacturer 1

Importer 2

Processor 3

X/P manufacturer reporting for customer who is a processor 4

X/P processor reporting for customer who is a processor 5

[ ] Mark (X) this box if you attach a continuation sheet.

1.03 Does the substance you are reporting on have an "x/p" designation associated with it in the above-listed Federal Register Notice?

CBI [ ]

Yes ..... [X] Go to question 1.04

No ..... [ ] Go to question 1.05

1.04 a. Do you manufacture, import, or process the listed substance and distribute it under a trade name(s) different than that listed in the Federal Register Notice? Circle the appropriate response.

CBI [ ]

Yes 1

No ..... (2)

b. Check the appropriate box below:

[ ] You have chosen to notify your customers of their reporting obligations

Provide the trade name(s) .... _____

_____

[ ] You have chosen to report for your customers

[ ] You have submitted the trade name(s) to EPA one day after the effective date of the rule in the Federal Register Notice under which you are reporting.

1.05 If you buy a trade name product and are reporting because you were notified of your reporting requirements by your trade name supplier, provide that trade name.

CBI [ ]

Trade name ..... Mondur TD

Is the trade name product a mixture? Circle the appropriate response.

Yes 1

No ..... (2)

1.06 Certification -- The person who is responsible for the completion of this form must sign the certification statement below:

CBI [ ]

"I hereby certify that, to the best of my knowledge and belief, all information entered on this form is complete and accurate."

D. C. OLFE	D. C. Olfe	6/2/89
NAME	SIGNATURE	DATE SIGNED
VICE PRESIDENT, INTERNATIONAL	( ) 612-332-7371	
TITLE	TELEPHONE NO.	

[ ] Mark (X) this box if you attach a continuation sheet.

1.07 Exemptions From Reporting -- If you have provided EPA or another Federal agency with the required information on a CAIR Reporting Form for the listed substance within the past 3 years, and this information is current, accurate, and complete for the time period specified in the rule, then sign the certification below. You are required to complete section 1 of this CAIR form and provide any information now required but not previously submitted. Provide a copy of any previous submissions along with your Section 1 submission.

CBI

[__]

"I hereby certify that, to the best of my knowledge and belief, all required information which I have not included in this CAIR Reporting Form has been submitted to EPA within the past 3 years and is current, accurate, and complete for the time period specified in the rule."

NA		
NAME	SIGNATURE	DATE SIGNED
TITLE	(_____) _____ - _____ TELEPHONE NO.	DATE OF PREVIOUS SUBMISSION

1.08 CBI Certification -- If you have asserted any CBI claims in this report you must certify that the following statements truthfully and accurately apply to all of those confidentiality claims which you have asserted.

CBI

[__]

"My company has taken measures to protect the confidentiality of the information, and it will continue to take these measures; the information is not, and has not been, reasonably ascertainable by other persons (other than government bodies) by using legitimate means (other than discovery based on a showing of special need in a judicial or quasi-judicial proceeding) without my company's consent; the information is not publicly available elsewhere; and disclosure of the information would cause substantial harm to my company's competitive position."

NA		
NAME	SIGNATURE	DATE SIGNED
TITLE	(_____) _____ - _____ TELEPHONE NO.	

[__] Mark (X) this box if you attach a continuation sheet.

PART B CORPORATE DATA

1.09 Facility Identification

CBI Name [E][N][T][E][R][P][R][I][S][E][ ][C][O][M][P][A][N][I][E][S][ ][ ][ ][ ][ ][ ]

[ ] Address [2][8][4][1][ ][S][O][U][T][H][ ][A][S][H][L][A][N][D][ ][A][V][E][N][U][E]
Street

[C][H][I][C][A][G][O][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ]
City

[I][L] [6][0][6][0][8]--[ ][ ][ ][ ]
State Zip

Dun & Bradstreet Number .....[0][4]-[7][9][0]-[7][5][5][5]

EPA ID Number .....ILD..[0][4][7][9][0][7][5][5][5]

Employer ID Number .....41..[-][1][3][9][3][8][6][6]

Primary Standard Industrial Classification (SIC) Code .....[2][8][5][1]

Other SIC Code .....[ ][ ][ ][ ]

Other SIC Code .....[ ][ ][ ][ ]

1.10 Company Headquarters Identification

CBI Name [T][H][E][ ][V][A][L][S][P][A][R][ ][C][O][R][P][O][R][A][T][I][O][N][ ][ ][ ]

[ ] Address [1][1][0][1][ ][T][H][I][R][D][ ][S][T][R][E][E][T][ ][S][O][U][T][H][ ][ ]
Street

[M][I][N][N][E][A][P][O][L][I][S][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ][ ]
City

[M][N] [5][5][4][1][5]--[ ][ ][ ][ ]
State Zip

Dun & Bradstreet Number .....[0][5]-[0][7][3]-[6][4][5][3]

Employer ID Number .....36..[-][2][4][4][3][5][8][0]

[ ] Mark (X) this box if you attach a continuation sheet.

1.11 Parent Company Identification

CBI Name [T H E _ V A L S P A R _ C O R P O R A T I O N _ _ _]

[_] Address [I I O I _ T H I R D _ S T R E E T _ S O U T H _ _]
Street

[M I N N E A P O L I S _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _]
City

[M N] [5 5 4 1 5]--[_ _ _ _]
State Zip

Dun & Bradstreet Number .....[0 5]-[0 7 3]-[6 4 5 3]

1.12 Technical Contact

CBI Name [W I L L I A M _ J _ S T E W A R T _ _ _ _ _ _ _ _]

[_] Title [D I R E C T O R, _ R E G U L A T O R Y _ A F F _ _]

Address [I I O I _ T H I R D _ S T R E E T _ S O U T H _ _]
Street

[M I N N E A P O L I S _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _]
City

[M N] [5 5 4 1 5]--[_ _ _ _]
State Zip

Telephone Number .....[6 1 2]-[3 7 5]-[7 9 7 3]

1.13 This reporting year is from ..... [1 1] [8 7] to [1 1] [8 8]
Mo. Year Mo. Year

[_] Mark (X) this box if you attach a continuation sheet.

1.14 Facility Acquired -- If you purchased this facility during the reporting year, provide the following information about the seller:

CBI Name of Seller [__]

[__] Mailing Address [__]
Street

NA [__]
City

[__][__] [__][__][__][__][__]--[__][__][__][__]
State Zip

Employer ID Number .....[__][__][__][__][__][__][__][__]

Date of Sale .....[__][__] [__][__] [__][__]
Mo. Day Year

Contact Person [__]

Telephone Number .....[__][__][__]-[__][__][__]-[__][__][__][__]

1.15 Facility Sold -- If you sold this facility during the reporting year, provide the following information about the buyer:

CBI Name of Buyer [__]

[__] Mailing Address [__]
Street

NA [__]
City

[__][__] [__][__][__][__][__]--[__][__][__][__]
State Zip

Employer ID Number .....[__][__][__][__][__][__][__][__]

Date of Purchase .....[__][__] [__][__] [__][__]
Mo. Day Year

Contact Person [__]

Telephone Number .....[__][__][__]-[__][__][__]-[__][__][__][__]

[__] Mark (X) this box if you attach a continuation sheet.

1.16 For each classification listed below, state the quantity of the listed substance that was manufactured, imported, or processed at your facility during the reporting year.

CBI

[__]

Classification	Quantity (kg/yr)
Manufactured	NA
Imported	NA
Processed (include quantity repackaged)	UK
Of that quantity manufactured or imported, report that quantity:	
In storage at the beginning of the reporting year	NA
For on-site use or processing	NA
For direct commercial distribution (including export)	NA
In storage at the end of the reporting year	NA
Of that quantity processed, report that quantity:	
In storage at the beginning of the reporting year	UK
Processed as a reactant (chemical producer)	UK
Processed as a formulation component (mixture producer)	NA
Processed as an article component (article producer)	NA
Repackaged (including export)	NA
In storage at the end of the reporting year	UK

[__] Mark (X) this box if you attach a continuation sheet.

PART C IDENTIFICATION OF MIXTURES

1.17 Mixture -- If the listed substance on which you are required to report is a mixture or a component of a mixture, provide the following information for each component chemical. (If the mixture composition is variable, report an average percentage of each component chemical for all formulations.)

CBI

[__]

Component Name	Supplier Name	Average % Composition by Weight (specify precision, e.g., 45% ± 0.5%)
NA		
		Total 100%

[__] Mark (X) this box if you attach a continuation sheet.

2.04 State the quantity of the listed substance that your facility manufactured, imported, or processed during the 3 corporate fiscal years preceding the reporting year in descending order.

CBI

[ ] Year ending ..... [ ][ ] [8][6]
Mo. Year

Quantity manufactured ..... NA kg

Quantity imported ..... UK kg

Quantity processed ..... UK kg

Year ending ..... [ ][ ] [8][5]
Mo. Year

Quantity manufactured ..... NA kg

Quantity imported ..... UK kg

Quantity processed ..... UK kg

Year ending ..... [ ][ ] [8][4]
Mo. Year

Quantity manufactured ..... NA kg

Quantity imported ..... UK kg

Quantity processed ..... UK kg

2.05 Specify the manner in which you manufactured the listed substance. Circle all appropriate process types.

CBI

[ ]

Continuous process ..... NA 1

Semicontinuous process ..... NA 2

Batch process ..... NA 3

[ ] Mark (X) this box if you attach a continuation sheet.

2.06 Specify the manner in which you processed the listed substance. Circle all
CBI appropriate process types.

[ ]

Continuous process 1

Semicontinuous process 2

Batch process 3

2.07 State your facility's name-plate capacity for manufacturing or processing the listed substance. (If you are a batch manufacturer or batch processor, do not answer this
CBI question.)

[ ]

Manufacturing capacity ..... NA kg/yr

Processing capacity ..... NA kg/yr

2.08 If you intend to increase or decrease the quantity of the listed substance manufactured, imported, or processed at any time after your current corporate fiscal year, estimate the increase or decrease based upon the reporting year's production
CBI volume.

[ ]

	Manufacturing Quantity (kg)	Importing Quantity (kg)	Processing Quantity (kg)
Amount of increase	NA	NA	402500
Amount of decrease	NA	NA	NA

[ ] Mark (X) this box if you attach a continuation sheet.

2.09 For the three largest volume manufacturing or processing process types involving the listed substance, specify the number of days you manufactured or processed the listed substance during the reporting year. Also specify the average number of hours per day each process type was operated. (If only one or two operations are involved, list those.)

CBI

[__]

	Days/Year	Average Hours/Day
Process Type #1 (The process type involving the largest quantity of the listed substance.)		
Manufactured	NA	NA
Processed	260	24
Process Type #2 (The process type involving the 2nd largest quantity of the listed substance.)		
Manufactured	NA	NA
Processed	260	24
Process Type #3 (The process type involving the 3rd largest quantity of the listed substance.)		
Manufactured	NA	NA
Processed		

2.10 State the maximum daily inventory and average monthly inventory of the listed substance that was stored on-site during the reporting year in the form of a bulk chemical.

CBI

[__]

Maximum daily inventory ..... NA kg

Average monthly inventory ..... _____ kg

[__] Mark (X) this box if you attach a continuation sheet.

2.11 Related Product Types -- List any byproducts, coproducts, or impurities present with the listed substance in concentrations greater than 0.1 percent as it is manufactured, imported, or processed. The source of byproducts, coproducts, or impurities means the source from which the byproducts, coproducts, or impurities are made or introduced into the product (e.g., carryover from raw material, reaction product, etc.).

CBI

[ ]

CAS No.	Chemical Name	Byproduct, Coproduct or Impurity[1]	Concentration (%) (specify ± % precision)	Source of By-products, Co-products, or Impurities
	Unknown			

[1]Use the following codes to designate byproduct, coproduct, or impurity:

B = Byproduct
C = Coproduct
I = Impurity

[ ] Mark (X) this box if you attach a continuation sheet.

2.12 Existing Product Types -- List all existing product types which you manufactured, imported, or processed using the listed substance during the reporting year. List the quantity of listed substance you use for each product type as a percentage of the total volume of listed substance used during the reporting year. Also list the quantity of listed substance used captively on-site as a percentage of the value listed under column b., and the types of end-users for each product type. (Refer to the instructions for further explanation and an example.)

CBI

[ ]

a. Product Types[1]	b. % of Quantity Manufactured, Imported, or Processed	c. % of Quantity Used Captively On-Site	d. Type of End-Users[2]
K	100%	0	I

[1]Use the following codes to designate product types:

A = Solvent
B = Synthetic reactant
C = Catalyst/Initiator/Accelerator/Sensitizer
D = Inhibitor/Stabilizer/Scavenger/Antioxidant
E = Analytical reagent
F = Chelator/Coagulant/Sequestrant
G = Cleanser/Detergent/Degreaser
H = Lubricant/Friction modifier/Antiwear agent
I = Surfactant/Emulsifier
J = Flame retardant
K = Coating/Binder/Adhesive and additives
L = Moldable/Castable/Rubber and additives
M = Plasticizer
N = Dye/Pigment/Colorant/Ink and additives
O = Photographic/Reprographic chemical and additives
P = Electrodeposition/Plating chemicals
Q = Fuel and fuel additives
R = Explosive chemicals and additives
S = Fragrance/Flavor chemicals
T = Pollution control chemicals
U = Functional fluids and additives
V = Metal alloy and additives
W = Rheological modifier
X = Other (specify) _____

[2]Use the following codes to designate the type of end-users:

I = Industrial
CM = Commercial
CS = Consumer
H = Other (specify) _____

[ ] Mark (X) this box if you attach a continuation sheet.

2.13 Expected Product Types -- Identify all product types which you expect to manufacture, import, or process using the listed substance at any time after your current corporate fiscal year. For each use, specify the quantity you expect to manufacture, import, or process for each use as a percentage of the total volume of listed substance used during the reporting year. Also list the quantity of listed substance used captively on-site as a percentage of the value listed under column b., and the types of end-users for each product type. (Refer to the instructions for further explanation and an example.)

CBI [ ]

a. Product Types[1]	b. % of Quantity Manufactured, Imported, or Processed	c. % of Quantity Used Captively On-Site	d. Type of End-Users[2]
K	100%	0	I

[1]Use the following codes to designate product types:

A = Solvent
B = Synthetic reactant
C = Catalyst/Initiator/Accelerator/Sensitizer
D = Inhibitor/Stabilizer/Scavenger/Antioxidant
E = Analytical reagent
F = Chelator/Coagulant/Sequestrant
G = Cleanser/Detergent/Degreaser
H = Lubricant/Friction modifier/Antiwear agent
I = Surfactant/Emulsifier
J = Flame retardant
K = Coating/Binder/Adhesive and additives
L = Moldable/Castable/Rubber and additives
M = Plasticizer
N = Dye/Pigment/Colorant/Ink and additives
O = Photographic/Reprographic chemical and additives
P = Electrodeposition/Plating chemicals
Q = Fuel and fuel additives
R = Explosive chemicals and additives
S = Fragrance/Flavor chemicals
T = Pollution control chemicals
U = Functional fluids and additives
V = Metal alloy and additives
W = Rheological modifier
X = Other (specify) _____

[2]Use the following codes to designate the type of end-users:

I = Industrial
CM = Commercial
CS = Consumer
H = Other (specify) _____

[ ] Mark (X) this box if you attach a continuation sheet.

2.14 Final Product -- Complete the following table for each type of final product
CBI manufactured, imported, or processed at your facility that contains the listed substance other than as an impurity.

[__]

a. Product Type[1]	b. Final Product's Physical Form[2]	c. Average % Composition of Listed Substance in Final Product	d. Type of End-Users[3]
K	B	0	I

[1]Use the following codes to designate product types:

A = Solvent
B = Synthetic reactant
C = Catalyst/Initiator/Accelerator/Sensitizer
D = Inhibitor/Stabilizer/Scavenger/Antioxidant
E = Analytical reagent
F = Chelator/Coagulant/Sequestrant
G = Cleanser/Detergent/Degreaser
H = Lubricant/Friction modifier/Antiwear agent
I = Surfactant/Emulsifier
J = Flame retardant
K = Coating/Binder/Adhesive and additives
L = Moldable/Castable/Rubber and additives
M = Plasticizer
N = Dye/Pigment/Colorant/Ink and additives
O = Photographic/Reprographic chemical and additives
P = Electrodeposition/Plating chemicals
Q = Fuel and fuel additives
R = Explosive chemicals and additives
S = Fragrance/Flavor chemicals
T = Pollution control chemicals
U = Functional fluids and additives
V = Metal alloy and additives
W = Rheological modifier
X = Other (specify) _____

[2]Use the following codes to designate the final product's physical form:

A = Gas
B = Liquid
C = Aqueous solution
D = Paste
E = Slurry
F1 = Powder
F2 = Crystalline solid
F3 = Granules
F4 = Other solid
G = Gel
H = Other (specify) _____

[3]Use the following codes to designate the type of end-users:

I = Industrial
CM = Commercial
CS = Consumer
H = Other (specify) _____

[__] Mark (X) this box if you attach a continuation sheet.

2.15 Circle all applicable modes of transportation used to deliver bulk shipments of the listed substance to off-site customers.
CBI

[ ] Truck ..... NA 1

Railcar ..... NA 2

Barge, Vessel ..... NA 3

Pipeline ..... NA 4

Plane ..... NA 5

Other (specify) NA 6

2.16 Customer Use -- Estimate the quantity of the listed substance used by your customers or prepared by your customers during the reporting year for use under each category of end use listed (i-iv).
CBI

[ ]

Category of End Use

i. Industrial Products

Chemical or mixture ..... NA kg/yr

Article ..... _____ kg/yr

ii. Commercial Products

Chemical or mixture ..... NA kg/yr

Article ..... _____ kg/yr

iii. Consumer Products

Chemical or mixture ..... NA kg/yr

Article ..... _____ kg/yr

iv. Other

Distribution (excluding export) ..... NA kg/yr

Export ..... _____ kg/yr

Quantity of substance consumed as reactant ..... _____ kg/yr

Unknown customer uses ..... _____ kg/yr

[ ] Mark (X) this box if you attach a continuation sheet.

SECTION 3 PROCESSOR RAW MATERIAL IDENTIFICATION

PART A GENERAL DATA

3.01 Specify the quantity purchased and the average price paid for the listed substance for each major source of supply listed. Product trades are treated as purchases.
CBI The average price is the market value of the product that was traded for the listed substance.
[ ]

Source of Supply	Quantity (kg)	Average Price ($/kg)
The listed substance was manufactured on-site.	NA	NA
The listed substance was transferred from a different company site.	NA	NA
The listed substance was purchased directly from a manufacturer or importer.	NA	NA
The listed substance was purchased from a distributor or repackager.	183040	$2.35
The listed substance was purchased from a mixture producer.	NA	

3.02 Circle all applicable modes of transportation used to deliver the listed substance to your facility.
CBI
[ ]

Truck 1

Railcar 2

Barge, Vessel 3

Pipeline 4

Plane 5

Other (specify) _____ 6

[ ] Mark (X) this box if you attach a continuation sheet.

3.03 a. Circle all applicable containers used to transport the listed substance to your facility.

CBI

[ ]

Bags 1

Boxes 2

Free standing tank cylinders 3

Tank rail cars 4

Hopper cars 5

Tank trucks 6

Hopper trucks 7

Drums 8

Pipeline 9

Other (specify) _____ 10

b. If the listed substance is transported in pressurized tank cylinders, tank rail cars, or tank trucks, state the pressure of the tanks.

Tank cylinders ..... NA mmHg

Tank rail cars ..... NA mmHg

Tank trucks ..... NA mmHg

[ ] Mark (X) this box if you attach a continuation sheet.

PART B RAW MATERIAL IN THE FORM OF A MIXTURE

3.04 If you obtain the listed substance in the form of a mixture, list the trade name(s) of the mixture, the name of its supplier(s) or manufacturer(s), an estimate of the average percent composition by weight of the listed substance in the mixture, and the amount of mixture processed during the reporting year.

CBI

[ ]

Trade Name	Supplier or Manufacturer	Average % Composition by Weight (specify ± % precision)	Amount Processed (kg/yr)
NA			

[ ] Mark (X) this box if you attach a continuation sheet.

PART C RAW MATERIAL VOLUME

3.05 CBI [__] State the quantity of the listed substance used as a raw material during the reporting year in the form of a class I chemical, class II chemical, or polymer, and the percent composition, by weight, of the listed substance.

	Quantity Used (kg/yr)	% Composition by Weight of Listed Substance in Raw Material (specify ± % precision)
Class I chemical	UK	100± UK
Class II chemical		
Polymer		

[__] Mark (X) this box if you attach a continuation sheet.

SECTION 4 PHYSICAL/CHEMICAL PROPERTIES

General Instructions:

If you are reporting on a mixture as defined in the glossary, reply to questions in Section 4 that are inappropriate to mixtures by stating "NA -- mixture."

For questions 4.06-4.15, if you possess any hazard warning statement, label, MSDS, or other notice that addresses the information requested, you may submit a copy or reasonable facsimile in lieu of answering those questions which it addresses.

PART A PHYSICAL/CHEMICAL DATA SUMMARY

4.01 Specify the percent purity for the three major[1] technical grade(s) of the listed substance as it is manufactured, imported, or processed. Measure the purity of the substance in the final product form for manufacturing activities, at the time you import the substance, or at the point you begin to process the substance.

CBI [ ]

	Manufacture	Import	Process
Technical grade #1	_____% purity	_____% purity	UK % purity
Technical grade #2	_____% purity	_____% purity	UK % purity
Technical grade #3	_____% purity	_____% purity	UK % purity

[1]Major = Greatest quantity of listed substance manufactured, imported or processed.

4.02 Submit your most recently updated Material Safety Data Sheet (MSDS) for the listed substance, and for every formulation containing the listed substance. If you possess an MSDS that you developed and an MSDS developed by a different source, submit your version. Indicate whether at least one MSDS has been submitted by circling the appropriate response.

Yes ..... (1)

No 2

Indicate whether the MSDS was developed by your company or by a different source.

Your company 1

Another source ..... (2)

[X] Mark (X) this box if you attach a continuation sheet.

4.03 Submit a copy or reasonable facsimile of any hazard information (other than an MSDS) that is provided to your customers/users regarding the listed substance or any formulation containing the listed substance. Indicate whether this information has been submitted by circling the appropriate response.

Yes 1

No 2

4.04 For each activity that uses the listed substance, circle all the applicable number(s) corresponding to each physical state of the listed substance during the activity listed. Physical states for importing and processing activities are determined at the time you import or begin to process the listed substance. Physical states for manufacturing, storage, disposal and transport activities are determined using the final state of the product.

CBI

[ ]

	Physical State				
Activity	Solid	Slurry	Liquid	Liquified Gas	Gas
Manufacture	1	2	3	4	5
Import	1	2	3	4	5
Process	1	2	3	4	5
Store	1	2	3	4	5
Dispose	1	2	3	4	5
Transport	1	2	3	4	5

[ ] Mark (X) this box if you attach a continuation sheet.

4.05 Particle Size -- If the listed substance exists in particulate form during any of the following activities, indicate for each applicable physical state the size and the percentage distribution of the listed substance by activity. Do not include particles ≥10 microns in diameter. Measure the physical state and particle sizes for importing and processing activities at the time you import or begin to process the listed substance. Measure the physical state and particle sizes for manufacturing storage, disposal and transport activities using the final state of the product.

CBI

[ ]

Physical State		Manufacture	Import	Process	Store	Dispose	Transport
Dust	<1 micron			NA			
	1 to <5 microns			NA			
	5 to <10 microns			NA			
Powder	<1 micron			NA			
	1 to <5 microns			NA			
	5 to <10 microns			NA			
Fiber	<1 micron			NA			
	1 to <5 microns			NA			
	5 to <10 microns			NA			
Aerosol	<1 micron			NA			
	1 to <5 microns			NA			
	5 to <10 microns			NA			

[ ] Mark (X) this box if you attach a continuation sheet.

SECTION 5 ENVIRONMENTAL FATE

PART A RATE CONSTANTS AND TRANSFORMATION PRODUCTS

5.01 Indicate the rate constants for the following transformation processes.

a. Photolysis:

Absorption spectrum coefficient (peak) .... UK (1/M cm) at _____ nm

Reaction quantum yield, ø ..... UK at _____ nm

Direct photolysis rate constant, k_p, at ... UK 1/hr _____ latitude

b. Oxidation constants at 25°C:

For $^1O_2$ (singlet oxygen), k_{ox} ..... UK 1/M hr

For RO_2 (peroxy radical), k_{ox} ..... UK 1/M hr

c. Five-day biochemical oxygen demand, BOD_5 ... UK mg/l

d. Biotransformation rate constant:

For bacterial transformation in water, k_b... UK 1/hr

Specify culture ..... UK

e. Hydrolysis rate constants:

For base-promoted process, k_B ..... UK 1/M hr

For acid-promoted process, k_A ..... UK 1/M hr

For neutral process, k_N ..... UK 1/hr

f. Chemical reduction rate (specify conditions) UK

g. Other (such as spontaneous degradation) ... UK

[ ] Mark (X) this box if you attach a continuation sheet.

PART B PARTITION COEFFICIENTS

5.02 a. Specify the half-life of the listed substance in the following media.

Media	Half-life (specify units)
Groundwater	UK
Atmosphere	UK
Surface water	UK
Soil	UK

b. Identify the listed substance's known transformation products that have a half-life greater than 24 hours.

CAS No.	Name	Half-life (specify units)		Media
UK			in	
			in	
			in	
			in	

5.03 Specify the octanol-water partition coefficient, K_{ow} ... UK at 25°C

Method of calculation or determination ..... UK

5.04 Specify the soil-water partition coefficient, K_d ..... UK at 25°C

Soil type ..... UK

5.05 Specify the organic carbon-water partition coefficient, K_{oc} ..... UK at 25°C

5.06 Specify the Henry's Law Constant, H ..... UK atm-m^3/mole

[ ] Mark (X) this box if you attach a continuation sheet.

5.07 List the bioconcentration factor (BCF) of the listed substance, the species for which it was determined, and the type of test used in deriving the BCF.

Bioconcentration Factor	Species	Test[1]
UK		
UK		
UK		

[1]Use the following codes to designate the type of test:

F = Flowthrough
S = Static

[ ] Mark (X) this box if you attach a continuation sheet.

6.04 For each market listed below, state the quantity sold and the total sales value of the listed substance sold or transferred in bulk during the reporting year.

CBI

[ ]

Market	Quantity Sold or Transferred (kg/yr)	Total Sales Value ($/yr)
Retail sales	NA	
Distribution -- Wholesalers		
Distribution -- Retailers		
Intra-company transfer		
Repackagers		
Mixture producers		
Article producers		
Other chemical manufacturers or processors		
Exporters		
Other (specify)		

6.05 Substitutes -- List all known commercially feasible substitutes that you know exist for the listed substance and state the cost of each substitute. A commercially feasible substitute is one which is economically and technologically feasible to use in your current operation, and which results in a final product with comparable performance in its end uses.

CBI

[ ]

Substitute	Cost ($/kg)
UK	

[ ] Mark (X) this box if you attach a continuation sheet.

SECTION 7 MANUFACTURING AND PROCESSING INFORMATION

General Instructions:

For questions 7.04-7.06, provide a separate response for each process block flow diagram provided in questions 7.01, 7.02, and 7.03. Identify the process type from which the information is extracted.

PART A MANUFACTURING AND PROCESSING PROCESS TYPE DESCRIPTION

7.01 In accordance with the instructions, provide a process block flow diagram showing the major (greatest volume) process type involving the listed substance.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE



[ ] Mark (X) this box if you attach a continuation sheet.

7.03 In accordance with the instructions, provide a process block flow diagram showing all process emission streams and emission points that contain the listed substance and which, if combined, would total at least 90 percent of all facility emissions if not treated before emission into the environment. If all such emissions are released from one process type, provide a process block flow diagram using the instructions for question 7.01. If all such emissions are released from more than one process type, provide a process block flow diagram showing each process type as a separate block.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

No Emissions

[ ] Mark (X) this box if you attach a continuation sheet.

7.04 Describe the typical equipment types for each unit operation identified in your process block flow diagram(s). If a process block flow diagram is provided for more than one process type, photocopy this question and complete it separately for each process type.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Unit Operation ID Number	Typical Equipment Type	Operating Temperature Range (°C)	Operating Pressure Range (mm Hg)	Vessel Composition
7.1	Reactor	100	760	Stainless Steel
7.2	Filter	60	45600	Stainless Steel

[ ] Mark (X) this box if you attach a continuation sheet.

7.05 Describe each process stream identified in your process block flow diagram(s). If a process block flow diagram is provided for more than one process type, photocopy this question and complete it separately for each process type.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Process Stream ID Code	Process Stream Description	Physical State[1]	Stream Flow (kg/yr)
7A	TDI (RAW MATERIAL)	OL	115588
7B	REACTOR VENT	GU	UK
7C	RESIN (RAW MATERIAL)	OL	UK
7D	SOLVENT (RAW MATERIAL)	OL	UK
7E	PRODUCT MOISTURE CURE	OL	UK
7F	PRODUCT MOISTURE CURE	OL	UK

[1]Use the following codes to designate the physical state for each process stream:

GC = Gas (condensible at ambient temperature and pressure)
GU = Gas (uncondensible at ambient temperature and pressure)
SO = Solid
SY = Sludge or slurry
AL = Aqueous liquid
OL = Organic liquid
IL = Immiscible liquid (specify phases, e.g., 90% water, 10% toluene)

[ ] Mark (X) this box if you attach a continuation sheet.

7.06 Characterize each process stream identified in your process block flow diagram(s). If a process block flow diagram is provided for more than one process type, photocopy this question and complete it separately for each process type. (Refer to the instructions for further explanation and an example.)

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

a. Process Stream ID Code	b. Known Compounds[1]	c. Concentrations[2,3] (% or ppm)	d. Other Expected Compounds	e. Estimated Concentrations (% or ppm)
7A	TDI	100%(A)(V)	NONE	
7B	AIR	5%(A)(V)	NONE	
	INERT GAS	95%(A)(V)	NONE	
7C	RESIN	100%(A)(V)	NONE	

7.06 continued below

7D	SOLVENT	100%(A)(V)	NONE
7E-F	MOISTURE CURE URETHANE	100%(A)(V)	NONE

[ ] Mark (X) this box if you attach a continuation sheet.

7.06 (continued)

[1]For each additive package introduced into a process stream, specify the compounds that are present in each additive package, and the concentration of each component. Assign an additive package number to each additive package and list this number in column b. (Refer to the instructions for further explanation and an example. Refer to the glossary for the definition of additive package.)

Additive Package Number	Components of Additive Package	Concentrations (% or ppm)
1	NA	
2		
3		
4		
5		

[2]Use the following codes to designate how the concentration was determined:

A = Analytical result
E = Engineering judgement/calculation

[3]Use the following codes to designate how the concentration was measured:

V = Volume
W = Weight

[ ] Mark (X) this box if you attach a continuation sheet.

PART A RESIDUAL TREATMENT PROCESS DESCRIPTION

8.01 In accordance with the instructions, provide a residual treatment block flow diagram which describes the treatment process used for residuals identified in question 7.01.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

NONE

[ ] Mark (X) this box if you attach a continuation sheet.

PART B RESIDUAL GENERATION AND CHARACTERIZATION

8.05 Characterize each process stream identified in your residual treatment block flow diagram(s). If a residual treatment block flow diagram is provided for more than one process type, photocopy this question and complete it separately for each process type. (Refer to the instructions for further explanation and an example.)

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

a. Stream ID Code	b. Type of Hazardous Waste[1]	c. Physical State of Residual[2]	d. Known Compounds[3]	e. Concentrations (% or ppm)[4,5,6]	f. Other Expected Compounds	g. Estimated Concentrations (% or ppm)
NA						

8.05 continued below

[ ] Mark (X) this box if you attach a continuation sheet.

8.05 (continued)

[1]Use the following codes to designate the type of hazardous waste:

I = Ignitable
C = Corrosive
R = Reactive
E = EP toxic
T = Toxic
H = Acutely hazardous

[2]Use the following codes to designate the physical state of the residual:

GC = Gas (condensible at ambient temperature and pressure)
GU = Gas (uncondensible at ambient temperature and pressure)
SO = Solid
SY = Sludge or slurry
AL = Aqueous liquid
OL = Organic liquid
IL = Immiscible liquid (specify phases, e.g., 90% water, 10% toluene)

8.05 continued below

[ ] Mark (X) this box if you attach a continuation sheet.

8.05 (continued)

[3]For each additive package introduced into a process stream, specify the compounds that are present in each additive package, and the concentration of each component. Assign an additive package number to each additive package and list this number in column d. (Refer to the instructions for further explanation and an example. Refer to the glossary for the definition of additive package.)

Additive Package Number	Components of Additive Package	Concentrations (% or ppm)
1	NA	
2		
3		
4		
5		

[4]Use the following codes to designate how the concentration was determined:

A = Analytical result
E = Engineering judgement/calculation

8.05 continued below

[ ] Mark (X) this box if you attach a continuation sheet.

8.05 (continued)

[5]Use the following codes to designate how the concentration was measured:

V = Volume
W = Weight

[6]Specify the analytical test methods used and their detection limits in the table below. Assign a code to each test method used and list those codes in column e.

Code	Method	Detection Limit (± ug/l)
1	NA	
2		
3		
4		
5		
6		

[ ] Mark (X) this box if you attach a continuation sheet.

8.06 Characterize each process stream identified in your residual treatment block flow diagram(s). If a residual treatment block flow diagram is provided for more than one process type, photocopy this question and complete it separately for each process type. (Refer to the instructions for further explanation and an example.)

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

a. Stream ID Code	b. Waste Description Code[1]	c. Management Method Code[2]	d. Residual Quantities (kg/yr)	e. Management of Residual (%) On-Site	e. Management of Residual (%) Off-Site	f. Costs for Off-Site Management (per kg)	g. Changes in Management Methods
NA							

[1]Use the codes provided in Exhibit 8-1 to designate the waste descriptions

[2]Use the codes provided in Exhibit 8-2 to designate the management methods

[ ] Mark (X) this box if you attach a continuation sheet.

8.22 Describe the combustion chamber design parameters for each of the three largest (by capacity) incinerators that are used on-site to burn the residuals identified in your process block or residual treatment block flow diagram(s).

CBI

[__]

Incinerator	Combustion Chamber Temperature (°C)		Location of Temperature Monitor		Residence Time In Combustion Chamber (seconds)	
	Primary	Secondary	Primary	Secondary	Primary	Secondary
1	NA					
2						
3						

Indicate if Office of Solid Waste survey has been submitted in lieu of response by circling the appropriate response.

Yes 1

No 2

8.23 Complete the following table for the three largest (by capacity) incinerators that are used on-site to burn the residuals identified in your process block or residual treatment block flow diagram(s).

CBI

[__]

Incinerator	Air Pollution Control Device[1]	Types of Emissions Data Available
1	NA	
2		
3		

Indicate if Office of Solid Waste survey has been submitted in lieu of response by circling the appropriate response.

Yes 1

No 2

---

[1]Use the following codes to designate the air pollution control device:

S = Scrubber (include type of scrubber in parenthesis)
E = Electrostatic precipitator
O = Other (specify) _____

[__] Mark (X) this box if you attach a continuation sheet.

SECTION 9 WORKER EXPOSURE

General Instructions:

Questions 9.03-9.25 apply only to those processes and workers involved in manufacturing or processing the listed substance. Do not include workers involved in residual waste treatment unless they are involved in this treatment process on a regular basis (i.e., exclude maintenance workers, construction workers, etc.).

[ ] Mark (X) this box if you attach a continuation sheet.

PART A EMPLOYMENT AND POTENTIAL EXPOSURE PROFILE

9.01 Mark (X) the appropriate column to indicate whether your company maintains records on the following data elements for hourly and salaried workers. Specify for each data element the year in which you began maintaining records and the number of years the records for that data element are maintained. (Refer to the instructions for further explanation and an example.)

CBI

[ ]

Data Element	Data are Maintained for: Hourly Workers	Salaried Workers	Year in Which Data Collection Began	Number of Years Records Are Maintained
Date of hire	X	X	UK	UK
Age at hire	X	X	UK	UK
Work history of individual before employment at your facility	X	X	UK	UK
Sex	X	X	UK	UK
Race	X	X	UK	UK
Job titles	X	X	UK	UK
Start date for each job title	X	X	UK	UK
End date for each job title	X	X	UK	UK
Work area industrial hygiene monitoring data	X	X	UK	UK
Personal employee monitoring data	N/A	N/A	'	
Employee medical history	X	X	UK	UK
Employee smoking history	X	X	UK	UK
Accident history	X	X	UK	UK
Retirement date	X	X	UK	UK
Termination date	X	X	UK	UK
Vital status of retirees	N/A	N/A	UK	UK.
Cause of death data	N/A*	N/A	'	

* ONLY IF INFORMED. X FOR THOSE WHO DIED WHILE STILL EMPLOYED
UK = UNKNOWN.

[ ] Mark (X) this box if you attach a continuation sheet.

9.02 In accordance with the instructions, complete the following table for each activity in which you engage.

CBI

[ ]

a. Activity	b. Process Category	c. Yearly Quantity (kg)	d. Total Workers	e. Total Worker-Hours
Manufacture of the listed substance	Enclosed	NA		
	Controlled Release	NA		
	Open	NA		
On-site use as reactant	Enclosed	NA		
	Controlled Release	119#	6	12480
	Open	NA		
On-site use as nonreactant	Enclosed	NA		
	Controlled Release	NA		
	Open	NA		
On-site preparation of products	Enclosed	NA		
	Controlled Release	NA		
	Open	NA		

[ ] Mark (X) this box if you attach a continuation sheet.

9.03 Provide a descriptive job title for each labor category at your facility that encompasses workers who may potentially come in contact with or be exposed to the listed substance.

CBI

[ ]

Labor Category	Descriptive Job Title
A	Lead Man
B	Urethane Operator
C	
D	
E	
F	
G	
H	
I	
J	

[ ] Mark (X) this box if you attach a continuation sheet.

BEST COPY AVAILABLE

31 A

9.04 In accordance with the instructions, provide your process block flow diagram(s) and indicate associated work areas.

CBI

[ ] **Process type .....** MOISTURE CURE URETHANE



[ ] **Mark (X) this box if you attach a continuation sheet.**

9.05 **Describe the various work area(s) shown in question 9.04 that encompass workers who may potentially come in contact with or be exposed to the listed substance. Add any additional areas not shown in the process block flow diagram in question 7.01 or 7.02. Photocopy this question and complete it separately for each process type.**

CBI

[ ] **Process type .....** MOISTURE CURE URETHANE

Work Area ID	Description of Work Areas and Worker Activities
1	REACTOR Workers load reactor, monitor temp, take samples
2	FILTER* Workers operate machinery
3	CHARGING AREA Resin and solvent pumped
4	STORAGE Drum storage. Workers move drums and transfer
5	FILLING Product filled into drums
6	FINISHED GOODS STORAGE
7	
8	
9	
10	

* MCU - 10" Cuno in filling room

Urethane sparkler press in kettle room

[ ] **Mark (X) this box if you attach a continuation sheet.**

9.06 Complete the following table for each work area identified in question 9.05, and for each labor category at your facility that encompasses workers who may potentially come in contact with or be exposed to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 1. Reactor

Labor Category	Number of Workers Exposed	Mode of Exposure (e.g., direct skin contact)	Physical State of Listed Substance[1]	Average Length of Exposure Per Day[2]	Number of Days per Year Exposed
A,B	6	Direct Skin Contact	OL	B	204
		Inhalation	OL	B	204

[1]Use the following codes to designate the physical state of the listed substance at the point of exposure:

GC = Gas (condensible at ambient temperature and pressure)
GU = Gas (uncondensible at ambient temperature and pressure; includes fumes, vapors, etc.)
SO = Solid
SY = Sludge or slurry
AL = Aqueous liquid
OL = Organic liquid
IL = Immiscible liquid (specify phases, e.g., 90% water, 10% toluene)

[2]Use the following codes to designate average length of exposure per day:

A = 15 minutes or less
B = Greater than 15 minutes, but not exceeding 1 hour
C = Greater than one hour, but not exceeding 2 hours
D = Greater than 2 hours, but not exceeding 4 hours
E = Greater than 4 hours, but not exceeding 8 hours
F = Greater than 8 hours

[ ] Mark (X) this box if you attach a continuation sheet.

9.06 Complete the following table for each work area identified in question 9.05, and for each labor category at your facility that encompasses workers who may potentially come in contact with or be exposed to the listed substance. Photocopy this question
CBI and complete it separately for each process type and work area.

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 2. FILTER

Labor Category	Number of Workers Exposed	Mode of Exposure (e.g., direct skin contact)	Physical State of Listed Substance[1]	Average Length of Exposure Per Day[2]	Number of Days per Year Exposed
A	1	NA			
B	1	NA			

[1]Use the following codes to designate the physical state of the listed substance at the point of exposure:

GC = Gas (condensible at ambient temperature and pressure)
GU = Gas (uncondensible at ambient temperature and pressure; includes fumes, vapors, etc.)
SO = Solid
SY = Sludge or slurry
AL = Aqueous liquid
OL = Organic liquid
IL = Immiscible liquid (specify phases, e.g., 90% water, 10% toluene)

[2]Use the following codes to designate average length of exposure per day:

A = 15 minutes or less
B = Greater than 15 minutes, but not exceeding 1 hour
C = Greater than one hour, but not exceeding 2 hours
D = Greater than 2 hours, but not exceeding 4 hours
E = Greater than 4 hours, but not exceeding 8 hours
F = Greater than 8 hours

[ ] Mark (X) this box if you attach a continuation sheet.

9.06 Complete the following table for each work area identified in question 9.05, and for each labor category at your facility that encompasses workers who may potentially come in contact with or be exposed to the listed substance. Photocopy this question
CBI and complete it separately for each process type and work area.

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 3. CHARGING AREA

Labor Category	Number of Workers Exposed	Mode of Exposure (e.g., direct skin contact)	Physical State of Listed Substance[1]	Average Length of Exposure Per Day[2]	Number of Days per Year Exposed
A,B	1	NA			

[1]Use the following codes to designate the physical state of the listed substance at the point of exposure:

GC = Gas (condensible at ambient temperature and pressure)
GU = Gas (uncondensible at ambient temperature and pressure; includes fumes, vapors, etc.)
SO = Solid
SY = Sludge or slurry
AL = Aqueous liquid
OL = Organic liquid
IL = Immiscible liquid (specify phases, e.g., 90% water, 10% toluene)

[2]Use the following codes to designate average length of exposure per day:

A = 15 minutes or less
B = Greater than 15 minutes, but not exceeding 1 hour
C = Greater than one hour, but not exceeding 2 hours
D = Greater than 2 hours, but not exceeding 4 hours
E = Greater than 4 hours, but not exceeding 8 hours
F = Greater than 8 hours

[ ] Mark (X) this box if you attach a continuation sheet.

9.06 Complete the following table for each work area identified in question 9.05, and for each labor category at your facility that encompasses workers who may potentially come in contact with or be exposed to the listed substance. Photocopy this question
CBI and complete it separately for each process type and work area.

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 4. STORAGE

Labor Category	Number of Workers Exposed	Mode of Exposure (e.g., direct skin contact)	Physical State of Listed Substance[1]	Average Length of Exposure Per Day[2]	Number of Days per Year Exposed
A,B	1	Direct skin contact	OL	B	204
		Inhalation	OL	B	204

[1]Use the following codes to designate the physical state of the listed substance at the point of exposure:

GC = Gas (condensible at ambient temperature and pressure)
GU = Gas (uncondensible at ambient temperature and pressure; includes fumes, vapors, etc.)
SO = Solid
SY = Sludge or slurry
AL = Aqueous liquid
OL = Organic liquid
IL = Immiscible liquid (specify phases, e.g., 90% water, 10% toluene)

[2]Use the following codes to designate average length of exposure per day:

A = 15 minutes or less
B = Greater than 15 minutes, but not exceeding 1 hour
C = Greater than one hour, but not exceeding 2 hours
D = Greater than 2 hours, but not exceeding 4 hours
E = Greater than 4 hours, but not exceeding 8 hours
F = Greater than 8 hours

[ ] Mark (X) this box if you attach a continuation sheet.

9.06 Complete the following table for each work area identified in question 9.05, and for each labor category at your facility that encompasses workers who may potentially come in contact with or be exposed to the listed substance. Photocopy this question
CBI and complete it separately for each process type and work area.

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 5. FILLING

Labor Category	Number of Workers Exposed	Mode of Exposure (e.g., direct skin contact)	Physical State of Listed Substance[1]	Average Length of Exposure Per Day[2]	Number of Days per Year Exposed
B	6	NA			

[1]Use the following codes to designate the physical state of the listed substance at the point of exposure:

GC = Gas (condensible at ambient temperature and pressure)
GU = Gas (uncondensible at ambient temperature and pressure; includes fumes, vapors, etc.)
SO = Solid
SY = Sludge or slurry
AL = Aqueous liquid
OL = Organic liquid
IL = Immiscible liquid (specify phases, e.g., 90% water, 10% toluene)

[2]Use the following codes to designate average length of exposure per day:

A = 15 minutes or less
B = Greater than 15 minutes, but not exceeding 1 hour
C = Greater than one hour, but not exceeding 2 hours
D = Greater than 2 hours, but not exceeding 4 hours
E = Greater than 4 hours, but not exceeding 8 hours
F = Greater than 8 hours

[ ] Mark (X) this box if you attach a continuation sheet.

9.06 Complete the following table for each work area identified in question 9.05, and for each labor category at your facility that encompasses workers who may potentially come in contact with or be exposed to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 6. FINISHED GOODS STORAGE

Labor Category	Number of Workers Exposed	Mode of Exposure (e.g., direct skin contact)	Physical State of Listed Substance[1]	Average Length of Exposure Per Day[2]	Number of Days per Year Exposed
A,B	6	NA			

[1]Use the following codes to designate the physical state of the listed substance at the point of exposure:

GC = Gas (condensible at ambient temperature and pressure)
GU = Gas (uncondensible at ambient temperature and pressure; includes fumes, vapors, etc.)
SO = Solid
SY = Sludge or slurry
AL = Aqueous liquid
OL = Organic liquid
IL = Immiscible liquid (specify phases, e.g., 90% water, 10% toluene)

[2]Use the following codes to designate average length of exposure per day:

A = 15 minutes or less
B = Greater than 15 minutes, but not exceeding 1 hour
C = Greater than one hour, but not exceeding 2 hours
D = Greater than 2 hours, but not exceeding 4 hours
E = Greater than 4 hours, but not exceeding 8 hours
F = Greater than 8 hours

[ ] Mark (X) this box if you attach a continuation sheet.

9.07 For each labor category represented in question 9.06, indicate the 8-hour Time Weighted Average (TWA) exposure levels and the 15-minute peak exposure levels. Photocopy this question and complete it separately for each process type and work area.

CBI

[__] Process type ..... MOISTURE CURE URETHANE

Work area ..... 1. REACTOR

Labor Category	8-hour TWA Exposure Level (ppm, mg/m^3, other-specify)	15-Minute Peak Exposure Level (ppm, mg/m^3, other-specify)
A	UK	UK

* Calculations

Series 7000 SN 4065 TDI Monitor, permanently mounted
1/11/87, highest readings for 8 hr. period

[__] Mark (X) this box if you attach a continuation sheet.

9.07 For each labor category represented in question 9.06, indicate the 8-hour Time Weighted Average (TWA) exposure levels and the 15-minute peak exposure levels. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 2. FILTER

Labor Category	8-hour TWA Exposure Level (ppm, mg/m^3, other-specify)	15-Minute Peak Exposure Level (ppm, mg/m^3, other-specify)
A	UK	UK
B	UK	UK

[ ] Mark (X) this box if you attach a continuation sheet.

9.07 For each labor category represented in question 9.06, indicate the 8-hour Time Weighted Average (TWA) exposure levels and the 15-minute peak exposure levels. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 3. CHARGING AREA

Labor Category	8-hour TWA Exposure Level (ppm, mg/m^3, other-specify)	15-Minute Peak Exposure Level (ppm, mg/m^3, other-specify)
A	UK	UK

[ ] Mark (X) this box if you attach a continuation sheet.

9.07 **For each labor category represented in question 9.06, indicate the 8-hour Time Weighted Average (TWA) exposure levels and the 15-minute peak exposure levels. Photocopy this question and complete it separately for each process type and work area.**

CBI

[ ] **Process type .....** MOISTURE CURE URETHANE

Work area ..... 4. STORAGE RAW MATERIALS

Labor Category	8-hour TWA Exposure Level (ppm, mg/m^3, other-specify)	15-Minute Peak Exposure Level (ppm, mg/m^3, other-specify)
A,B	0.2 ppb*	UK

* Calculations

Series 7000 SN 4065 TDI monitor permanently mounted

1/11/87 highest reading for 8 hr period.

[ ] **Mark (X) this box if you attach a continuation sheet.**

9.07 For each labor category represented in question 9.06, indicate the 8-hour Time Weighted Average (TWA) exposure levels and the 15-minute peak exposure levels. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 5. FILLING

Labor Category	8-hour TWA Exposure Level (ppm, mg/m^3, other-specify)	15-Minute Peak Exposure Level (ppm, mg/m^3, other-specify)
A	UK	UK
B	UK	UK

[ ] Mark (X) this box if you attach a continuation sheet.

9.07 For each labor category represented in question 9.06, indicate the 8-hour Time Weighted Average (TWA) exposure levels and the 15-minute peak exposure levels. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 6 FINISHED GOODS STORAGE

Labor Category	8-hour TWA Exposure Level (ppm, mg/m^3, other-specify)	15-Minute Peak Exposure Level (ppm, mg/m^3, other-specify)
A	NA	NA
B	NA	NA

[ ] Mark (X) this box if you attach a continuation sheet.

PART B WORK PLACE MONITORING PROGRAM

9.08 If you monitor worker exposure to the listed substance, complete the following table.

CBI

[ ]

Sample/Test	Work Area ID	Testing Frequency (per year)	Number of Samples (per test)	Who Samples[1]	Analyzed In-House (Y/N)	Number of Years Records Maintained
Personal breathing zone	4	continuous	--	D	N	0
General work area (air)						
Wipe samples						
Adhesive patches						
Blood samples						
Urine samples						
Respiratory samples						
Allergy tests						
Other (specify)						
Other (specify)						
Other (specify)						

[1]Use the following codes to designate who takes the monitoring samples:

A = Plant industrial hygienist
B = Insurance carrier
C = OSHA consultant
D = Other (specify) Series 7000 TDI monitor see 9.10

[ ] Mark (X) this box if you attach a continuation sheet.

9.09 For each sample type identified in question 9.08, describe the type of sampling and analytical methodology used for each type of sample.
CBI

[ ]

Sample Type	Sampling and Analytical Methodology
General work area	Chemically impregnated dry reaction substrate - sample
	Gas reacts with chemicals on a chemscassette and forms a stain

9.10 If you conduct personal and/or ambient air monitoring for the listed substance, specify the following information for each equipment type used.
CBI

[ ]

Equipment Type[1]	Detection Limit[2]	Manufacturer	Averaging Time (hr)	Model Number
E	.001 D	MDA Scientific, Inc	24	Series 7100

[1]Use the following codes to designate personal air monitoring equipment types:

A = Passive dosimeter
B = Detector tube
C = Charcoal filtration tube with pump
D = Other (specify) _____

Use the following codes to designate ambient air monitoring equipment types:

E = Stationary monitors located within work area
F = Stationary monitors located within facility
G = Stationary monitors located at plant boundary
H = Mobile monitoring equipment (specify) _____
I = Other (specify) _____

[2]Use the following codes to designate detection limit units:

A = ppm
B = Fibers/cubic centimeter (f/cc)
C = Micrograms/cubic meter (μ/m^3)
D = Parts per billion

[ ] Mark (X) this box if you attach a continuation sheet.

9.11 If you conduct routine medical tests for monitoring the health effects of exposure to the listed substance, specify the type and frequency of the tests.

CBI

[ ] Test Description	Frequency (weekly, monthly, yearly, etc.)
Urinalysis	yearly
CBC	yearly
Chest X-ray	yearly
Pulmonary function	yearly

[ ] Mark (X) this box if you attach a continuation sheet.

PART C ENGINEERING CONTROLS

9.12 Describe the engineering controls that you use to reduce or eliminate worker exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 1. Reactor

Engineering Controls	Used (Y/N)	Year Installed	Upgraded (Y/N)	Year Upgraded
Ventilation:				
Local exhaust				
General dilution	Y	NA	NA	NA
Other (specify)				
Vessel emission controls				
Mechanical loading or packaging equipment				
Other (specify)				

[ ] Mark (X) this box if you attach a continuation sheet.

PART C ENGINEERING CONTROLS

9.12 Describe the engineering controls that you use to reduce or eliminate worker exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 2. Filter

Engineering Controls	Used (Y/N)	Year Installed	Upgraded (Y/N)	Year Upgraded
Ventilation:				
Local exhaust	NA			
General dilution	NA			
Other (specify)				
Vessel emission controls	NA			
Mechanical loading or packaging equipment	NA			
Other (specify)				
	1			

[ ] Mark (X) this box if you attach a continuation sheet.

PART C ENGINEERING CONTROLS

9.12 Describe the engineering controls that you use to reduce or eliminate worker exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 3 Charging Area

Engineering Controls	Used (Y/N)	Year Installed	Upgraded (Y/N)	Year Upgraded
Ventilation:				
Local exhaust	NA			
General dilution	NA			
Other (specify)				
Vessel emission controls	NA			
Mechanical loading or packaging equipment	NA			
Other (specify)				

[ ] Mark (X) this box if you attach a continuation sheet.

PART C ENGINEERING CONTROLS

9.12 Describe the engineering controls that you use to reduce or eliminate worker exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 4. Storage

Engineering Controls	Used (Y/N)	Year Installed	Upgraded (Y/N)	Year Upgraded
Ventilation:				
Local exhaust	Y	1987	N	NA
General dilution				
Other (specify)				
Vessel emission controls				
Mechanical loading or packaging equipment				
Other (specify)				

[ ] Mark (X) this box if you attach a continuation sheet.

PART C ENGINEERING CONTROLS

9.12 Describe the engineering controls that you use to reduce or eliminate worker exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 5. Filling

Engineering Controls	Used (Y/N)	Year Installed	Upgraded (Y/N)	Year Upgraded
Ventilation:				
Local exhaust	NA			
General dilution	NA			
Other (specify)				
Vessel emission controls	NA			
Mechanical loading or packaging equipment	NA			
Other (specify)				

[ ] Mark (X) this box if you attach a continuation sheet.

PART C ENGINEERING CONTROLS

9.12 Describe the engineering controls that you use to reduce or eliminate worker exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE DURE URETHANE

Work area .....6. Storage Area

Engineering Controls	Used (Y/N)	Year Installed	Upgraded (Y/N)	Year Upgraded
Ventilation:				
Local exhaust	NA			
General dilution				
Other (specify)				
Vessel emission controls				
Mechanical loading or packaging equipment				
Other (specify)				

[ ] Mark (X) this box if you attach a continuation sheet.

9.13 Describe all equipment or process modifications you have made within the 3 years prior to the reporting year that have resulted in a reduction of worker exposure to the listed substance. For each equipment or process modification described, state the percentage reduction in exposure that resulted. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 1. Reactor

Equipment or Process Modification	Reduction in Worker Exposure Per Year (%)
NA	UK

[ ] Mark (X) this box if you attach a continuation sheet.

9.13 Describe all equipment or process modifications you have made within the 3 years prior to the reporting year that have resulted in a reduction of worker exposure to the listed substance. For each equipment or process modification described, state the percentage reduction in exposure that resulted. Photocopy this question and complete it separately for each process type and work area.

CBI

[__] Process type ..... MOISTURE CURE URETHANE

Work area ..... 2. Filter

Equipment or Process Modification	Reduction in Worker Exposure Per Year (%)
NA	

[__] Mark (X) this box if you attach a continuation sheet.

9.13 Describe all equipment or process modifications you have made within the 3 years prior to the reporting year that have resulted in a reduction of worker exposure to the listed substance. For each equipment or process modification described, state the percentage reduction in exposure that resulted. Photocopy this question and complete it separately for each process type and work area.

CBI

[__] Process type ..... MOISTURE CURE URETHANE

Work area ..... 3. Charging

Equipment or Process Modification	Reduction in Worker Exposure Per Year (%)
NA	

[__] Mark (X) this box if you attach a continuation sheet.

9.13 Describe all equipment or process modifications you have made within the 3 years prior to the reporting year that have resulted in a reduction of worker exposure to the listed substance. For each equipment or process modification described, state the percentage reduction in exposure that resulted. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 4. Storage

Equipment or Process Modification	Reduction in Worker Exposure Per Year (%)
WEIGH BOOTH	UK

[ ] Mark (X) this box if you attach a continuation sheet.

9.13 Describe all equipment or process modifications you have made within the 3 years prior to the reporting year that have resulted in a reduction of worker exposure to the listed substance. For each equipment or process modification described, state the percentage reduction in exposure that resulted. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 5. Filling

Equipment or Process Modification	Reduction in Worker Exposure Per Year (%)
NA	

[ ] Mark (X) this box if you attach a continuation sheet.

9.13 Describe all equipment or process modifications you have made within the 3 years prior to the reporting year that have resulted in a reduction of worker exposure to the listed substance. For each equipment or process modification described, state the percentage reduction in exposure that resulted. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 6. Storage

Equipment or Process Modification	Reduction in Worker Exposure Per Year (%)
NA	

[ ] Mark (X) this box if you attach a continuation sheet.

PART D PERSONAL PROTECTIVE AND SAFETY EQUIPMENT

9.14 Describe the personal protective and safety equipment that your workers wear or use in each work area in order to reduce or eliminate their exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 1. Reactor

Equipment Types	Wear or Use (Y/N)
Respirators	Y
Safety goggles/glasses	Y
Face shields	N
Coveralls	N
Bib aprons	N
Chemical-resistant gloves	Y
Other (specify)	
Safety Shoes	Y
Hard Hats	Y

[ ] Mark (X) this box if you attach a continuation sheet.

PART D PERSONAL PROTECTIVE AND SAFETY EQUIPMENT

9.14 Describe the personal protective and safety equipment that your workers wear or use in each work area in order to reduce or eliminate their exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 2. Filter

Equipment Types	Wear or Use (Y/N)
Respirators	N
Safety goggles/glasses	Y
Face shields	N
Coveralls	N
Bib aprons	N
Chemical-resistant gloves	N
Other (specify)	
Safety Shoes	Y
Hard Hats	Y

[ ] Mark (X) this box if you attach a continuation sheet.

PART D PERSONAL PROTECTIVE AND SAFETY EQUIPMENT

9.14 Describe the personal protective and safety equipment that your workers wear or use in each work area in order to reduce or eliminate their exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 3. Charging

Equipment Types	Wear or Use (Y/N)
Respirators	Y
Safety goggles/glasses	Y
Face shields	N
Coveralls	N
Bib aprons	Y
Chemical-resistant gloves	Y
Other (specify)	
Safety Shoes	Y
Hard Hats	Y

[ ] Mark (X) this box if you attach a continuation sheet.

PART D PERSONAL PROTECTIVE AND SAFETY EQUIPMENT

9.14 Describe the personal protective and safety equipment that your workers wear or use in each work area in order to reduce or eliminate their exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 4. Storage

Equipment Types	Wear or Use (Y/N)
Respirators	Y
Safety goggles/glasses	Y
Face shields	N
Coveralls	N
Bib aprons	N
Chemical-resistant gloves	Y
Other (specify)	
Safety Shoes	Y
Hard Hats	Y

[ ] Mark (X) this box if you attach a continuation sheet.

PART D PERSONAL PROTECTIVE AND SAFETY EQUIPMENT

9.14 Describe the personal protective and safety equipment that your workers wear or use in each work area in order to reduce or eliminate their exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 5. Filling

Equipment Types	Wear or Use (Y/N)
Respirators	N
Safety goggles/glasses	Y
Face shields	N
Coveralls	N
Bib aprons	N
Chemical-resistant gloves	N
Other (specify)	
Safety Shoes	Y
Hard Hats	Y

[ ] Mark (X) this box if you attach a continuation sheet.

PART D PERSONAL PROTECTIVE AND SAFETY EQUIPMENT

9.14 Describe the personal protective and safety equipment that your workers wear or use in each work area in order to reduce or eliminate their exposure to the listed substance. Photocopy this question and complete it separately for each process type and work area.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work area ..... 6. Finished Goods Storage

Equipment Types	Wear or Use (Y/N)
Respirators	N
Safety goggles/glasses	Y
Face shields	N
Coveralls	N
Bib aprons	N
Chemical-resistant gloves	N
Other (specify)	
Safety Shoes	Y
Hard Hats	Y

[ ] Mark (X) this box if you attach a continuation sheet.

9.15 If workers use respirators when working with the listed substance, specify for each process type, the work areas where the respirators are used, the type of respirators used, the average usage, whether or not the respirators were fit tested, and the type and frequency of the fit tests. Photocopy this question and complete it separately for each process type.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Work Area	Respirator Type	Average Usage[1]	Fit Tested (Y/N)	Type of Fit Test[2]	Frequency of Fit Tests (per year)
1	Disposal neg. pressure/ particles	E	N	NA	NA
4	Disposal neg. pressure/ particles	E	N	NA	NA

[1]Use the following codes to designate average usage:

A = Daily
B = Weekly
C = Monthly
D = Once a year
E = Other (specify) 3 months

[2]Use the following codes to designate the type of fit test:

QL = Qualitative
QT = Quantitative

[ ] Mark (X) this box if you attach a continuation sheet.

PART E WORK PRACTICES

9.19 Describe all of the work practices and administrative controls used to reduce or eliminate worker exposure to the listed substance (e.g., restrict entrance only to authorized workers, mark areas with warning signs, insure worker detection and monitoring practices, provide worker training programs, etc.). Photocopy this question and complete it separately for each process type and work area.

CBI

[ ]

Process type ..... MOISTURE CURE URETHANE

Work area ..... 1. Reactor

OSHA Hazard Communication Training

9.20 Indicate (X) how often you perform each housekeeping task used to clean up routine leaks or spills of the listed substance. Photocopy this question and complete it separately for each process type and work area.

Process type ..... MOISTURE CURE URETHANE

Work area ..... 1. Reactor

Housekeeping Tasks	Less Than Once Per Day	1-2 Times Per Day	3-4 Times Per Day	More Than 4 Times Per Day
Sweeping		Y		
Vacuuming		N		
Water flushing of floors		N		
Other (specify)				
Neutralization	Y			

[ ] Mark (X) this box if you attach a continuation sheet.

PART E WORK PRACTICES

9.19 Describe all of the work practices and administrative controls used to reduce or eliminate worker exposure to the listed substance (e.g., restrict entrance only to authorized workers, mark areas with warning signs, insure worker detection and monitoring practices, provide worker training programs, etc.). Photocopy this question and complete it separately for each process type and work area.

CBI

[ ]

Process type ..... MOISTURE CURE URETHANE

Work area ..... 2. Filter

OSHA Hazard Communication Training

9.20 Indicate (X) how often you perform each housekeeping task used to clean up routine leaks or spills of the listed substance. Photocopy this question and complete it separately for each process type and work area.

Process type ..... MOISTURE CURE URETHANE

Work area ..... 2. Filter

Housekeeping Tasks	Less Than Once Per Day	1-2 Times Per Day	3-4 Times Per Day	More Than 4 Times Per Day
Sweeping		Y		
Vacuuming		N		
Water flushing of floors		N		
Other (specify)				

[ ] Mark (X) this box if you attach a continuation sheet.

PART E WORK PRACTICES

9.19 Describe all of the work practices and administrative controls used to reduce or eliminate worker exposure to the listed substance (e.g., restrict entrance only to authorized workers, mark areas with warning signs, insure worker detection and monitoring practices, provide worker training programs, etc.). Photocopy this question and complete it separately for each process type and work area.

CBI

[ ]

Process type ..... MOISTURE CURE URETHANE

Work area ..... 3. Charging

OSHA Hazard Communication Training

9.20 Indicate (X) how often you perform each housekeeping task used to clean up routine leaks or spills of the listed substance. Photocopy this question and complete it separately for each process type and work area.

Process type ..... MOISTURE CURE URETHANE

Work area ..... 3. Charging

Housekeeping Tasks	Less Than Once Per Day	1-2 Times Per Day	3-4 Times Per Day	More Than 4 Times Per Day
Sweeping		Y		
Vacuuming		N		
Water flushing of floors		N		
Other (specify)				

[ ] Mark (X) this box if you attach a continuation sheet.

PART E WORK PRACTICES

9.19 Describe all of the work practices and administrative controls used to reduce or eliminate worker exposure to the listed substance (e.g., restrict entrance only to authorized workers, mark areas with warning signs, insure worker detection and monitoring practices, provide worker training programs, etc.). Photocopy this question and complete it separately for each process type and work area.

CBI

[ ]

Process type ..... MOISTURE CURE URETHANE

Work area ..... 4. Storage

OSHA Hazard Communication Training

9.20 Indicate (X) how often you perform each housekeeping task used to clean up routine leaks or spills of the listed substance. Photocopy this question and complete it separately for each process type and work area.

Process type ..... MOISTURE DURE URETHANE

Work area ..... 4. Storage

Housekeeping Tasks	Less Than Once Per Day	1-2 Times Per Day	3-4 Times Per Day	More Than 4 Times Per Day
Sweeping	Y			
Vacuuming	N			
Water flushing of floors	N			
Other (specify)				
Neutralization				

[ ] Mark (X) this box if you attach a continuation sheet.

PART E WORK PRACTICES

9.19 Describe all of the work practices and administrative controls used to reduce or eliminate worker exposure to the listed substance (e.g., restrict entrance only to authorized workers, mark areas with warning signs, insure worker detection and monitoring practices, provide worker training programs, etc.). Photocopy this question and complete it separately for each process type and work area.

CBI

[ ]

Process type ..... MOISTURE CURE URETHANE

Work area ..... 5. Filling

OSHA Hazard Communication Training

9.20 Indicate (X) how often you perform each housekeeping task used to clean up routine leaks or spills of the listed substance. Photocopy this question and complete it separately for each process type and work area.

Process type ..... MOISTURE CURE URETHANE

Work area ..... 5. Filling

Housekeeping Tasks	Less Than Once Per Day	1-2 Times Per Day	3-4 Times Per Day	More Than 4 Times Per Day
Sweeping		Y		
Vacuuming		N		
Water flushing of floors		N		
Other (specify)				

[ ] Mark (X) this box if you attach a continuation sheet.

PART E WORK PRACTICES

9.19 Describe all of the work practices and administrative controls used to reduce or eliminate worker exposure to the listed substance (e.g., restrict entrance only to authorized workers, mark areas with warning signs, insure worker detection and monitoring practices, provide worker training programs, etc.). Photocopy this question and complete it separately for each process type and work area.

CBI

[ ]

Process type ..... MOISTURE CURE URETHANE

Work area ..... 6. Finished Goods Storage

OSHA Hazard Communication Training

9.20 Indicate (X) how often you perform each housekeeping task used to clean up routine leaks or spills of the listed substance. Photocopy this question and complete it separately for each process type and work area.

Process type ..... MOISTURE CURE URETHANE

Work area ..... 6. Finished Goods Storage

Housekeeping Tasks	Less Than Once Per Day	1-2 Times Per Day	3-4 Times Per Day	More Than 4 Times Per Day
Sweeping	Y			
Vacuuming	N			
Water flushing of floors	N			
Other (specify)				

[ ] Mark (X) this box if you attach a continuation sheet.

9.21 Do you have a written medical action plan for responding to routine or emergency exposure to the listed substance?

Routine exposure

NA

Yes 1

No 2

Emergency exposure

Yes 1

No 2

If yes, where are copies of the plan maintained?

Routine exposure: _____

Emergency exposure: _____

9.22 Do you have a written leak and spill cleanup plan that addresses the listed substance? Circle the appropriate response.

Yes 1

No 2

If yes, where are copies of the plan maintained? Plant Office/Prod. Supv. Office

Has this plan been coordinated with state or local government response organizations? Circle the appropriate response.

Yes 1

No 2

9.23 Who is responsible for monitoring worker safety at your facility? Circle the appropriate response.

Plant safety specialist ..... NA 1

Insurance carrier 2

OSHA consultant 3

Other (specify) _____ 4

[ ] Mark (X) this box if you attach a continuation sheet.

SECTION 10 ENVIRONMENTAL RELEASE

General Instructions:

Complete Part E (questions 10.23-10.35) for each non-routine release involving the listed substance that occurred during the reporting year. Report on all releases that are equal to or greater than the listed substance's reportable quantity value, RQ, unless the release is federally permitted as defined in 42 U.S.C. 9601, or is specifically excluded under the definition of release as defined in 40 CFR 302.3(22). Reportable quantities are codified in 40 CFR Part 302. If the listed substance is not a hazardous substance under the Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) and, thus, does not have an RQ, then report releases that exceed 2,270 kg. If such a substance however, is designated as a CERCLA hazardous substance, then report those releases that are equal to or greater than the RQ. The facility may have answered these questions or similar questions under the Agency's Accidental Release Information Program and may already have this information readily available. Assign a number to each release and use this number throughout this part to identify the release. Releases over more than a 24-hour period are not single releases, i.e., the release of a chemical substance equal to or greater than an RQ must be reported as a separate release for each 24-hour period the release exceeds the RQ.

For questions 10.25-10.35, answer the questions for each release identified in question 10.23. Photocopy these questions and complete them separately for each release.

PART A GENERAL INFORMATION

10.01 Where is your facility located? Circle all appropriate responses.

CBI

[ ] Industrial area 1

Urban area 2

Residential area 3

Agricultural area 4

Rural area 5

Adjacent to a park or a recreational area 6

Within 1 mile of a navigable waterway 7

Within 1 mile of a school, university, hospital, or nursing home facility 8

Within 1 mile of a non-navigable waterway 9

Other (specify) _____ 10

[ ] Mark (X) this box if you attach a continuation sheet.

10.02 Specify the exact location of your facility (from central point where process unit is located) in terms of latitude and longitude or Universal Transverse Mercader (UTM) coordinates.

Latitude ..... 41 ° 50 ' 29 "

Longitude ..... 87 ° 40 ' 00 "

UTM coordinates ..... Zone UK, Northing UK, Easting UK

10.03 If you monitor meteorological conditions in the vicinity of your facility, provide the following information.

Average annual precipitation ..... NA inches/year

Predominant wind direction .....

10.04 Indicate the depth to groundwater below your facility.

Depth to groundwater ..... NA meters

10.05 For each on-site activity listed, indicate (Y/N/NA) all routine releases of the listed substance to the environment. (Refer to the instructions for a definition of Y, N, and NA.)

CBI

[ ]

On-Site Activity	Environmental Release Air	Water	Land
Manufacturing	NA	NA	NA
Importing	NA	NA	NA
Processing	Y	N	N
Otherwise used	NA	NA	NA
Product or residual storage	Y	N	N
Disposal	NA	NA	NA
Transport	NA	NA	NA

[ ] Mark (X) this box if you attach a continuation sheet.

10.06 Provide the following information for the listed substance and specify the level of precision for each item. (Refer to the instructions for further explanation and an example.)

CBI

[ ]

Quantity discharged to the air	54.1	kg/yr	± 5	%
Quantity discharged in wastewaters	N	kg/yr	±	%
Quantity managed as other waste in on-site treatment, storage, or disposal units	N	kg/yr	±	%
Quantity managed as other waste in off-site treatment, storage, or disposal units	N	kg/yr	±	%

[ ] Mark (X) this box if you attach a continuation sheet.

10.08 Describe the control technologies used to minimize release of the listed substance for each process stream containing the listed substance as identified in your process block or residual treatment block flow diagram(s). Photocopy this question and complete it separately for each process type.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Stream ID Code	Control Technology	Percent Efficiency
NA		

[ ] Mark (X) this box if you attach a continuation sheet.

PART B RELEASE TO AIR

10.09 Point Source Emissions -- Identify each emission point source containing the listed substance in terms of a Stream ID Code as identified in your process block or residual treatment block flow diagram(s), and provide a description of each point source. Do not include raw material and product storage vents, or fugitive emission sources (e.g., equipment leaks). Photocopy this question and complete it separately for each process type.

CBI

[ ]

Process type ..... MOISTURE CURE URETHANE

Point Source ID Code	Description of Emission Point Source
NA	

[ ] Mark (X) this box if you attach a continuation sheet.

10.10 Emission Characteristics - - Characterize the emissions for each Point Source ID Code identified in question 10.09 by completing the following table.

CBI

[ ]

Point Source ID Code	Physical State[1]	Average Emissions (kg/day)	Frequency[2] (days/yr)	Duration[3] (min/day)	Average Emission Factor[4]	Maximum Emission Rate (kg/min)	Maximum Emission Rate Frequency (events/yr)	Maximum Emission Rate Duration (min/event)
NA								

[1]Use the following codes to designate physical state at the point of release:
G = Gas; V = Vapor; P = Particulate; A = Aerosol; O = Other (specify) _____

[2]Frequency of emission at any level of emission

[3]Duration of emission at any level of emission

[4]Average Emission Factor — Provide estimated (± 25 percent) emission factor (kg of emission per kg of production of listed substance)

[ ] Mark (X) this box if you attach a continuation sheet.

10.11 Stack Parameters -- Identify the stack parameters for each Point Source ID Code identified in question 10.09 by completing the following table.

CBI

[ ]

Point Source ID Code	Stack Height(m)	Stack Inner Diameter (at outlet) (m)	Exhaust Temperature (°C)	Emission Exit Velocity (m/sec)	Building Height(m)[1]	Building Width(m)[2]	Vent Type[3]
NA							

[1]Height of attached or adjacent building

[2]Width of attached or adjacent building

[3]Use the following codes to designate vent type:

H = Horizontal
V = Vertical

[ ] Mark (X) this box if you attach a continuation sheet.

10.12 If the listed substance is emitted in particulate form, indicate the particle size distribution for each Point Source ID Code identified in question 10.09. Photocopy this question and complete it separately for each emission point source.

CBI

[ ]

Point source ID code ..... NA

Size Range (microns)	Mass Fraction (% ± % precision)
< 1	NA
≥ 1 to < 10	NA
≥ 10 to < 30	NA
≥ 30 to < 50	NA
≥ 50 to < 100	NA
≥ 100 to < 500	NA
≥ 500	NA
	Total = 100%

[ ] Mark (X) this box if you attach a continuation sheet.

PART C FUGITIVE EMISSIONS

10.13 Equipment Leaks -- Complete the following table by providing the number of equipment types listed which are exposed to the listed substance and which are in service according to the specified weight percent of the listed substance passing through the component. Do this for each process type identified in your process block or residual treatment block flow diagram(s). Do not include equipment types that are not exposed to the listed substance. If this is a batch or intermittently operated process, give an overall percentage of time per year that the process type is exposed to the listed substance. Photocopy this question and complete it separately for each process type.

CBI

[ ] Process type ..... MOISTURE CURE URETHANE

Percentage of time per year that the listed substance is exposed to this process type ..... 8 %

Equipment Type	Number of Components in Service by Weight Percent of Listed Substance in Process Stream					
	Less than 5%	5-10%	11-25%	26-75%	76-99%	Greater than 99%
Pump seals[1]						
Packed						
Mechanical						X
Double mechanical[2]						
Compressor seals[1]						
Flanges						X
Valves						
Gas[3]						
Liquid						X
Pressure relief devices[4] (Gas or vapor only)						
Sample connections						
Gas						
Liquid						X
Open-ended lines[5] (e.g., purge, vent)						
Gas						
Liquid						X

[1]List the number of pump and compressor seals, rather than the number of pumps or compressors

10.13 continued on next page

[ ] Mark (X) this box if you attach a continuation sheet.

10.13 (continued)

[2]If double mechanical seals are operated with the barrier (B) fluid at a pressure greater than the pump stuffing box pressure and/or equipped with a sensor (S) that will detect failure of the seal system, the barrier fluid system, or both, indicate with a "B" and/or an "S", respectively

[3]Conditions existing in the valve during normal operation

[4]Report all pressure relief devices in service, including those equipped with control devices

[5]Lines closed during normal operation that would be used during maintenance operations

10.14 Pressure Relief Devices with Controls -- Complete the following table for those pressure relief devices identified in 10.13 to indicate which pressure relief devices in service are controlled. If a pressure relief device is not controlled, enter "None" under column c.

CBI

[ ]

a. Number of Pressure Relief Devices	b. Percent Chemical in Vessel[1]	c. Control Device	d. Estimated Control Efficiency[2]
NA			

[1]Refer to the table in question 10.13 and record the percent range given under the heading entitled "Number of Components in Service by Weight Percent of Listed Substance" (e.g., <5%, 5-10%, 11-25%, etc.)

[2]The EPA assigns a control efficiency of 100 percent for equipment leaks controlled with rupture discs under normal operating conditions. The EPA assigns a control efficiency of 98 percent for emissions routed to a flare under normal operating conditions

[ ] Mark (X) this box if you attach a continuation sheet.

10.15 Equipment Leak Detection -- If a formal leak detection and repair program is in place, complete the following table regarding those leak detection and repair procedures. Photocopy this question and complete it separately for each process type.

CBI

[ ] Process type ..... NONE

Equipment Type	Leak Detection Concentration (ppm or mg/m^3) Measured at ____ Inches from Source	Detection Device[1]	Frequency of Leak Detection (per year)	Repairs Initiated (days after detection)	Repairs Completed (days after initiated)
Pump seals					
Packed					
Mechanical					
Double mechanical					
Compressor seals					
Flanges					
Valves					
Gas					
Liquid					
Pressure relief devices (gas or vapor only)					
Sample connections					
Gas					
Liquid					
Open-ended lines					
Gas					
Liquid					

[1]Use the following codes to designate detection device:

POVA = Portable organic vapor analyzer
FPM = Fixed point monitoring
O = Other (specify) _____

[ ] Mark (X) this box if you attach a continuation sheet.

BEST COPY AVAILABLE

10.16 Raw Material, Intermediate and Product Storage Emissions - - Complete the following table by providing the information on each liquid raw material, intermediate, and product storage vessel containing the listed substance as identified in your process block or residual treatment block flow diagram(s).

CBI

[ ]

Vessel Type[1]	Floating Roof Seals[2]	Composition of Stored Materials[3]	Throughput (liters per year)	Vessel Filling Rate (gpm)	Vessel Filling Duration (min)	Vessel Inner Diameter (m)	Vessel Height (m)	Operating Vessel Volume (l)	Vessel Emission Controls[4]	Design Flow Rate[5]	Vent Diameter (cm)	Control Efficiency (%)	Basis for Estimate[6]
NA													

[1]Use the following codes to designate vessel type:

F = Fixed roof
CIF = Contact internal floating roof
NCIF = Noncontact internal floating roof
EFR = External floating roof
P = Pressure vessel (indicate pressure rating)
H = Horizontal
U = Underground

[2]Use the following codes to designate floating roof seals:

MS1 = Mechanical shoe, primary
MS2 = Shoe-mounted secondary
MS2R = Rim-mounted, secondary
LM1 = Liquid-mounted resilient filled seal, primary
LM2 = Rim-mounted shield
LMW = Weather shield
VM1 = Vapor mounted resilient filled seal, primary
VM2 = Rim-mounted secondary
VMW = Weather shield

[3]Indicate weight percent of the listed substance. Include the total volatile organic content in parenthesis

[4]Other than floating roofs

[5]Gas/vapor flow rate the emission control device was designed to handle (specify flow rate units)

[6]Use the following codes to designate basis for estimate of control efficiency:

C = Calculations
S = Sampling

[ ] Mark (X) this box if you attach a continuation sheet.

PART E NON-ROUTINE RELEASES

10.23 Indicate the date and time when the release occurred and when the release ceased or was stopped. If there were more than six releases, attach a continuation sheet and list all releases.

Release	Date Started	Time (am/pm)	Date Stopped	Time (am/pm)
1	NONE			
2				
3				
4				
5				
6				

10.24 Specify the weather conditions at the time of each release.

Release	Wind Speed (km/hr)	Wind Direction	Humidity (%)	Temperature (°C)	Precipitation (Y/N)
1	NA				
2					
3					
4					
5					
6					

[ ] Mark (X) this box if you attach a continuation sheet.

APPENDIX I: List of Continuation Sheets

Attach continuation sheets for sections of this form and optional information after this page. In column 1, clearly identify the continuation sheet by listing the question number to which it relates. In column 2, enter the inclusive page numbers of the continuation sheet for each question number.

Question Number (1)	Continuation Sheet Page Numbers (2)
4.02	1-8 incl.
4.02	1-5 incl.
4.02	1-2 incl.
4.02	1-2 incl.

[ ] Mark (X) this box if you attach a continuation sheet.

MATERIAL SAFETY DATA SHEET

pg 1

Mobay Corporation
A Bayer USA INC. COMPANY

Bayer

DIVISION ADDRESS

MOBAY CORPORATION
Polyurethane Division
Mobay Road
Pittsburgh, PA 15205-9741

ISSUE DATE 1/2/89
SUPERSEDES 1/12/87

TRANSPORTATION EMERGENCY: CALL CHEMTREC
TELEPHONE NO: 800-424-9300; DISTRICT OF COLUMBIA: 202-483-7616

MOBAY NON-TRANSPORTATION EMERGENCY NO.:
(412) 923-1800

I. PRODUCT IDENTIFICATION

PRODUCT NAME.....: Mondur TD
PRODUCT CODE NUMBER.....: E-001
CHEMICAL FAMILY.....: Aromatic Isocyanate
CHEMICAL NAME.....: Toluene Diisocyanate (TDI)
SYNONYMS.....: Benzene,1,3-Diisocyanato Methyl-
CAS NUMBER.....: 26471-62-5
T.S.C.A. STATUS.....: This product is listed on the TSCA Inventory.
OSHA HAZARD COMMUNICATION
STATUS.....: This product is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.
CHEMICAL FORMULA.....: $C_9H_6N_2O_2$

II. HAZARDOUS INGREDIENTS

COMPONENTS:	%:	OSHA-PEL	ACGIH-TLV
2,4-Toluene Diisocyanate (TDI) CAS# 584-84-9	65	0.02 ppm Ceiling	0.005 ppm TWA 0.02 ppm STEL
2,6-Toluene Diisocyanate (TDI) CAS# 91-08-7	35	Not Established	Not Established

III. PHYSICAL DATA

APPEARANCE.....: Liquid
COLOR.....: Water White to Pale Yellow
ODOR.....: Sharp, Pungent
ODOR THRESHOLD.....: Greater than TLV of 0.005 ppm
MOLECULAR WEIGHT.....: 174
MELT POINT/FREEZE POINT...: Approx. 55°F (13°C) for TDI
BOILING POINT.....: Approx. 484°F (251°C) for TDI
VAPOR PRESSURE.....: Approx. 0.025 mm Hg @ 77°F (25°C) for TDI
VAPOR DENSITY (AIR=1).....: 6.0 for TDI
pH.....: Not Applicable
SPECIFIC GRAVITY.....: 1.22 @ 77°F (25°C)
BULK DENSITY.....: 10.18 lbs/gal
SOLUBILITY IN WATER.....: Not Soluble. Reacts slowly with water at normal room temperature to liberate CO_2 gas.
% VOLATILE BY VOLUME.....: Negligible

IV. FIRE & EXPLOSION DATA

FLASH POINT $^{o}F(^{o}C)$.....: $260^{o}F$ ($127^{o}C$) Pensky Martens Closed Cup
FLAMMABLE LIMITS -
Lel.....: 0.9% for TDI
Uel.....: 9.5% for TDI
EXTINGUISHING MEDIA.....: Dry chemical (e.g. monoammonium phosphate, potassium sulfate, and potassium chloride), carbon dioxide, high expansion (proteinic) chemical foam, water spray for large fires. Caution: Reaction between water or foam and hot TDI can be vigorous.
SPECIAL FIRE FIGHTING PROCEDURES/UNUSUAL FIRE OR EXPLOSION HAZARDS:
Full emergency equipment with self-contained breathing apparatus and full protective clothing (such as rubber gloves, boots, bands around legs, arms and waist) should be worn by fire fighters. No skin surface should be exposed. During a fire, TDI vapors and other irritating, highly toxic gases may generated by thermal decomposition or combustion. (See Section VIII). At temperatures greater than $350^{o}F$ ($177^{o}C$) TDI forms carbodiimides with the release of CO_2 which can cause pressure build-up in closed containers. Explosive rupture is possible. Therefore, use cold water to cool fire-exposed containers.

V. HUMAN HEALTH DATA

PRIMARY ROUTE(S) OF ENTRY.....: Inhalation. Skin contact from liquid, vapors or aerosols.
EFFECTS AND SYMPTOMS OF OVEREXPOSURE
INHALATION

Acute Exposure. TDI vapors or mist at concentrations above the TLV can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing obstruction). Persons with a preexisting, nonspecific bronchial hyperreactivity can respond to concentrations below the TLV with similar symptoms as well as asthma attack. Exposure well above the TLV may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). These effects are usually reversible. Chemical or hypersensitive pneumonitis, with flu-like symptoms (e.g., fever, chills), has also been reported. These symptoms can be delayed up to several hours after exposure.

Chronic Exposure. As a result of previous repeated overexposures or a single large dose, certain individuals may develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthmatic attack, could be immediate or delayed up to several hours after exposure. Similar to many non-specific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air or other irritants. This increased lung sensitivity can persist for weeks and in severe cases for several years. Chronic overexposure to isocyanate has also been reported to cause lung damage (including decrease in lung function) which may be permanent. Sensitization can either be temporary or permanent.

V. HUMAN HEALTH DATA - Continued

SKIN CONTACT

Acute Exposure. Isocyanates react with skin protein and moisture and can cause irritation which may include the following symptoms: reddening, swelling, rash, scaling or blistering. Cured material is difficult to remove.

Chronic Exposure. Prolonged contact can cause reddening, swelling, rash, scaling, blistering, and, in some cases, skin sensitization. Individuals who have developed a skin sensitization can develop these symptoms as a result of contact with very small amounts of liquid material or as a result of exposure to vapor.

EYE CONTACT

Acute Exposure. Liquid, aerosols or vapors are severely irritating and can cause pain, tearing, reddening and swelling. If left untreated, corneal damage can occur and injury is slow to heal. However, damage is usually reversible. See Section VI for treatment.

Chronic Exposure. Prolonged vapor contact may cause conjunctivitis.

INGESTION

Acute Exposure. Can result in irritation and corrosive action in the mouth, stomach tissue and digestive tract. Symptoms can include sore throat, abdominal pain, nausea, vomiting and diarrhea.

Chronic Exposure. None found.

MEDICAL CONDITIONS

AGGRAVATED BY EXPOSURE..: Asthma, other respiratory disorders (bronchitis, emphysema, bronchial hyperreactivity), skin allergies, eczema.

CARCINOGENICITY.....: No carcinogenic activity was observed in lifetime inhalation studies in rats and mice (International Isocyanate Institute).

NTP.....: The National Toxicology Program reported that TDI caused an increase in the number of tumors in exposed rats over those counted in non-exposed rats. The TDI was administered in corn-oil and introduced into the stomach through a tube. Based on this study, the NTP has listed TDI as a substance that may reasonably be anticipated to be a carcinogen in its Fourth Annual Report on Carcinogens.

IARC.....: IARC has announced that it will list TDI as a substance for which there is sufficient evidence for its carcinogenicity in experimental animals but inadequate evidence for the carcinogenicity of TDI to humans (IARC Monograph 39).

OSHA.....: Not listed.

EXPOSURE LIMITS

OSHA PEL.....: 0.02 ppm Ceiling

ACGIH TLV.....: 0.005 ppm TWA/0.02 ppm STEL

VI. EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT.....: Flush with copious amounts of water, preferably lukewarm for at least 15 minutes holding eyelids open all the time. Refer individual to physician or an ophthalmologist for immediate follow-up.
SKIN CONTACT.....: Remove contaminated clothing immediately. Wash affected areas thoroughly with soap and water for at least 15 minutes. Tincture of green soap and water is also effective in removing isocyanates. Wash contaminated clothing thoroughly before reuse. For severe exposures, get under safety shower after removing clothing, then get medical attention. For lesser exposures, seek medical attention if irritation develops or persists after the area is washed.
INHALATION.....: Move to an area free from risk of further exposure. Administer oxygen or artificial respiration as needed. Obtain medical attention. Asthmatic-type symptoms may develop and may be immediate or delayed up to several hours. Consult physician.
INGESTION.....: Do not induce vomiting. Give 1 to 2 cups of milk or water to drink. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. Consult physician.
NOTE TO PHYSICIAN.....: Eyes. Stain for evidence of corneal injury. If cornea is burned, instill antibiotic steroid preparation frequently. Workplace vapors have produced reversible corneal epithelial edema impairing vision. Skin. This compound is a known skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burns. **Ingestion**. Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of this compound. Respiratory. This compound is a known pulmonary sensitizer. Treatment is essentially symptomatic. An individual having a skin or pulmonary sensitization reaction to this material should be removed from exposure to any isocyanate.

VII. EMPLOYEE PROTECTION RECOMMENDATIONS

EYE PROTECTION.....: Liquid chemical goggles or full-face shield. Contact lenses should not be worn. If vapor exposure is causing irritation, use a full-face, air-supplied respirator.
SKIN PROTECTION.....: Chemical resistant gloves (butyl rubber, nitrile rubber, polyvinyl alcohol). However, please note that PVA degrades in water. Cover as much of the exposed skin area as possible with appropriate clothing. If skin creams are used, keep the area covered only by the cream to a minimum.
RESPIRATORY PROTECTION....: An approved positive pressure air-supplied respirator is required whenever TDI concentrations are not known or exceed the Short-Term Exposure or Ceiling Limit of 0.02 ppm or exceed the 8-hour Time Weighted Average TLV of 0.005 ppm. An approved air-supplied respirator with full facepiece must also be worn during spray application, even if exhaust ventilation is used. For emergency and other conditions where the exposure limits may be greatly exceeded, use an approved, positive pressure self-contained breathing apparatus. TDI has poor warning properties since the odor at which TDI can be smelled is substantially higher than 0.02 ppm. Observe OSHA regulations for respirator use (29 CFR 1910.134).

VII. EMPLOYEE PROTECTION RECOMMENDATIONS - Continued

VENTILATION.....: Local exhaust should be used to maintain levels below the TLV whenever TDI is handled, processed, or spray-applied. At normal room temperatures (70°F) TDI levels quickly exceed the TLV unless properly ventilated. Standard reference sources regarding industrial ventilation (e.g., ACGIH Industrial Ventilation) should be consulted for guidance about adequate ventilation.

MONITORING.....: TDI exposure levels must be monitored by accepted monitoring techniques to ensure that the TLV is not exceeded. (Contact Mobay for guidance). See Volume 1 (Chapter 17) and Volume 3 (Chapter 3) in Patty's Industrial Hygiene and Toxicology for sampling strategy.

MEDICAL SURVEILLANCE.....: Medical supervision of all employees who handle or come in contact with TDI is recommended. These should include preemployment and periodic medical examinations with respiratory function tests (FEV, FVC as a minimum). Persons with asthmatic-type conditions, chronic bronchitis, other chronic respiratory diseases or recurrent skin eczema or sensitization should be excluded from working with TDI. Once a person is diagnosed as sensitized to TDI, no further exposure can be permitted.

OTHER.....: Safety showers and eyewash stations should be available. Educate and train employees in safe use of product. Follow all label instructions.

VIII. REACTIVITY DATA

STABILITY.....: Stable under normal conditions.

POLYMERIZATION.....: May occur if in contact with moisture or other materials which react with isocyanates. Self-reaction may occur at temperatures over 350°F (177°C) or at lower temperatures if sufficient time is involved. See Section IV.

INCOMPATIBILITY
(MATERIALS TO AVOID)....: Water, amines, strong bases, alcohols. Will cause some corrosion to copper alloys and aluminum. Reacts with water to form heat, CO_2 and insoluble ureas.

HAZARDOUS DECOMPOSITION
PRODUCTS.....: By high heat and fire: carbon monoxide, oxides of nitrogen, traces of HCN, TDI vapors and mist.

IX. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment, including respiratory equipment during clean-up. (See Section VII).

Major Spill: Call Mobay at 412/923-1800. If transportation spill, call CHEMTREC 800/424-9300. If temporary control of isocyanate vapor is required, a blanket of protein foam (available at most fire departments) may be placed over the spill. Large quantities may be pumped into closed, but not sealed, container for disposal.

IX. SPILL OR LEAK PROCEDURES - Contineud

Minor Spill: Absorb isocyanate with sawdust or other absorbent, shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%), or; water (90%), concentrated ammonia (3-8%) and detergent (2%). Add about 10 parts or neutralizer per part of isocyanate, with mixing. Allow to stand uncovered for 48 hours to let CO_2 escape.
Clean-up: Decontaminate floor with decontamination solution letting stand for at least 15 minutes.
CERCLA (SUPERFUND) REPORTABLE QUANTITY: 100 pounds for TDI
WASTE DISPOSAL METHOD.....: Follow all federal, state or local regulations. TDI must be disposed of in a permitted incinerator or landfill. Incineration is the preferred method for liquids. Solids are usually incinerated or landfilled. Empty containers must be handled with care due to product residue. Decontaminate containers prior to disposal. Empty decontaminated containers should be crushed to prevent reuse. DO NOT HEAT OR CUT EMPTY CONTAINER WITH ELECTRIC OR GAS TORCH. (See Sections IV and VIII). Vapors and gases may be highly toxic.
RCRA STATUS.....: TDI is listed as a hazardous waste (No. U-223) under Title 40 Code of Federal Regulations, Section 261.33 (f). The residue from decontaminating a TDI spill is also classified as a hazardous waste under Section 261.3 (c)(2) or RCRA.
SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA), TITLE III:
Section 302 - Extremely Hazardous Substances:
2,4-Toluene Diisocyanate (TDI) CAS# 584-84-9 = 65%
2,6-Toluene Diisocyanate (TDI) CAS# 91-08-7 = 35%
Section 313 - Toxic Chemicals:
2,4-Toluene Diisocyanate (TDI) CAS# 584-84-9 = 65%
2,6-Toluene Diisocyanate (TDI) CAS# 91-08-7 = 35%

X. SPECIAL PRECAUTIONS & STORAGE DATA

STORAGE TEMPERATURE
(MIN./MAX.).....: $70^{o}F$ ($21^{o}C$)/$90^{o}F$ ($32^{o}C$)
AVERAGE SHELF LIFE.....: 12 months
SPECIAL SENSITIVITY
(HEAT, LIGHT, MOISTURE).: If container is exposed to high heat, $375^{o}F$ ($177^{o}C$) it can be pressurized and possibly rupture. TDI reacts slowly with water to form polyureas and liberates CO_2 gas. This gas can cause sealed containers to expand and possibly rupture.
PRECAUTIONS TO BE TAKEN
IN HANDLING AND STORING.: Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. Prevent all contact. Do not breathe the vapors. Warning properties (irritation of the eyes, nose and throat or odor) are not adequate to prevent chronic overexposure from inhalation. This material can produce asthmatic sensitization upon either single inhalation exposure to a relatively high concentration or upon repeated inhalation exposures to lower concentrations. Exposure to vapors of heated TDI can be extremely dangerous. Employee education and training in safe handling of this product are required under the OSHA Hazard Communication Standard.

XI. SHIPPING DATA

D.O.T. SHIPPING NAME.....: Toluene Diisocyanate
TECHNICAL SHIPPING NAME...: Toluene Diisocyanate
D.O.T. HAZARD CLASS.....: Poison B
UN/NA NO.....: UN 2078
PRODUCT RQ.....: 100 lbs.
D.O.T. LABELS.....: Poison
D.O.T. PLACARDS.....: Poison
FRT. CLASS BULK.....: Toluene Diisocyanate
FRT. CLASS PKG.....: Chemicals, NOI (Toluene Diisocyanate) NMFC 60000
PRODUCT LABEL.....: Mondur TD Product Label

XII. ANIMAL TOXICITY DATA

ACUTE TOXICITY

ORAL, LD50.....: Range of 4130-6170 mg/kg (Rats and Mice)
DERMAL, LD50.....: Greater than 10,000 mg/kg (Rabbits)
INHALATION, LC50.(4 hr).: Range of 16-50 ppm (Rat), 10 ppm (Mouse), 11 ppm (Rabbit), 13 ppm (Guinea Pig).
EYE EFFECTS.....: Severe eye irritant capable of inducing corneal opacity.
SKIN EFFECTS.....: Moderate skin irritant. Primary dermal irritation score: 4.12/8.0 (Draize). However, repeated or prolonged contact may culminate in severe skin irritation and/or corrosion.
SENSITIZATION.....: Skin sensitizer in guinea pigs. One study using guinea pigs reported that repeated skin contact with TDI caused respiratory sensitization. Although poorly defined in experimental animal models, TDI is known to be a pulmonary sensitizer in humans. In addition, there is some evidence that cross-sensitization between different types of diisocyanates may occur.

SUB-CHRONIC/CHRONIC TOXICITY: Sub-chronic and chronic animal studies show that the primary effects of inhaling vapors and/or aerosols of TDI are restricted to the pulmonary systems. Emphysema, pulmonary edema, pneumonitis and rhinitis are common pathologic effects. Extended exposures to as low as 0.1 ppm TDI have induces pulmonary inflammation.

OTHER

CARCINOGENICITY.....: The NTP conducted carcinogenesis studies of a commercial grade TDI using rats and mice in which the test material was diluted in corn oil and administered by gavage. The investigators concluded that TDI was carcinogenic in male and female rats (fibrosarcomas, pancreatic adenomas, neoplastic liver nodules and mammary gland fibrosarcomas) and female mice (hemangiosarcomas and hepatocellular adenomas). However, chronic inhalation studies in which rats and mice were exposed to 0.05 and 0.15 ppm TDI (10-30 times recommended TLV, 8-hr level) induced no treatment-related tumorigenic effects. In these studies, both exposure levels produced extensive irritation to the nasal passages and upper respiratory system of the test animals indicating that suitable effective exposures were administered.
MUTAGENICITY.....: TDI is positive in the Ames assay with activation. However, mammalian cell transformation assays using human lung cells and Syrian hamster kidney cells were negative, as were micronucleus tests using rats and mice.

XII. ANIMAL TOXICITY DATA - Continued

AQUATIC TOXICITY.....: LC_{50} - 96 hr (static): 165 mg/liter (Fathead minnow)
LC_{50} - 96 hr (static): Greater than 508 mg/liter (Grass shrimp)
LC_{50} - 24 hr (static): Greater than 500 mg/liter (Daphnia magna)

XIII. APPROVALS

REASON FOR ISSUE.....: Adding SARA Title III; Revising Section XII
PREPARED BY.....: G. L. Copeland
APPROVED BY.....: D. R. Hackathorn
TITLE.....: Manager, Product Safety

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Mobay Corporation. The data on this sheet relates only to the specific material designated herein. Mobay Corporation assumes no legal responsibility for use or reliance upon these data.

MATERIAL SAFETY DATA SHEET

PRODUCT CODE: 92097 PAGE: 1

PRODUCT NAME: TOLUENE DIISOCYANATE

EFFECTIVE DATE: 10/15/86 DATE PRINTED: 10/17/86 MSD: 000609

1. INGREDIENTS:

TOLUENE DIISOCYANATE (TDI) CAS# 026471-62-5 100%

SUBSTANCES LISTED IN THE INGREDIENTS SECTION ARE THOSE IDENTIFIED AS BEING PRESENT AT A CONCENTRATION OF 1% OR GREATER, OR 0.1% IF THE SUBSTANCE IS ON THE LIST OF POTENTIAL CARCINOGENS CITED IN OSHA HAZARD COMMUNICATION STANDARD. WHERE PROPRIETARY INGREDIENT SHOWS, THE IDENTITY OF THIS SUBSTANCE MAY BE MADE AVAILABLE AS PROVIDED IN 29 CFR 1910.1200(I).

2. PHYSICAL DATA:

BOILING POINT: 250C (482F)
VAP PRESS: 0.01 MMHG @ 20C
VAP DENSITY: 6.0
SOL. IN WATER: INSOLUBLE
SP. GRAVITY: 1.22 @ 25/15.5C
APPEARANCE: WATER WHITE TO PALE YELLOW LIQUID.
ODOR: SHARP PUNGENT ODOR.

3. FIRE AND EXPLOSION HAZARD DATA:

FLASH POINT: 127C (260F)
METHOD USED: PMCC, ASTM D-93

FLAMMABLE LIMITS
LFL: NOT DETERMINED
UFL: NOT DETERMINED

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM, HALON 1211. IF WATER IS USED, IT SHOULD BE IN VERY LARGE QUANTITY. THE REACTION BETWEEN WATER AND HOT ISOCYANATE MAY BE VIGOROUS.

FIRE & EXPLOSION HAZARDS: DOWN-WIND PERSONNEL MUST BE EVACUATED. DO NOT RESEAL CONTAMINATED CONTAINERS SINCE PRESSURE BUILD-UP MAY CAUSE RUPTURE. FIRE POINT: 146C (295F).

FIRE-FIGHTING EQUIPMENT: PEOPLE WHO ARE FIGHTING ISOCYANATE FIRES MUST BE PROTECTED AGAINST NITROGEN OXIDE FUMES AND ISOCYANATE VAPORS BY WEARING POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.

4. REACTIVITY DATA:

STABILITY: (CONDITIONS TO AVOID) STABLE WHEN STORED UNDER RECOMMENDED STORAGE CONDITIONS. STORE IN A DRY PLACE AT

(CONTINUED ON PAGE 2)
(R) INDICATES A TRADEMARK OF THE DOW CHEMICAL CO.

4. REACTIVITY DATA: (CONTINUED)

TEMPERATURES BETWEEN 18-41C (65-105F).

INCOMPATIBILITY: (SPECIFIC MATERIALS TO AVOID) WATER, ACID, BASE, ALCOHOLS, METAL COMPOUNDS, SURFACE ACTIVE MATERIALS. AVOID WATER AS IT REACTS TO FORM HEAT, CO2 AND INSOLUBLE UREA. THE COMBINED EFFECT OF THE CO2 AND HEAT CAN PRODUCE ENOUGH PRESSURE TO RUPTURE A CLOSED CONTAINER.

HAZARDOUS DECOMPOSITION PRODUCTS: ISOCYANATE VAPOR AND MIST, CARBON DIOXIDE, CARBON MONOXIDE, NITROGEN OXIDES AND TRACES OF HYDROGEN CYANIDE.

HAZARDOUS POLYMERIZATION: MAY OCCUR WITH INCOMPATIBLE REACTANTS, ESPECIALLY STRONG BASES, WATER OR TEMPERATURES OVER 41C (105F).

5. ENVIRONMENTAL AND DISPOSAL INFORMATION:

ACTION TO TAKE FOR SPILLS/LEAKS: EVACUATE AND VENTILATE SPILL AREA, DIKE SPILL TO PREVENT ENTRY INTO WATER SYSTEM, WEAR FULL PROTECTIVE EQUIPMENT INCLUDING RESPIRATORY EQUIPMENT DURING CLEAN UP. MAJOR SPILL: CALL DOW CHEMICAL U.S.A. (409) 238-2112. IF TRANSPORTATION SPILL INVOLVED CALL CHEMTREC (800) 424-9300. IF TEMPORARY CONTROL OF ISOCYANATE VAPOR IS REQUIRED A BLANKET OF PROTEIN FOAM (AVAILABLE AT MOST FIRE DEPARTMENTS) MAY BE PLACED OVER THE SPILL. LARGE QUANTITIES MAY BE PUMPED INTO CLOSED BUT NOT SEALED CONTAINERS FOR DISPOSAL. MINOR SPILL: ABSORB THE ISOCYANATE WITH SAWDUST OR OTHER ABSORBENT, SHOVEL INTO SUITABLE UNSEALED CONTAINERS, TRANSPORT TO WELL-VENTILATED AREA (OUTSIDE) AND TREAT WITH NEUTRALIZING SOLUTION CONSISTING OF A MIXTURE OF WATER AND 3-8% CONCENTRATED AMMONIUM HYDROXIDE (OR 5-10% SODIUM CARBONATE). ADD ABOUT 10 PARTS OF NEUTRALIZER PER PART OF ISOCYANATE WITH MIXING. ALLOW TO STAND FOR 48 HOURS LETTING EVOLVED CO2 ESCAPE.

CLEAN-UP: DECONTAMINATE FLOOR USING WATER/AMMONIA SOLUTION WITH 1-2% ADDED DETERGENT LETTING STAND OVER AFFECTED AREA FOR AT LEAST 10 MINUTES. COVER MOPS AND BROOMS USED FOR THIS WITH PLASTIC AND DISPOSE PROPERLY (OFTEN BY INCINERATION).

DISPOSAL METHOD: FOLLOW ALL FEDERAL, STATE AND LOCAL REGULATIONS. LIQUIDS ARE USUALLY INCINERATED IN A PROPER FACILITY. SOLIDS ARE USUALLY ALSO INCINERATED OR LANDFILLED. EMPTY DRUMS SHOULD BE FILLED WITH WATER; LET STAND FOR AT LEAST 48 HOURS; DRUMS SHOULD BE DRAINED, TRIPLE RINSED, AND HOLED OR CRUSHED TO

(CONTINUED ON PAGE 3)
(R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY

5. ENVIRONMENTAL AND DISPOSAL INFORMATION: (CONTINUED)

PREVENT REUSE. DISPOSE OF DRAIN AND RINSE FLUID ACCORDING TO LOCAL REGULATIONS.

6. HEALTH HAZARD DATA:

EYE: MAY CAUSE PAIN, SEVERE EYE IRRITATION AND MODERATE CORNEAL INJURY. VAPORS MAY IRRITATE EYES.

SKIN CONTACT: IS LIKELY TO CAUSE AN ALLERGIC SKIN REACTION. PROLONGED OR REPEATED EXPOSURE MAY CAUSE SEVERE IRRITATION, EVEN A BURN.

SKIN ABSORPTION: A SINGLE PROLONGED EXPOSURE IS NOT LIKELY TO RESULT IN THE MATERIAL BEING ABSORBED THROUGH SKIN IN HARMFUL AMOUNTS. THE LD50 FOR SKIN ABSORPTION IN RABBITS IS >9400 MG/KG.

INGESTION: SINGLE DOSE ORAL TOXICITY IS LOW. THE ORAL LD50 FOR RATS IS 5800 MG/KG. INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION OR ULCERATION.

INHALATION: EXCESSIVE VAPOR CONCENTRATIONS ARE ATTAINABLE AND COULD BE HAZARDOUS ON SINGLE EXPOSURE. SINGLE AND REPEATED EXCESSIVE EXPOSURE MAY CAUSE SEVERE IRRITATION TO UPPER RESPIRATORY TRACT AND LUNGS (CHOKING SENSATION, CHEST TIGHTNESS), RESPIRATORY SENSITIZATION, DECREASED VENTILATORY CAPACITY, LIVER EFFECTS, CHOLINESTERASE DEPRESSION, GASTRO-INTESTINAL DISTRESS AND/OR NEUROLOGIC DISORDERS. THE 4-HOUR LC50 FOR TDI FOR RATS IS 13.9 PPM.

SYSTEMIC & OTHER EFFECTS: BASED ON AVAILABLE DATA, REPEATED EXPOSURES ARE NOT ANTICIPATED TO CAUSE ANY ADDITIONAL SIGNIFI-CANT ADVERSE EFFECTS. FOR HAZARD COMMUNICATION PURPOSES UNDER OSHA STANDARD 29 CFR PART 1910.1200, THIS CHEMICAL IS LISTED AS A POTENTIAL CARCINOGEN BY NAT'L. TOX. PROGRAM. AN ORAL STUDY IN WHICH HIGH DOSES OF TDI WERE REPORTED TO CAUSE CANCER IN ANIMALS HAS BEEN FOUND TO CONTAIN NUMEROUS DEFICIENCIES WHICH COMPROMISE THE VALIDITY OF THE STUDY. TDI DID NOT CAUSE CANCER IN LABORATORY ANIMALS EXPOSED BY INHALATION, THE MOST LIKELY ROUTE OF EXPOSURE. RESULTS OF IN VITRO ("TEST TUBE") MUTA-GENICITY TESTS HAVE BEEN INCONCLUSIVE.

7. FIRST AID:

EYES: IRRIGATE WITH FLOWING WATER IMMEDIATELY AND CONTINUOUSLY

(CONTINUED ON PAGE 4)
(R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY

7. FIRST AID: (CONTINUED)

FOR 15 MINUTES. CONSULT MEDICAL PERSONNEL.

SKIN: IN CASE OF CONTACT, IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. CALL A PHYSICIAN IF IRRITATION PERSISTS. WASH CLOTHING BEFORE REUSE. DESTROY CONTAMINATED SHOES.

INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN AND/OR TRANSPORT TO EMERGENCY FACILITY IMMEDIATELY.

INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE MOUTH-TO-MOUTH RESUSCITATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN.

NOTE TO PHYSICIAN: CORROSIVE. MAY CAUSE STRICTURE. IF LAVAGE IS PERFORMED, SUGGEST ENDOTRACHEAL AND/OR ESOPHAGOSCOPIC CONTROL. IF BURN IS PRESENT, TREAT AS ANY THERMAL BURN, AFTER DECONTAMINATION. NO SPECIFIC ANTIDOTE. SUPPORTIVE CARE. TREATMENT BASED ON JUDGMENT OF THE PHYSICIAN IN RESPONSE TO REACTIONS OF THE PATIENT. THE MANIFESTATIONS OF THE RESPIRATORY SYMPTOMS, INCLUDING PULMONARY EDEMA, RESULTING FROM ACUTE EXPOSURE MAY BE DELAYED. MAY CAUSE RESPIRATORY SENSITIZATION. CHOLINESTERASE INHIBITION HAS NOT BEEN NOTED IN HUMAN EXPOSURE AND IS NOT OF BENEFIT IN DETERMINING EXPOSURE.

8. HANDLING PRECAUTIONS:

EXPOSURE GUIDELINE(S): OSHA PEL IS 0.02 PPM AS A CEILING LIMIT FOR TOLUENE 2,4-DIISOCYANATE. ACGIH TLV IS 0.005 PPM; 0.02 PPM STEL FOR TOLUENE 2,4-DIISOCYANATE. DOW INDUSTRIAL HYGIENE GUIDE IS 0.02 PPM AS A CEILING LIMIT FOR TOLUENE DIISOCYANATE.

VENTILATION: PROVIDE GENERAL AND/OR LOCAL EXHAUST VENTILATION TO CONTROL AIRBORNE LEVELS BELOW THE EXPOSURE GUIDELINES.

RESPIRATORY PROTECTION: ATMOSPHERIC LEVELS SHOULD BE MAINTAINED BELOW THE EXPOSURE GUIDELINE. WHEN RESPIRATORY PROTECTION IS REQUIRED FOR CERTAIN OPERATIONS, USE AN APPROVED SUPPLIED-AIR RESPIRATOR. FOR EMERGENCY AND OTHER CONDITIONS WHERE THE EXPOSURE GUIDELINE MAY BE GREATLY EXCEEDED, USE AN APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS.

SKIN PROTECTION: USE PROTECTIVE CLOTHING IMPERVIOUS TO THIS MATERIAL. SELECTION OF SPECIFIC ITEMS SUCH AS GLOVES, BOOTS, APRON, OR FULL-BODY SUIT WILL DEPEND ON OPERATION. REMOVE

(CONTINUED ON PAGE 5)
(R) INDICATES A TRADEMARK OF THE DOW CHEMICAL COMPANY

8. HANDLING PRECAUTIONS: (CONTINUED)

CONTAMINATED CLOTHING IMMEDIATELY, WASH SKIN AREA WITH SOAP AND WATER, AND LAUNDER CLOTHING BEFORE REUSE. SAFETY SHOWER SHOULD BE LOCATED IN IMMEDIATE WORK AREA.

EYE PROTECTION: USE CHEMICAL GOGGLES. IF VAPOR EXPOSURE CAUSES EYE IRRITATION, USE A FULL-FACE, SUPPLIED-AIR RESPIRATOR. EYE WASH FOUNTAIN SHOULD BE LOCATED IN IMMEDIATE WORK AREA.

9. ADDITIONAL INFORMATION:

SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: WARNING PROPERTIES OF THIS MATERIAL (IRRITATION OF EYES, NOSE AND THROAT) NOT ADEQUATE TO PREVENT CHRONIC OVEREXPOSURE FROM INHALATION. THIS MATERIAL CAN PRODUCE ASTHMATIC SENSITIZATION UPON EITHER SINGLE INHALATION EXPOSURE TO A RELATIVELY HIGH CONCENTRATION OR UPON REPEATED INHALATION EXPOSURE TO LOWER CONCENTRATIONS. EXPOSURES TO VAPORS OF HEATED TDI CAN BE EXTREMELY DANGEROUS. (HAVE TDI NEUTRALIZER AVAILABLE FOR SPILLS.)

MSDS STATUS: REVISED 6.

THE INFORMATION HEREIN IS GIVEN IN GOOD FAITH, BUT NO WARRANTY, EXPRESS OR IMPLIED, IS MADE. CONSULT THE DOW CHEMICAL COMPANY FOR FURTHER INFORMATION.

Material Safety Data Sheet

QUICK IDENTIFIER (In Plant Common Name)

~~BEST COPY AVAILABLE~~

IMPORTED BY MONTEDISON U.S.A., INC.

Manufacturer's Name	Montedipe S.p.A.	Emergency Telephone No.	212-764-0260
Address	Via Taramelli 26, 20124 Milan, Italy	Other Information Calls	
Signature of Person Responsible for Preparation		Date Prepared	November 1986

SECTION 1 - IDENTITY

Common Name: (used on label) (Trade Name & Synonyms)	Tedimon 80	Cas No.	See Section 2
Chemical Name	Toluene Diisocyanate	Chemical Family	Isocyanates
Formula	2,4 - 2,6 OCN-$C_6H_3(CH_3)$ - NCO		

SECTION 2 - HAZARDOUS INGREDIENTS

Principal Hazardous Component(s) (chemical & common name(s))	%	Threshold Limit Value (units)
Mixture of: 2,4 Toluenediisocyanate CAS n° 584-84-9	80%	TLV-TWA 0.04 mg/m^3
2,6 Toluenediisocyanate CAS n° 91-08-7	20%	TLV-STEL 0.15 mg/m^3
		(ACGIH 1985-86)

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS (Fire & Explosion Data)

Boiling Point	251°C	Specific Gravity (H_2O=1)	1,22 at 15°C
Vapor Pressure (mm Hg)	0,02 at 20°C	Percent Volatile by Volume (%)	100%
Vapor Density (Air = 1)	6	Evaporation Rate (_____ = 1)	NA
Solubility in Water	Insoluble	Reactivity in Water	Reacts, Develops, CO_2
Appearance and Odor	Clear Colorless Liquid; Pungent Odor		

Flash Point	135°C (C.O.C.)	Flammable Limits in Air % by Volume	Lower 0.9%	Upper 9.5%	Extinguisher Media	Foam, Powder, Water Spray	Auto-Ignition Temperature NA

Special Fire Fighting Procedures: Full Emergency Equipment; Use Self Containing Breathing Apparatus: TOXIC Vapors Develop in Fire

Unusual Fire and Explosion Hazards: NA

MAY 23 '89 16:19 PAGE.002

SECTION 4 - PHYSICAL HAZARDS

Stability: Unstable ☐ Conditions to Avoid; Stable XX — Avoid Contact with Moisture

Incompatibility (Materials to Avoid): Water, Alcohols, Amines and Basic Materials

Hazardous Decomposition Products: NA

Hazardous Polymerization: May Occur ☐ Conditions to Avoid; Will Not Occur XX

SECTION 5 - HEALTH HAZARDS *TDI May Reasonably be Anticipated to be Carcinogenic

Threshold Limit Value: TLV-TWA: 0.04 mg/m^3 TLV-STEL: 0.15 mg/m^3 (ACGIH 1985-86)

Signs and Symptoms of Exposure — 1. Acute Overexposure: Severe Irritation of Respiratory Tract

2. Chronic Overexposure: Possible Sensitization

Medical Conditions Generally Aggravated by Exposure: Respiratory Diseases Aggravated

Chemical Listed as Carcinogen or Potential Carcinogen — National Toxicology Program: Yes ☒ No ☐ — I.A.R.C. Monographs: Yes ☒** No ☐ — OSHA: Yes ☐ No ☐

OSHA Permissible Exposure Limit: 1983 0.14 mg/m^3 (C) — ACGIH Threshold Limit Value: 1984-85 TLV-TWA: 0.005 ppm — Other Exposure Limit Used: Not Available

Emergency and First Aid Procedures: Seek Medical Advice Immediately in All Cases of Exposure to TDI

1. Inhalation: Remove Patient from Contaminated Area, Administer O_2 - Call Physician

2. Eyes: Flush with Plenty of Water; Call Physician

3. Skin: Remove Contaminated Garments. Wash Throughly with Soap and Water

4. Ingestion: Drink Large Amount of Water; Call Physician

SECTION 6 - SPECIAL PROTECTION INFORMATION

Respiratory Protection (Specify Type): Face Mask with Filter for Organic Vapors

Ventilation: Local Exhaust X — Mechanical (General) X — Special NA — Other NA

Protective Gloves: Rubber Gloves — Eye Protection: Safety Goggles

Other Protective Clothing or Equipment: Rubber Aprons and Boots

SECTION 7 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be Taken in Handling and Storage: Store in Adequately Ventilated Building

Other Precautions: Store Separate from Polyol, Alcohols, Amines. Protect from Moisture

Steps to be Taken in Case Material is Released or Spilled: Cover Spills with Absorbent Materials; Use Decontaminants (Water & Ammonia or Amines). Sweep Up and Take to Disposal (Follow Local Regulations).

Waste Disposal Methods: Send to Suitable Incinerator. Neutralize Small Quantities at Time with Polyol. Observe All Local Regulations.

IMPORTANT *Listed in Fourth Annual Report on Cacinogens

Do not leave any blank spaces. If required information is unavailable, unknown, or does not apply, so indicate.

**Will be Listed in Monograph 39.

MAY 23 '89 16:19 PAGE.003

Olin MATERIAL SAFETY DATA

MM24
Rec'd. McNhorter
DB 4/21/89
pg. 1

OCEAN® Network
EMERGENCY PHONE 1-800-OLIN-911

MSDS FILE 563

SECTION I - IDENTIFICATION

CHEMICAL NAME & SYNONYMS Toluene Diisocyanate 80-20		
CHEMICAL FAMILY Isocyanate	**FORMULA** $C_9H_6N_2O_2$	**PRODUCT** TDI 80-20
DESCRIPTION Clear colorless to pale yellow liquid with sharp pungent odor		**CAS NO.** 26471-62-5

SECTION II - NORMAL HANDLING PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Harmful if swallowed. Avoid contact with eyes, skin or clothing. Upon contact with skin or eyes, wash off with water. Avoid breathing mist or vapor. Protect against physical damage. Store in a cool, dry, well-ventilated place, away from areas where a fire hazard may be acute. Outside or detached storage is preferred. Blanket storage tanks with inert gas (nitrogen) or dry air. Separate from oxidizing materials.

PROTECTIVE EQUIPMENT	VENTILATION REQUIREMENTS
EYES Goggles **GLOVES** Rubber, NBR or PVA **OTHER** Coveralls, impervious footwear	As required to keep airborne concentrations below TLV

SECTION III - HAZARDOUS INGREDIENTS

BASIC MATERIAL	OSHA PEL	LD50	LC50	SIGNIFICANT EFFECTS
*Toluene-2,4-diisocyanate (80%) CAS No.: 584-84-9	0.02 ppm ceiling	5.8 g/kg (rat)	10 ppm/4 hrs (mouse)	Skin, eye, mucous membrane irritation. Pulmonary irritant. Allergic sensitization to skin and respiratory tract. May cause asthma attacks.
*Toluene-2,6-diisocyanate(20%),CAS No.:91-08-7	None established	No data	11 ppm/4 hrs-mouse	Irritation

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT 270°F COC **METHOD**	**OSHA CLASSIFICATION** Not Regulated (Ignitable)	**FLAMMABLE EXPLOSIVE LIMIT**	**LOWER** 0.9%	**UPPER** 9.5%

EXTINGUISHING MEDIA Water, carbon dioxide or dry chemical. Use water to keep the exposed containers cool.

SPECIAL FIRE HAZARD & FIRE FIGHTING PROCEDURES Use NIOSH/MSHA approved positive pressure self-contained breathing apparatus when any material is involved in a fire.

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE
0.005 ppm TWA, 0.02 ppm STEL - 2,4 TDI (ACGIH 1987-88)

SYMPTOMS OF OVER EXPOSURE May cause irritation to eyes, throat, lungs, stomach, skin. Allergic sensitization to skin and respiratory tract. May cause asthma attacks

EMERGENCY FIRST-AID PROCEDURES

SKIN Immediately flush thoroughly with water for 15 minutes, call a physician.

EYES Immediately flush thoroughly with water for 15 minutes, call a physician.

INGESTION Immediately drink large quantities of water to dilute.

INHALATION Immediately remove victim to fresh air. Call a physician.

SECTION VI - TOXICOLOGY (PRODUCT)

ACUTE ORAL LD 50 5.8 g/kg (rats). Harmful if swallowed.
ACUTE DERMAL LD 50
> 2 g/kg (rabbits)
ACUTE INHALATION LC 50
10 ppm/4 hrs (mouse)

CARCINOGENICITY Oral Exposure-Positive NTP Bioassay
MUTAGENICITY Not known to be mutagenic
EYE IRRITATION Irritation and/or burns
PRIMARY SKIN IRRITATION
Irritation and/or burns

PRINCIPAL ROUTES OF ABSORPTION
Inhalation, dermal contact

EFFECTS OF ACUTE EXPOSURE May cause irritation to lungs, eyes, throat, stomach, skin. Allergic sensitization of skin and respiratory tract. Corneal injury may occur.

EFFECTS OF CHRONIC EXPOSURE Damage/allergic sensitization to lungs. Inhalation studies indicate not carcinogenic. Carcinogenic risk from industrial use is not significant.

SECTION VII - SPILL AND LEAKAGE PROCEDURES (CONTROL PROCEDURES)

ACTION FOR MATERIAL RELEASE OR SPILL
Wear NIOSH/MSHA approved positive pressure supplied air respirator. Follow OSHA regulations for respirator use (see 29 CFR 1910.134). Wear goggles, coveralls and impervious gloves and boots. Add dry non-combustible absorbent, sweep up material and place in an approved DOT container. Add an equal amount of neutralizing solution to the container (90-95% water, 5-10% ammonia). Clean remaining surfaces with neutralizing solution and add this to container. Isolate container in a well-ventilated place and do not seal for 24 hrs. Ammonia vapors may be generated until solution is neutralized. Wash all contaminated clothing before reuse. In the event of a large spill use the telephone number shown on the front of this sheet.

TRANSPORTATION EMERGENCY, CONTACT CHEMTREC 800-424-9300

THE MIXTURE OR TRADE NAME PRODUCT HEREIN CONTAINS A TOXIC CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372. THE SARA 313 CHEMICALS ARE LISTED IN SECTION III AND ARE INDICATED BY AN ASTERISK (*).

SECTION VIII - SHIPPING DATA

D.O.T. Toluene diisocyanate Poison B UN 2078

SECTION IX - REACTIVITY DATA

STABLE X UNSTABLE AT____C ____ F	HAZARDOUS POLYMERIZATION	MAY OCCUR X WILL NOT OCCUR

CONDITIONS TO AVOID
Water or incompatible materials in a closed system, excess heat
INCOMPATIBILITY(MATERIAL TO AVOID)
Acids, bases and alcohols, surface active materials
HAZARDOUS DECOMPOSITION PRODUCTS
Carbon monoxide, nitrogen oxides, hydrogen cyanide

SECTION X - PHYSICAL DATA

MELTING POINT 53-56°F	VAPOR PRESSURE .01mmHg,20°C	VOLATILES No data
BOILING POINT 484°F	SOLUBILITY IN WATER Insoluble	EVAPORATION RATE No data
SPECIFIC GRAVITY(H2O=1) 1.22	PH No data	VAPOR DENSITY(AIR=1) 6.0

INFORMATION: FURNISHED TO 10012220 **FURNISHED BY** **DATE** APRIL 13, 1989

ATTN: DEPT HANDLING MATL SAFETY DATA SHEETS
MCWHORTER INC
200 SAYRE STREET
ROCKFORD IL 61101

Department of Environmental Hygiene and Toxicology
(203) 789-5436

Olin CORPORATION
120 Long Ridge Road, Stamford, Connecticut 06904
OCEAN® Network
EMERGENCY PHONE 1-800-OLIN-911

AIRBORNE EXPRESS

RECEIVER'S COPY

202 (5/86)

AIRBILL NO. 659340146

FROM	TO
VALSPAR	US EPA, DOCUMENT PROCESSING CTR OFFICE OF TOXIC SUBSTANCES, TS -790 401 M STREET, SW
1101 S 3RD ST	
MINNEAPOLIS MN 55415	WASHINGTON, DC 20460
RICHARD FRICKER	CAIR REPORTING OFFICE £201
BILLING REFERENCE INFORMATION TO APPEAR ON INVOICE 55-499-23	RECEIVER'S AIRBORNE EXPRESS ACCOUNT NO.

TYPE OF PACKAGING

- [x] EXPRESS/AD PACK ENVELOPE
- [ ] LETTER EXPRESS (UP TO 8 OZ.)
- [ ] EXPRESS PACK BOX/TUBE
- [ ] MAG TAPE PACK

DESCRIPTION OF CONTENTS

NO. OF PACKAGES	WEIGHT (LBS.)
1	2

SENDER'S C.O.D. $.

ROUTING

DCA

DC 20

BILL CHARGES TO (ASSUMED SENDER UNLESS OTHERWISE SPECIFIED)

- [ ] SENDER
- [ ] RECEIVER
- [ ] 3RD PARTY _____ AIRBORNE EXPRESS ACCOUNT NO.
- [ ] PAID IN ADVANCE $ _____
- CHECK NUMBER _____

TYPE OF SPECIAL SERVICE (EXTRA CHARGES MAY APPLY)

- [ ] SPECIAL PICKUP
- [ ] SATURDAY DELIVERY
- [ ] SPECIAL DELIVERY _____ : TIME
- [ ] HOLD AT AIRBORNE FOR PICKUP (NO CHARGE)
- [ ]

659340146 AIRBORNE SIGNATURE | DATE RECEIVED

TO REMOVE COPY INSERT PENCIL

BEST COPY AVAILABLE