NATIONAL COUNCIL FOR AIR AND STREAM IMPROVEMENT, INC.
Mailing Address: PO Box 340317, Clemson, SC 29634-0317
Physical Address: Room 261 Lehotsky Hall, Clemson, SC 29634
Phone (864) 656-0840 Fax (864) 656-3304

T. Bently Wigley, Ph.D.
Manager, Sustainable Forestry and
Eastern Wildlife Program
(864) 656-0840
bwigley@ncasi.org

TECHNICAL REVIEW
Draft Chesapeake Bay Total Maximum Daily Load
Docket Number EPA-R03-OW-2010-0736

Erik B. Schilling, George G. Ice, and T. Bently Wigley,

November 5, 2010

In the September 22, 2010 *Federal Register*, the U.S. Environmental Protection Agency (EPA) announced the availability of EPA's Draft Chesapeake Bay Draft Total Maximum Daily Load (TMDL) for nutrients and sediment for public review and comment (*FR 75* 57776-57778). In the Notice, the EPA reported that it was establishing the Draft TMDL for nutrients (nitrogen and phosphorus) and sediment for each of the 92 segments in the tidal portion of the Chesapeake Bay watershed pursuant to Sections 117(g) and 303(d) of the Clean Water Act. Thus, the Draft TMDL contains segment-specific point and non-point allocations for nitrogen, phosphorous and sediment that will assure the attainment and maintenance of all applicable water quality standards for each of the 92 segments.

The National Council for Air and Stream Improvement, Inc. (NCASI) is a non-profit organization that serves the forest products industry as a center of excellence for providing technical information and scientific research needed to achieve the industry's environmental goals and principles. NCASI (http://www.ncasi.org) has a long history of supporting research to help its member companies better manage forest and manufacturing operations to meet environmental objectives including the protection of water quality. In 1977, NCASI established a formal research program addressing watershed issues. The mission of the Forest Watershed Program is to develop, document, and communicate scientific information regarding the effects of forest practices and natural processes on aquatic resources. This includes developing or documenting solutions to undesirable watershed effects of forest practices. Because NCASI is interested in developing cost-effective measures for protecting water quality, we offer the following observations about the draft Chesapeake Bay TMDL.

1. Forestry best management practices are implemented at high rates nationally and in states within the Chesapeake Bay watershed.

Forestry activities in the United States are now conducted under a comprehensive program of best management practices (BMPs). Since enactment of the Federal Water Pollution Control Act Amendments of 1972, all states with significant forest management activities have developed either regulatory or non-regulatory BMP programs under Sections 208, 319 and 404 to achieve water quality goals. The rate at which forestry best management practices are implemented is a key factor in judging the effectiveness of state forestry nonpoint source control programs. Using weighted annual state timber harvest volumes and BMP implementation rates from state assessment reports, Ice et al. (2010) calculated an adjusted national average implementation rate of 89%. Generally, implementation rates are increasing over time (Ice et al. 2010, NCASI 2009). Specific data on harvest levels and BMP implementation rates for states in the Chesapeake Bay watershed are shown in Table 1.

Table 1. Annual Harvest Removals and Reported BMP Implementation Rates for States in the Chesapeake Bay Watershed. Adapted from Ice et al. 2010[1].

State	Removals (1000 ft^3)	Implementation Rate (%)
Virginia	644,260	82
Pennsylvania	211,921	85 [est.]
New York	158,454	77 (1998)
West Virginia	158,373	85
Maryland	38,091	81
Delaware	7,560	50 [est.]

[1]Annual harvest data are 2006 estimates from the USDA Forest Service Draft National Sustainable Forestry: 2010 Report. State BMP implementation data from NCASI 2009.

2. When implemented, forestry BMPs are effective at protecting water quality.

Research results overwhelmingly document that properly installed and maintained forestry BMPs effectively reduce sediment impacts as well as maintain stream water temperatures and dissolved oxygen levels. In fact, BMPs can reduce pollution loads to streams by as much as 80 to 90% (Ice et al. 2004). Ice (2004b) and Ice et al. (1997, 2004a, 2005a, 2005b) present results from studies of BMP effectiveness and summarize this body of research. Other sources of publications that document BMP effectiveness are a 2004 special issue of *Water, Air, and Soil Pollution* (Volume 4, Issue 1), presentations from a 2003 Workshop on Predicting Sediment from Forest Road Systems in the South (http://fri.sfasu.edu/pages/projects/alto/html/

forest_roads_03.html), and proceedings of the 2006 International Conference on Hydrology and Management of Forested Wetlands (http://www.asabe.org/pubs/PubCat02/environment.html).

3. There have been numerous studies in the Chesapeake Bay Region documenting BMP effectiveness, many of which do not appear to have been considered by EPA.

There have been numerous studies in the Chesapeake Bay Region documenting BMP effectiveness, many of which do not appear to have been considered by EPA. A brief synopsis of key findings from these studies is as follows.

A watershed study conducted in central Pennsylvania suggested that the BMPs were effective in controlling non-point source pollution from a 44.5-hectare commercial clearcut (Lynch et al. 1985). Among the BMPs used were: protective buffer strips; a prohibition on skidding over streams; supervision of logging by a qualified forester; division of timber sales into blocks with cutting restricted to one block at a time; no disposal of tops or slash within 8 m of streams; proper location of haul roads, skid trails and log landings; retirement of skid trails, haul roads and culverts after logging; posting of a performance bond prior to logging. Slight increases in stream temperature, turbidity, and nitrate and potassium concentrations were observed, but these increases did not exceed drinking water standards. The authors concluded that the slight increases in temperature and nutrients were possibly temporarily beneficial to the aquatic ecosystem.

Passhaus et al. (2003) used macroinvertebrate sampling to monitor ephemeral stream water quality in partially harvested and reference watersheds in the Catskill Mountain Region of southern New York. A variety of diversity indices showed no evidence that partial harvest using BMPs negatively impacted aquatic communities or water quality. Within the reference sites, the structure of the macroinvertebrate community varied greatly between years.

In New York, Schuler and Briggs (2000) found that implementation rates for 42 suggested BMPs were 78% for haul roads, 87% for landings, 59% for skid trails, 88% for equipment maintenance/operation, and 73% for buffer strips. Departures were common for BMPs concerned with draining water off haul roads and skid trails, and for stream crossings; thus, the authors concluded that more attention must be devoted to those practices. BMPs were reported to be effective when they were applied correctly.

Wang et al. (2006) reported small changes in stream water chemistry following a partial harvest with BMPs in 2002 of a catchment in the Catskill Mountains of southern New York. Stream water chemistry concentrations increased significantly after harvest treatments and peak concentrations were reached 5 months or more after initiation of the harvest. Stream water chemistry returned to values similar to those of the preharvest period and to reference levels by early spring 2003. Nitrate concentrations, however, remained elevated above background levels for approximately 18 to 20 months after harvest.

In the Hubbard Brook Watershed of New Hampshire, Trimble and Sartz (1957) evaluated the performance of recommended buffer widths for protecting water quality for two situations. The authors concluded that, for municipal watersheds where minor impacts on water quality are not

acceptable, a 50-ft buffer width on flat terrain would be adequate, and that width of the buffer should increase 4 ft for each 1-percent increase in slope between the road and stream. For general purpose situations where small or infrequent impacts on water quality can occasionally be tolerated, they concluded that a starting buffer width of 25-ft on level ground was effective and buffer widths should increase by 2-ft for each 1-percent increase in slope of the land between the road and stream.

In Frederick County, Maryland, MD DNR (2000) used a paired watershed design to monitor effectiveness of Maryland's BMPs for timber harvest operations. They found that total suspended solids, stream temperature, and benthic macroinvertebrate populations did not change significantly as a result of timber harvesting.

Martin et al. (2000) monitored stream water quality following clearcutting and progressive strip cutting in the Hubbard Brook Experimental Forest. Reduced transpiration and interception increased water yield while peak flows only increased moderately. Water yield and peak flow increases returned to normal levels within 4-6 years. Sediment yields increased during and after harvest but were maintained within normal ranges of reference streams. Increases in sediment yield and stream water nutrient levels returned to preharvest levels within 3-5 years due to rapidly growing vegetation and effective best management practices.

Martin et al. (1984) observed small differences in water chemistry between recently clearcut and reference watershed across a wide range of forest and soil types in New England. The amount of observed responses to clearcutting was of the same magnitude as natural variations among streams draining similar watersheds. They concluded that limiting clearcut sizes, utilizing patch and strip cutting, and installing streamside management zones all appeared to effectively reduce the magnitude of changes in stream water chemistry.

Wynn et al. (2000) evaluated the effects of clearcutting on water quality and the effectiveness of forestry BMPs in Westmoreland County, VA. One watershed was clearcut without BMPs, one watershed was clearcut with BMPs and a third watershed was left undisturbed as a control. Storm event concentrations and loadings of sediment, nitrogen, and phosphorus increased following clearcutting and site preparation when BMPs were not utilized. During the study period both the clearcut BMP watershed and the control watershed showed few changes in pollutant storm concentrations and loadings.

4. The Chesapeake Bay Model used by EPA appears to underestimate BMP efficiency.

Nutrient loading values estimated by the Bay Model appear to be based on literature values calculated by Edwards and Williard (2010). In their paper the authors state, "*For sediment, BMP efficiencies ranged from 53 to 94% during harvest and up to 1-year after harvesting. For nutrients, BMP efficiencies were higher for total nitrogen (60-80%) and phosphorus (85-86%), which included particulate and sediment bound forms, than for nitrate-nitrogen (12%) which occurs primarily in the dissolved phase.*" However, values published in the documentation for Scenario Builder Version 2.2 (Brosch 2010) under the section of forest harvesting practices (see table, page 10-108) have BMP efficiencies that are lower than the range of values estimated by Edwards and Williard (e.g., total N = 50%, total P = 60% and sediment = 60%). Thus, it appears

that BMP efficiencies used in Scenario Builder were derived through expert opinion and are more conservative than those identified by Edwards and Williard (2010).

If nutrient and sediment removal efficiencies used in Scenario Builder were based solely on the three referenced studies in Edwards and Williard (2010), data from a substantial number of forestry BMP effectiveness studies conducted in the eastern US (see BMP effectiveness resources and specific research noted above) have been unnecessarily ignored. There are literally hundreds of paired watershed studies and other controlled experiments that have tested or are testing the effectiveness of contemporary forest practices and BMPs (Ice 2004, Ice and Stednick 2004, Ice et al. 2007). Some of these, such the Piedmont Watershed Studies (Williams et al. 1999), the Alto Watershed Study in East Texas (McBroom et al. 2008), and the Alsea Watershed Study and Watersheds Research Cooperative in Oregon (OFRI 2009), have measured or are measuring improvements in water quality from managed forests for contemporary practices compared to historic impacts. Unfortunately, the forest management scenarios used in the Bay Watershed Model will lead users to incorrectly conclude that forest management is a significant source of nutrient and sediment pollution.

5. Sustainable forest management provides incentives for landowners to retain forest land in forest cover.

Today the greatest threat to water quality impairment in the Chesapeake Bay Watershed results from deforestation that results from the conversion of forests to non-forest uses that produce a higher economic value. The families, businesses and individuals that own nearly 60% of our nation's forests depend on the returns they get from the products their forests produce to make additional investments in sound, long-term forest management. When existing markets for their products are strong, or when new markets like energy emerge, they provide forest owners the means to keep their land forested by keeping their forests economically competitive with other uses. However, when regulatory costs are imposed, this reduces a landowner's ability to maintain the land in forest cover and at some point will tip the balance in favor of non-forest uses.

Literature Cited

Brosch, C. 2010. Estimates of county-level nitrogen and phosphorus data for use in modeling pollutant reduction. Documentation for Scenario Builder Ver. 2.2. 126pp.

Edwards, P.J. and K.W.J. Williard. 2010. Efficiencies of forestry best management practices for reducing sediment and nutrient losses in the eastern United States. Journal of Forestry 108(5):245-249.

Ice, G. 2004. History of innovative Best Management Practice development and its role in addressing water quality limited waterbodies. Journal of Environmental Engineering 130(6):684-689.

Ice, G. 2005. Assessing Best Management Practice effectiveness in multiple dimensions and scales. Hydrological Science and Technology 21(1-4):77-86.

Ice, G., L. Dent, J. Robben, P. Cafferata, J. Light, B. Sugden, and T. Cundy. 2004. Programs assessing implementation and effectiveness of state forest practice rules and BMPs in the West. Water, Air, and Soil Pollution: Focus 4(1):143-169.

Ice, G.G. 2005. BMP effectiveness and related water issues. Proceedings of Louisiana Natural Resources Symposium. Shupe, T.F. and M.A. Dunn [eds.]. Baton Rouge, LA: Louisiana State University School of Renewable Natural Resources.

Ice, G.G. and J.D. Stednick. 2004. A century of forest and wildland watershed lessons. Bethesda, MD: Society of American Foresters.

Ice, G.G., E.B. Schilling, and J. Vowell. 2010. Trends for forestry best management practices implementation. Journal of Forestry 108(6):267-273.

Lynch, J.A., E.S. Corbett, and K. Mussallem. 1985. Best management practices for controlling nonpoint-source pollution on forested watersheds. Journal of Soil and Water Conservation 40(1):164-167.

Martin, C.W., D.S. Noel, and C.A. Federer. 1984. The effects of forest clearcutting in New England on stream chemistry. Journal of Environmental Quality 13:204-210.

Martin, C.W., J.W. Hornbeck, G.E. Likens, and D.C. Buso. 2000. Impacts of intensive harvesting on hydrology and nutrient dynamics of northern hardwood forests. Canadian Journal of Fisheries and Aquatic Science 57(Suppl. 2):19-29.

McBroom, M.W., R.S. Beasley, and M. Chang. 2008. Water quality effects of clearcut harvesting and forest fertilization with best management practices. Journal of Environmental Quality 37:114-124.

MD DNR. 2000. Evaluating the effectiveness of Maryland's best management practices for forest harvest operations. Maryland Department of Natural Resources and Chesapeake & Coastal Watershed Service. Annapolis, Maryland. FWHS-FS-00-01

National Council for Air and Stream Improvement, Inc. (NCASI). 2009. *Compendium of forestry best management practices for controlling nonpoint source pollution in North America.* Technical Bulletin No. 966. Research Triangle Park, N.C.: National Council for Air and Stream Improvement, Inc.

Oregon Forest Resources Institute (OFRI). 2009. *Watershed science at work in Oregon's forests.* Special report. Portland, OR: Oregon Forest Resources Institute. http://library.state.or.us/repository/2009/200906251557084/.

Paashaus, E.J., R.D. Briggs, and N.H. Ringler. 2004. Partial cutting impacts on macroinvertebrates in ephemeral streams in southern NY. In: J.S. Ward and M.J. Twery (eds.) Forestry Across Borders Proceedings of the New England Society of American Foresters 84th

Winter Meeting, Quebec City, Quebec Canada, March 23-26, 2004. USDA For. Serv. NE Res. Stn. Gen. Tech. Rept. NE-314. pp. 38-40.

Schuler, J.L. and R.D. Briggs. 2000. Assessing Application and Effectiveness of Forestry Best Management Practices in New York. Northern Journal of Applied Forestry 17(4):125–134.
Trimble, G.R. and R.S. Sartz. 1957. How far from a stream should a logging road be located? Journal of Forestry 55(5):339-341.

Wang, X., D.A. Burns, R.D. Yanai, R.D. Briggs, and R.H. Germain. 2006. Changes in stream chemistry and nutrient export following a partial harvest in the Catskill Mountains, New York, USA. Forest Ecology and Management 223:103-112.

Williams, T.M., Hook, D.D., Lipscomb, D.J., Zeng, X., and Albiston, J.W. 1999. Effectiveness of best management practices to protect water quality in the South Carolina Piedmont. 271-276 in Haywood, J.D. (ed.). *Proceedings of the Tenth Biennial Southern Silvicultural Research Conference*, Shreveport, LA, February 16-18, 1999. General Technical Report SRS-30. Asheville, NC: USDA Forest Service, Southern Research Station. 618 p.

Wynn, T.M., S. Mostaghimi, J.W. Frazee, P.W. McClellan, R.M. Shaffer, and W.M. Aust. 2000. Effects of forest harvesting best management practices on surface water quality in the Virginia Coastal Plain. Transactions of the American Society of Agricultural and Biological Engineers 43:927-936.