# MATERIAL SAFETY DATA SHEET

R15740-02

SCM CORPORATION
Form 3001 Printed in U.S.A. 5/77

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U S Department of Labor "Essentially Similar" to Form OSHA-20)

FEB 01 1982

DATE OF PREP. 05/05/78

## Section I

MANUFACTURER'S NAME
SCM - COATINGS AND RESINS DIVISION

STREET ADDRESS
900 UNION COMMERCE BLDG

CITY, STATE, AND ZIP CODE
CLEVELAND, OHIO 44115

EMERGENCY TELEPHONE NO.
216-771-5121 EXT 2291

PRODUCT CLASS
STYRENATED VT ALKYD

MANUFACTURERS CODE IDENTIFICATION
908 R 2100

TRADE NAME NON-SLIP WALKWAY CTG

## Section II — HAZARDOUS INGREDIENTS

| INGREDIENT | PERCENT WGT. | TLV PPM | TLV mg/M³ | LEL | VAPOR PRESSURE |
|---|---|---|---|---|---|
| DIETHYLAMINE | .03 | 00025 | | 1.8 | 180.0 |
| LITHARGE 93 0/0 LEAD | 1 | | 000.2 | | |
| VMP SUPER NAPHTHA | 4 | 00200 | | .9 | 30.0 |
| XYLENE | 34 | 00100 | | 1.0 | 10.0 |

## Section III — PHYSICAL DATA

BOILING RANGE 128 TO 311 F.

VAPOR DENSITY [X] HEAVIER. [ ] LIGHTER THAN AIR

EVAPORATION RATE [ ] FASTER [X] SLOWER THAN ETHER

PERCENT VOLATILE BY VOLUME 56.7

WEIGHT PER GALLON 10.40

## Section IV — FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY
RED LABEL

FLASH POINT
55 F. TCC

LEL
.9

EXTINGUISHING MEDIA
CO2, DRY CHEMICAL OR FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT OR FIRE. DO NOT APPLY TO HOT SURFACES.

SPECIAL FIRE FIGHTING PROCEDURES

WATER MAY BE INEFFECTIVE ON FIRE BUT WATER SPRAY MAY BE USED TO COOL CLOSED CONTAINERS EXPOSED TO EXTREME HEAT OR FIRE TO PREVENT PRESSURE BUILD UP AND POSSIBLE AUTOIGNITION OR EXPLOSION.

## Section V — HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE SEE SECTION II

EFFECTS OF OVEREXPOSURE
IRRITATION OF EYES, SKIN, AND RESPIRATORY TRACT. POSSIBLE DERMATITIS ON REPEATED & PROLONGED SKIN CONTACT. POSSIBLE HEADACHE, DIZZINESS AND EVENTUAL UNCONSCIOUSNESS OR COMA.

EMERGENCY AND FIRST AID PROCEDURES
FUMES - MOVE PERSON TO WELL VENTILATED AREA, RESTORE BREATHING. GET MEDICAL ATTENTION.
SKIN CONTACT - WIPE WITH CLEAN CLOTH, WASH THOROUGHLY WITH SOAP AND WATER.
EYE CONTACT - FLUSH THOROUGHLY WITH WATER, GET MEDICAL ATTENTION.

## Section VI — REACTIVITY DATA

STABILITY [ ] UNSTABLE [X] STABLE CONDITIONS TO AVOID
INCOMPATABILITY (*Materials to avoid*) AVOID CONTAMINATION WITH FOREIGN MATERIALS.
HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION [ ] MAY OCCUR [X] WILL NOT OCCUR
CONDITIONS TO AVOID

## Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. MOP SPILLS WITH INERT ABSORBENT. BURN SWEEPINGS IN A SAFE AREA.
WASTE DISPOSAL METHOD DISPOSE IN ACCORDANCE WITH LOCAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

## Section VIII — SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION
SPRAY APPLICATION
OPEN AREAS - USE PAINT SPRAY MASK, MECHANICAL FILTER RESPIRATOR
RESTRICTED VENTILATION AREAS - USE PAINT SPRAY MASK AND APPROVED CHEMICAL-MECHANICAL FILTER
CONFINED AREAS - USE AIR LINE RESPIRATORS OR HOODS
VENTILATION
PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO KEEP VAPORS BELOW THRESHOLD LIMIT VALUES - SEE SECTION II

PROTECTIVE GLOVES SOLVENT RESISTANT GLOVES WHERE PROLONGED CONTACT IS INVOLVED
EYE PROTECTION SPLASH PROOF GOGGLES IN WORKING AREAS SUBJECT TO SPLASHING.
OTHER PROTECTIVE EQUIPMENT

## Section IX — SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
STORE BELOW 100 DEGREES F. KEEP CONTAINERS CLOSED & AWAY FROM HEAT AND OPEN FLAME
OTHER PRECAUTIONS
AVOID PROLONGED CONTACT WITH SKIN AND BREATHING VAPORS OR SPRAY MIST. DO NOT TAKE INTERNALLY.

908 B 2100

SCM® GLIDDEN-DURKEE
DIVISION OF SCM CORPORATION
COATINGS AND RESINS GROUP
EASTERN REGION

THIRD & BERN STREETS • READING, PENNA. 19601

May 19, 1978

TELEPHONE: (215) 373-4111

Douglas Aircraft Company
3855 Lakewood Blvd.
Long Beach, CA 90846

Attn: Mr. M. J. Veneroso, Dept.
C1-726 - Materials Handling & Packaging
Engineering

DPM 3465-604
Coating, Walkway, Black

Dear Mr. Veneroso:

Reference is made to your letter of January 16th under file C1-725-15 addressed to our division in Los Angeles, California, relative to our material Black Walkway Coating, RGL-27787.

We wish to advise that the D.O.T. proper shipping name per Section 172.101 is Paint, Enamel, Lacquer, Stain, Shellac, or Varnish Liquid. The D.O.T. hazard classification for this same section is Flammable, Liquid. The flash point on this material is 65°F., and the closed cup method we use is Penske - Martin's Method. The IATA article number is ~~320.~~ 1343

We are also attaching herewith a copy of the material safety data sheet as requested.

If we can be of any further assistance to you, please advise.

Very truly yours,

GLIDDEN COATING & RESINS
DIVISION, SCM CORPORATION

F. R. Quinter

F. R. Quinter
Asst. Traffic Manager

FRQ/lap

Attachment: