FEB 02 1982

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1357

AUG 8 - 1977

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME: Rust-Lick, Inc.	EMERGENCY TELEPHONE NO.: (203) 792-0052
ADDRESS (Number, Street, City, State, and ZIP Code): 92 Taylor Street - P. O. Box 1326 - Danbury, CT 06810	
CHEMICAL NAME AND SYNONYMS: Triazine/Amine	TRADE NAME AND SYNONYMS: Kill-Cide 700
CHEMICAL FAMILY: Amine	FORMULA: Hexahydro 1,3,5-tris (2-hydroxyethyl)-s-triazine

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS	0		BASE METAL	0	
CATALYST	0		ALLOYS	0	
VEHICLE	0		METALLIC COATINGS	0	
SOLVENTS	0		FILLER METAL PLUS COATING OR CORE FLUX	0	
ADDITIVES	0		OTHERS	0	
OTHERS	0				

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	212°F.	SPECIFIC GRAVITY (H2O=1)	1.155-1.158 @ 25°C
VAPOR PRESSURE (mm Hg.)	Unknown	PERCENT VOLATILE BY VOLUME (%)	0.0%
VAPOR DENSITY (AIR=1)	Unknown	EVAPORATION RATE (_____=1)	Unknown
SOLUBILITY IN WATER	100.0%		
APPEARANCE AND ODOR	Yellow, viscous liquid - Odor - Light Amine		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	260°F. Tag Open Cup	FLAMMABLE LIMITS	Lel	Uel
		Non-flammable		
EXTINGUISHING MEDIA	Carbon Dioxide, Dry Chemical or Foam			
SPECIAL FIRE FIGHTING PROCEDURES	N/A			
UNUSUAL FIRE AND EXPLOSION HAZARDS	N/A			

(Continued on reverse side)

BOE-C6-0201400

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

EFFECTS OF OVEREXPOSURE Kill-Cide 700 is harmful if swallowed. Avoid skin contact and splashing in eyes.

EMERGENCY AND FIRST AID PROCEDURES Contact of concentrate with eyes or skin should be flushed with copious amounts of water.

SECTION VI - REACTIVITY DATA

STABILITY			CONDITIONS TO AVOID
	UNSTABLE		
	STABLE	X	

INCOMPATABILITY (Materials to avoid) Phenols

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	MAY OCCUR		
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Wash with water.

WASTE DISPOSAL METHOD No special methods required.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) None

VENTILATION				
	LOCAL EXHAUST	None	SPECIAL	None
	MECHANICAL (General)	None	OTHER	N/A

PROTECTIVE GLOVES		EYE PROTECTION
	None	Protect eyes from splashing concentrate

OTHER PROTECTIVE EQUIPMENT None

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Normal precautions

OTHER PRECAUTIONS None

GPO 934-190

Form OSHA-20
Rev. May 77

BOE-C6-0201401

Rust-Lick INCORPORATED

P.O. BOX 1326 • 92 TAYLOR STREET • DANBURY, CT. 06810 • (203) 792-0052

Reply to:
Rust-Lick of California
303 North Manchester
Anaheim, California 92802
Telephone: (714) 535-6075

August 2, 1977

Mr. M. J. Veneroso - Dept. CI-726 (52-11)
Douglas Aircraft Company
3855 Lakewood Blvd.
Long Beach, Calif. 90846

Dear Mr. Veneroso:

Sorry for the delay in sending you the information requested in your June 28, 1977 letter. Enclosed please find new Material Safety Data Sheets concerning Kill-Cide 700 and Kleenzol 70.

Kleenzol 70 is classified as a liquid soap, class 55 and is not restricted or regulated. There is no flash point for this product since it is water base.

Kill-Cide 700 is also a non regulated or restricted article, with no flash point. This product is listed as non hazardous chemical, N.O.I.

We trust this information is sufficient.

Yours truly,
Rust-Lick Inc.

Charles R. Vollaro

Charles R. Vollaro
General Manager
West Coast Sales

CRV:ljh
enc.
cc: Jim Guerrera