DPM 5238 Coating, Peelable, Scratch Resistant

MATERIAL SAFETY DATA SHEET

Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

FEB 05 1982

DATE PREPARED 3/14/80

MAR 25 1980

Section I — IDENTIFICATION OF PRODUCT

EEDER CHEMICALS, INC.

.6961 KNOTT AVENUE
.A MIRADA, CA 90638

EMERGENCY TELEPHONE NO. (213)-583-9761

INFORMATION TELEPHONE NO.

ET ADDRESS

CITY, STATE and ZIP CODE

DUCT CLASS

MANUFACTURER'S CODE IDENTIFICATION TEC #755-A LOT BA

DE NAME MODIFIED RUBBER STRIPPABLE COATING

Section II — HAZARDOUS INGREDIENTS

REDIENT	PERCENT	THRESHOLD LIMIT VALUE PPM	mg/m³	LEL	VAPOR PRESSURE
METHLY ETHYL KETONE	50.0	200	590		
TOLUENE	15.0	200	750		
CELLOSOLVE ACETATE	10.0	100	540		
N-BUTYL ACETATE	10.0	150	710		

Section III — PHYSICAL DATA

ILING RANGE

VAPOR DENSITY: ☒ HEAVIER THAN AIR ☐ LIGHTER THAN AIR

APORATION RATE: ☐ FASTER THAN ETHER ☒ SLOWER THAN ETHER

PERCENT VOLATILE BY VOLUME: 91

WEIGHT PER GALLON: 7.50

Section IV — FIRE AND EXPLOSION HAZARD DATA

ammability Classification: FLAMMABLE

FLASHPOINT: 24° F TCC

LEL

TINGUISHING MEDIA: WATER FOG, FOAM, DRY CHEMICALS OR CO_2

USUAL FIRE AND EXPLOSION HAZARDS: KEEP AWAY FROM HEAT, SPARKS OR OPEN FLAME

PECIAL FIRE FIGHTING PROCEDURES: USE AIR SUPPLIED EQUIPMENT FOR ENCLOSED AREAS. COOL EXPOSED CONTAINERS WITH WATER.

While Leeder Chemicals, Inc. believes that the data contained herein are accurate and derived from qualified sources the data are not to be taken as a

BOE-C6-0202066

Section V — HEALTH HAZARD DATA

RESHOLD LIMIT VALUE: 100 PPM

FECTS OF OVEREXPOSURE:
ACUTE: INVITATION TO EYES, NOSE AND THROAT. HIGHER CONCENTRATIONS CAUSE DROWSINESS AND DIZZINESS. SKIN IRRITANT.

CHRONIC:

MERGENCY AND FIRST AID PROCEDURES: IF INHALED, REMOVE TO FRESH AIR, ADMINISTER OXYGEN IF ECESSARY. CALL PHYSICIAN. IN CASE OF CONTACT, WASH SKIN THOROUGHLY WITH WATER F SWALLOWED, CALL A PHYSICIAN IMMEDIATELY.

Section VI — REACTIVITY DATA

TABILITY. ☐ UNSTABLE ☒ STABLE CONDITIONS TO AVOID:

ICOMPATABILITY (Materials to Avoid): STRONG OXIDIZING AGENTS

IAZARDOUS DECOMPOSITION PRODUCTS: NONE

IAZARDOUS POLYMERIZATION. ☐ MAY OCCUR ☒ WILL NOT OCCUR

ONDITIONS TO AVOID:

Section VII — SPILL OR LEAK PROCEDURES

TEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: RECOVER ALL POSSIBLE, THEN WIPE UP WITH RAGS, SAWDUST AND ETC.

/ASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH LOCAL APPLICABLE REGULATIONS.

Section VIII — SPECIAL PROTECTION INFORMATION

ESPIRATORY PROTECTION: ORGANIC VAPOR CANISTER WHERE OXYGEN CONTENT IS ADEQUATE AND VAPOR CONCENTRATION IS LESS THAN 2% OR USE AIR SUPPLIED FACE MASK.

/ENTILATION:

PROTECTIVE GLOVES: NEOPRENE RUBBER GLOVES

EYE PROTECTION: GOGGLES

OTHER PROTECTIVE EQUIPMENT:

Section IX — SPECIAL PRECAUTIONS

RECAUTIONS TO BE TAKEN IN HANDLING AND STORING: KEEP CONTAINERS CLOSED. AVOID FLAMES, WELDING, SMOKING, SPARKS, OPEN LIGHTS, ETC.

OL STORAGE CATEGORY:

THER PRECAUTIONS: MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN CONFINED AREAS, TANK OR PIT WITHOUT ADEQUATE VENTILATION.