DPM 0555

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

FEB 08 1982

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME: FreKote, Inc.	EMERGENCY TELEPHONE NO.: (305) 395-3083
ADDRESS (Number, Street, City, State, and ZIP Code): P.O. Box 825, Boca Raton, Florida 33432	
CHEMICAL NAME AND SYNONYMS: proprietary	TRADE NAME AND SYNONYMS: FreKote 33
CHEMICAL FAMILY: semi-organic polymer	FORMULA: n.a.

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS see below			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Methylene Chloride (DICHLOROMETHANE) ORA IATA 591	31.0	
Trichlorotrifluoroethane NOT REST.	40.0	
Xylene — distill F.C.	3.8	
~~Perchloroethylene~~	0.9	
Medium boiling aliphatic hydrocarbon	24.3	

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	n.a.	SPECIFIC GRAVITY (H_2O=1)	1.1281 ± 2%
VAPOR PRESSURE (mm Hg.)	n.a.	PERCENT, VOLATILE BY VOLUME (%)	n.a.
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____ =1)	
SOLUBILITY IN WATER	slight		
APPEARANCE AND ODOR	essentially colorless; mild		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used): 175°F (open cup) less 10% for ca 157.5	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA: powder or foam recommended			
SPECIAL FIRE FIGHTING PROCEDURES: n.a.			
UNUSUAL FIRE AND EXPLOSION HAZARDS: n.a.			

(Continued on reverse side)

Form OSHA-20
Rev. May 72

BOE-C6-0202368