MATERIAL SAFETY DATA SHEET

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

ATE OF PREP. 7/10/75

Section I

ANUFACTURER'S NAME AIRTECH INTERNATIONAL, INC.

TREET ADDRESS 2750 Oregon Court, Bl. M CITY, STATE, AND ZIP CODE Torrance, Calif. 90509

MERGENCY TELEPHONE NO. 213-320-7950

RODUCT CLASS Plastic release agent MANUFACTURERS CODE IDENTIFICATION

RADE NAME Release All #100

Section II — HAZARDOUS INGREDIENTS

NGREDIENT	PERCENT	TLV PPM	TLV mg/m³	LEL	VAPOR PRESSURE
Alcoholic and Aliphatic hydrocarbon solvent	96.5	200-400		1.2	

Section III — PHYSICAL DATA

OILING RANGE N.A. VAPOR DENSITY [X] HEAVIER, [ ] LIGHTER, THAN AIR

VAPORATION RATE [ ] FASTER [X] SLOWER, THAN ETHER PERCENT VOLATILE BY VOLUME 96.5 WEIGHT PER GALLON 6.4 lbs.

Section IV — FIRE AND EXPLOSION HAZARD DATA

OT CATEGORY Red Label; extremely flammable. FLASH POINT 23°F. (TOC) LEL 1.2

(-10% face) 20° (est. closed cup)

XTINGUISHING MEDIA Foam or CO_2, dry chemical, CCl_4

NUSUAL FIRE AND EXPLOSION HAZARDS Highly flammable composition

PECIAL FIRE FIGHTING PROCEDURES