Section V — HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE 200-400 ppm

EFFECTS OF OVEREXPOSURE Mild irritation of eyes, nose and throat above 400 ppm. May induce mild narcosis.

EMERGENCY AND FIRST AID PROCEDURES Move patient to fresh air. For eye or skin contact, flush thoroughly with water; obtain medical attention for eyes.

Section VI — REACTIVITY DATA

STABILITY [ ] UNSTABLE [X] STABLE CONDITIONS TO AVOID

INCOMPATABILITY (*Materials to avoid*)

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION [ ] MAY OCCUR [X] WILL NOT OCCUR

CONDITIONS TO AVOID

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Flush residue away with water.

WASTE DISPOSAL METHOD Pick up with inert absorbent and discard. Dissipate vapors.

Section VIII — SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION Not usually needed, unless concentrations are excessively high.

VENTILATION Normal ventilation adequate as with other solvent materials.

PROTECTIVE GLOVES Not normally needed.

EYE PROTECTION Goggles suggested in case of splashes

OTHER PROTECTIVE EQUIPMENT

Section IX — SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Treat as flammable solvent blend. Store in cool place, well away from all heat sources, sparks and open flames. Close container after use.

OTHER PRECAUTIONS