DPM 53c 7

Fluid, Metal working

Reliance

Chemical Coatings/Resins

# Reliance Universal Inc.

1215 W. Lambert Rd., Brea, California 92621 • Phones 213-694-1873 714-525-2714

January 26, 1978

Mr. M. J. Veneroso, Dept. C1-726 (52-11)
Materials Handling & Packaging Engineering
3855 Lakewood Blvd.
Long Beach, CA 90846

Dear Mr. Veneroso:

This letter is written to you in answer to your request of January 16, 1978, for compliance with the Hazardous Materials Regulations of the Department of Transportation, Title 49, Code of Federal Regulations.

On our product 50-C018-151 High Speed Drilling Fluid:

1. DOT Proper Shipping Name Section 172.101, 49 CFR. is: Solvent, N.O.S.
2. DOT Hazard Classification per Section 172.101, 49 CFR is: Combustible Liquid.
3. Flash Point and Closed Cup method per Section 173.115, 49 CFR. is: 190°F Closed Cup.
4. IATA Article Number is: 2448.

DPM 5172

On our product 50-C4-130 Metal Working Fluid:

1. DOT Proper Shipping Name per Section 172.101, 49 CFR. is: Solvent, N.O.S.
2. DOT Hazard Classification per Section 172.101, 49 CFR. is: Combustible Liquid.
3. Flash Point and Closed Cup method per Section 173.115, 49 CFR. is: 165°F Closed Cup.
4. IATA Article Number is: 2448.

DPM 5389

Sincerely,

RELIANCE UNIVERSAL INC.

Darlene Totten

Darlene Totten
Secretary

/d

cc: S. E. Sadlak

OUR GUARANTEE: "Since methods and conditions of application and use are beyond our control, all merchandise is sold and received subject to the condition that our liability for any defect in quality, or for any lack of fitness for the use made thereof, is limited to the return of the purchase price if written claim is made within 90 days from the date of shipment."

TECHNICAL ADVICE: The technical advice contained herein is based on tests believed to be reliable and is offered as a helpful suggestion. It is expressly understood, however, that all such technical advice is given gratis and Reliance assumes no obligation or liability for the advice given or the results obtained, all such advice being given and accepted at buyer's risk. Further, where equipment or other companies' products are mentioned, we do not imply an unqualified recommendation as there are undoubtedly others of similar types on the market which may be equally or better suited for the purpose.

**ADVANCED**
COATINGS AND CHEMICALS
2213 NORTH TYLER AVENUE, SOUTH EL MONTE, CALIFORNIA 91733 TELEPHONE (213) 579-6270

January 27, 1978

Mr. M. J. Veneroso, D/C1-726 (52-11)
Materials Handling & Packaging Engrg.
Douglas Aircraft Co.
3855 Lakewood /Blvd.
Long Beach, Ca. 90846

Dear Mr. Veneroso:

In reply to your letter of January 16th, following is the information you requested for DOT markings on our materials.

| | | | | | |
|---|---|---|---|---|---|
| DPM 3689 | Cad Coat 30C-53 | Aqueous | Non Restricted Article | | |
| DPM 5172 | Drilling Fluid 30C-52 | 157° F. | " | " | " |
| | Metal Working Fluid, | | " | " | " |
| DPM 5389 | 30C-51 | 157° F. | " | " | " |
| DPM 5958 | Coating, 26W-1 | 150° F. | " | " | " |
| | Water Base Finish, | | | | |
| DPM 5948 | 47 Series | Aquaeous | " | " | " |
| DPM 5858-1 | Solvent 30C-5 | 105° F. | " | " | " |
| DPM 5858-2 | Reducer, 30C-9 | 40° F. | Reducing Compound, ~~Corrosive~~ Flammable Liquid | | |
| | Coating, EM 45 | 20° F. | Resin Solution, Flammable Liquid | | |
| DPM 5864 | Catalyst EM 46 | 101° F. | Non Restricted Articles | | |

IATA Article No. for Resin Solution is 1547, Iata No. 320. ?
IATA No. fo Solvent 30C-9 is 820. NO!

I hope this is the information you require. If not, please let me know.

Sincerely,

ADVANCED COATINGS & CHEMICALS

Ethel Stern

Ethel Stern,
Sales Coordinator

Called Ethel Stern 30C-9 (Corr. Liq. is in error - should be Flam. Liq.)



BOE-C6-0202563