DPM5535-1 Part A FEB 09 1982

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME Dexter Corporation, Hysol Division	EMERGENCY TELEPHONE NO. 415/687-4201 or 415/682-9440 after 12:00 PM & Weekends
ADDRESS *(Number, Street, City, State, and ZIP Code)* 2850 Willow Pass Road (P.O. Box 312), Pittsburg, California 94565	
CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS EA 956 Part A
CHEMICAL FAMILY Epoxy Resins	FORMULA

SECTION II · HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE Epoxy Resins	100		METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)

SECTION III · PHYSICAL DATA

BOILING POINT (°F.)	Decomposes before boiling	SPECIFIC GRAVITY (H_2O=1)	1.25
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT, VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____=1)	N/A
SOLUBILITY IN WATER	Negligible		
APPEARANCE AND ODOR	Amber liquid with slight odor		

SECTION IV · FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	>212°F TCC	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA	Chemical Foam, Dry Chemicals, CO_2			
SPECIAL FIRE FIGHTING PROCEDURES	None			
UNUSUAL FIRE AND EXPLOSION HAZARDS	Dense smoke may be liberated.			

(Continued on reverse side)

Form OSHA-20
Rev. May 72

BOE-C6-0203041