JAN 17 1982

DPM 1177

Form Approved
Budget Bureau No. 44-R1387
Approval Expires April 30, 1971

Form No. LSB-OOS-4
May 1969

U.S. DEPARTMENT OF LABOR

WORKPLACE STANDARDS ADMINISTRATION

Bureau of Labor Standards

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME: Essex Chemical Corp., Coast Pro-Seal Division	EMERGENCY TELEPHONE NO.: (213) 636-0851
ADDRESS (Number, Street, City, State, and ZIP Code): 19451 Susana Road Compton, California 90221	
CHEMICAL NAME AND SYNONYMS: N/A	TRADE NAME AND SYNONYMS: Pro-Seal 727B (Accelerator)
CHEMICAL FAMILY: N/A	FORMULA: N/A

SECTION II HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST Lead peroxide	55-60%		ALLOYS		
VEHICLE Plasticizer	35-45%		METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)

SECTION III PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H_2O=1)	2.2
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	0
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____=1)	N/A
SOLUBILITY IN WATER	Nil		
APPEARANCE AND ODOR	Brown paste, slight odor		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used): Over 200°F	FLAMMABLE LIMITS: N/A	Lel	Uel
EXTINGUISHING MEDIA: Dry chemical, foam, CO_2, water			
SPECIAL FIRE FIGHTING PROCEDURES: None			
UNUSUAL FIRE AND EXPLOSION HAZARDS: None			

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	Unknown
EFFECTS OF OVEREXPOSURE	Do not ingest.
EMERGENCY AND FIRST AID PROCEDURES	Give emetic, consult physician immediately.

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATABILITY *(Materials to avoid)*	Strong reducing agents
HAZARDOUS DECOMPOSITION PRODUCTS	None

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Clean spillage with rags or sweeping compound and solvents.

WASTE DISPOSAL METHOD

Preferably burn waste.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION *(Specify type)* Recommended confined areas- cannister type

VENTILATION	LOCAL EXHAUST	Recommended	SPECIAL
	MECHANICAL *(General)*		OTHER

PROTECTIVE GLOVES	Recommended	EYE PROTECTION	Recommended

OTHER PROTECTIVE EQUIPMENT Coveralls, apron

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Avoid contact and ingestion. Store in closed container below 80 deg. F

OTHER PRECAUTIONS Red label material.