JAN 17 1982

PPM 1310-1

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Resin, Epoxy, Low Temp Resisting

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME: POLY-RESINS	EMERGENCY TELEPHONE NO.: (213) 768-6600
ADDRESS (Number, Street, City, State, and ZIP Code): 11737 Wicks St., Sun Valley, Ca. 91352	
CHEMICAL NAME AND SYNONYMS: Polymeric Epoxies	TRADE NAME AND SYNONYMS: Qualitool 214 Resin
CHEMICAL FAMILY	FORMULA

SECTION II HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Polymeric Epoxies	100	

SECTION III PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H_2O=1)	
VAPOR PRESSURE (mm Hg.)		PERCENT VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____=1)	
SOLUBILITY IN WATER	Insoluble		
APPEARANCE AND ODOR	Slight yellow liquid; odor slightly aromatic		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used): 470°F (243°C) Pensky-Marten cc	FLAMMABLE LIMITS	Lel	Uel

EXTINGUISHING MEDIA
CO_2, dry chemical, chemical foam or water fog may be used

SPECIAL FIRE FIGHTING PROCEDURES
The usual fireman's body protection should be worn as well as self-contained breathing apparatus to protect from smoke and vapors

UNUSUAL FIRE AND EXPLOSION HAZARDS

(Continued on reverse side)

Form OSHA-20
Rev. April 72

BOE-C6-0203430

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

EFFECTS OF OVEREXPOSURE
Prolonged or frequent contact may cause dermatitis, thus good industrial hygiene practices should be observed.

EMERGENCY AND FIRST AID PROCEDURES
Skin contact - wash with soap and water. Eye contact - flush the eyes thoroughly with water and consult a physician immediately.

SECTION VI REACTIVITY DATA

STABILITY			CONDITIONS TO AVOID
	UNSTABLE		
	STABLE	X	250°F to 350°F

INCOMPATABILITY *(Materials to avoid)*

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	MAY OCCUR		
	WILL NOT OCCUR		

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Absorb in absorbent sweeping/cleaning compound.

WASTE DISPOSAL METHOD

Disposal of waste should be in accordance with Federal, State and local regulations regarding environmental control.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION *(Specify type)*

VENTILATION	LOCAL EXHAUST	SPECIAL
	MECHANICAL *(General)*	OTHER

PROTECTIVE GLOVES
Chemical resistant rubber

EYE PROTECTION
Safety goggles - chemical resistant

OTHER PROTECTIVE EQUIPMENT
Safety showers and eye stations should be available.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

OTHER PRECAUTIONS

Form OSHA-20
Rev. April 72

BOE-C6-0203431