JAN 17 1982

MATERIAL SAFETY DATA SHEET

NPCA 1-

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

DPM1336 -11136

DATE OF PREP. NOV 1 1 1974

Section I

MANUFACTURER'S NAME: Sprayon Products, Inc.

EMERGENCY TELEPHONE NO. 216/292-7400

STREET ADDRESS: 26300 Fargo Avenue

CITY, STATE, AND ZIP CODE: Bedford Hts., Ohio 44146

PRODUCT CLASS (aerosol) Paint

MANUFACTURERS CODE IDENTIFICATION No. 1110

TRADE NAME: Red Enamel

Lab No. 18301 8/23/74

Section II — HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV PPM	TLV mg/M³	LEL	VAPOR PRESSURE
VM&P Naphtha	10	500		0.9	
Methylene Chloride	20	500		none	
Toluol	20	100		1.2	
Butyl Alcohol	less than 5	100		1.4	
Propellant-50/50 blend	25				
Propane		1000		2.3	
Isobutane		1000		1.8	
Aerosol - Contents Under Pressure					40 ± 5 psig

Section III — PHYSICAL DATA

BOILING RANGE: Propellant below 0°F.

VAPOR DENSITY [X] HEAVIER [ ] LIGHTER, THAN AIR

EVAPORATION RATE [*] FASTER [ ] SLOWER, THAN ETHER
*propellants

PERCENT VOLATILE BY VOLUME 90

WEIGHT PER GALLON n.a.

Section IV — FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY: Flammable Compressed Gas
No label required

FLASH POINT: propellant below 0°F. (T.O.C.)

LEL: See Section II

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical or foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Do not spray near open flame. Keep at room temperature as exposure to direct sunlight or other heat may cause bursting.

SPECIAL FIRE FIGHTING PROCEDURES: Water may be ineffective - Water may be used to keep fire exposed containers cool.

Section V — HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II Hazardous Ingredients

EFFECTS OF OVEREXPOSURE: Possible dizziness or nausea

EMERGENCY AND FIRST AID PROCEDURES: Remove to fresh air - call physician.
If sprayed in eye, flush thoroughly with water - call physician.

Section VI — REACTIVITY DATA

STABILITY [ ] UNSTABLE [X] STABLE

CONDITIONS TO AVOID: Do not store above 120°F.

INCOMPATABILITY (*Materials to avoid*)

HAZARDOUS DECOMPOSITION PRODUCTS: By open flame: Carbon Monoxide, Carbon Dioxide
Hydrogen Chloride

HAZARDOUS POLYMERIZATION [ ] MAY OCCUR [X] WILL NOT OCCUR

CONDITIONS TO AVOID

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition, ventilate.
Avoid breathing vapors and remove with inert absorbent

WASTE DISPOSAL METHOD: Do not incinerate - Dispose in accordance with Federal, State and local regulations regarding pollution.

Section VIII — SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Avoid breathing of vapor or spray mist

VENTILATION: Provide local exhaust ventilation in volume and pattern to keep TLV of most hazardous ingredients in Section II below acceptable limit, and LEL in Section IV below stated limit.

PROTECTIVE GLOVES

EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

Section IX — SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120°F. Keep at room temperature as exposure to direct sunlight or other heat may cause bursting.

OTHER PRECAUTIONS: Do not puncture or incinerate. Do not spray near fire or open flame. Keep away from children.