DPM 1337 - Series
Deleted 1210, 17875 + 11105

MATERIAL SAFETY DATA SHEET

NPCA 1

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

DPM 1337 - 1210

DATE OF PREP

Superseded to DPM 1336-1210

Section I

MANUFACTURER'S NAME: Sprayon Products, Inc.

EMERGENCY TELEPHONE NO. 216/292-7400

STREET ADDRESS: 26300 Fargo Avenue

CITY, STATE, AND ZIP CODE: Bedford Hts., Ohio 44146

PRODUCT CLASS (aerosol): Paint

MANUFACTURERS CODE IDENTIFICATION: No. 1210

TRADE NAME: Sprayon Orange Enamel

Lab No. 34420 8/23/74

Section II — HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV PPM	TLV mg/M³	LEL	VAPOR PRESSURE
VM&P Naphtha	15	500		0.9	
Toluol	15	100		1.2	
Xylol	10	100		1.1	
Butyl Alcohol less than	5	100		1.4	
Methylene Chloride	15	500		none	
Propellant-50/50 blend	25				
Isobutane		1000		1.8	
Propane		1000		2.3	
Aerosol - Contents Under Pressure					40 ± 5 psig

Section III — PHYSICAL DATA

BOILING RANGE: Propellant-below 0°F.

VAPOR DENSITY: [X] HEAVIER [ ] LIGHTER, THAN AIR

EVAPORATION RATE: [*] FASTER [ ] SLOWER, THAN ETHER
*propellants

PERCENT VOLATILE BY VOLUME: 90

WEIGHT PER GALLON: n.a.

Section IV — FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY: Flammable Compressed Gas
No label required

FLASH POINT: propellant below 0°F. (T.O.C.)

LEL: See Section I

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical or foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Do not spray near open flame. Keep at room temperature as exposure to direct sunlight or other heat may cause bursting.

SPECIAL FIRE FIGHTING PROCEDURES: Water may be ineffective - Water may be used to keep fire exposed containers cool.

Section V — HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	See Section II Hazardous Ingredients
EFFECTS OF OVEREXPOSURE	Possible dizziness or nausea
EMERGENCY AND FIRST AID PROCEDURES	Remove to fresh air - call physician. If sprayed in eye, flush thoroughly with water - call physician.

Section VI — REACTIVITY DATA

STABILITY [ ] UNSTABLE [X] STABLE

CONDITIONS TO AVOID Do not store above 120°F.

INCOMPATABILITY (*Materials to avoid*)

HAZARDOUS DECOMPOSITION PRODUCTS By open flame: Carbon Monoxide, Carbon Dioxide Hydrogen Chloride

HAZARDOUS POLYMERIZATION [ ] MAY OCCUR [X] WILL NOT OCCUR

CONDITIONS TO AVOID

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Remove all sources of ignition, ventilate Avoid breathing vapors and remove with inert absorbent
WASTE DISPOSAL METHOD	Do not incinerate - Dispose in accordance with Federal, State and local regulations regarding pollution.

Section VIII — SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION	Avoid breathing of vapor or spray mist
VENTILATION	Provide local exhaust ventilation in volume and pattern to keep TLV of most hazardous ingredients in Section II below acceptable limit, and LEL in Section IV below stated limit.
PROTECTIVE GLOVES	
EYE PROTECTION	
OTHER PROTECTIVE EQUIPMENT	

Section IX — SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Do not store above 120°F. Keep at room temperature as exposure to direct sunlight or other heat may cause bursting.
OTHER PRECAUTIONS	Do not puncture or incinerate. Do not spray near fire or open flame. Keep away from children.