JAN 22 1982

MATERIAL SAFETY DATA SHEET

NPCA 1-7

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

DPM1337

DATE OF PREP

Section I

-12197

MANUFACTURER'S NAME: **Sprayon Products, Inc.** EMERGENCY TELEPHONE NO. **216/292-7400**

STREET ADDRESS: **26300 Fargo Avenue**

CITY, STATE, AND ZIP CODE: **Bedford Hts., Ohio 44146**

PRODUCT CLASS (aerosol) **Coating** MANUFACTURERS CODE IDENTIFICATION **L-38**

TRADE NAME: **Sprayon Orange** Lab No. **23185** 1/27/75

Section II — HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV PPM	TLV mg/M³	LEL	VAPOR PRESSURE
Acetone	25	1000		2.6	
Methyl Ethyl Ketone	25	200		1.8	
Toluol	10	100		1.2	
Methylene Chloride	5	500		none	
Butyl Acetate	5	150		1.7	
Pentoxone (Shell Chemical) less than	5	75		1.1	
Propellant - Propane	15	1000		2.3	
Aerosol - Contents Under Pressure					40 ± 5 psig

Section III — PHYSICAL DATA

BOILING RANGE **Propellant below 0°F.** VAPOR DENSITY [X] HEAVIER [ ] LIGHTER THAN AIR

EVAPORATION RATE [*] FASTER [ ] SLOWER, THAN ETHER *propellants

PERCENT VOLATILE BY VOLUME **90** WEIGHT PER GALLON n.a.

Section IV — FIRE AND EXPLOSION HAZARD DATA

DOT CATEGORY: Flammable Compressed Gas No label required

FLASH POINT: propellant below 0°F. (T.O.C.)

LEL: **See Section II**

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical or foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Do not spray near open flame. Keep at room temperature as exposure to direct sunlight or other heat may cause bursting.

SPECIAL FIRE FIGHTING PROCEDURES: Water may be ineffective - Water may be used to keep fire exposed containers cool.

Section V — HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II Hazardous Ingredients

EFFECTS OF OVEREXPOSURE: Possible dizziness or nausea

EMERGENCY AND FIRST AID PROCEDURES: Remove to fresh air - call physician.
If sprayed in eye, flush thoroughly with water - call physician.

Section VI — REACTIVITY DATA

STABILITY [ ] UNSTABLE [X] STABLE

CONDITIONS TO AVOID: Do not store above 120 F.

INCOMPATABILITY (*Materials to avoid*)

HAZARDOUS DECOMPOSITION PRODUCTS: By open flame: Carbon Monoxide, Carbon Dioxide
Hydrogen Chloride

HAZARDOUS POLYMERIZATION [ ] MAY OCCUR [X] WILL NOT OCCUR

CONDITIONS TO AVOID

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition, ventilate
Avoid breathing vapors and remove with inert absorbent

WASTE DISPOSAL METHOD: Do not incinerate - Dispose in accordance with Federal,
State and local regulations regarding pollution.

Section VIII — SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Avoid breathing of vapor or spray mist

VENTILATION: Provide local exhaust ventilation in volume and pattern to keep
TLV of most hazardous ingredients in Section II below
acceptable limit, and LEL in Section IV below stated limit.

PROTECTIVE GLOVES

EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

Section IX — SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120°F. Keep at room temperature
as exposure to direct sunlight or other heat may cause bursting.

OTHER PRECAUTIONS: Do not puncture or incinerate. Do not spray near fire or open flame.
Keep away from children.