DPm 22 92-6

MATERIAL SAFETY DATA SHEET

REC'D SEP 11 1987

SECTION I

U

PRODUCT NAME: PR-1422 B-6, Part B

MSDS IDENTIFICATION NO: MS3548B00
DATE OF ISSUE: 11-21-86
PREPARED BY: LR

DESCRIPTION: Polysulfide rubber compound.

MANUFACTURER: Products Research & Chemical Corporation
5430 San Fernando Road, P.O. Box 1800, Glendale, CA 91209

EMERGENCY TELEPHONE: (818) 240-2060

SECTION II - HAZARDOUS INGREDIENTS

CHEMICAL NAME	COMMON NAME	CAS NO	OSHA PEL	CALOSHA PEL	ACGIH TLV
4,4'-Isopropylidene phenol epichlorohydrin polymer	epoxy resin	25068-38-6	Not est.	Not est.	Not est.
Phenol polymer with formaldehyde	phenolic resin	9003-35-4	Not est.	Not est.	Not est.
Methyl benzene	Toluene	108-88-3	200 ppm	100 ppm	100 ppm

SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point, °F.:	Not applicable.	Specific Gravity:	1.37
Vapor Pressure, mm Hg:	Not applicable.	% Volatiles, by Vol:	2.0
Vapor Density:	Not applicable.	Evaporation Rate:	Unk.
Solubility in Water:	Negligible.		

BOE-C6-0203994

SECTION IV - PHYSICAL HAZARD INFORMATION

Flash Point:	92°F, PMCC	Flammable Limits:	Not applicable.
Extinguishing Media:	CO_2, dry chemical, water spray.		
Spec. Fire Fighting Proc:	Use air-supplied respirator.		
Unusual Fire Hazards:	None known.		
Stability:	Stable.		
Incompatibility:	None known.		
Decomposition products:	Oxides of carbon, SO_2, traces of H_2S.		
Hazardous polymerization:	Will not occur.		

SECTION V - HEALTH HAZARD INFORMATION

EFFECTS OF OVER-EXPOSURE:

Eyes:	Irritation. Possible eye damage.
Skin:	Local irritation. May produce allergic skin rash in sensitized individuals.
Inhalation:	Nose and throat irritation.
Ingestion:	May cause nausea, vomiting, and liver and kidney damage.

SECTION VI - EMERGENCY FIRST AID PROCEDURES

Eyes:	Flush with luke warm water for 15 minutes. If symptoms persist, consult a physician.
Skin:	Wash with soap and water. If symptoms persist, consult a physician.
Inhalation:	Remove to fresh air. If symptoms are present, consult a physician.
Ingestion:	Consult a physician.

SECTION VII - SUGGESTED CONTROL PROCEDURES

Ventilation:	General ventilation.
Skin Protection:	Solvent resistant gloves.
Eye Protection:	Safety glasses.

SECTION VIII - SPILL OR LEAKAGE PROCEDURES

Release or Spillage:	Scoop into container. Clean residue with 1,1,1-trichloroethane.
Waste Disposal:	EPA Waste No. D-001. Dispose of spillage in compliance with Federal and State regulations.

SECTION IX - SPECIAL PRECAUTIONS

None.

The information provided herein is, to the best of the manufacturer's knowledge, current, accurate and complete, based on information reasonably available.

BOE-C6-0203996