D/M 2301

JAN 14 1982

Rexco Chemical Company

P.O. BOX 1045 CARPENTERIA, CALIFORNIA 93013 (805) 969-1214

MATERIAL SAFETY DATA SHEET, FORM NO. LSB-00S-4

TEST RESULTS: PARTALL FILM #10

HAZARDOUS INGREDIENTS	%	TLV
Quakersol #190 (AMSCO)	50	Unknown
Normal butyl alcohol	8	Unknown

PHYSICAL DATA	
Boiling Point (Range)	158 to 220° F
Vapor Pressure	26.67 mm/Hg
Vapor Density	1.2
Solubility in Water	Complete
Specific Gravity (H_2O=1)	0.914
Percent Volatile by Volume	15% in one week
Evaporation Rate (Ether = 1)	0.039
Appearance	Watery green liquid
Odor	Alcoholic

FIRE AND EXPLOSION HAZARD	
Flash Point (Cleveland Open Cup)	70° F
Extinguishing Media	Alcohol type foam
Special Fire Fighting Procedures	Smother; same as for alcohol
Unusual Fire and Explosion Hazards	Low flash point

HEALTH HAZARD DATA	
Threshold Limit Value	Unknown
Effect of Overexposure	Overexposure to Fumes - Light Headed, Nauseous
Emergency and First Aid Procedures	
Overexposure to Fumes	Expose victim to fresh air
Contact with Eyes	Flush immediately with cold water
Contact with Skin	Wash with soap and water
Ingestion of fluid	Induce vomiting immediately; call physician as soon as possible

REACTIVITY DATA	
Stability	Stable
Incompatability	None
Hazardous Decomposition Products	None
Hazardous Polymerization	None

SPILL OR LEAK PROCEDURES	
Steps to be taken in case material is released or spilled	Avoid open flames; do not smoke; flush with water
Waste disposal method	Controlled burning

SPECIAL PROTECTIVE INFORMATION	
Respiratory Protection	Adequate ventilation
Protective Gloves	Avoid prolonged contact with skin
Eye Protection	Avoid direct contact with eyes

SPECIAL PRECAUTIONS	
Precautions to be taken in handling and storing	Avoid open flames or high temperatures

This information is presented in good faith, but warranty as to accuracy of results is not given, nor is freedom from patent infringement to be inferred. It is offered solely for your consideration, investigation and verification.