U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

DPM 2449-2

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME: Turco Products, Inc.	EMERGENCY TELEPHONE NO.: (213) 634-3300
ADDRESS (Number, Street, City, State, and ZIP Code): 24600 South Main Street, Carson, California 90745	
CHEMICAL NAME AND SYNONYMS:	TRADE NAME AND SYNONYMS: Turco Dy-Chek Remover LS
CHEMICAL FAMILY:	FORMULA:

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Alaphatic petroleum solvent	95	200PPM
Other ingredients not defined as hazardous by U.S. Dept. of Labor		
Carcinogens	None	

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	350°F	SPECIFIC GRAVITY (H_2O=1)	0.81
VAPOR PRESSURE (mm Hg.)	Less than 1	PERCENT, VOLATILE BY VOLUME (%)	95
VAPOR DENSITY (AIR=1)	6mm	EVAPORATION RATE (butyl acetate)	Less than 1
SOLUBILITY IN WATER	Moderate		
APPEARANCE AND ODOR	Clear light brown liquid-solvent odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	140°F	FLAMMABLE LIMITS	Lel 1 / Uel 7
EXTINGUISHING MEDIA	Carbon dioxide, dry chemical, foam		
SPECIAL FIRE FIGHTING PROCEDURES			
UNUSUAL FIRE AND EXPLOSION HAZARDS			

(Continued on reverse side)

BOE-C6-0204120

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II

EFFECTS OF OVEREXPOSURE: Eye; irritation, Skin; defatting, Inhalation; headache, nausea Ingestion; nausea

EMERGENCY AND FIRST AID PROCEDURES: Eyes; flush with water, if irritation persists obtain med. att. Skin; wash with water. Ingestion; DO NOT INDUCE VOMITING, obtain med. att. Inhalation; remove to fresh air

SECTION VI - REACTIVITY DATA

STABILITY			CONDITIONS TO AVOID
	UNSTABLE		
	STABLE	x	

INCOMPATABILITY (Materials to avoid): Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide

HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	MAY OCCUR		
	WILL NOT OCCUR	x	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate sources of ingnition. Absorb on rags or other material

WASTE DISPOSAL METHOD

As for petroleum hydrocarbons

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type): recommended for enclosed spaces

VENTILATION			
	LOCAL EXHAUST	x	SPECIAL
	MECHANICAL (General)		OTHER

PROTECTIVE GLOVES	x	EYE PROTECTION	x

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Transport and store at temperatures between 30°F and 100°F

OTHER PRECAUTIONS

Form OSHA-20
Rev. May 72

BOE-C6-0204121