DPM 3025

MAR 1 0 1980

910-758
Catalyst.

CONTAINS ALIPHATIC ISOCYANATE MONOMER, POLYMER, KETONE, ESTER, AND TOLUOL OR XYLOL SOLVENTS

W A R N I N G

FLAMMABLE

proper shipping name is: paint, enamel, liquid

VAPOR AND SPRAY MIST HARMFUL. MAY CAUSE LUNG IRRITATION AND ALLERGIC RESPIRATORY REACTION. MAY IRRITATE SKIN AND EYES.

Hazard Classification is: flammable liquid

Flash point is 22°

IATA art: # is 1343

USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING OF VAPOR OR SPRAY MIST. WEAR APPROPRIATE RESPIRATORY PROTECTION IF GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IS NOT ADEQUATE TO KEEP VAPOR OR PARTICULATE CONCENTRATIONS BELOW REGULATED OR RECOMMENDED LEVELS.

AVOID CONTACT WITH EYES AND SKIN. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. KEEP CONTAINER CLOSED WHEN NOT IN USE AND UPRIGHT TO PREVENT LEAKAGE. IN CASE OF SPILLAGE, ABSORB AND FLUSH WITH LARGE VOLUMES OF WATER IMMEDIATELY.

FIRST AID: IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE TO FRESH AIR. IF BREATHING DIFFICULTY PERSISTS OR OCCURS LATER, CONSULT A PHYSICIAN AND HAVE LABEL INFORMATION AVAILABLE. IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR 15 MINUTES; CALL A PHYSICIAN. IN CASE OF SKIN CONTACT, WASH THOROUGHLY WITH SOAP AND WATER. IF SWALLOWED, C A L L A P H Y S I C I A N I M M E D I A T E L Y. INDUCE VOMITING.

IMPORTANT! THE CONTENTS OF THIS PACKAGE MUST BE BLENDED WITH OTHER COMPONENTS BEFORE THE PRODUCT CAN BE USED. BEFORE OPENING THE PACKAGES. READ ALL WARNING LABELS (AND AVAILAB LE TECHNICAL BULLETIN).
FOLLOW ALL PRECAUTIONS. KEEP OUT OF REACH OF CHILDREN.

F O R I N D U S T R I A L U S E O N L Y.

DeSOTO, INC.
DES PLAINES, IL 60018 PREC. #244

820-732 Base

MAR 1 0 1980

- proper shipping name is Paint, enamel, liquid
- Hazard Classification is flammable liquid
- Flash point is 28°F
- IATA art. # is 1343

CONTAINS ESTER AND KETONE SOLVENTS

WARNING

FLAMMABLE
VAPOR MAY BE HARMFUL
MAY CAUSE IRRITATION

Keep away from heat, sparks and open flame.

Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Wear appropriate respiratory protection if general dilution or local exhaust ventilation is not adequate to keep vapor or particulate concentrations below regulated or recommended levels.

Avoid contact with eyes or skin.

Keep container closed when not in use and upright to prevent leakage. In case of spillage, absorb and flush with large volumes of water immediately.

FIRST AID: In case of eye contact, flush with plenty of water for 15 minutes and get medical attention; for skin contact, flush with water. In case of exposure to high concentration of vapor, remove to fresh air. If swallowed, CALL A PHYSICIAN IMMEDIATELY. Induce vomiting.

KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL USE ONLY.

DeSoto, Inc.
Des Plaines, IL 60018

Prec. # 139

BOE-C6-0204614

910-730 Curing sol.

MAR 1 0 1980

1. proper shipping name is:
Paint, enamel, liquid

2. Hazard Classification is
flammable liquid

3. Flash point is: 30° F.

4. IATA art. # is 1343

CONTAINS ALIPHATIC ISOCYANATE MONOMER, POLYMER, KETONE AND ESTER SOLVENTS

WARNING

FLAMMABLE

VAPOR AND SPRAY MIST HARMFUL. MAY CAUSE LUNG IRRITATION AND ALLERGIC RESPIRATORY REACTION. MAY IRRITATE SKIN AND EYES.

Use only with adequate ventilation.

Avoid breathing of vapor or spray mist. Wear appropriate respiratory protection if general dilution or local exhaust ventilation is not adequate to keep vapor or particulate concentrations below regulated or recommended levels.

Avoid contact with eyes and skin.

Keep away from heat, sparks and open flame.

Keep container closed when not in use and upright to prevent leakage. In case of spillage, absorb and flush with large volumes of water immediately.

FIRST AID: If affected by inhalation of vapor or spray mist, remove to fresh air. If breathing difficulty persists or occurs later, consult a physician and have label information available. In case of eye contact, flush immediately with plenty of water for 15 minutes; call a physician. In case of skin contact, wash thoroughly with soap and water. If swallowed, CALL A PHYSICIAN IMMEDIATELY. Induce vomiting.

IMPORTANT! The contents of this package must be blended with other components before the product can be used. Before opening the packages, read all warning labels (and available Technical Bulletin). Follow all precautions. **KEEP OUT OF REACH OF CHILDREN.**

FOR INDUSTRIAL USE ONLY.

DeSoto, Inc.
Des Plaines, IL 60018

Prec. # 198

MAR 1 0 1980

020 X 338 Cleaner

Oxsolv Concentrate

- proper shipping name is Compounds, paint thinning, liquid
- Hazard Classification is flammable liquid
- Flash point is 75°F
- IATA art. # is 2336

CONTAINS ALCOHOL, KETONE, GLYOCOL ETHER SOLVENT

WARNING

FLAMMABLE, VAPOR MAY BE HARMFUL, MAY CAUSE IRRITATION, ABSORPTION THROUGH SKIN MAY BE HARMFUL.

Keep away from heat, sparks and open flame.

Use only with adequate ventilation. Avoid breathing vapor or spray mist. Wear appropriate respiratory protection if general dilution or local exhaust ventilation is not adequate to keep vapor or particulate concentrations below regulated or recommended levels.

Avoid contact with eyes or skin. Do not take internally.

Keep container closed when not in use and upright to prevent leakage. In case of spillage, absorb and flush with large volumes of water immediately. Remove and wash contaminated clothing before reuse. Discard contaminated shoes.

FIRST AID: In case of skin contact, wash thoroughly with soap and water; for eyes, flush immediately with plenty of water for 15 minutes and CALL A PHYSICIAN. In case of exposure to high concentration of vapor, remove to fresh air. If swallowed, CALL A PHYSICIAN IMMEDIATELY. Induce vomiting.

KEEP OUT OF REACH OF CHILDREN

FOR INDUSTRIAL USE ONLY

DeSoto, Inc.
Des Plaines, IL 60018

Prec. # 181

BOE-C6-0204616

MAR 1 0 1980

798-700 Korotherm

1. proper shipping name is paint
. Hazard Class is flammable liquid
. flash point is 74° F
. IATA Arc. # is 2422

CONTAINS KETONE, TOLUOL
OR XYLOL SOLVENTS

WARNING

FLAMMABLE
VAPOR HARMFUL
MAY CAUSE IRRITATION

Keep away from heat, sparks and open flame.

Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Wear appropriate respiratory protection if general dilution or local exhaust ventilation is not adequate to keep vapor or particulate concentrations below regulated or recommended levels.

Avoid contact with eyes or skin.

Keep container closed when not in use and upright to prevent leakage. In case of spillage, absorb and flush with large volumes of water immediately.

FIRST AID: In case of eye contact, flush with plenty of water for 15 minutes and get medical attention; for skin contact, flush with water. In case of exposure to high concentration of vapor, remove to fresh air. If swallowed, CALL A PHYSICIAN IMMEDIATELY.

KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL USE ONLY.

DeSoto, Inc.
Des Plaines, IL 60018

Prec. # 154

BOE-C6-0204617