FEB 01 1982

MATERIAL SAFETY DATA SHEET

NUMBER 385

(Approved by U.S. Department of Labor as "essentially similar" to Form LS3-OCS-4)

SECTION I IDENTIFICATION OF PRODUCT

MANUFACTURER'S NAME	AMERICAN CYANAMID COMPANY
EMERGENCY TELEPHONE NO.	(201) 835-3100
ADDRESS	Old Post Road, Havre de Grace, Maryland 21078
TRADE NAME AND SYNONYMS	HT-424 Primer, Part B
CHEMICAL NAME AND SYNONYMS	Solution of resin in mixture of organic solvents
CHEMICAL FAMILY	(Mixture)
MOLECULAR FORMULA	(Mixture)

SECTION II HAZARDOUS COMPONENTS OF MIXTURES

COMPONENT	%	THRESHOLD LIMIT VALUE (UNITS)	COMPONENT	%	THRESHOLD LIMIT VALUE (UNITS)
Dioxane	<10	100 parts per million (skin)			
Ethylene dichloride	<20	50 parts per million			
Toluene	<10	100 parts per million			

SECTION III PHYSICAL DATA

APPEARANCE AND ODOR	Dark-colored liquid; odor of chloroform		
BOILING POINT (DEGREES FAHRENHEIT)	Not available	SPECIFIC GRAVITY (WATER = 1)	About 1
VAPOR PRESSURE (MM. OF MERCURY)	67 at 75 F	PERCENT VOLATILE (BY VOLUME)	About 60
VAPOR DENSITY (AIR = 1)	Not available	EVAPORATION RATE (BUTYL ACETATE = 1)	Not available
SOLUBILITY IN WATER	Slight	EVAPORATION RATE (ETHYL ETHER = 1)	Not available

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (SPECIFY METHOD) (DEGREES FAHRENHEIT)	54 Tag Closed Cup	FLAMMABLE LIMITS (PERCENT BY VOLUME)	LOWER / UPPER: Not available
FIRE-EXTINGUISHING MEDIA	Dry chemical, carbon dioxide or foam; water spray may be ineffective.		
SPECIAL FIRE-FIGHTING PROCEDURES	Use water to keep fire-exposed containers cool		
UNUSUAL FIRE AND EXPLOSION HAZARDS	Burning produces hydrochloric acid gas. Wear self-contained breathing apparatus.		

THIS INFORMATION IS GIVEN WITHOUT A WARRANTY OR REPRESENTATION. WE DO NOT ASSUME ANY LEGAL RESPONSIBILITY FOR SAME, NOR DO WE GIVE PERMISSION, INDUCEMENT, OR RECOMMENDATION TO PRACTICE ANY PATENTED INVENTION WITHOUT A LICENSE. IT IS OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION. BEFORE USING ANY PRODUCT, READ ITS LABEL.

READ THE BACK

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

Not applicable

EFFECTS OF OVEREXPOSURE

Prolonged or repeated inhalation of vapor may cause dizziness or drowsiness. Prolonged or repeated contact of liquid with skin may cause dryness and irritation.

EMERGENCY AND FIRST AID PROCEDURES

If symptoms occur from inhalation of vapor, proceed to fresh air. Flush skin and eye contact promptly with plenty of water.

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID: None
	STABLE	X	

INCOMPATIBILITY (Materials to avoid): No specific incompatibility

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce carbon monoxide carbon dioxide and/or hydrogen chloride.

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID: None
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove sources of ignition and wear respiratory protection. Cover with some inert absorbent material; sweep up and place in a waste disposal container. Flush area with water.

WASTE DISPOSAL METHOD

Incinerate or bury in a landfill

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type): If concentration exceeds TLV, wear a respirator approved by the U.S. Bureau of Mines for organic vapors

VENTILATION	LOCAL EXHAUST	Preferable	SPECIAL	None
	MECHANICAL (General)	Acceptable	OTHER	None

PROTECTIVE GLOVES	Rubber or plastic	EYE PROTECTION	Splashproof goggles

OTHER PROTECTIVE EQUIPMENT: None

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Precautions for a Class IB flammable liquid

OTHER PRECAUTIONS: None

SECTION X DATE AND SOURCE OF INFORMATION

DATE	NAME AND TITLE	SHEET NUMBER
June 27, 1972	C. Boyd Shaffer, Ph.D. Director of Toxicology	395

NA 5743-01 (BACKER) REV. 9-71 9-71