Bostik®

EPOXY TOP COAT GLOSS
COLOR: WHITE
CODE 443-3-R66
SPEC DPM 110-508
DATE OF MFG. 11/8/77 BATCH. 14466

NON-PHOTOCHEMICALLY REACTIVE

NET ONE [redacted] QUART

Use th
Bostik
Bostik

BOE-C6-0208124

1. CAUTION: This material must be mixed only with the converter indicated on the face of this label.

2. Completely drain the converter solution into this material and stir thoroughly.

3. The base-converter mixture may be reduced only with the Bostik reducer indicated on the face of this label.

4. All equipment must be cleaned with the appropriate Bostik reducer or its equivalent.

NON-WARRANTY: We certify that this material conforms to our latest specifications. Since we do not have control of the application of our products we disclaim any guarantee for performance or responsibility for injuries arising from their use.

WARNING: FLAMMABLE; Keep away from heat, sparks or open flame. Avoid breathing of vapor or spray mist and prolonged contact with skin. Injurious if taken internally. Before smoking, eating or after using, cleanse hands thoroughly. USE WITH ADEQUATE VENTILATION.

KEEP OUT OF REACH OF CHILDREN.

is base material with
Converter No: **X-304**
Reducer No: **TL-66**

Bostik Chemical Group
USM Corporation

Bostik Division
Middleton, Mass. 01949
617-777-0100

Bostik Finch
Torrance, Cal. 90502
213-320-6800

Bostik South
Greenville, S.C. 29606
803-277-1870

BOE-C6-0208125