DPR 275

JAN 15 1982

FEB 4 1980

APPENDIX D

Form Approved
Budget Bureau No. 44-R1387
Approval Expires April 30, 1971

Form No. LSB 005-4
Rev. 1969

U.S. DEPARTMENT OF LABOR

WORKPLACE STANDARDS ADMINISTRATION
Bureau of Labor Standards

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME: TOLBER CORP.	EMERGENCY TELEPHONE NO.: (501) 777-3251
ADDRESS (Number, Street, City, State, and ZIP Code): 220 W. 5th St., Hope, Ark. 71801	
CHEMICAL NAME AND SYNONYMS: Vinyl Lacquer	TRADE NAME AND SYNONYMS: MICCROSTOP
CHEMICAL FAMILY	FORMULA

SECTION II HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE Modified vinyl resins	25		METALLIC COATINGS		
SOLVENTS Ketones, i.e. M.E.K.	75		FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)

SECTION III PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H2O=1)	
VAPOR PRESSURE (mm Hg.)		PERCENT VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____=1)	
SOLUBILITY IN WATER			
APPEARANCE AND ODOR	Red color, strong Ketone odor		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used): 1° D. T.C.C.	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA: CO_2, dry chemical, fog nozzle			
SPECIAL FIRE FIGHTING PROCEDURES			
UNUSUAL FIRE AND EXPLOSION HAZARDS			

BOE-C6-0208561

FEB 4 1980

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 200 - 250 ppm

EFFECTS OF OVEREXPOSURE:

EMERGENCY AND FIRST AID PROCEDURES: Wash thoroughly if eye contact. Induce vomiting if swallowed. Remove from area if reaction from inhalation

SECTION VI REACTIVITY DATA

STABILITY			CONDITIONS TO AVOID
	UNSTABLE		
	STABLE	S	Smoking - flammability

INCOMPATABILITY (Materials to avoid):

HAZARDOUS DECOMPOSITION PRODUCTS:

HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	MAY OCCUR		
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wipe up. Fire hazard; Ketone

WASTE DISPOSAL METHOD: As with flammable solvents

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type):

VENTILATION	LOCAL EXHAUST	SPECIAL
	MECHANICAL (General) Exhaust Ketone fumes	OTHER

PROTECTIVE GLOVES | EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

SECTION IX SPECIAL INFORMATION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Red label - flammable

OTHER PRECAUTIONS:

BOE-C6-0208562