JAN 15 1982

OCT 30 1980

F COATINGS, RESINS AND RELATE MATERIALS

1201

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

DATE OF PREP. 10/04/72

DPM 464

Section I Varnish

RECEIVED OCT 27 1980 G. E. S. CO. LONG BEACH, CALIF.

MANUFACTURER'S NAME GENERAL ELECTRIC CO., PAINT OPERATION

STREET ADDRESS 305 EASTERN AVENUE CITY, STATE, AND ZIP CODE CHELSEA, MASS. 02150

EMERGENCY TELEPHONE NO. 617-884-6918, DIAL COMM: *8-263-2526

PRODUCT CLASS ALKYD ENAMEL MANUFACTURERS CODE IDENTIFICATION 1201

TRADE NAME GLYPTAL GLYPTAL RED ENAMEL

Section II — HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV PPM	TLV mg/M³	LEL	VAPOR PRESSURE
XYLENE	35.0	100	435	1.0	9.5
V. M. & P. NAPHTHA	5.0	100	200	1.3	23.0

Section III — PHYSICAL DATA

BOILING RANGE 230-267 F VAPOR DENSITY [X] HEAVIER [ ] LIGHTER THAN AIR

EVAPORATION RATE [ ] FASTER [X] SLOWER THAN ETHER PERCENT VOLATILE BY VOLUME 56.1 WEIGHT PER GALLON 9.92

Section IV — FIRE AND EXPLOSION HAZARD DATA

FIRE CATEGORY FLAMMABLE, RED LABEL FLASH POINT 50 F LEL 1.0

EXTINGUISHING MEDIA CARBON DIOXIDE OR DRY CHEMICAL

UNUSUAL FIRE AND EXPLOSION HAZARDS EXPLOSION HAZARD DUE TO PRESSURE BUILD-UP DUE TO HEAT

SPECIAL FIRE FIGHTING PROCEDURES

BOE-C6-0208940

Section V — HEALTH HAZARD DATA

OCT 30 1980

SHOLD LIMIT VALUE SEE SECTION II

ECTS OF OVEREXPOSURE

INHALATION: RESPIRATORY IRRITATION, DIZZINESS, UNCONSCIOUSNESS.
EYE CONTACT: EXTREME IRRITATION, BURNS.
SKIN CONTACT: MILD IRRITATION, BURNS AND POSSIBLE ALLERGIC REACTION.

RGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE FROM EXPOSURE. UNCONSCIOUS, BUT BREATHING: ADMINISTER OXYGEN. NOT BREATHING: ARTIFICIAL RESUSCITATION.
EYE CONTACT: FLUSH WITH COPIOUS AMOUNTS OF WATER. SEE PHYSICIAN.
SKIN CONTACT: WASH THOROUGHLY WITH SOAP AND WATER. USE HAND LOTION.

Section VI — REACTIVITY DATA

BILITY [ ] UNSTABLE [X] STABLE CONDITIONS TO AVOID EXCESSIVE HEAT, SPARKS AND OPEN FLAMES.

OMPATABILITY (Materials to avoid) STRONG OXIDIZERS

ARDOUS DECOMPOSITION PRODUCTS CARBON MONOXIDE MAY BE FORMED BY INCOMPLETE COMBUSTION

ARDOUS POLYMERIZATION [ ] MAY OCCUR [X] WILL NOT OCCUR

DITIONS TO AVOID EXCESSIVE HEAT, SPARKS AND OPEN FLAMES.

Section VII — SPILL OR LEAK PROCEDURES

PS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT, SPARKS AND OPEN FLAMES. CLEAN UP WITH RAGS; PLACE DIRTY RAGS IN CONTAINER OF WATER.

TE DISPOSAL METHOD DISTILL OFF SOLVENTS UNDER STRICTLY SAFE CONDITIONS. RE-USE DISTILLATE. DISPOSE OF RESIDUE AS LAND FILL.

Section VIII — SPECIAL PROTECTION INFORMATION

PIRATORY PROTECTION USE APPROPRIATE RESPIRATORS.

TILATION KEEP VAPORS BELOW L.E.L.(SECTION IV) AND T.L.V.(SECTION II). SOLVENT VAPORS SHOULD BE REMOVED BY DILUTION VENTILATION FROM LOWER LEVELS. ELIMINATE ALL IGNITION SOURCES(OPEN MOTORS, SWITCHES ETC.).

TECTIVE GLOVES YES

PROTECTION YES

ER PROTECTIVE EQUIPMENT AS REQUIRED TO AVOID SKIN CONTACT

Section IX — SPECIAL PRECAUTIONS

CAUTIONS TO BE TAKEN IN HANDLING AND STORING STORE IN A COOL WELL VENTILATED AREA. AVOID EXCESSIVE HEAT, SPARKS AND OPEN FLAMES. GROUND CONTAINERS AND TRANSFER VESSELS. KEEP FREE FALL OF LIQUID TO A FEW INCHES TO AVOID BUILD-UP OF STATIC ELECTRICITY. DO NOT TAKE INTERNALLY. AVOID PROLONGED BREATHING OF VAPORS. AVOID PROLONGED CONTACT WITH SKIN.

ER PRECAUTIONS