DAC 25-2140 (12-73)

DPM/QPL REQUEST ✓

DPM NO. 843
DMS QPL NO.
ISSUE NO.

NEW ☐ REV. ☒ DATE: 4-8-81 ENGINEER CP Borton

Adhesive, Rubber	Comml	Gmb.	3B	24°F	10 mos (2)
GENERAL TITLE	SPEC. OR CLASS	ST. TEMP.	TOX.	FL. PT.	SHELF LIFE LABEL

DAC CODE NO.

P.O. NOTES: P.O. TO SPECIFY Viscosity 1000 ± 250 cps, Brookfield Viscometer RVF # 2 spindle @ 20 rpm. P.O. to specify container size, specify DMQR no.

GEN. NOTES:

USED BY DPS:

	MANUFACTURER'S NAME	CITY, STATE	MFR.'S DESIGNATION
1.	Minn. Mining & Mfg. Co.	L.A. Ca.	EC-826, DMQR No 1002B
2.			
3.			
4.			
5.			

LAB REPORT NO.

REASON FOR REQUEST: 3M has changed the viscosity range.

SPECIFY CHANGE(S) MADE: Changed the viscosity range. (PO NOTES)

DMQR No. Changed St. Temp. to Ambient

BUYER: Joe Valerie

CHANGE INFO.	REQ'D	COMPL.
DPM LIST	✓	✓
DMS QPL LIST		
MMS LIST		
ALPHABETICAL LIST		
NUM. VENDOR # LIST		
SPEC. CROSS INDEX		

NO. 843

JaL Mail Release, E L Klinger, M G Collen, M Veneroso, E C Wolfe, J Mocarey (A3)

M Rust 4-10-81

BOE-C6-0209525

3M COMPANY

GENERAL OFFICES • 3M CENTER • SAINT PAUL, MINNESOTA 55101 • TEL. (612) 733-1110

ADHESIVES, COATINGS AND SEALERS DIVISION • 3M COMPANY
6411 RANDOLPH STREET • LOS ANGELES, CALIFORNIA 90040
TEL. (213) 726-1511

February 23, 1977

Douglas Aircraft Co.
3855 Lakewood Blvd.
Long Beach, Calif. 90846

Attention: M. J. Venerosa, Dept. C1-726 (52-11)
Materials Handling & Packaging Engineering

Reference: C1-726-40

Gentlemen:

In response to your letter of February 15, 1977, requested information for reshipment of our 3M Products is listed below.

	Product	DOT Proper Shipping Name	DOT Hazard Classification	C.C. Flash Point
849)	EC 1022	Cements, Adhesives, NOI	Flammable Liquid	15°F
845)	EC 1711	Cements, Adhesives, NOI	Flammable Liquid	-14°F
843)	EC 826	Cements, Adhesives, NOI	Flammable Liquid	24°F
842) 842-2)	EC 776	Paint, Liquid (Paints, NOI, Liquid)	Flammable Liquid	73°F
842-2)	EC 776SR	Paint, Liquid (Paints, NOI, Liquid)	Flammable Liquid	73°F
104)	EC 1099	Cements, Adhesives, NOI	Flammable Liquid	5°F
1633)	*EC 1660	Paint, Liquid (Paints, NOI, Liquid)	Flammable Liquid	40°F

*EC 1660 Material is heat sensitive and would require dry ice for shipping.

51 EC 1415 has been obsoleted from our product line.