DPM 1034-1 & 1034-3
Coating, Rain Erosion Resistant
Stiffener, Neoprene

WILHOLD

WILHOLD GLUES, INC.

GENERAL OFFICES: 8707 MILLERGROVE DRIVE, SANTA FE SPRINGS, CALIFORNIA 90670 • (213) 692-0911

August 26, 1977

Mr. J.J. Veneroso, Dept. C1-726 (52-11)
Materials Handling & Packaging Engineering
DOUGLAS AIRCRAFT COMPANY
3855 Lakewood Boulevard
Long Beach, California 90846

Dear Sir:

#223

We have your letter regarding reshipping our product Wilhold 707A Base with 707B Accelerator. Enclosed is a current copy of the OSHA Material Safety Data Sheet which your requested.

In answer to your questions:

		707A Base	707B Accelerator
1.	DOT Proper Shipping Name:	Paint, Viscous Liq. Flam. in Cans & Glass	Compound, Vulcanizing Liq. Flam. in Glass
2.	DOT Hazard Classification:	Flam. Liquid	Flam. Liquid
3.	Flash Point :	44 deg. Closed Cup	44 deg. Closed Cup
4.	IATA Article No.:	343	507

MAX 10 gal Cargo Air

If we can be of further assistance, please advise.

Very truly yours,

C. J. Comegys

C. J. Comegys
WILHOLD GLUES, INC.
Santa Fe Springs, California

kc
Enc: OSHA-20