FEB 17 1982

QPL 1766

Form Approved
Budget Bureau No. 44-R1387
Approval Expires April 30, 1972

Form No. OSHA-20
June 1971

# U.S. DEPARTMENT OF LABOR

## Occupational Safety & Health Adm.

# MATERIAL SAFETY DATA SHEET

### SECTION I

| | |
|---|---|
| MANUFACTURER'S NAME: FARBEST CORPORATION | EMERGENCY TELEPHONE NO.: (213) 758-3181 |
| ADDRESS (Number, Street, City, State, and ZIP Code): 6715 McKinley Ave. Los Angeles, Calif. 90001 | |
| CHEMICAL NAME AND SYNONYMS: Not Applicable | TRADE NAME AND SYNONYMS: CW-50 |
| CHEMICAL FAMILY: Not Applicable | FORMULA: Petroleum Lubricant Mixture |

### SECTION II HAZARDOUS INGREDIENTS

| PAINTS, PRESERVATIVES, & SOLVENTS | % | TLV (Units) | ALLOYS AND METALLIC COATINGS | % | TLV (Units) |
|---|---|---|---|---|---|
| PIGMENTS | | | BASE METAL | | |
| CATALYST | | | ALLOYS | | |
| VEHICLE | | | METALLIC COATINGS | | |
| SOLVENTS | | | FILLER METAL PLUS COATING OR CORE FLUX | | |
| ADDITIVES | | | OTHERS | | |
| OTHERS | | | | | |

| HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES | % | TLV (Units) |
|---|---|---|
| Within the definition of Hazardous materials contained in the Longshormen's and Harbor Worker's compensation Act (33VSC941) Section 1501.2 Amended, this product is not hazardous. | | |

### SECTION III PHYSICAL DATA

| | | | |
|---|---|---|---|
| BOILING POINT (°F.) | ND* | SPECIFIC GRAVITY ($H_2O$=1) | 1.091 |
| VAPOR PRESSURE (mm Hg.) | ND | PERCENT VOLATILE BY VOLUME (%) | ND |
| VAPOR DENSITY (AIR=1) | ND | EVAPORATION RATE ( =1) | ND |
| SOLUBILITY IN WATER | Insoluble | | |
| APPEARANCE AND ODOR | Straw colored light viscosity liquid | | |

### SECTION IV FIRE AND EXPLOSION HAZARD DATA

| | | | |
|---|---|---|---|
| FLASH POINT (Method used): No flash | FLAMMABLE LIMITS | Lel | Uel |
| EXTINGUISHING MEDIA: $CO_2$, Dry Chemical, Foam | | | |
| SPECIAL FIRE FIGHTING PROCEDURES: ND | | | |
| UNUSUAL FIRE AND EXPLOSION HAZARDS: ND | | | |

ND = Not Determined

BOE-C6-0226319