Tables

Table 1. Summary of Soil Analytical Results - Volatile Organic Compounds (VOCs), Total Petroleum Hydrocarbons (TPH), and Metals, BRC Property, Torrance, California

Sample ID	Sample Date	Sample Depth (feet)	VOCs by Method 8260[1]	TPH by Method 8015[1]	Dissolved Metals[2] (in mg/kg)																
					Arsenic	Selenium	Aluminum	Barium	Cadmium	Chromium	Hexavalent Chromium	Cobalt	Antimony	Lead	Beryllium	Molybdenum	Nickel	Titanium	Zinc	Vanadium	Copper
BL-1	2/2/99	11.5	--	--	4.8	0.74	24,500	150	0.62	32	0.4J	13	1.4J	ND(2.5)	0.56	ND(2.5)	25	1,690	77	60	25U
	2/2/99	21	--	--	3.7	ND(0.5)	22,600	189	0.52	26	--	12	ND(0.5)UJ	ND(2.5)	0.50	ND(2.5)	19	1,690	81	53	26U
	2/2/99	23.7	--	--	3.6	ND(0.5)	22,500	183	0.83	27	--	12	0.80J	ND(2.5)	0.50	ND(2.5)	20	1,670	85	54	23U
BL-2	2/3/99	11.5	--	--	5.2	1.3	22,500	191	ND(0.5)	26	--	12	0.72J	5.5	0.92	ND(2.5)	21	1,710J	73	59	29U
	2/3/99	21.5	--	--	5.2	1.0	23,900	182	ND(0.5)	25	--	13	ND(0.5)UJ	6.5	1.0	ND(2.5)	21	1,600J	76	64	38U
BL-3	2/8/99	13	--	--	5.7	ND(0.50)	19,500	193	ND(0.5)	23	--	12	0.89J	5.3	0.75	ND(2.5)	20	7,490	70J	60	34U
	2/8/99	23	--	--	3.0	ND(0.50)	20,300	105	ND(0.5)	23	--	11	0.59J	5.6	0.74	ND(2.5)	16	1,350J	70J	50	30U
	2/8/99	25.7	--	--	3.0	ND(0.50)	23,300	148	ND(0.5)	25	--	12	1.0J	5.9	0.83	ND(2.5)	17	1,630J	74J	58	33U
BL-4	2/16/99	7	--	--	4.5	ND(0.50)	21,000	211	ND(0.5)	23	--	12	1.0J	5.9	0.84	ND(2.5)	21	1,330	61	59	31U
	2/16/99	17	--	--	3.9	ND(0.50)	18,300	161	ND(0.5)	22	--	9.5	ND(0.5)UJ	5.1	0.76	ND(2.5)	15	1,330	63	56	27U
BL-5	2/4/99	8	ND	ND	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
	2/4/99	10	--	--	4.2	1.6	26,800	150	ND(0.5)	28	1.2J	13	ND(0.5)UJ	6.0	1.0	ND(2.5)	21	1,670J	77	65	33U
	2/4/99	20	--	--	3.8	1.3	22,000	219	0.50	22	--	12	0.52J	5.7	0.93	ND(2.5)	17	1,620J	76	59	31U
BL-6	2/3/99	11	--	--	6.4	1.3	22,800	165	ND(0.5)	26	--	13	ND(0.5)UJ	6.0	0.97	ND(2.5)	22	1,890J	77	65	34U
	2/3/99	21	--	--	5.6	1.2	21,500	194	ND(0.5)	26	--	14	ND(0.5)UJ	5.9	0.93	ND(2.5)	21	1,900J	97	67	44U
BL-7	2/8/99	14.5	--	--	4.0	ND(0.50)	27,400	213	ND(0.5)	26	--	14	1.2J	7.5	0.99	ND(2.5)	20	1,890	86	69	40U
	2/8/99	24.5	--	--	6.9	ND(0.50)	15,300	85	ND(0.5)	22	--	7.2	0.86J	4.0	0.72	2.8	18	899	46	49	18
BL-8	2/16/99	12	--	--	3.8	ND(0.50)	18,600	196	ND(0.5)	22	--	10	1.1J	4.9	0.75	ND(2.5)	16	1,480	60	54	26U
	2/16/99	22	--	--	3.6	ND(0.50)	13,500	108	ND(0.5)	17	--	6.1	ND(0.5)UJ	4.0	0.56	ND(2.5)	12	825	45	39	18U

TABLE 1

[1]Results of all analyses are reported in Appendices E and F.
[2]Only detected analytes are reported in table; results of all analyses are reported in Appendices D and E.

mg/kg	Milligram per kilogram
ND( )	Analyte not detected above the practical quantitation limit (in parentheses)
--	Not sampled/analyzed

Data Validation Qualifers (for more information, see Appendix E)

U	Not detected
J	Estimated, detected
UJ	Estimated, not detected

BOE-C6-0234098

Table 2. Groundwater Analytical Sampling Plan, Former ILM Facility and BRC Property, Torrance, California

Well ID	VOCs (EPA Method 8260)	TPH (EPA Method 8015M)	Metals (Dissolved and Total)					
			Arsenic and Selenium (EPA Method 3114)	Hexavalent Chromium (EPA Method 7196)	Lead (EPA Method 7421)	Mercury (EPA Method 7470)	Thallium (EPA Method 7841)	Metals (EPA Method 6010)
P-1	X	X	X	X	X	X	X	X
P-2	X	X	X	X	X	X	X	X
P-3	X	X	X	X	X	X	X	X
P-5	X	X	X	X	X	X	X	X
P-6B	X	X	X	X	X	X	X	X
P-7	X	X	X	X	X	X	X	X
P-9B	X	X	X	X	X	X	X	X
P-10	X	X	X	X	X	X	X	X
P-12	X	X	X	X	X	X	X	X
P-16A	X	X	X	X	X	X	X	X
P-16C	X	X	X	X	X	X	X	X
P-17	X	X	X	X	X	X	X	X
P-20	X	X	X	X	X	X	X	X
P-22	X	X	X	X	X	X	X	X
P-24	X	X	X	X	X	X	X	X
BL-1	X	X	X	X	X	X	X	X
BL-2	X		X	X	X	X	X	X
BL-3	X		X	X	X	X	X	X
BL-4	X		X	X	X	X	X	X
BL-5	X	X	X	X	X	X	X	X
BL-6	X		X	X	X	X	X	X
BL-7	X		X	X	X	X	X	X
BL-8	X		X	X	X	X	X	X

Note: All samples to be analyzed for metals were prepared and analyzed for both total and dissolved metals.

VOCs Volatile organic compounds
TPH Total petroleum hydrocarbons

BOE-C6-0234099

Table 3. Water-Level Elevations, Former ILM Facility, Torrance, California

Well	Datum Elevation (ft msl)	Date	DTW (ft)	WL (ft msl)
P-1	52.50	8/30/94	69.50	-17.00
		10/19/94	69.05	-16.55
		12/29/94	68.94	-16.44
		1/12/95	69.02	-16.52
		3/16/95	68.90	-16.40
		4/28/95	68.67	-16.17
		5/18/95	68.61	-16.11
		6/16/95	68.56	-16.06
		7/11/95	68.58	-16.08
		8/28/95	68.33	-15.83
		9/12/95	68.36	-15.86
		10/12/95	68.37	-15.87
		11/13/95	68.36	-15.86
		12/18/95	68.93	-16.43
		1/15/96	68.87	-16.37
		3/11/96	68.00	-15.50
		4/22/96	68.01	-15.51
		5/21/96	68.02	-15.52
		6/17/96	67.52	-15.02
	56.53	7/24/96	72.62	-16.09
		8/14/96	71.54	-15.01
		9/9/96	71.51	-14.98
		7/7/97	70.67	-14.14
	55.21	3/1/99	69.16	-13.95
P-2	55.31	8/30/94	65.41	-10.10
		10/19/94	68.05	-12.74
		12/29/94	65.03	-9.72
		1/12/95	65.08	-9.77
		3/16/95	64.12	-8.81
		4/28/95	64.08	-8.77
		5/18/95	64.13	-8.82
		6/16/95	64.29	-8.98
		7/11/95	64.31	-9.00
		8/28/95	63.44	-8.13
		9/12/95	63.45	-8.14
		10/12/95	63.45	-8.14
		11/13/95	63.44	-8.13
		12/18/95	64.16	-8.85
		1/15/96	64.10	-8.79
		3/11/96	64.56	-9.25
		4/22/96	64.53	-9.22
		5/21/96	64.54	-9.23
		6/17/96	64.42	-9.11
	58.91	7/24/96	68.61	-9.70
		8/14/96	NR*	--
		9/9/96	68.39	-9.48
		7/7/97	67.84	-8.93
	59.11	3/1/99	67.35	-8.24

BOE-C6-0234100

Table 3. Water-Level Elevations, Former ILM Facility, Torrance, California

Well	Datum Elevation (ft msl)	Date	DTW (ft)	WL (ft msl)
P-3	55.94	8/30/94	68.57	-12.63
		10/19/94	68.25	-12.31
		12/29/94	68.46	-12.52
		1/12/95	68.36	-12.42
		3/16/95	68.11	-12.17
		4/28/95	67.87	-11.93
		5/18/95	67.80	-11.86
		6/16/95	67.78	-11.84
		7/11/95	67.80	-11.86
		8/28/95	67.70	-11.76
		9/12/95	67.71	-11.77
		10/12/95	67.72	-11.78
		11/13/95	67.72	-11.78
		12/18/95	68.14	-12.20
		1/15/96	68.08	-12.14
		3/11/96	67.68	-11.74
		4/22/96	NR*	--
		5/21/96	NR*	--
		6/17/96	67.46	-11.52
	59.97	7/24/96	NR*	--
		8/14/96	71.44	-11.47
		9/9/96	71.42	-11.45
		7/7/97	71.22	-11.25
	59.87	3/1/99	70.38	-10.51
P-4	56.20	8/30/94	72.20	-16.00
		10/19/94	71.76	-15.56
		12/29/94	71.68	-15.48
		1/12/95	71.72	-15.52
		3/16/95	71.45	-15.25
		4/28/95	71.02	-14.82
		5/18/95	70.94	-14.74
		6/16/95	70.98	-14.78
		7/11/95	70.97	-14.77
		8/28/95	70.89	-14.69
		9/12/95	70.91	-14.71
		10/12/95	70.91	-14.71
		11/13/95	70.94	-14.74
		12/18/95	70.89	-14.69
		1/15/96	70.84	-14.64
		3/11/96	70.74	-14.54
		4/22/96	70.72	-14.52
		5/21/96	70.71	-14.51
		6/17/96	NR	--
	60.54	7/24/96	74.78	-14.24
		8/14/96	74.70	-14.16
		9/9/96	74.67	-14.13
		7/7/97	74.04	-13.50
		10/97	well abandoned	--

BOE-C6-0234101

Table 3. Water-Level Elevations, Former ILM Facility, Torrance, California

Well	Datum Elevation (ft msl)	Date	DTW (ft)	WL (ft msl)
P-5	51.84	8/30/94	68.58	-16.74
		10/19/94	68.25	-16.41
		12/29/94	68.20	-16.36
		1/12/95	68.14	-16.30
		3/16/95	66.90	-15.06
		4/28/95	66.18	-14.34
		5/18/95	66.13	-14.29
		6/16/95	66.34	-14.50
		7/11/95	66.37	-14.53
		8/28/95	66.66	-14.82
		9/12/95	66.64	-14.80
		10/12/95	66.67	-14.83
		11/13/95	66.66	-14.82
		12/18/95	66.93	-15.09
		1/15/96	66.86	-15.02
		3/11/96	66.50	-14.66
		4/22/96	NR*	--
		5/21/96	NR*	--
		6/17/96	66.07	-14.23
	55.88	7/24/96	70.00	-14.12
		8/14/96	69.92	-14.04
		9/9/96	69.88	-14.00
		7/7/97	69.03	-13.15 [1]
	55.04	3/1/99	67.13	-11.25 [1]
P-6	54.18	3/16/95	71.70	-17.52
		4/28/95	71.48	-17.30
		5/18/95	71.39	-17.21
		6/16/95	71.38	-17.20
		7/11/95	71.41	-17.23
		8/28/95	71.18	-17.00
		9/12/95	71.19	-17.01
		10/12/95	71.20	-17.02
		11/13/95	NR	--
		12/18/95	71.74	-17.56
		1/15/96	71.68	-17.50
		3/11/96	70.65	-16.47
		4/22/96	70.51	-16.33
		5/21/96	NR	--
		6/17/96	70.22	-16.04
	58.13	7/24/96	74.22	-16.09
		8/14/96	73.91	-15.78
		9/9/96	73.98	-15.85
		7/7/97	73.09	-14.96
		10/97	well abandoned	--
P-6B	55.83	3/1/99	69.32	-13.49

BOE-C6-0234102

Table 3. Water-Level Elevations, Former ILM Facility, Torrance, California

Well	Datum Elevation (ft msl)	Date	DTW (ft)	WL (ft msl)
P-7	53.41	3/16/95	71.27	-17.86
		4/28/95	71.02	-17.61
		5/18/95	70.96	-17.55
		6/16/95	70.94	-17.53
		7/11/95	71.00	-17.59
		8/28/95	71.71	-18.30
		9/12/95	71.73	-18.32
		10/12/95	71.73	-18.32
		11/13/95	73.19	-19.78
		12/18/95	71.30	-17.89
		1/15/96	71.25	-17.84
		3/11/96	70.32	-16.91
		4/22/96	70.17	-16.76
		5/21/96	70.53	-17.12
		6/17/96	69.92	-16.51
	57.34	7/24/96	74.92	-17.58
		8/14/96	73.79	-16.45
		9/9/96	73.75	-16.41
		7/7/97	72.79	-15.45
	53.92	3/1/99	67.75	-13.83
P-8	56.32	3/16/95	74.29	-17.97
		4/28/95	74.05	-17.73
		5/18/95	73.97	-17.65
		6/16/95	73.91	-17.59
		7/11/95	73.93	-17.61
		8/28/95	73.64	-17.32
		9/12/95	73.66	-17.34
		10/12/95	73.65	-17.33
		11/13/95	73.73	-17.41
		12/18/95	72.20	-15.88
		1/15/96	72.14	-15.82
		4/22/96	73.00	-16.68
		5/21/96	73.01	-16.69
		6/17/96	72.52	-16.20
		7/24/96	76.58	-20.26
		8/7/96	well abandoned	--

BOE-C6-0234103

Table 3. Water-Level Elevations, Former ILM Facility, Torrance, California

Well	Datum Elevation (ft msl)	Date	DTW (ft)	WL (ft msl)
P-9	56.38	3/16/95	70.10	-13.72
		4/28/95	69.92	-13.54
		5/18/95	69.90	-13.52
		6/16/95	68.91	-12.53
		7/11/95	68.93	-12.55
		8/28/95	69.80	-13.42
		9/12/95	69.81	-13.43
		10/12/95	69.80	-13.42
		11/13/95	69.66	-13.28
		12/18/95	68.85	-12.47
		1/15/96	68.79	-12.41
		3/11/96	69.76	-13.38
		4/22/96	69.68	-13.30
		5/21/96	NR	--
		6/17/96	69.54	-13.16
	60.48	7/24/96	73.72	-13.24
		8/14/96	73.55	-13.07
		9/9/96	73.52	-13.04
		7/7/97	72.66	-12.18
		10/97	well abandoned	--
P-9B	57.54	3/1/99	69.62	-12.08
P-10	57.31	3/16/95	69.60	-12.29
		4/28/95	69.40	-12.09
		5/18/95	69.32	-12.01
		6/16/95	69.26	-11.95
		7/11/95	69.30	-11.99
		8/28/95	68.98	-11.67
		9/12/95	68.98	-11.67
		10/12/95	68.98	-11.67
		11/13/95	68.97	-11.66
		12/18/95	69.33	-12.02
		1/15/96	69.27	-11.96
		3/11/96	68.73	-11.42
		4/22/96	68.75	-11.44
		5/21/96	68.74	-11.43
		6/17/96	68.66	-11.35
	61.08	7/24/96	72.58	-11.50
		8/14/96	72.55	-11.47
		9/9/96	72.52	-11.44
		7/7/97	72.42	-11.34
	57.64	3/1/99	68.83	-11.19

BOE-C6-0234104

Table 3. Water-Level Elevations, Former ILM Facility, Torrance, California

Well	Datum Elevation (ft msl)	Date	DTW (ft)	WL (ft msl)
P-11	56.06	12/18/95	66.20	-10.14
		1/15/96	66.15	-10.09
		3/11/96	66.30	-10.24
		4/22/96	66.28	-10.22
		5/21/96	66.27	-10.21
		6/17/96	66.14	-10.08
	59.89	7/24/96	70.35	-10.46
		8/14/96	70.12	-10.23
		9/9/96	70.08	-10.19
	63.83	7/7/97	73.63	-9.80
		10/97	well abandoned	--
P-12	56.00	12/18/95	71.10	-15.10
		1/15/96	71.04	-15.04
		3/11/96	70.96	-14.96
		4/22/96	70.93	-14.93
		5/21/96	70.72	-14.72
		6/17/96	70.55	-14.55
	59.95	7/24/96	75.00	-15.05
		8/14/96	74.62	-14.67
		9/9/96	74.48	-14.53
		7/7/97	73.52	-13.57
	59.73	3/1/99	72.16	-12.43
P-13	55.78	12/18/95	71.72	-15.94
		1/15/96	71.67	-15.89
		3/11/96	71.34	-15.56
		4/22/96	71.31	-15.53
		5/21/96	71.33	-15.55
		6/17/96	70.92	-15.14
	59.97	7/24/96	75.30	-15.33
		8/14/96	74.64	-14.67
		9/9/96	74.60	-14.63
		7/7/97	73.68	-13.71
		10/97	well abandoned	--
P-14	55.92	12/18/95	71.80	-15.88
		1/15/96	71.76	-15.84
		3/11/96	71.44	-15.52
		4/22/96	71.42	-15.50
		5/21/96	71.45	-15.53
		6/17/96	71.02	-15.10
	60.04	7/24/96	75.08	-15.04
		8/14/96	75.04	-15.00
		9/9/96	75.00	-14.96
	63.71	7/8/97	77.95	-14.24
		10/97	well abandoned	--

BOE-C6-0234105

Table 3. Water-Level Elevations, Former ILM Facility, Torrance, California

Well	Datum Elevation (ft msl)	Date	DTW (ft)	WL (ft msl)
P-15	52.64	12/18/95	68.20	-15.56
		1/15/96	68.14	-15.50
		3/11/96	68.08	-15.44
		4/22/96	68.06	-15.42
		5/21/96	68.01	-15.37
		6/17/96	67.70	-15.06
	56.40	7/24/96	71.40	-15.00
		8/14/96	71.43	-15.03
		9/9/96	71.39	-14.99
		7/7/97	70.45	-14.05
		10/97	well abandoned	--
P-16A	56.43	12/18/95	73.40	-16.97
		1/15/96	73.36	-16.93
		3/11/96	73.12	-16.69
		4/22/96	72.93	-16.50
		5/21/96	72.95	-16.52
		6/17/96	72.61	-16.18
	60.49	7/24/96	76.60	-16.11
		8/14/96	76.59	-16.10
		9/9/96	76.58	-16.09
		7/7/97	75.59	-15.10
	52.76	3/1/99	66.50	-13.74
P-16B	56.51	12/18/95	73.59	-17.08
		1/15/96	73.53	-17.02
		3/11/96	73.16	-16.65
		4/22/96	73.01	-16.50
		5/21/96	73.02	-16.51
		6/17/96	72.73	-16.22
		7/24/96	NR*	--
		8/6/96	well destroyed	--
P-16C	60.44	8/14/96	76.58	-16.14
		9/9/96	76.52	-16.08
		7/7/97	75.61	-15.17
	52.35	3/1/99	66.20	-13.85
P-17	56.56	12/18/95	73.40	-16.84
		1/15/96	73.34	-16.78
		3/11/96	73.00	-16.44
		4/22/96	72.97	-16.41
		5/21/96	72.97	-16.41
		6/17/96	NR	--
	60.25	7/24/96	76.38	-16.13
		8/14/96	NR*	--
		9/9/96	NR*	--
		7/7/97	75.08	-14.83
	54.83	3/1/99	68.34	-13.51

BOE-C6-0234106

Table 3. Water-Level Elevations, Former ILM Facility, Torrance, California

Well	Datum Elevation (ft msl)	Date	DTW (ft)	WL (ft msl)
P-18	56.44	12/18/95	73.60	-17.16
		1/15/96	73.54	-17.10
		3/11/96	73.28	-16.84
		4/22/96	73.04	-16.60
		5/21/96	73.08	-16.64
		6/17/96	NR	--
	60.16	7/24/96	NR	--
		8/14/96	76.36	-16.20
		9/9/96	76.32	-16.16
		7/7/97	75.29	-15.13
		10/97	well abandoned	--
P-19	53.93	12/18/95	71.09	-17.16
		1/15/96	71.03	-17.10
		3/11/96	70.80	-16.87
		4/22/96	70.60	-16.67
		5/21/96	70.61	-16.68
		6/17/96	70.27	-16.34
	57.75	7/24/96	74.63	-16.88
		8/14/96	74.09	-16.34
		9/9/96	74.06	-16.31
	62.85	7/7/97	78.11	-15.26
		10/97	well abandoned	--
P-20	52.00	12/18/95	67.78	-15.78
		1/15/96	67.72	-15.72
		3/11/96	67.58	-15.58
		4/22/96	67.56	-15.56
		5/21/96	67.58	-15.58
		6/17/96	67.14	-15.14
	55.94	7/24/96	72.16	-16.22
		8/14/96	71.10	-15.16
		9/9/96	71.06	-15.12
		7/7/97	70.24	-14.30
	55.30	3/1/99	68.28	-12.98
P-21	54.37	12/18/95	71.48	-17.11
		1/15/96	71.42	-17.05
		3/11/96	71.10	-16.73
		4/22/96	70.95	-16.58
		5/21/96	70.96	-16.59
		6/17/96	70.66	-16.29
	58.05	7/24/96	75.48	-17.43
		8/14/96	74.43	-16.38
		9/9/96	74.39	-16.34
	62.34	7/8/97	77.65	-15.31
		10/97	well abandoned	--

BOE-C6-0234107

Table 3. Water-Level Elevations, Former ILM Facility, Torrance, California

Well	Datum Elevation (ft msl)	Date	DTW (ft)	WL (ft msl)
P-22	57.72	12/18/95	75.21	-17.49
		1/15/96	75.15	-17.43
		3/11/96	74.80	-17.08
		4/22/96	74.61	-16.89
		5/21/96	NR	--
		6/17/96	74.30	-16.58
	61.82	7/24/96	NR*	--
		8/14/96	78.17	-16.35
		9/9/96	78.13	-16.31
		7/7/97	77.24	-15.42
	54.49	3/1/99	68.39	-13.90
P-23	56.27	12/18/95	69.80	-13.53
		1/15/96	69.74	-13.47
		3/11/96	69.74	-13.47
		4/22/96	69.71	-13.44
		5/21/96	69.72	-13.45
		6/17/96	69.50	-13.23
	60.19	7/24/96	NR*	--
		8/14/96	73.34	-13.15
		9/9/96	73.30	-13.11
		7/7/97	72.74	-12.55
		10/97	well abandoned	--
P-24	56.05	12/18/95	70.50	-14.45
		1/15/96	70.43	-14.38
		3/11/96	70.22	-14.17
		4/22/96	70.20	-14.15
		5/21/96	70.22	-14.17
		6/17/96	70.90	-14.85
	60.14	7/24/96	72.80	-12.66
		8/14/96	73.88	-13.74
		9/9/96	73.84	-13.70
		7/7/97	73.17	-13.03
	59.89	3/1/99	72.00	-12.11

BOE-C6-0234108

Table 3. Water-Level Elevations, Former ILM Facility, Torrance, California

Well	Datum Elevation (ft msl)	Date	DTW (ft)	WL (ft msl)
P-25	56.35	12/18/95	72.30	-15.95
		1/15/96	72.32	-15.97
		3/11/96	72.04	-15.69
		4/22/96	72.01	-15.66
		5/21/96	73.02	-16.67
		6/17/96	71.55	-15.20
	60.45	7/24/96	76.10	-15.65
		8/14/96	75.63	-15.18
		9/9/96	75.60	-15.15
		7/7/97	74.76	-14.31
		10/97	well abandoned	--

Note: Well elevations for P-11, P-14, P-19, and P-21 were resurveyed on 8/15/97 following completion of on-site regrading activities.

Note: Well elevations for all existing wells were resurveyed on 3/27/99, following 1998 site development

[1]A sheen of free product was detected. Water levels did not require correction. July 1997 was the first observation of free product at this well.

ft	Feet
ft msl	Feet relative to mean sea level
DTW	Depth to static water
WL	Water-level elevation
NR	Water level not recorded
NR*	Erroneous datum - not included on hydrograph or groundwater elevation figures
--	Computation not completed

BOE-C6-0234109

Table 4. Water-Level Elevations, BRC Property, Torrance, California

Well	Datum Elevation (ft msl)	Date	DTW (ft)	WL (ft msl)
BL-1	58.34	3/4/99	70.75	-12.41
BL-2	58.15	3/3/99	71.47	-13.32
BL-3	59.33	3/3/99	73.22	-13.89
BL-4	55.04	3/2/99	69.55	-14.51
BL-5	55.18	3/4/99	67.70	-12.52
BL-6	54.70	3/1/99	67.62	-12.92
BL-7	55.19	3/1/99	80.50	-25.31
BL-8	57.13	3/2/99	71.40	-14.27

ft Feet
ft msl Feet relative to mean sea level
DTW Depth to static water
WL Water-level elevation
NR Water level not recorded

BOE-C6-0234110

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-1	1/24/95	1048	15	21.0	6.97	1,131	166	cloudy	--
		1053	25	21.1	7.58	1,040	37	cloudy	--
		1058	35	20.1	7.29	1,068	15	cloudy	--
		1103	45	--	--	--	--	--	--
		TOTAL:	45						
		AVERAGE:*		20.7	7.28	1,080	73		--
	3/17/95	1440	5	22.0	7.50	1,500	30	clear	0.6
		1443	10	23.0	7.60	1,500	30	clear	0.6
		1447	20	23.0	7.80	1,500	30	clear	0.6
		1455	30	23.0	7.50	1,500	30	clear	0.6
		TOTAL:	30						
		AVERAGE:*		23.0	7.63	1,500	30		0.6
	12/27/95	1317	5	22.4	7.61	2,240	20	clear	--
		1320	10	22.6	7.69	2,260	<10	clear	--
		1323	20	22.8	7.71	2,280	<10	clear	--
		1326	30	22.8	7.70	2,280	<10	clear	--
		TOTAL:	30						
		AVERAGE:*		22.7	7.70	2,273	<10		--
	3/19/96	1219	10	22.5	7.77	1,580	39	clear	--
		1221	20	22.9	7.85	1,510	72	clear	--
		1224	30	22.9	7.87	1,510	179	tan	--
		1227	40	22.9	7.86	1,520	111	tan	--
		TOTAL:	40						
		AVERAGE:*		22.9	7.86	1,513	121		--
	6/26/96	1400	5	22.9	7.52	1,690	-10	sl. cloudy	--
		1402	10	23.1	7.51	1,650	-10	sl. cloudy	--
		1404	15	23.1	7.52	1,680	-10	sl. cloudy	--
		1406	20	23.0	7.51	1,670	-10	sl. cloudy	--
		TOTAL:	20						
		AVERAGE:*		23.1	7.51	1,667	-10		--
	9/18/96	1213	5	24.7	7.59	1,580	-6	clear	--
		1216	10	24.2	7.60	1,600	-3	clear	--
		1219	15	24.0	7.60	1,580	-10	clear	--
		1224	25	24.1	7.60	1,570	-10	clear	--
		TOTAL:	25						
		AVERAGE:*		24.1	7.60	1,583	-8		--
	7/10/97	1452	0	26.2	7.54	1,440	394	cloudy	--
		1458	10	24.1	7.08	1,780	4	clear	--
		1505	20	24.0	7.08	1,740	0	clear	--
		1511	30	24.0	7.08	1,710	0	clear	--
		1518	40	24.0	7.08	1,690	0	clear	--
		TOTAL:	40						
		AVERAGE:*		24.0	7.08	1,713	0		--
	3/4/99	1455	0	20.5	6.96	2,000	447	light brown	--
		1459	5	20.7	6.84	1,940	105	light brown	--
		1503	10	22.6	6.81	1,930	241	light brown	--
		1506	15	22.8	6.85	1,940	56	light brown	--
		1510	20	22.6	6.82	1,950	32	clear	--
		1517	30	22.3	6.88	1,930	5	clear	--
		1523	40	22.6	6.96	1,960	24	clear	--
		TOTAL:	40						
		AVERAGE:*		22.5	6.89	1,947	20		--

BOE-C6-0234111

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-2	1/27/95	1445	4	18.3	7.40	1,751	109	lt. brown	--
		1447	10 (dry)	--	--	--	--	--	2.0
		1452	15	20.0	7.78	1,633	70	lighter	1.9
		--	16 (dry)	--	--	--	--	--	--
		1518	18	19.5	7.27	1,755	115	lighter	2.2
		TOTAL:	18						
		AVERAGE:*		19.3	7.48	1,713	98		1.4
	3/17/95	1257	6	22.0	8.80	4,000	300	tan	0.6
		1304	10	22.0	8.70	4,000	680	brown	0.6
		1307	15	22.0	8.70	4,000	660	tan	0.6
		1315	20	22.0	8.60	4,000	270	tan	0.6
		1320	22	22.0	8.60	4,000	80	clear	0.5
		1325	24	22.0	8.60	4,000	100	clear	0.5
		1327	26	22.0	8.60	4,000	100	clear	--
		TOTAL:	26						
		AVERAGE:*		22.0	8.60	4,000	93		0.3
	12/27/95	1016	3	22.6	8.11	1,280	190	gray	--
		1018	5	22.7	8.12	1,300	194	gray	--
		1020	10	23.0	8.10	1,310	260	gray	--
		1022	17	23.0	8.10	1,300	140	gray	--
		TOTAL:	17						
		AVERAGE:*		22.9	8.11	1,303	198		--
	3/19/96	1405	4	22.1	7.78	1,980	310	gray	--
		1407	8	22.3	7.91	2,020	77	clear	--
		TOTAL:	8						
		AVERAGE:*		22.4	7.93	1,768	195		--
	6/20/96	1348	3	26.3	6.90	4,710	445	silty	--
		1352	6	24.8	6.97	4,720	999	dk. silt	--
		1355	9	24.4	6.93	4,680	457	silty	--
		TOTAL:	9						
		AVERAGE:*		25.2	6.93	4,703	634		--
	9/17/96	1239	3	27.2	7.16	4,880	999	silty-dark	--
		1241	6	24.7	7.22	4,490	125	clear	--
		1243	9	24.9	7.22	4,530	254	sl. silty	--
		1244	11	24.5	7.20	4,590	100	sl. silty	--
		TOTAL:	11						
		AVERAGE:*		24.7	7.21	4,537	160		--
	7/8/97	1234	0	26.8	6.84	5,390	256	clear	--
		1238	5	25.3	6.88	5,300	134	clear	--
		1243	10	25.5	6.92	5,200	82	clear	--
		1253	15	26.7	6.94	5,190	69	clear	--
		1309	20	27.7	6.97	5,000	43	clear	--
		TOTAL:	20						
		AVERAGE:*		26.6	6.94	5,130	65		--
	3/2/99	0910	0	21.1	6.45	6,200	40	clear	--
		0916	5	21.6	6.86	3,970	10	clear	--
		0922	10	22.3	6.90	4,520	10	clear	--
		0927	15	22.9	6.84	5,220	10	clear	--
		TOTAL:	15						
		AVERAGE:*		22.3	6.87	4,570	10		--

BOE-C6-0234112

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-3	1/24/95	1259	5	19.1	7.89	1,700	168	cloudy	--
		1320	10	19.7	7.86	2,300	91	cloudy	--
		1330	15	19.3	7.78	2,300	90	cloudy	--
		1350	20	18.5	8.08	2,300	63	cloudy	--
		1400	25	--	--	--	--	--	--
		TOTAL:	25						
		AVERAGE:*		19.1	7.91	2,300	81		--
	3/17/95	1019	5	20.9	7.43	3,000	--	brown	0.7
		1025	10	20.9	7.44	3,000	--	tan	0.7
		1035	12	20.9	7.48	3,000	4	tan	0.7
		1038	15	21.0	7.38	3,000	253	tan	0.6
		1040	16	21.0	7.38	3,000	224	lt. tan	0.6
		1044	19	21.0	7.38	3,000	173	tan	0.6
		1050	21	20.9	7.37	3,000	148	tan	0.6
		1055	24	21.0	7.40	3,000	100	tan	0.6
		1056	25	21.0	7.41	2,500	51	clear	--
		TOTAL:	25						
		AVERAGE:*		21.0	7.39	2,833	100		0.4
	12/20/95	0702	2	22.5	7.81	2,610	off scale	tan	--
		0704	4	22.3	7.79	2,620	420	tan	--
		0706	6	22.3	7.78	2,610	118	cloudy	--
		0708	8	22.3	7.79	2,610	29	clear	--
		0709	10	22.3	7.81	2,630	25	clear	--
		TOTAL:	10						
		AVERAGE:*		22.3	7.79	2,617	57		--
	3/14/96	0925	3	21.0	7.41	2,490	48	clear	--
		0928	6	21.3	7.48	2,440	170	tan	--
		TOTAL:	6						
		AVERAGE:*		21.2	7.45	2,465	109		--
	6/19/96	0940	3	24.3	7.93	2,680	197	clear	--
		0947	6	23.4	7.38	2,750	27	clear	--
		0952	9	23.3	7.44	2,560	<10	clear	--
		0955	12	23.2	7.49	2,570	<10	clear	--
		TOTAL:	12						
		AVERAGE:*		23.3	7.44	2,627	27		--
	9/11/96	1125	3	24.7	8.01	1,560	98	clear	--
		1131	6	22.7	8.03	2,600	265	clear	--
		TOTAL:	6						
		AVERAGE:*		23.7	8.02	2,080	182		--
	7/8/97	1020	0	25.7	8.10	1,790	450	clear	--
		1023	3	23.8	7.05	2,370	112	clear	--
		1027	6	24.0	7.03	2,440	26	clear	--
		1030	9	24.4	7.06	2,370	5	clear	--
		1036	12	24.7	7.07	2,340	0	clear	--
		TOTAL:	12						
		AVERAGE:*		24.4	7.05	2,383	10		--

BOE-C6-0234113

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-3 (Cont.)	3/2/99	1000	0	22.0	7.00	2,770	48	clear	--
		1005	5	22.6	7.00	2,810	10	clear	--
		1010	10	21.7	7.04	2,680	10	clear	--
		1013	15	22.6	7.01	2,540	10	clear	--
		1016	20	22.5	7.02	2,580	10	clear	--
		1020	27	22.7	6.99	2,540	10	clear	--
		TOTAL:	27						
		AVERAGE:*		22.6	7.01	2,553	10		--
P-4	1/26/95	1355	5	19.4	7.95	1,300	off scale	brown	5.2
		1420	11	20.7	7.98	1,508	<2.0**	brown	--
		1435	16	20.2	7.80	1,555	**	brown	--
		1445	18	18.4	7.92	1,527	**	lt. brown	6.1
		1510	22	19.8	7.83	1,602	180	lt. brown	--
		1530	26	19.8	7.90	1,762	170	lt. brown	--
		TOTAL:	26						
		AVERAGE:*		19.4	7.88	1,630	175		2.0
	3/17/95	0751	8	23.0	7.57	2,710	off scale	lt brown	--
		0757	12	23.5	7.40	2,570	off scale	lt brown	--
		0804	30	23.4	7.43	2,720	off scale	lt brown	--
		0811	36	23.6	7.37	2,777	off scale	lt brown	--
		0814	45	23.6	7.40	2,776	off scale	lt brown	--
		0825	55	23.5	7.39	2,730	off scale	lt brown	--
		0835	65	23.7	7.38	2,690	off scale	lt brown	--
		0840	78	23.7	7.42	2,710	52	lt brown	--
		0855	85	22.0	7.28	2,650	60	lt brown	--
		0905	96	24.6	7.21	2,700	39	lt brown	--
		0910	100	24.7	7.23	2,710	30	lt. brown	--
		TOTAL:	100						
		AVERAGE:*		23.8	7.24	2,687	43		--
	12/21/96	0932	5	22.5	7.41	2,110	off scale	tan	--
		0934	10	22.3	7.44	2,120	110	clear	--
		0936	15	22.5	7.46	2,140	71	clear	--
		0938	20	22.5	7.45	2,130	24	clear	--
		TOTAL:	20						
		AVERAGE:*		22.4	7.45	2,130	68		--
	3/18/96	1314	5	23.2	7.82	2,140	15	clear	--
		1316	10	23.4	7.70	2,160	4	clear	--
		1318	15	23.4	7.71	2,200	9	clear	--
		1321	20	23.4	7.67	2,180	5	clear	--
		TOTAL:	20						
		AVERAGE:*		23.4	7.69	2,180	6		--
	9/16/96	0958	3	24.1	7.57	2,960	776	cloudy	--
		1000	8	24.2	7.51	3,220	208	cloudy	--
		1002	11	24.4	7.52	3,130	173	sl. cloudy	--
		TOTAL:	11						
		AVERAGE:*		24.2	7.53	3,103	386		--
	7/9/97	1500	3	--	--	--	--	--	--
		TOTAL:	3						
		AVERAGE:*		--	--	--	--		--

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-5	1/26/95	1705	5	17.5	7.59	1,511	162	clear	1.5
		1710	18	19.2	7.38	1,600	57	clear	--
		1712	28	19.4	7.39	1,545	23	clear	1.4
		1715	40	19.5	7.39	1,510	20	clear	2.6
		TOTAL:	40						
		AVERAGE:*		19.4	7.39	1,552	33		1.3
	3/17/95	1129	3	21.0	8.60	2,000	190	clear	0.5
		1131	18	22.0	8.70	2,000	90	clear	0.6
		1133	23	22.0	8.70	2,000	60	clear	0.6
		1136	28	22.0	8.70	2,000	30	clear	0.6
		1140	38	22.0	8.70	2,000	20	clear	0.6
		1143	45	22.0	8.70	2,000	20	clear	0.6
		TOTAL:	45						
		AVERAGE:*		22.0	8.70	2,000	23		0.6
	12/27/95	0902	5	22.8	7.79	2,100	<10	clear	--
		0904	10	22.6	7.81	2,140	33	cloudy	--
		0908	25	22.6	7.82	2,140	21	clear	--
		0910	35	22.6	7.81	2,110	22	clear	--
		TOTAL:	35						
		AVERAGE:*		22.6	7.81	2,130	25		--
	3/19/96	0926	5	21.7	7.16	2,920	436	gray	--
		0931	15	22.5	7.19	2,890	116	clear	--
		0934	25	22.7	7.21	2,870	110	clear	--
		0937	35	22.7	7.22	2,860	40	clear	--
		TOTAL:	35						
		AVERAGE:*		22.6	7.21	2,873	89		--
	6/25/96	1436	5	23.4	6.98	2,460	999	silty	--
		1438	10	23.1	6.96	2,980	642	silty	--
		1440	15	23.0	6.94	3,060	238	cloudy	--
		1442	20	22.9	6.98	3,060	114	cloudy	--
		1445	25	22.6	6.94	3,070	81	cloudy	--
		TOTAL:	25						
		AVERAGE:*		22.8	6.95	3,063	144		--
	9/17/96	1427	5	24.1	7.05	3,230	199	sl.cloudy	--
		1429	10	23.5	7.01	3,280	93	sl. cloudy	--
		1432	15	23.4	7.00	3,350	37	clear	--
		1437	25	23.4	6.98	3,380	16	clear	--
		TOTAL:	25						
		AVERAGE:*		23.4	7.00	3,337	49		--
	7/9/97	1118	0	24.8	6.97	1,410	>999	silty brown	--
		1126	10	24.2	6.91	2,510	>999	silty brown	--
		1129	14	--	--	--	--	--	--
		TOTAL:	14						
		AVERAGE:*		24.5	6.94	1,960	>999		--
P-6	3/17/95	1123	3	22.3	7.48	2,400	60	clear	--
		1128	10	23.1	7.38	2,440	61	clear	--
		1134	18	23.3	7.34	2,500	64	clear	--
		TOTAL:	18						
		AVERAGE:*		22.9	7.40	2,447	62		--

BOE-C6-0234115

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-6 (Cont.)	12/20/95	0910	4	21.2	9.65	2,990	540	tan	--
		0912	8	22.2	9.51	2,680	256	tan	--
		0914	12	22.2	9.58	2,710	72	cloudy	--
		0915	16	22.5	9.47	2,720	141	cloudy	--
		0916	20	22.5	9.46	2,720	91	cloudy	--
		TOTAL:	20						
		AVERAGE:*		22.4	9.50	2,717	101		--
	3/18/96	0840	5	21.4	7.97	2,740	10	clear	--
		0843	10	21.5	7.81	2,700	10	clear	--
		0844	15	21.8	7.76	2,770	10	clear	--
		0846	20	22.2	7.75	2,810	10	clear	--
		TOTAL:	20						
		AVERAGE:*		21.8	7.77	2,760	10		--
	6/20/96	1003	3	24.5	7.54	3,490	95	clear	--
		1005	6	22.5	7.41	2,730	32	clear	--
		1007	9	23.1	7.41	2,730	15	clear	--
		1010	12	23.2	7.43	2,780	26	clear	--
		1013	15	23.1	7.42	2,770	20	clear	--
		TOTAL:	15						
		AVERAGE:*		23.1	7.42	2,760	20		--
	9/12/96	0841	5	22.3	7.28	2,420	90	clear	--
		0844	10	22.7	7.42	2,320	78	clear	--
		0847	15	22.6	7.42	2,320	139	clear	--
		TOTAL:	15						
		AVERAGE:*		22.5	7.39	2,518	69		--
	7/9/97	1024	0	24.6	7.28	2,111	133	clear	--
		1030	5	24.7	7.23	2,020	40	clear	--
		1035	10	25.2	7.26	1,930	0	clear	--
		1040	15	25.2	7.27	1,920	0	clear	--
		1045	20	25.2	7.28	1,920	0	clear	--
		1050	25	25.3	7.28	1,910	0	clear	--
		TOTAL:	25						
		AVERAGE:*		25.2	7.28	1,917	0		--
P-6B	3/3/99	0913	0	21.7	7.18	2,000	145	lt. Brown	--
		0918	5	22.1	7.46	2,000	685	brown	--
		0923	10	21.7	7.44	2,000	999	brown	--
		0927	15	22.7	7.50	2,000	999	brown	--
		0932	20	22.9	7.45	2,000	999	brown	--
		0936	25	23.1	7.46	2,000	999	brown	--
		TOTAL:	25						
		AVERAGE:*		22.9	7.47	2,000	999		--
P-7	3/17/95	1345	6	23.0	8.50	1,000	30	clear	0.4
		1400	17	23.0	8.60	1,000	20	clear	0.5
		1405	25	23.0	8.70	1,000	20	clear	0.5
		1410	30	23.0	8.60	1,000	20	--	0.6
		TOTAL:	30						
		AVERAGE:*		23.0	8.63	1,000	20		0.5
	12/21/95	1123	5	21.1	7.63	1,110	<10	clear	--
		1124	10	21.9	7.56	1,110	<10	clear	--
		1127	20	22.2	7.56	1,100	<10	clear	--
		1130	30	22.2	7.58	1,100	<10	clear	--
		TOTAL:	30						
		AVERAGE:*		22.1	7.57	1,103	<10		--

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-7 (Cont.)	3/18/96	1138	5	23.0	7.78	1,190	41	clear	--
		1141	10	23.0	7.72	1,160	20	clear	--
		1144	20	23.1	7.73	1,150	28	clear	--
		1147	32	23.1	7.72	1,160	33	clear	--
		TOTAL:	32						
		AVERAGE:*		23.1	7.72	1,157	27		--
	6/24/96	1016	5	22.1	7.84	1,280	45	clear	--
		1018	10	21.3	7.63	1,220	9	clear	--
		1021	15	22.5	7.71	1,230	0	clear	--
		1024	20	22.6	7.61	1,220	-1	clear	--
		1027	25	21.3	7.62	1,210	-2	clear	--
		TOTAL:	25						
		AVERAGE:*		22.1	7.65	1,220	-1		--
	9/16/96	0905	5	22.6	7.40	1,220	28	clear	--
		0908	10	22.6	7.58	1,270	5	clear	--
		0911	15	22.6	7.60	1,160	1	clear	--
		0914	20	22.7	7.58	1,240	3	clear	--
		0917	25	22.6	7.60	1,240	0	clear	--
		TOTAL:	25						
		AVERAGE:*		22.6	7.59	1,213	1		--
	7/9/97	1420	0	26.3	7.17	1,390	>999	silty brown	--
		1428	10	24.2	6.96	1,680	>999	light brown	--
		1429	11	--	--	--	--	--	--
		TOTAL:	11						
		AVERAGE:*		16.8	4.71	1,023	>999		--
	3/4/99	0820	0	20.4	6.55	--	19	grey/blue	--
		0901	5	21.7	6.85	--	380	grey	--
		0907	10	22.5	7.05	--	712	dark gray	--
		0911	15	22.4	7.12	--	816	dark brown	--
		0916	20	22.5	7.06	--	641	brown	--
		0920	24	22.6	7.09	--	552	brown	--
		TOTAL:	24						
		AVERAGE:*		22.5	7.09	--	670		--
P-8	3/17/95	1020	5	20.0	7.85	1,460	74	clear	--
		1032	18	22.3	7.53	1,460	97	clear	--
		1036	25	22.4	7.51	1,470	111	--	--
		1040	30	22.4	7.51	1,450	95	--	--
		1043	35	22.3	7.47	1,430	63	--	--
		1047	40	22.4	7.43	1,430	40	clear	--
		1050	43	--	--	--	--	--	--
		TOTAL:	43						
		AVERAGE:*		22.4	7.45	1,430	52		--
P-9	3/17/95	0923	2	20.7	7.37	2,940	40	clear	-0.1
		0928	10	21.6	7.38	2,920	91	clear	--
		0931	18	21.2	7.35	2,910	64	clear	--
		0935	25	21.3	7.36	2,920	53	clear	--
		0940	30	21.7	7.34	3,050	50	clear	--
		0945	35	22.0	7.38	2,950	40	clear	--
		TOTAL:	35						
		AVERAGE:*		21.7	7.36	2,973	48		-0.1

BOE-C6-0234117

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-9 (Cont.)	12/20/95	0959	5	21.8	7.67	2,360	off scale	tan	--
		1003	10	22.2	7.66	2,320	436	tan	--
		1008	20	21.7	7.60	2,320	61	cloudy	--
		1011	25	22.2	7.61	2,390	off scale	tan	--
		1014	36	22.2	7.60	2,380	300	tan	--
		TOTAL:	36						
		AVERAGE:*		22.0	7.60	2,363	181		--
	3/18/96	1102	5	21.8	7.98	2,560	10	clear	--
		1104	15	21.8	8.05	248	110	tan	--
		1107	25	22.0	8.07	2,490	120	tan	--
		1111	35	22.0	8.06	2,490	141	tan	--
		TOTAL:	35						
		AVERAGE:*		21.9	8.06	1,743	124		--
	6/26/96	1002	5	22.1	7.47	2,620	4	sl. cloudy	--
		1005	10	22.2	7.50	2,430	4	clear	--
		1009	15	22.2	7.50	2,450	-10	clear	--
		1012	20	22.1	7.52	2,400	-10	clear	--
		1015	25	22.0	7.51	2,270	-10	clear	--
		TOTAL:	25						
		AVERAGE:*		22.1	7.51	2,373	-10		--
	9/12/96	1229	5	24.9	7.61	2,500	113	clear	--
		1231	10	24.2	7.60	2,470	88	clear	--
		1234	15	23.7	7.59	2,450	507	clear	--
		1237	20	23.2	7.60	2,440	134	clear	--
		1240	25	23.0	7.56	2,400	13	clear	--
		TOTAL:	25						
		AVERAGE:*		23.3	7.58	2,430	218		--
	7/9/97	1317	0	26.4	7.84	874	>999	silty brown	--
		1324	10	24.0	7.24	2,220	95	clear	--
		1332	20	24.0	7.23	2,190	52	clear	--
		1341	30	24.0	7.23	2,170	15	clear	--
		1350	40	24.0	7.23	2,160	13	clear	--
		TOTAL:	40						
		AVERAGE:*		24.0	7.23	2,173	27		--
P-9B	3/3/99	1126	0	21.2	7.47	1,790	427	light brown	--
		1130	5	21.8	7.00	3,370	33	clear	--
		1134	10	22.0	7.05	3,210	7	clear	--
		1141	20	22.1	7.09	3,110	1	clear	--
		1147	30	21.9	7.09	3,080	1	clear	--
		1158	45	21.8	7.10	3,090	2	clear	--
		TOTAL:	45						
		AVERAGE:*		21.9	7.09	3,093	1		--
P-10	3/17/95	0755	4	17.1	8.51	1,880	30	clear	0.4
		0807	8	20.4	7.88	1,980	226	clear	0.2
		0817	10	21.8	7.42	2,000	162	--	0.2
		0827	12	21.8	7.44	1,950	55	clear	0.1
		0840	15	22.0	7.44	1,920	23	clear	0.1
		TOTAL:	15						
		AVERAGE:*		21.9	7.43	1,957	80		0.1

BOE-C6-0234118

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-10 (Cont.)	12/19/95	1054	2	25.5	7.59	2,350	off scale	tan	--
		1056	5	24.5	7.67	1,900	458	tan	--
		1058	7	23.3	7.72	1,820	169	tan	--
		1059	12	22.8	7.78	1,790	14	clear	--
		1101	16	22.6	7.77	1,840	18	clear	--
		1104	18	22.5	7.77	1,810	19	clear	--
		TOTAL:	18						
		AVERAGE:*		22.6	7.77	1,813	17		--
	3/14/96	0734	5	19.1	7.45	1,930	113	cloudy	--
		0738	10	20.2	7.83	1,750	6	clear	--
		0741	13	21.2	7.90	1,880	10	clear	--
		0745	18	21.2	7.90	1,890	4	clear	--
		TOTAL:	18						
		AVERAGE:*		20.9	7.88	1,840	7		--
	6/18/96	1422	5	24.1	7.78	2,000	<10	clear	--
		1425	10	--	--	--	--	tan	--
		TOTAL:	10						
		AVERAGE:*		--	--	--	--		--
	9/11/96	0938	3	22.4	6.83	1,780	137	cloudy	--
		0940	6	22.3	7.51	1,700	21	clear	--
		0942	9	22.2	7.57	1,710	15	clear	--
		0944	12	22.3	7.67	1,770	5	clear	--
		TOTAL:	12						
		AVERAGE:*		22.3	7.58	1,727	14		--
	7/8/97	0840	0	23.9	7.36	432	139	clear	--
		0846	5	23.1	6.89	1,600	122	clear	--
		0852	10	23.3	6.92	1,630	0	clear	--
		0857	15	23.4	6.98	1,710	0	clear	--
		0903	20	23.5	7.03	1,730	0	clear	--
		TOTAL:	20						
		AVERAGE:*		23.4	6.98	1,690	0		--
	3/1/99	1545	0	22.6	6.56	2,170	149	clear	--
		1550	5	22.5	7.07	2,140	348	clear	--
		1552	10	22.2	7.09	2,040	102	clear	--
		1558	15	21.7	7.09	2,090	0	clear	--
		1604	22	21.8	7.08	2,030	0	clear	--
		TOTAL:	22						
		AVERAGE:*		21.9	7.09	2,053	34		--
P-11	12/27/95	0932	5	22.6	7.77	1,000	<10	clear	--
		0934	10	22.8	7.78	990	<10	clear	--
		0936	15	22.8	7.79	980	<10	clear	--
		0938	20	22.8	7.78	970	<10	clear	--
		TOTAL:	20						
		AVERAGE:*		22.8	7.78	980	<10		--
	3/14/96	0802	5	21.0	7.38	3,980	10	clear	--
		0805	9	21.3	7.43	3,940	10	clear	--
		0818	12	21.8	7.43	4,120	10	clear	--
		0821	15	21.5	7.45	4,190	10	clear	--
		TOTAL:	15						
		AVERAGE:*		21.5	7.44	4,083	10		--

BOE-C6-0234119

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-11 (Cont.)	6/19/96	0700	5	21.6	6.97	4,300	463	clear	--
		0702	10	21.7	7.11	4,160	123	clear	--
		0703	13	--	--	--	--	--	--
		TOTAL:	13						
		AVERAGE:*		14.4	4.69	2,820	195		--
	9/11/96	1014	3	22.5	7.58	3,890	106	sl. cloudy	--
		1016	6	22.6	7.53	3,760	87	clear	--
		1018	9	22.4	7.60	3,830	69	clear	--
		1020	12	22.5	7.64	3,810	79	clear	--
		1022	15	22.6	7.57	3,930	83	sl. cloudy	--
		TOTAL:	15						
		AVERAGE:*		22.5	7.60	3,857	77		--
	7/8/97	1114	0	23.8	7.00	3,600	168	clear	--
		1117	5	23.4	7.05	3,460	171	clear	--
		1122	10	23.8	7.02	3,616	66	clear	--
		1126	15	24.0	7.08	3,320	91	clear	--
		1132	20	24.1	7.10	3,480	62	clear	--
		1134	22	24.1	7.11	3,480	69	clear	--
		TOTAL:	22						
		AVERAGE:*		24.1	7.10	3,427	74		--
P-12	12/21/95	1147	5	22.1	7.61	1,100	460	tan	--
		1150	10	22.1	7.41	1,110	120	tan	--
		1153	20	22.1	7.45	1,090	<10	clear	--
		1154	25	22.1	7.44	1,090	<10	clear	--
		TOTAL:	25						
		AVERAGE:*		22.1	7.43	1,097	120		--
	3/19/96	1038	5	22.2	7.75	2,130	23	clear	--
		1040	10	22.5	7.68	2,220	>999	brown	--
		TOTAL:	10						
		AVERAGE:*		22.4	7.72	2,175	--		--
	6/26/96	0936	3	22.7	7.70	2,250	36	clear	--
		0938	6	22.1	7.45	2,160	-10	clear	--
		0940	9	22.2	7.49	2,230	715	cloudy	--
		0942	12	22.4	7.45	2,220	716	cloudy	--
		TOTAL:	12						
		AVERAGE:*		22.2	7.46	2,203	474		--
	9/18/96	0734	4	21.0	7.21	2,090	40	clear	--
		0736	8	21.7	7.45	2,010	9	clear	--
		0739	12	22.0	7.50	1,950	76	sl. cloudy	--
		TOTAL:	12						
		AVERAGE:*		21.6	7.39	2,017	42		--
	7/10/97	0721	0	22.1	7.06	1,460	57	clear	--
		0726	3	23.0	6.95	2,250	48	clear	--
		0729	6	23.2	6.99	1,980	0	clear	--
		0732	9	23.3	6.97	2,080	0	clear	--
		0736	12	23.4	6.97	2,020	0	clear	--
		TOTAL:	12						
		AVERAGE:*		23.3	6.98	2,027	0		--

BOE-C6-0234120

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-12 (Cont.)	3/3/99	1514	0	21.1	7.04	2,850	30	light green	--
		1516	2	21.6	7.04	2,750	64	light green	--
		1518	3	21.7	7.02	2,750	28	light green	--
		1519	4	21.6	7.06	2,800	155	clear	--
		1521	6	21.1	7.03	2,700	2	clear	--
		1523	8	22.4	7.05	2,630	59	clear	--
		1525	10	22.0	7.05	2,590	23	clear	--
		1527	12	22.2	7.05	2,620	10	clear	--
		1529	15	22.1	7.08	2,710	5	clear	--
		TOTAL:	15						
		AVERAGE:*		22.1	7.06	2,640	13		--
P-13	12/21/95	1046	5	20.5	8.46	1,110	560	tan	--
		1048	10	21.5	8.51	1,150	97	clear	--
		1052	20	21.5	8.52	1,180	50	clear	--
		1056	30	21.5	8.51	1,160	<10	clear	--
		TOTAL:	30						
		AVERAGE:*		21.5	8.51	1,163	74		--
	3/14/96	1425	5	22.2	8.62	967	43	tan	--
		1427	10	21.8	8.35	912	90	tan	--
		1430	15	21.7	8.32	901	118	tan	
		1432	20	21.6	8.27	893	--	--	--
		1434	25	--	--	--	--	--	--
		TOTAL:	25						
		AVERAGE:*		21.7	8.31	902	104		--
	6/19/96	1404	5	24.3	8.07	1,050	376	silty	--
		1407	10	23.7	8.27	920	464	silty	--
		1408	15	23.1	8.33	915	312	silty	--
		--	18	--	--	--	--	--	--
		TOTAL:	18						
		AVERAGE:*		23.7	8.22	962	384		--
	9/11/96	1229	5	24.3	8.73	1,010	65	cloudy	--
		1233	10	23.4	8.26	1,000	-1	clear	--
		1236	15	22.9	8.27	990	0	clear	--
		1240	20	22.6	8.29	876	-1	clear	--
		TOTAL:	20						
		AVERAGE:*		23.0	8.27	955	-1		--
	7/8/97	1614	0	27.7	8.11	444	11	clear	--
		1617	5	22.9	7.63	847	132	clear	--
		1621	10	22.7	7.66	846	16	clear	--
		1624	15	22.7	7.62	846	8	clear	--
		1627	20	22.6	7.61	846	3	clear	--
		1631	25	22.6	7.60	847	3	clear	--
		1635	30	22.6	7.59	847	3	clear	--
		1638	35	22.7	7.59	847	0	clear	--
		TOTAL:	35						
		AVERAGE:*		22.6	7.59	847	2		--
P-14	12/21/95	1004	10	22.3	7.10	1,810	91	cloudy	--
		1005	15	22.5	7.08	1,820	19	clear	--
		1010	25	22.5	7.01	1,800	<10	clear	--
		1013	32	22.5	6.99	1,810	<10	clear	--
		TOTAL:	32						
		AVERAGE:*		22.5	7.03	1,810	19		--

BOE-C6-0234121

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-14 (Cont.)	3/19/96	0824	5	21.3	7.86	1,560	43	yellow	--
		0826	15	21.7	7.87	1,580	202	yellow tan	--
		0830	25	22.1	7.84	1,550	18	yellow tan	--
		0834	35	22.5	7.81	1,530	17	clear	--
		TOTAL:	35						
		AVERAGE:*		22.1	7.84	1,553	79		--
	6/26/96	0818	5	21.2	7.21	1,580	-10	sl. cloudy	--
		0821	10	21.6	7.48	1,570	-10	sl. cloudy	--
		0824	15	22.5	7.51	1,550	-10	sl. cloudy	--
		0827	20	22.6	7.15	1,610	13	sl. cloudy	--
		0830	25	22.5	7.45	1,610	-10	sl. cloudy	--
		TOTAL:	25						
		AVERAGE:*		22.5	7.37	1,590	-2		--
	9/17/96	0925	5	22.4	7.76	1,290	14	clear	--
		0928	10	22.8	7.68	1,370	4	clear	--
		0931	15	22.9	7.70	1,530	6	clear	--
		0936	25	23.0	7.67	1,550	8	clear	--
		TOTAL:	25						
		AVERAGE:*		22.9	7.68	1,483	6		--
	7/10/97	0840	0	22.6	7.31	1,500	318	cloudy	--
		0846	10	23.3	7.17	1,320	16	clear	--
		0852	20	23.4	7.16	1,340	0	clear	--
		0858	30	23.5	7.13	1,360	0	clear	--
		0904	40	23.5	7.12	1,360	0	clear	--
		TOTAL:	40						
		AVERAGE:*		23.5	7.14	1,353	0		--
P-15	12/27/95	1053	10	22.4	7.29	2,610	61	clear	--
		1056	15	22.8	7.66	2,600	20	clear	--
		1059	25	22.8	7.67	2,660	<10	clear	--
		1102	30	22.8	7.67	2,630	<10	clear	--
		TOTAL:	30						
		AVERAGE:*		22.8	7.67	2,630	20		--
	3/19/96	1003	5	21.7	8.01	1,410	28	clear	--
		1007	15	22.5	7.97	1,450	15	clear	--
		1010	25	22.6	7.91	1,470	9	clear	--
		1012	30	22.7	7.92	1,440	13	clear	--
		TOTAL:	30						
		AVERAGE:*		22.6	7.93	1,453	12		--
	6/26/96	0855	5	22.2	7.93	1,400	-10	clear	--
		0857	10	22.1	7.73	1,300	-10	clear	--
		0900	15	22.7	7.72	1,320	-10	clear	--
		0902	20	22.6	7.68	1,330	-10	clear	--
		TOTAL:	20						
		AVERAGE:*		22.5	7.71	1,317	-10		--
	9/18/96	0805	5	21.9	7.81	1,300	12	sl. cloudy	--
		0808	10	22.5	7.76	1,310	10	clear	--
		0810	15	22.8	7.73	1,330	-10	clear	--
		0816	22	22.9	7.73	1,300	-10	clear	--
		TOTAL:	22						
		AVERAGE:*		22.7	7.74	1,313	-3		--

BOE-C6-0234122

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-15 (Cont.)	7/10/97	1130	0	25.5	7.85	571	55	clear	--
		1138	10	24.2	7.29	1,250	0	clear	--
		1146	20	24.1	7.26	1,240	0	clear	--
		1153	30	24.1	7.25	1,230	0	clear	--
		1156	34	24.1	7.25	1,220	0	clear	--
		TOTAL:	34						
		AVERAGE:*		24.1	7.25	1,230	0		--
P-16A	12/26/95	1124	10	22.8	7.61	2,060	152	cloudy	--
		1127	20	22.8	7.66	2,080	100	cloudy	--
		1130	30	22.7	7.71	2,090	66	cloudy	--
		1132	33	22.8	7.78	2,080	71	cloudy	--
		TOTAL:	33						
		AVERAGE:*		22.8	7.72	2,083	79		--
	3/18/96	1340	5	22.2	7.64	2,070	39	clear	--
		1344	15	22.3	7.61	2,080	19	clear	--
		1349	25	22.5	7.59	2,160	79	cloudy	--
		1353	35	22.4	7.62	2,180	34	cloudy	--
		TOTAL:	35						
		AVERAGE:*		22.4	7.61	2140	44		--
	6/25/96	0828	5	21.4	6.86	1,680	-10	clear	--
		0831	10	21.4	7.31	1,660	-10	sl. cloudy	--
		0834	15	22.0	7.35	1,700	-10	sl. cloudy	--
		0838	20	22.2	7.35	1,800	-10	sl. cloudy	--
		0841	25	22.2	7.51	1,800	-10	sl. cloudy	--
		TOTAL:	25						
		AVERAGE:*		22.1	7.40	1,767	-10		--
	9/16/96	1037	5	22.8	7.46	2,720	46	clear	--
		1040	10	23.0	7.44	2,710	14	clear	--
		1043	15	23.0	7.46	2,670	25	clear	--
		1046	20	22.9	7.57	2,670	14	clear	--
		1049	25	22.9	7.46	2,680	7	clear	--
		TOTAL:	25						
		AVERAGE:*		22.9	7.50	2,673	15		--
	7/9/97	1533	0	26.0	7.63	2,160	642	cloudy	--
		1540	10	23.9	7.05	2,280	26	clear	--
		1549	20	24.0	7.03	2,340	14	clear	--
		1558	30	23.8	7.02	2,340	2	clear	--
		1605	40	23.7	7.02	2,340	0	clear	--
		TOTAL:	40						
		AVERAGE:*		23.8	7.02	2,340	5		--
	3/4/99	1000	0	21.6	7.09	--	999	lt. tan	--
		1005	5	22.1	7.03	--	999	lt. tan	--
		1009	10	22.5	7.07	--	334	lt. tan	--
		1013	15	22.4	7.15	--	999	lt. tan	--
		1016	20	22.3	7.02	4,450	999	lt. tan	--
		1023	30	22.5	7.05	4,190	670	lt. tan	--
		1031	40	21.9	7.00	4,130	408	lt. tan	--
		TOTAL:	40						
		AVERAGE:*		22.2	7.02	4,257	692		--

BOE-C6-0234123

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-16B	12/19/95	1151	10	22.5	7.92	3,450	<10	very clear	--
		1155	20	22.5	7.76	3,420	<10	very clear	--
		1202	40	22.3	7.74	3,390	<10	very clear	--
		1212	60	22.3	7.71	3,380	<10	very clear	--
		1250	80	22.3	7.72	3,360	<10	very clear	--
		1304	100	22.4	7.69	3,380	<10	very clear	--
		1310	112	22.4	7.70	3,380	<10	very clear	--
		TOTAL:	112						
		AVERAGE:*		22.4	7.70	3,373	< 10		--
	3/18/96	0925	10	21.5	8.05	3,540	9	clear	--
		0931	30	21.8	7.85	3,570	12	clear	--
		0935	40	22.0	7.83	3,610	9	clear	--
		0939	50	22.0	7.84	3,610	45	clear	--
		0945	70	22.0	7.83	3,610	4	clear	--
		0952	90	22.1	7.77	3,600	6	clear	--
		1000	115	22.1	7.81	3,610	5	clear	--
		TOTAL:	115						
		AVERAGE:*		22.1	7.80	3,607	5		--
	6/24/96	0859	10	21.7	7.31	3,770	10	clear	--
		0904	20	21.9	7.72	3,810	5	clear	--
		0909	30	22.0	7.81	3,800	1	clear	--
		0918	50	22.2	7.68	3,810	2	clear	--
		0924	70	22.3	7.67	3,810	1	clear	--
		0932	85	22.2	7.70	3,830	1	clear	--
		TOTAL:	85						
		AVERAGE:*		22.2	7.68	3,817	1		--
P-16C	9/12/96	0935	10	22.6	7.76	3,630	117	cloudy	--
		0940	20	22.5	7.72	3,610	109	cloudy	--
		TOTAL:	20						
		AVERAGE:*		22.6	7.74	3,620	113		--
	7/9/97	0755	0	22.4	7.37	3,300	16	clear	--
		0812	20	23.3	7.23	3,430	0	clear	--
		0829	40	23.4	7.26	3,450	0	clear	--
		0844	60	23.5	7.27	3,460	0	clear	--
		0858	80	23.5	7.28	3,450	0	clear	--
		0912	100	23.5	7.28	3,450	0	clear	--
		0930	125	23.6	7.29	3,440	0	clear	--
		TOTAL:	125						
		AVERAGE:*		23.5	7.28	3,447	0		--
	3/2/99	1151	0	22.3	6.64	3,850	148	light brown	--
		1157	10	22.1	6.91	3,930	71	light brown	--
		1214	30	21.7	6.95	3,870	135	light brown	--
		1227	50	21.8	6.96	4,050	7	clear	--
		1242	70	21.9	7.00	4,010	5	clear	--
		1258	90	22.0	7.02	3,990	2	clear	--
		1630	110	21.9	7.20	3,860	164	light brown	--
		1637	125	22.3	7.08	3,880	107	light brown	--
		TOTAL:	125						
		AVERAGE:*		22.1	7.10	3,910	91		--

BOE-C6-0234124

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-17	12/21/95	1217	5	21.3	8.12	2,200	<10	clear	--
		1220	10	22.5	7.84	2,050	15	cloudy	--
		1223	20	22.6	7.82	2,110	346	tan	--
		1226	30	22.6	7.79	2,100	300	tan	--
		TOTAL:	30						
		AVERAGE:*		22.6	7.82	2,087	220		--
	3/19/96	1151	5	22.9	7.95	2,050	26	clear	--
		1155	15	23.1	7.86	2,010	135	clear	--
		1157	25	23.2	7.81	2,020	165	clear	--
		1200	35	23.0	7.82	2,080	156	clear	--
		TOTAL:	35						
		AVERAGE:*		23.1	7.83	2,037	152		--
	9/18/96	0953	5	22.7	7.63	2,010	36	clear	--
		0956	10	23.0	7.64	2,020	12	clear	--
		0958	15	23.0	7.63	2,030	11	clear	--
		1003	25	23.2	7.63	2,090	8	clear	--
		TOTAL:	25						
		AVERAGE:*		23.1	7.63	2,047	10		--
	7/10/97	1233	0	25.9	7.92	1,370	19	clear	--
		1240	10	24.1	7.15	1,870	2	clear	--
		1248	20	24.1	7.13	1,940	0	clear	--
		1255	30	24.1	7.12	1,960	0	clear	--
		1259	36	24.2	7.12	1,980	7	clear	--
		TOTAL:	36						
		AVERAGE:*		24.1	7.12	1,960	2		--
	3/4/99	1304	0	20.0	7.10	2,280	55	clear	--
		1307	5	21.0	6.90	1,810	113	clear	--
		1311	10	22.1	6.68	1,860	15	clear	--
		1315	15	22.2	6.87	2,000	2	clear	--
		1319	20	22.6	6.95	2,000	0	clear	--
		1326	30	22.5	6.94	2,100	0	clear	--
		1333	40	22.4	6.87	2,140	0	clear	--
		TOTAL:	40						
		AVERAGE:*		22.5	6.92	2,080	0		--
P-18	12/26/95	1030	5	20.4	7.15	2,100	46	clear	--
		1032	15	20.8	7.86	1,940	120	cloudy	--
		1035	25	20.7	7.85	1,970	71	cloudy	--
		1038	30	20.9	7.77	1,990	115	cloudy	--
		TOTAL:	30						
		AVERAGE:*		20.8	7.83	1,967	102		--
	3/14/96	1504	7	21.5	7.61	2,290	10	clear	--
		1506	14	21.8	7.68	2,010	10	clear	--
		1511	21	21.9	7.72	2,020	10	clear	--
		1515	30	22.0	7.76	2,010	10	clear	--
		TOTAL:	30						
		AVERAGE:*		21.9	7.72	2,013	10		--
	9/12/96	0758	5	21.0	6.99	1,990	97	sl. sloudy	--
		0801	10	21.5	7.49	1,980	62	sl. cloudy	--
		0804	15	21.9	7.51	1,990	33	clear	--
		0808	20	22.0	7.51	2,020	31	clear	--
		TOTAL:	20						
		AVERAGE:*		21.8	7.50	1,997	42		--

BOE-C6-0234125

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-18 (Cont.)	7/8/97	1502	0	24.4	7.29	1,730	168	clear	--
		1506	5	23.6	7.28	1,680	124	clear	--
		1509	10	23.4	7.25	1,730	70	clear	--
		1513	15	23.5	7.25	1,750	26	clear	--
		1517	20	23.5	7.24	1,750	15	clear	--
		1521	25	23.5	7.22	1,740	12	clear	--
		1525	30	23.5	7.21	1,770	8	clear	--
		1529	36	23.5	7.21	1,760	3	clear	--
		TOTAL:	36						
		AVERAGE:*		23.5	7.21	1,757	8		--
P-19	12/26/95	1053	10	20.1	7.78	1,950	71	clear	--
		1056	20	20.2	7.77	1,990	<10	clear	--
		1059	30	20.4	7.79	2,020	<10	clear	--
		1105	35	20.4	7.78	2,030	<10	clear	--
		TOTAL:	35						
		AVERAGE:*		20.3	7.78	2,013	<10		--
	3/19/96	0734	5	20.6	7.66	2,180	11	clear	--
		0736	15	21.3	7.65	2,190	14	clear	--
		0739	25	21.7	7.65	2,140	25	clear	--
		0744	37	21.8	7.62	2,180	18	clear	--
		TOTAL:	37						
		AVERAGE:*		21.6	7.64	2,170	19		--
	6/25/96	1115	5	22.8	7.33	2,330	-10	cloudy	--
		1118	10	22.6	7.34	2,320	-10	cloudy	--
		1121	15	22.5	7.33	2,330	-10	cloudy	--
		1124	20	22.6	7.33	2,340	-10	clear	--
		1127	25	22.5	7.33	2,320	-10	clear	--
		TOTAL:	25						
		AVERAGE:*		22.5	7.33	2,330	-10		--
	9/17/96	0722	5	20.8	7.09	2,330	17	clear	--
		0725	10	21.5	7.37	2,310	12	clear	--
		0728	15	22.1	7.40	2,300	2	clear	--
		0724	25	22.3	7.42	2,330	0	clear	--
		TOTAL:	25						
		AVERAGE:*		22.0	7.40	2,313	5		--
	7/9/97	1635	0	25.3	7.41	1,360	37	clear	--
		1643	10	23.6	7.25	1,520	2	clear	--
		1650	20	23.5	7.27	1,460	0	clear	--
		1658	30	23.6	7.27	1,450	0	clear	--
		1707	42	23.5	7.27	1,450	0	clear	--
		TOTAL:	42						
		AVERAGE:*		23.5	7.27	1,453	0		--
P-20	12/27/95	1252	5	22.3	7.44	2,100	160	clear	--
		1254	10	22.4	7.49	2,270	40	clear	--
		1257	20	22.5	7.51	2,260	<10	clear	--
		1300	30	22.5	7.50	2,250	<10	clear	--
		TOTAL:	30						
		AVERAGE:*		22.5	7.50	2,260	40		--
	3/18/96	1420	5	23.2	7.92	2,050	11	clear	--
		1422	10	23.2	8.25	2,070	14	clear	--
		1425	20	23.4	8.31	2,080	60	tan	--
		1427	30	23.5	8.31	2,090	41	tan	--
		TOTAL:	30						
		AVERAGE:*		23.4	8.29	2,080	38		--

BOE-C6-0234126

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-20 (Cont.)	6/25/96	1339	5	23.7	7.20	2,230	47	clear	--
		1342	10	23.4	7.41	1,930	81	sl. cloudy	--
		1344	15	23.3	7.48	1,910	75	sl. cloudy	--
		1347	20	23.2	7.49	1,900	66	sl. cloudy	--
		TOTAL:	20						
		AVERAGE:*		23.3	7.46	1,913	74		--
	9/16/96	1233	5	24.1	7.51	2,390	14	clear	--
		1235	10	23.5	7.51	2,380	34	clear	--
		1238	15	23.6	7.52	2,380	17	clear	--
		1241	20	23.3	7.56	2,340	70	clear	--
		TOTAL:	20						
		AVERAGE:*		23.5	7.53	2,367	40		--
	7/10/97	1028	0	24.2	7.25	1,920	59	clear	--
		1035	10	23.8	6.90	2,820	0	clear	--
		1043	20	23.8	6.90	2,860	0	clear	--
		1051	30	23.9	6.90	2,880	0	clear	--
		1053	34	23.9	6.90	2,880	0	clear	--
		TOTAL:	34						
		AVERAGE:*		23.9	6.90	2,873	0		--
	3/4/99	1112	0	19.5	6.36	3,890	361	tan	--
		1116	5	21.1	6.67	2,540	15	clear	--
		1120	10	22.0	6.69	2,480	2	clear	--
		1124	15	21.7	6.72	2,490	0	clear	--
		1127	20	22.3	6.71	2,470	0	clear	--
		1136	30	22.5	6.70	2,440	3	clear	--
		1141	37	22.3	6.72	2,420	3	clear	--
		TOTAL:	37						
		AVERAGE:*		22.4	6.71	2,443	2		--
P-21	12/26/95	1213	10	22.1	7.66	1,990	280	tan	--
		1216	20	22.3	7.71	1,990	<10	clear	--
		1219	30	22.6	7.76	2,050	<10	clear	--
		1221	35	22.8	7.73	2,100	<10	clear	--
		TOTAL:	35						
		AVERAGE:*		22.6	7.73	2,047	<10		--
	3/18/96	1530	5	22.3	7.49	1,090	10	clear	--
		1534	15	21.0	7.51	1,100	20	tan	--
		1537	25	21.3	7.53	1,070	27	tan	--
		1543	36	21.3	7.55	1,080	23	tan	--
		TOTAL:	36						
		AVERAGE:*		21.2	7.53	1,083	23		--
	6/25/96	1554	5	21.9	7.24	1,810	999	clear	--
		1557	10	22.3	7.19	1,770	8	clear	--
		1600	15	22.5	7.16	1,790	4	clear	--
		1603	20	22.5	7.16	1,790	6	cloudy	--
		1606	25	22.4	7.12	1,790	0	clear	--
		TOTAL:	25						
		AVERAGE:*		22.5	7.15	1,790	3		--
	9/17/96	0806	5	21.6	7.33	1,850	44	clear	--
		0808	10	21.9	7.29	1,820	12	clear	--
		0811	15	22.1	7.29	1,820	9	clear	--
		0816	25	22.4	7.27	1,840	7	clear	--
		TOTAL:	25						
		AVERAGE:*		22.1	7.28	1,827	9		--

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-21 (Cont.)	7/10/97	0942	0	22.8	7.03	1,900	35	clear	--
		0950	10	23.3	6.79	1,890	4	clear	--
		0952	14	--	--	--	-	--	--
		TOTAL:	14						
		AVERAGE:*		15.4	4.61	1,263	13		--
P-22	12/20/95	0732	5	21.2	7.89	990	15	cloudy	--
		0733	10	22.3	7.91	1,030	<10	clear	--
		0735	15	22.3	7.90	1,030	<10	clear	--
		0739	25	22.3	7.90	1,020	<10	clear	--
		TOTAL:	25						
		AVERAGE:*		22.3	7.90	1,027	<10		--
	3/18/96	1242	5	22.0	7.95	1,870	29	clear	--
		1245	15	22.1	7.99	1,890	27	clear	--
		1250	25	22.1	7.97	1,900	10	clear	--
		1253	32	22.1	7.98	1,900	13	clear	--
		TOTAL:	32						
		AVERAGE:*		22.1	7.98	1,897	17		--
	6/20/96	1359	5	23.5	7.73	910	6	some silt	--
		1401	10	22.4	7.61	900	17	some silt	--
		1403	15	23.0	7.58	830	167	silty	--
		1405	20	22.2	7.62	850	90	silty	--
		1407	25	22.7	7.62	860	44	clear/silt	--
		TOTAL:	25						
		AVERAGE:*		22.6	7.61	847	100		--
	9/12/96	1307	5	23.5	7.99	990	18	clear	--
		1310	10	23.3	7.82	960	137	clear	--
		1313	15	23.0	7.77	930	4	clear	--
		1316	20	22.8	7.72	1,000	91	clear	--
		1319	25	22.8	7.69	930	127	clear	--
		TOTAL:	25						
		AVERAGE:*		22.9	7.73	953	74		--
	7/9/97	1214	0	25.1	7.40	705	172	clear	--
		1224	10	24.4	7.38	708	35	clear	--
		1233	20	24.4	7.29	755	20	clear	--
		1243	30	24.5	7.24	799	7	clear	--
		1253	40	24.5	7.22	823	7	clear	--
		TOTAL:	40						
		AVERAGE:*		24.5	7.25	792	11		--
	3/3/99	1254	0	22.1	6.95	2,750	151	light brown	--
		1257	5	22.5	6.92	2,760	28	clear	--
		1302	10	22.4	6.93	2,640	5	clear	--
		1311	20	23.1	6.91	2,570	0	clear	--
		1319	30	23.2	6.91	2,680	132	clear	--
		1327	40	23.1	6.94	2,710	4	clear	--
		TOTAL:	40						
		AVERAGE:*		23.1	6.92	2,653	45		--
P-23	12/20/95	1112	2	21.1	7.65	2,480	off scale	cloudy tan	--
		1114	5	23.8	7.55	3,130	<10	very clear	--
		1116	8	23.7	7.58	3,130	<10	veryclear	--
		1119	15	23.7	7.57	3,120	<10	very clear	--
		TOTAL:	15						
		AVERAGE:*		23.7	7.57	3,127	<10		--

BOE-C6-0234128

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-23 (Cont.)	3/14/96	0942	3	21.9	7.82	3,340	10	clear	--
		0956	6	22.3	7.79	3,260	10	clear	--
		TOTAL:	6						
		AVERAGE:*		22.1	7.81	3,300	10		--
	6/20/96	0929	3	23.0	7.18	3,460	51	silty	--
		--	3.5	--	--	--	--	--	--
		TOTAL:	3.5						
		AVERAGE:*		--	--	--	--		--
	9/11/96	1040	3	23.5	7.83	3,170	109	clear	--
		1042	6	23.6	7.84	2,970	9	clear	--
		1044	9	23.9	7.80	3,090	-10	clear	--
		TOTAL:	9						
		AVERAGE:*		23.7	7.82	3,077	36		--
	7/8/97	1410	0	28.8	7.40	2,460	279	clear	--
		1418	5	26.2	7.23	2,770	21	clear	--
		1425	10	26.2	7.22	2,690	3	clear	--
		1432	16	25.3	7.21	2,780	0	clear	--
		TOTAL:	16						
		AVERAGE:*		25.9	7.22	2,747	8		--
P-24	12/20/95	1042	3	22.2	7.47	3,100	no read	cloudy tan	--
		1043	5	22.5	7.50	3,150	410	clear	--
		1045	7	22.5	7.51	3,140	100	cloudy	--
		1047	9	22.5	7.52	3,140	60	cloudy	--
		1050	11	22.5	7.51	3,130	33	cloudy	--
		TOTAL:	11						
		AVERAGE:*		22.5	7.51	3,137	64		--
	3/19/96	0852	2	21.3	7.41	1,570	14	clear	--
		TOTAL:	2						
		AVERAGE:*		--	--	--	--		--
	6/24/96	1248	5	23.8	7.42	2,700	94	cloudy	--
		TOTAL:	5						
		AVERAGE:*		--	--	--	--		--
	9/17/96	1311	3	24.3	7.30	2,880	290	clear	--
		1313	6	24.0	7.45	2,560	102	clear	--
		1315	9	23.8	7.38	2,700	42	clear	--
		TOTAL:	9						
		AVERAGE:*		24.0	7.38	2,713	145		--
	7/9/97	0722	0	22.1	8.48	676	>999	silty brown	--
		0725	4	--	--	--	--	--	--
		TOTAL:	4						
		AVERAGE:*		--	--	--	--		--
	3/2/99	1055	0	22.3	7.52	1,960	>999	brown	--
		1059	5	21.9	7.30	1,850	640	lt brown	--
		TOTAL:	5						
		AVERAGE:*		22.1	7.41	1,905	640		--
P-25	12/26/95	1150	4	22.4	7.78	1,100	19	clear	--
		1151	8	22.4	7.71	1,150	<10	clear	--
		1153	12	22.4	7.68	1,150	<10	clear	--
		1156	18	22.6	7.69	1,170	<10	clear	--
		TOTAL:	18						
		AVERAGE:*		22.5	7.69	1,157	<10		--

BOE-C6-0234129

Table 5. Summary of Groundwater Results - Field Water Quality Parameters, Former ILM Facility, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
P-25 (Cont.)	3/19/96	1300	5	21.8	7.77	1,900	491	tan	--
		1302	10	22.1	7.77	1,890	461	tan	--
		TOTAL:	10						
		AVERAGE:*		22.0	7.77	1,895	476		--
	6/26/96	1232	3	22.8	7.58	2,060	122	clear	--
		1234	6	22.4	7.57	2,090	47	clear	--
		1236	9	22.3	7.57	2,040	210	cloudy	--
		1238	12	22.0	7.60	1,990	148	cloudy	--
		TOTAL:	12						
		AVERAGE:*		22.2	7.58	2,040	135		--
	9/18/96	1032	5	22.9	7.68	1,990	30	clear	--
		1035	10	22.9	7.63	1,990	40	clear	--
		1037	15	22.8	7.64	1,950	18	clear	--
		TOTAL:	15						
		AVERAGE:*		22.9	7.65	1,977	29		--
	7/10/97	1342	0	25.9	7.19	1,820	170	clear	--
		1348	5	24.5	7.12	1,850	0	clear	--
		1354	10	24.5	7.11	1,840	0	clear	--
		1400	15	24.5	7.11	1,820	0	clear	--
		1407	20	24.7	7.11	1,810	0	clear	--
		1414	25	24.7	7.11	1,810	0	clear	--
		TOTAL:	25						
		AVERAGE:*		24.6	7.11	1,813	0		--

**	Turbidity meter failed to stabilize following calibration to a 10 NTU standard.
gal	Purged water volume in gallons
°C	Degrees Centigrade
µmhos/cm	Micromhos per centimeter
NTU	Nephelometric Turbidity Units
DO	Dissolved oxygen
mg/L	Milligrams per liter
--	No reading recorded
sl.	Slightly

*Note: When more than three measurements of parameters have been made, the average values are of the last three measurements taken.

BOE-C6-0234130

Table 6. Summary of Groundwater Results - Field Water Quality Parameters, BRC Property, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
BL-1	3/4/99	1351	0	20.4	7.02	1,740	>1100	--	48.4
		1355	2	21.2	6.54	1,890	>1100	--	20.0
		1359	4	21.8	6.45	2,000	>1100	--	15.2
		1403	6	22.8	6.40	2,060	732	--	11.6
		1407	8	22.7	6.38	2,080	580	--	10.0
		1409	9	23.1	6.37	2,110	307	--	9.6
		1411	10	22.9	6.37	2,110	198	--	8.8
		1413	11	22.8	6.36	2,110	117	--	8.9
		TOTAL:	11						
		AVERAGE:*		22.2	6.37	2,110	207		9.1
BL-2	3/3/99	1354	0	21.1	7.63	834	>1100	--	96.4
		1358	2	21.6	7.31	716	>1100	--	84.8
		1402	4	22.5	7.12	764	>1100	--	86.0
		1406	6	22.8	7.08	772	476	--	81.2
		1410	8	23.3	7.09	777	322	--	84.6
		1413	9.5	23.1	7.08	748	295	--	84.2
		1415	11	23.2	7.05	754	285	--	86.1
		TOTAL:	11						
		AVERAGE:*		22.5	7.07	760	301		85.0
BL-3	3/3/99	1009	0	22.9	7.64	3,800	275	--	77.5
		1013	2	23.4	7.20	3,890	161	--	47.6
		1017	4	23.6	6.90	3,980	112	--	49.2
		1021	6	23.4	6.70	3,720	73	--	52.7
		1024	7.5	23.6	6.67	3,700	64	--	52.5
		1026	8.5	23.5	6.66	3,690	66	--	54.9
		1028	9.5	23.3	6.60	3,680	60	--	53.9
		TOTAL:	9.5						
		AVERAGE:*		23.4	6.64	3,690	63		53.8
BL-4	3/2/99	1235	0	21.6	8.04	596	>1100	--	56.7
		1239	2	21.7	7.52	569	>1100	--	49.6
		1243	4	21.9	7.45	576	823	--	52.1
		1247	6	22.7	7.39	588	258	--	47.2
		1249	7	23.4	7.37	584	140	--	51.0
		1251	8	23.4	7.33	579	112	--	47.8
		1253	9	23.5	7.33	577	86	--	47.0
		TOTAL:	9						
		AVERAGE:*		23.44	7.34	580	113		48.6
BL-5	3/4/99	1022	0	21.2	5.92	2,590	265	--	64.2
		1026	2	20.8	6.31	2,590	185	--	29.9
		1030	4	21.9	6.37	2,640	144	--	29.2
		1034	6	21.5	6.45	2,610	127	--	28.4
		1038	8	22.2	6.46	2,490	91	--	26.9
		1041	10	22.1	6.47	2,480	83	--	27.3
		1043	11	22.3	6.48	2,450	60	--	26.5
		TOTAL:	11						
		AVERAGE:*		21.7	6.47	2,473	78		26.9

Table 6. Summary of Groundwater Results - Field Water Quality Parameters, BRC Property, Torrance, California

Well Number	Date	Time	Volume (gal)	Temp. (°C)	pH (pH units)	Conductivity (µmhos/cm)	Turbidity (NTU)	Color	DO (mg/L)
BL-6	3/1/99	1135	0	22.6	6.08	1,710	>1100	--	77.3
		1137	2	23.3	6.60	1,690	>1100	--	70.9
		1139	4	21.9	6.56	1,640	>1100	--	70.1
		1141	5	21.7	6.56	1,630	>1100	--	72.1
		1143	6	21.4	6.57	1,620	1087	--	74.6
		1145	7	22.5	6.77	1,680	1053	--	68.5
		1147	8	22.3	6.78	1,650	924	--	69.8
		1151	10	24.0	6.76	1,730	422	--	69.5
		1155	12	24.3	6.75	1,740	344	--	69.4
		TOTAL:	12						
		AVERAGE:*		22.7	6.76	1,707	563		69.6
BL-7	3/1/99	0823	0	20.8	8.79	1,102	>1100	--	78.8
		0825	1	22.4	7.79	930	958	--	77.1
		0827	2	23.2	7.47	813	940	--	77.0
		0829	3	23.8	7.42	799	492	--	74.9
		0831	4	23.5	7.32	808	175	--	74.8
		0835	6	23.3	7.24	799	32	--	77.7
		0839	8	23.2	7.18	779	98	--	78.0
		0841	9	23.4	7.18	807	47	--	79.3
		0843	10	23.1	7.14	800	32	--	79.1
		0845	11	23.2	7.12	809	34	--	80.3
		TOTAL:	11						
		AVERAGE:*		23.0	7.15	805	38		79.6
BL-8	3/2/99	1508	0	20.8	7.63	1,940	>1100	--	75.1
		1512	2	22.4	7.28	2,040	906	--	70.1
		1516	4	23.1	7.13	2,080	456	--	67.3
		1520	6	23.2	7.03	2,090	339	--	68.6
		1523	7.5	23.3	7.00	2,100	233	--	68.4
		1525	8.5	23.2	6.99	2,090	187	--	68.7
		1527	9.5	23.3	6.97	2,100	148	--	68.6
		TOTAL:	9.5						
		AVERAGE:*		22.8	6.99	2,097	189		68.6

gal	Purged water volume in gallons
°F	Degrees Farenheit
µmhos/cm	Micromhos per centimeter
NTU	Nephelometric Turbidity Units
DO	Dissolved oxygen
mg/L	Milligrams per liter
--	No reading recorded

*Note: When more than three measurements of parameters have been made, the average values are of the last three measurements taken.

BOE-C6-0234132

Table 7. Summary of Groundwater Analytical Results - Volatile Organic Compounds (VOCs), Former ILM Facility, Torrance, California

Sample ID	Sample Date	Volatile Organic Compounds[1] (in µg/L)																		
		TCE	PCE	1,1-DCA	1,1-DCE	1,1,1-TCA	Bromodi-chloro-methane	Bromoform	Chloroform	1,2- Dichloro-propane	Trans-1,2-DCE	Cis-1,2-DCE	Dibromo-chloro-methane	Toluene	Benzene	Ethyl benzene	Total Xylenes	Vinyl Chloride	1,1,2-TCA	1,2-DCA
P-6	3/16/95	510	ND(10)	ND(10)	ND(10)	ND(10)	ND(10)	ND(10)	ND(10)	ND(10)	ND(10)	NA	ND(10)	ND(10)	ND(10)	ND(10)	ND(20)	ND(2)	ND(10)	ND(10)
	12/20/95	570	18	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(1)	ND(5)	ND(5)
	3/18/96	510	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(50)	ND(5)	ND(30)	ND(30)
	6/20/96	500	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(60)	ND(5)	ND(30)	ND(30)
	9/12/96	520	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(60)	ND(6)	ND(30)	ND(30)
	7/9/97	530.0	ND(10)	ND(10)	ND(10)	13.0	ND(10)	ND(10)	ND(10)	ND(10)	ND(10)	ND(10)	ND(10)	ND(10)	ND(10)	ND(10)	ND(20)	ND(5)	ND(10)	ND(10)
P-6B	3/3/99	280	7.4	ND(0.5)	1.2	ND(0.5)	ND(0.5)	ND(0.5)	0.94	ND(0.5)	ND(0.5)	1.7	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-7	3/17/95	2,500	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	NA	ND(100)	ND(100)	ND(100)	ND(100)	ND(200)	ND(20)	ND(100)	ND(100)
	3/17/95(D)	2,400	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	NA	ND(100)	ND(100)	ND(100)	ND(100)	ND(200)	ND(20)	ND(100)	ND(100)
	12/21/95	1,700	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(100)	ND(10)	ND(50)	ND(50)
	3/18/96	1,500	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(100)	ND(10)	ND(50)	ND(50)
	6/24/96	1,700	ND(70)	ND(200)	ND(200)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(200)	ND(200)	ND(70)	ND(70)	ND(70)	ND(200)	ND(20)	ND(200)	ND(200)
	9/16/96	1,700	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(100)	ND(10)	ND(50)	ND(50)
	7/9/97	3,200	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(200)	ND(30)	ND(70)	ND(70)
	3/4/99	900	13	2.2	7.8	7.2	ND(0.5)	ND(0.5)	12	ND(0.5)	3.3	75	ND(0.5)	ND(0.5)	0.61	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-8	3/16/95	3,100	ND(60)	ND(60)	ND(60)	ND(60)	ND(60)	ND(60)	ND(60)	ND(60)	ND(60)	NA	ND(60)	ND(60)	ND(60)	ND(60)	ND(100)	ND(10)	ND(60)	ND(60)
P-9	3/16/95	910	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	NA	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(6)	ND(30)	ND(30)
	12/20/95	1,100	ND(5)	ND(5)	6.2	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(1)	ND(5)	ND(5)
	3/18/96	1,100	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(100)	ND(10)	ND(50)	ND(50)
	6/26/96	1,300	ND(40)	ND(40)	ND(40)	ND(40)	ND(40)	ND(40)	ND(40)	ND(40)	ND(40)	ND(40)	ND(40)	ND(40)	ND(40)	ND(40)	ND(80)	ND(8)	ND(40)	ND(40)
	9/12/96	1,200	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(60)	ND(6)	ND(30)	ND(30)
	7/9/97	1000	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(60)	ND(10)	ND(30)	ND(30)
P-9B	3/3/99	280	1.70	ND(0.5)	4.50	ND(0.5)	ND(0.5)	ND(0.5)	2.20	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-10	3/16/95	2.8	ND(0.5)	ND(0.5)	0.64	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	NA	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	12/19/95	1.2	ND(0.5)	0.60	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(1)	ND(0.5)	ND(0.5)
	3/14/96	0.62	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	6/18/96	1.2	ND(0.5)	ND(0.5)	0.55	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	9/11/96	0.74	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(5)	ND(5)	ND(5)
	7/8/97	3.4	1.2	ND(0.5)	2.9	13	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	1.0	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.2)	ND(0.5)	ND(0.5)
	3/1/99	3.7	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-11	12/27/95	1.8	0.57	ND(0.5)	ND(0.5)	ND(0.5)	1.5	ND(0.5)	1.9	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(1)	ND(0.5)	ND(0.5)
	3/14/96	1.6	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	0.88	ND(0.5)	1.4	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	6/19/96	7.3	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	0.94	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	9/11/96	2.8	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	0.97	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(60)	ND(6)	ND(30)	ND(30)
	7/8/97	4.3	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.2)	ND(0.5)	ND(0.5)
P-12	12/21/95	10,000	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(200)	ND(20)	ND(100)	ND(200)
	3/19/96	8,500	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(700)	ND(70)	ND(400)	ND(700)
	6/26/96	9,200	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(800)	ND(80)	ND(400)	ND(800)
	6/26/96(D)	9,400	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(800)	ND(80)	ND(400)	ND(800)
	9/18/96	5,000	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(600)	ND(60)	ND(300)	ND(300)
	7/10/97	3,000	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(200)	ND(30)	ND(70)	ND(200)
	3/3/99	1,500	1.5	31	29	8.9	ND(0.5)	ND(0.5)	31	2.9	ND(0.5)	2.9	ND(0.5)	ND(0.5)	6.7	ND(0.5)	ND(1)	ND(0.5)	1.6	0.54

TABLE 7 P-6

BOE-C6-0234133

Table 7. Summary of Groundwater Analytical Results - Volatile Organic Compounds (VOCs), Former ILM Facility, Torrance, California

Sample ID	Sample Date	Volatile Organic Compounds[1] (in µg/L)																		
		TCE	PCE	1,1-DCA	1,1-DCE	1,1,1-TCA	Bromodi-chloro-methane	Bromoform	Chloroform	1,2- Dichloro-propane	Trans-1,2-DCE	Cis-1,2-DCE	Dibromo-chloro-methane	Toluene	Benzene	Ethyl benzene	Total Xylenes	Vinyl Chloride	1,1,2-TCA	1,2-DCA
P-1	1/24/95	22,000	38	0.53	9.7	0.74	1.3	ND(0.5)	64	ND(0.5)	2.2	NA	ND(0.5)	30	12	1.8	11	ND(0.5)	ND(0.5)	ND(0.5)
	3/17/95	23,000	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	NA	ND(600)	ND(600)	ND(600)	ND(600)	ND(1,000)	ND(100)	ND(600)	ND(600)
	12/27/95	24,000	ND(600)	ND(0.5)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(1,000)	ND(100)	ND(600)	ND(600)
	12/27/95(D)	23,000	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(600)	ND(1,000)	ND(100)	ND(600)	ND(600)
	3/19/96	22,000	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(3,000)	ND(300)	ND(2,000)	ND(2,000)
	6/26/96	24,000	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(2,000)	ND(200)	ND(900)	ND(900)
	6/26/96(D)	23,000	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(900)	ND(2,000)	ND(200)	ND(900)	ND(900)
	9/18/96	23,000	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(2,000)	ND(4,000)	ND(400)	ND(2,000)	ND(2,000)
	7/10/97	15,000	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(1,000)	ND(200)	ND(500)	ND(500)
	7/10/97(D)	15,000	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(1,000)	ND(200)	ND(500)	ND(500)
	3/4/99	8,100	83	1.7	10	ND(0.5)	ND(0.5)	ND(0.5)	13	ND(0.5)	1.2	24	ND(0.5)	ND(0.5)	1.3	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-2	1/27/95	87	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	NA	ND(3)	100	20	7.2	60	ND(3)	ND(3)	ND(3)
	3/17/95	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	NA	ND(3)	ND(3)	ND(3)	ND(3)	24	ND(3)	ND(3)	ND(3)
	12/27/95	ND(5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	2.1	ND(0.5)	0.83	23	ND(1)	ND(0.5)	ND(0.5)
	3/19/96	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	1.5	ND(0.1)	ND(0.5)	ND(0.5)
	3/19/96(D)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	2.0	ND(0.1)	ND(0.5)	ND(0.5)
	6/20/96	0.52	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	1.2	ND(0.1)	ND(0.5)	ND(0.5)
	6/20/96(D)	0.59	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	1.2	ND(0.1)	ND(0.5)	ND(0.5)
	9/17/96	0.92	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	7/8/97	11	7.9	ND(0.5)	19	110	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	9.2	ND(0.5)	1.1	ND(0.5)	ND(0.5)	1.6	ND(0.2)	ND(0.5)	ND(0.5)
	3/2/99	0.70	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-3	1/24/95	140	ND(0.5)	ND(0.5)	1.6	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	NA	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
	3/17/95	26	ND(0.5)	ND(0.5)	1.1	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	NA	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	12/20/95	50	ND(0.5)	ND(0.5)	1.8	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(1)	ND(0.5)	ND(0.5)
	3/14/96	56	ND(0.5)	ND(0.5)	2.7	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	6/19/96	52	ND(0.5)	ND(0.5)	3.0	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	9/11/96	64	ND(5)	ND(5)	3.4	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(5)	ND(5)	ND(5)
	7/8/97	35	ND(0.5)	ND(0.5)	2.3	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.2)	ND(0.5)	ND(0.5)
	3/2/99	39	ND(0.5)	ND(0.5)	2.3	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-4	1/26/95	2,500	ND(50)	ND(50)	86	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	NA	ND(50)	ND(50)	ND(50)	ND(50)	ND(100)	ND(50)	ND(50)	ND(50)
	3/17/95	2,200	ND(60)	ND(60)	77	ND(60)	ND(60)	ND(60)	ND(60)	ND(60)	ND(60)	NA	ND(60)	ND(60)	ND(60)	ND(60)	ND(100)	ND(60)	ND(60)	ND(60)
	12/21/95	3,400	ND(100)	ND(600)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(200)	ND(20)	ND(100)	ND(100)
	3/18/96	3,500	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(30)	ND(30)	ND(200)	ND(200)
	9/16/96	3,500	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(400)	ND(40)	ND(200)	ND(200)
	7/9/97	1,500	39	ND(30)	71	54	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(60)	ND(10)	ND(30)	ND(30)
P-5	1/26/95	27	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	NA	ND(3)	23	6.9	ND(3)	10	ND(3)	ND(3)	ND(3)
	3/17/95	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	NA	ND(3)	ND(3)	ND(3)	ND(3)	ND(6)	ND(3)	ND(3)	ND(3)
	12/27/95	2.5	ND(0.5)	0.62	0.87	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	0.81	0.51	190	ND(0.5)	ND(0.5)	3.2	ND(0.5)	2.2	ND(1)	ND(0.5)	ND(0.5)
	3/19/96	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	180	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	11	ND(5)	ND(5)
	6/25/96	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	140	ND(7)	ND(7)	ND(7)	ND(7)	ND(20)	23	ND(7)	ND(7)
	9/17/96	1.1	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	0.56	ND(0.5)	ND(1)	34	ND(0.5)	ND(0.5)
	9/17/96(D)	1.0	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	0.58	ND(0.5)	ND(1)	30	ND(0.5)	ND(0.5)
	7/97	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

TABLE 7 P-1

BOE-C6-0234134

Table 7. Summary of Groundwater Analytical Results - Volatile Organic Compounds (VOCs), Former ILM Facility, Torrance, California

Sample ID	Sample Date	Volatile Organic Compounds[1] (in µg/L)																		
		TCE	PCE	1,1-DCA	1,1-DCE	1,1,1-TCA	Bromodi-chloro-methane	Bromoform	Chloroform	1,2- Dichloro-propane	Trans-1,2-DCE	Cis-1,2-DCE	Dibromo-chloro-methane	Toluene	Benzene	Ethyl benzene	Total Xylenes	Vinyl Chloride	1,1,2-TCA	1,2-DCA
P-20	12/27/95	4,200	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(200)	ND(20)	ND(100)	ND(100)
	3/18/96	4,400	6.0	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	12	ND(5)	ND(5)	5.1	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(1)	ND(5)	ND(5)
	6/25/96	6,800	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(400)	ND(40)	ND(200)	ND(200)
	9/16/96	6,400	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(400)	ND(40)	ND(200)	ND(200)
	7/10/97	4,800	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(400)	ND(80)	ND(200)	ND(200)
	3/4/99	6,900	17	0.59	8.2	ND(0.5)	0.65	ND(0.5)	24	ND(0.5)	1.7	22	ND(0.5)	ND(0.5)	2.3	ND(0.5)	ND(1)	ND(0.5)	7.5	ND(0.5)
	3/4/99(D)[2]	6,800	15	0.55	7.8	ND(0.5)	ND(0.5)	ND(0.5)	23	ND(0.5)	1.7	21	ND(0.5)	ND(0.5)	2.1	ND(0.5)	ND(1)	ND(0.5)	7.3	ND(0.5)
P-21	12/26/95	4,400	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(200)	ND(20)	ND(100)	ND(100)
	3/18/96	4,200	83	53	150	27	ND(5)	ND(5)	19	ND(5)	ND(5)	780	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(1)	ND(5)	ND(5)
	6/25/96	5,600	ND(200)	ND(200)	170	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	320	ND(200)	ND(200)	ND(200)	ND(200)	ND(400)	ND(40)	ND(200)	ND(200)
	9/17/96	5,500	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(400)	ND(40)	ND(200)	ND(200)
	7/10/97	2,100	ND(100)	ND(100)	ND(100)	110	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(200)	ND(40)	ND(100)	ND(100)
P-22	12/20/95	1,200	8.2	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(1)	ND(5)	ND(5)
	3/18/96	1,200	12	ND(0.5)	2.0	ND(0.5)	ND(0.5)	ND(0.5)	1.6	ND(0.5)	ND(0.5)	5.2	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	6/20/96	1,400	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(50)	ND(100)	ND(50)	ND(50)	ND(50)
	9/12/96	1,000	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(200)	ND(20)	ND(70)	ND(70)
	7/9/97	1,200	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(60)	ND(10)	ND(30)	ND(30)
	3/3/99	1,100	30	1.5	18	ND(0.5)	ND(0.5)	ND(0.5)	8.4	ND(0.5)	0.59	18	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-23	12/20/95	160	0.53	3.6	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	1.1	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
	3/14/96	100	0.57	ND(0.5)	0.60	ND(0.5)	ND(0.5)	ND(0.5)	0.83	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	6/20/96	100	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(1)	ND(5)	ND(5)
	9/11/96	96	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(5)	ND(5)	ND(5)
	7/8/97	89	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	ND(5)	ND(1)	ND(3)	ND(3)
P-24	12/20/95	430	ND(5)	ND(5)	5.4	ND(5)	ND(5)	ND(5)	7.6	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(1)	ND(5)	ND(5)
	3/19/96	380	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)
	6/24/96	330	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(40)	ND(4)	ND(20)	ND(20)
	9/17/96	320	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(40)	ND(4)	ND(20)	ND(20)
	9/17/96(D)	350	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(60)	ND(6)	ND(30)	ND(30)
	7/9/97	120	ND(3)	ND(3)	15	72	ND(3)	ND(3)	ND(3)	ND(3)	ND(3)	10	ND(3)	ND(3)	ND(3)	ND(3)	ND(6)	ND(3)	ND(3)	ND(3)
	3/3/99	210	0.99	ND(0.5)	1.4	ND(0.5)	ND(0.5)	ND(0.5)	6.7	ND(0.5)	ND(0.5)	0.75	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-25	12/26/95	14,000	6,900	500	2,000	1,300	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(200)	ND(20)	ND(100)	ND(100)
	3/19/96	15,000	4,800	ND(700)	1,800	730	ND(700)	ND(700)	ND(700)	ND(700)	ND(700)	ND(700)	ND(700)	ND(700)	ND(700)	ND(700)	ND(2,000)	ND(200)	ND(700)	ND(700)
	6/26/96	16,000	4,700	ND(500)	1,600	760	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(1,000)	ND(100)	ND(500)	ND(500)
	9/18/96	14,000	3,300	ND(500)	1,200	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(1,000)	ND(100)	ND(500)	ND(500)
	7/10/97	13,000	2,100	ND(300)	910	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(600)	ND(100)	ND(300)	ND(300)
	7/10/97(D)	12,000	1,800	ND(500)	810	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(1,000)	ND(200)	ND(500)	ND(500)

TABLE 7 P-20

[1]Only detected analytes are reported in table; results of all analyses are reported in Appendices E and F.

[2]Duplicate sample for P-20 is identified as P-29 in Appendices E and F.

µg/L	Micrograms per liter
ND( )	Analyte not detected above the practical quantitation limit (in parentheses)
(D)	Duplicate sample
TCE	Trichloroethene
PCE	Tetrachloroethene
DCA	Dichloroethane
DCE	Dichloroethene
TCA	Trichloroethane
--	Not sampled

BOE-C6-0234135

Table 7. Summary of Groundwater Analytical Results - Volatile Organic Compounds (VOCs), Former ILM Facility, Torrance, California

Sample ID	Sample Date	Volatile Organic Compounds[1] (in µg/L)																		
		TCE	PCE	1,1-DCA	1,1-DCE	1,1,1-TCA	Bromodi-chloro-methane	Bromoform	Chloroform	1,2- Dichloro-propane	Trans-1,2-DCE	Cis-1,2-DCE	Dibromo-chloro-methane	Toluene	Benzene	Ethyl benzene	Total Xylenes	Vinyl Chloride	1,1,2-TCA	1,2-DCA
P-13	12/21/95	160	ND(5)	ND(5)	5.6	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(1)	ND(5)	ND(5)
	3/14/96	160	3.0	ND(0.5)	5.7	ND(0.5)	ND(0.5)	ND(0.5)	1.2	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	6/19/96	160	3.7	6.3	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	1.5	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.1)	ND(0.5)	ND(0.5)
	9/11/96	170	ND(5)	ND(5)	5.2	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(5)	ND(5)	ND(5)
	7/8/97	240	ND(5)	ND(5)	6.2	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(2)	ND(5)	ND(5)
P-14	12/21/95	6,300	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	40	ND(30)	ND(30)	ND(30)	ND(30)	ND(60)	ND(6)	ND(30)	ND(30)
	3/19/96	5,900	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(500)	ND(50)	ND(300)	ND(300)
	6/26/96	6,700	ND(300)	ND(300)	ND(200)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(600)	ND(60)	ND(300)	ND(200)
	9/17/96	5,400	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(600)	ND(60)	ND(300)	ND(300)
	7/10/97	3,100	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(400)	ND(80)	ND(200)	ND(200)
P-15	12/27/95	9,300	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(600)	ND(50)	ND(300)	ND(300)
	3/19/96	9,200	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(300)	ND(400)	ND(700)	ND(70)	ND(400)	ND(400)
	6/26/96	9,800	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(400)	ND(800)	ND(80)	ND(400)	ND(400)
	9/18/96	8,200	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(600)	ND(60)	ND(300)	ND(300)
	7/10/97	6,200	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(600)	ND(100)	ND(300)	ND(300)
P-16A	12/26/95	3,100	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(200)	ND(20)	ND(100)	ND(100)
	3/18/96	3,500	4.3	0.95	29	1.6	ND(0.5)	ND(0.5)	14	ND(0.5)	ND(0.5)	28	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(1)	ND(0.5)	ND(0.5)
	3/18/96(D)	3,300	ND	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(70)	ND(200)	ND(20)	ND(70)	ND(70)
	6/25/96	3,800	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(600)	ND(60)	ND(300)	ND(300)
	9/16/96	4,100	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(400)	ND(40)	ND(200)	ND(200)
	7/9/97	3,400	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(200)	ND(40)	ND(100)	ND(100)
	3/4/99	370	9.5	0.62	14	1.7	ND(0.5)	ND(0.5)	3.4	ND(0.5)	0.56	8.7	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-16B	12/19/95	48	ND(0.5)	ND(0.5)	5.3	ND(0.5)	8.0	1.5	ND(0.5)	ND(0.5)	ND(0.5)	0.94	8.4	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	0.10	ND(0.5)	ND(0.5)
	12/19/95(D)	51	ND(0.5)	ND(0.5)	5.8	ND(0.5)	7.8	1.6	6.3	ND(0.5)	ND(0.5)	1.1	8.0	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(1)	ND(0.5)	ND(0.5)
	3/18/96	49	ND(0.5)	ND(0.5)	6.6	ND(0.5)	5.7	1.1	5.8	ND(0.5)	ND(0.5)	1.0	5.8	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	0.25	ND(0.5)	ND(0.5)
	6/24/96	480	ND(1)	1.2	61	ND(1)	ND(1)	ND(1)	1.6	ND(1)	ND(1)	ND(1)	ND(1)	ND(1)	ND(1)	ND(1)	ND(2)	ND(2)	ND(1)	ND(1)
P-16C	9/12/96	440	ND(30)	ND(30)	56	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(60)	ND(6)	ND(30)	ND(30)
	7/9/97	340	ND(7)	ND(7)	40	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(7)	ND(20)	ND(3)	ND(7)	ND(7)
	3/2/99	210	0.78	0.94	43	ND(0.5)	ND(0.5)	ND(0.5)	1.7	ND(0.5)	ND(0.5)	0.65	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-17	12/21/95	13,000	700	ND(30)	340	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(30)	ND(60)	ND(6)	ND(30)	ND(30)
	3/19/96	12,000	780	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(500)	ND(1000)	ND(100)	ND(500)	ND(500)
	9/18/96	9,600	1,000	ND(300)	530	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(600)	ND(60)	ND(300)	ND(300)
	7/10/97	6,900	1,300	ND(300)	690	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(300)	ND(600)	ND(100)	ND(300)	ND(300)
	3/4/99	1,400	270	23	140	24	ND(0.5)	ND(0.5)	6.0	ND(0.5)	0.51	4.3	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
P-18	12/26/95	270	ND(6)	ND(6)	12	ND(6)	ND(6)	ND(6)	ND(6)	ND(6)	ND(6)	ND(6)	ND(6)	ND(6)	ND(6)	ND(6)	ND(10)	ND(1)	ND(6)	ND(6)
	3/19/96	180	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(30)	ND(3)	ND(20)	ND(20)
	9/12/96	200	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(40)	ND(4)	ND(20)	ND(20)
	9/12/96(D)	200	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(20)	ND(40)	ND(4)	ND(20)	ND(20)
	7/8/97	180	ND(5)	ND(5)	5.0	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(5)	ND(10)	ND(2)	ND(5)	ND(5)
P-19	12/26/95	4,400	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	ND(100)	140	ND(100)	ND(100)	ND(100)	ND(100)	ND(200)	ND(20)	ND(100)	ND(100)
	3/19/96	4,500	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	230	ND(200)	ND(200)	ND(200)	ND(200)	ND(300)	ND(30)	ND(200)	ND(200)
	6/25/96	4,900	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	280	ND(200)	ND(200)	ND(200)	ND(200)	ND(400)	ND(40)	ND(200)	ND(200)
	9/17/96	4,300	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(200)	ND(400)	ND(40)	ND(200)	ND(200)
	7/9/97	170	2.3	ND(2)	ND(2)	ND(2)	ND(2)	ND(2)	ND(2)	ND(2)	ND(2)	2.8	ND(2)	ND(2)	ND(2)	ND(2)	ND(4)	ND(1)	ND(2)	ND(2)

TABLE 7 P-13

BOE-C6-0234136

Table 8. Summary of Groundwater Analytical Results - Volatile Organic Compounds (VOCs), BRC Property, Torrance, California

Sample ID	Sample Date	Volatile Organic Compounds[1] (in µg/L)																		
		TCE	PCE	1,1-DCA	1,1-DCE	1,1,1-TCA	Bromodi-chloro-methane	Bromoform	Chloroform	1,2- Dichloro-propane	Trans-1,2- DCE	Cis-1,2-DCE	Dibromo-chloro-methane	Toluene	Benzene	Ethyl benzene	Total Xylenes	Vinyl Chloride	Carbon Tetrachloride	1,1,2-TCA
BL-1	3/4/99	6.6	ND(0.5)	1.0	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	0.57	ND(0.5)	ND(0.5)	15	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
	3/4/99[2]	6.8	ND(0.5)	0.95	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	0.60	ND(0.5)	ND(0.5)	14	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
BL-2	3/3/99	250	0.91	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	0.81	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
BL-3	3/3/99	720	73	0.72	3.8	2.1	ND(0.5)	ND(0.5)	3	ND(0.5)	ND(0.5)	0.76	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
BL-4	3/2/99	58	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	8.4	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	0.62	ND(0.5)
BL-5	3/4/99	4.1	ND(0.5)	0.54	1.3	ND(0.5)	ND(0.5)	ND(0.5)	2.8	ND(0.5)	3.2	71	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
BL-6	3/1/99	6,700	2.9	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	11	ND(0.5)	0.65	15	ND(0.5)	0.60	0.84	ND(0.5)	ND(1)	ND(0.5)	1.1	0.61
BL-7	3/2/99	32	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	0.67	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	5.2	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)
BL-8	3/2/99	23	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	1.2	ND(0.5)	ND(0.5)	ND(0.5)	ND(0.5)	5.0	ND(0.5)	ND(0.5)	ND(1)	ND(0.5)	ND(0.5)	ND(0.5)

TABLE 8

[1]Only detected analytes are reported in table; results of all analyses are reported in Appendices E and F.

[2]Duplicate sample for BL-1 is identified as B-17 in Appendices E and F.

µg/L	Micrograms per liter
ND( )	Analyte not detected above the practical quantitation limit (in parentheses)
TCE	Trichloroethene
PCE	Tetrachloroethene
DCA	Dichloroethane
DCE	Dichloroethene
TCA	Trichloroethane
--	Not sampled

Table 9. Summary of Groundwater Analytical Results - Total Petroleum Hydrocarbons (TPH), Former ILM Facility, Torrance, California

Sample ID	Sample Date	TPH[1] in µg/L			
		Crude/Waste Oil	Diesel-FFP	Kerosene/Jet Fuel	Z-Oil
P-1	1/24/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/17/95	ND(1,000)	1,200	ND(200)	ND(1,000)
	12/27/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	12/27/95(D)	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/19/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/26/96	ND(1,000)	310	ND(200)	ND(1,000)
	6/26/96(D)	ND(1,000)	330	ND(200)	ND(1,000)
	9/18/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/10/97	ND(500)	ND(200)	ND(200)	ND(1,000)
	7/10/97(D)	ND(500)	ND(200)	ND(200)	ND(1,000)
	3/4/99	ND(1,000)	ND(200)	ND(200)	ND(1,000)
P-2	1/27/95	ND(10,000)	ND(2,000)	22,000	ND(10,000)
	3/17/95	ND(22,000)	ND(4,000)	40,000	ND(20,000)
	12/27/95	ND(40,000)	ND(8,000)	60,000	ND(40,000)
	3/19/96	11,000	ND(2,000)	19,000	ND(10,000)
	3/19/96(D)	14,000	ND(2,000)	22,000	ND(10,000)
	6/20/96	7,500	ND(200)	16,000	ND(1,000)
	6/20/96(D)	6,000	ND(200)	13,000	ND(1,000)
	9/17/96	4,600	ND(1,000)	ND(1,000)	ND(2,000)
	7/8/97	ND(10,000)	ND(4,000)	20,000	ND(20,000)
	3/2/99	ND(2,000)	ND(400)	2,300	ND(2,000)
P-3	1/24/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/17/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	12/20/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/14/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/19/96	ND(1,000)	310	ND(200)	ND(1,000)
	9/11/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/8/97	ND(500)	ND(200)	ND(200)	ND(1,000)
	3/2/99	ND(1,000)	ND(200)	ND(200)	ND(1,000)
P-4	1/26/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/17/95	ND(1,000)	300	ND(200)	ND(1,000)
	12/21/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/18/96	2,600	ND(200)	ND(200)	ND(1,000)
	9/16/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/9/97	ND(500)	ND(200)	ND(200)	ND(1,000)
P-5	1/26/95	ND(10,000)	15,000	ND(2,000)	ND(10,000)
	3/17/95	ND(5,000)	10,000	ND(1,000)	ND(5,000)
	12/27/95	ND(8,000)	11,000	ND(2,000)	ND(8,000)
	3/19/96	ND(5,000)	11,000	ND(1,000)	ND(5,000)
	6/25/96	ND(5,000)	8,200	ND(1,000)	ND(5,000)
	9/17/96	ND(4,000)	5,200	ND(800)	ND(4,000)
	9/17/96(D)	ND(2,000)	5,000	ND(400)	ND(2,000)
	7/97	--	--	--	--

BOE-C6-0234138

Table 9. Summary of Groundwater Analytical Results - Total Petroleum Hydrocarbons (TPH), Former ILM Facility, Torrance, California

Sample ID	Sample Date	TPH[1] in µg/L			
		Crude/Waste Oil	Diesel-FFP	Kerosene/Jet Fuel	Z-Oil
P-6	3/16/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	12/20/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/18/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/20/96	ND(1,000)	230	ND(200)	ND(1,000)
	9/12/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/9/97	--	--	--	--
P-6B	3/3/99	1,100	ND(200)	ND(200)	ND(1,000)
P-7	3/17/95	ND(1,000)	220	ND(200)	ND(1,000)
	3/17/95(D)	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	12/21/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/18/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/24/96	ND(1,000)	200	ND(200)	ND(1,000)
	9/16/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/9/97	--	--	--	--
	3/4/99	ND(1,000)	270	ND(200)	ND(1,000)
P-8	3/16/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
P-9	3/16/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	12/20/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/18/96	ND(1,000)	570	ND(200)	ND(1,000)
	6/26/96	ND(1,000)	330	ND(200)	ND(1,000)
	9/12/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/9/97	--	--	--	--
P-9B	3/3/99	ND(1,000)	ND(200)	ND(200)	ND(1,000)
P-10	3/16/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	12/19/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/14/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/18/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	9/11/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/8/97	--	--	--	--
	3/1/99	1,500	ND(200)	ND(200)	ND(1,000)
P-11	12/27/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/14/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/19/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	9/11/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/8/97	ND(500)	ND(200)	ND(200)	ND(1,000)
P-12	12/21/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/19/96	ND(1,000)	280	ND(200)	ND(1,000)
	6/26/96	ND(1,000)	430	ND(200)	ND(1,000)
	6/26/96(D)	ND(1,000)	370	ND(200)	ND(1,000)
	9/18/96	ND(2,000)	ND(400)	ND(400)	ND(2,000)
	7/10/97	ND(500)	ND(200)	ND(200)	ND(1,000)
	3/3/99	ND(1,000)	ND(200)	ND(200)	ND(1,000)

BOE-C6-0234139

Table 9. Summary of Groundwater Analytical Results - Total Petroleum Hydrocarbons (TPH), Former ILM Facility, Torrance, California

Sample ID	Sample Date	TPH[1] in µg/L			
		Crude/Waste Oil	Diesel-FFP	Kerosene/Jet Fuel	Z-Oil
P-13	12/21/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/14/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/19/96	ND(1,000)	270	ND(200)	ND(1,000)
	9/11/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/8/97	ND(500)	ND(200)	ND(200)	ND(1,000)
P-14	12/21/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/19/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/26/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	9/17/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/10/97	ND(500)	220	ND(200)	ND(1,000)
P-15	12/27/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/19/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/26/96	ND(1,000)	250	ND(200)	ND(1,000)
	9/18/96	1,900	ND(200)	ND(200)	ND(1,000)
	7/10/97	ND(500)	ND(200)	ND(200)	ND(1,000)
P-16A	12/26/95	ND(1,000)	350	ND(200)	ND(1,000)
	3/18/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/18/96(D)	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/25/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	9/16/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/9/97	--	--	--	--
	3/4/99	ND(1,000)	210	ND(200)	ND(1,000)
P-16B	12/19/95	ND(1,000)	ND(200)	ND(200)	2,300
	3/18/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/24/96	ND(1,000)	430	ND(200)	ND(1,000)
P-16C	9/12/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/9/97	--	--	--	--
	3/2/99	ND(1,000)	ND(200)	ND(200)	ND(1,000)
P-17	12/21/95	ND(1,000)	750	ND(200)	ND(1,000)
	3/19/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	9/18/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/10/97	--	--	--	--
	3/4/99	ND(1,000)	ND(200)	ND(200)	ND(1,000)
P-18	12/26/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/19/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	9/12/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	9/18/96(D)	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/8/97	--	--	--	--
P-19	12/26/95	ND(1,000)	330	ND(200)	ND(1,000)
	3/19/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/25/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	9/17/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/9/97	--	--	--	--

BOE-C6-0234140

Table 9. Summary of Groundwater Analytical Results - Total Petroleum Hydrocarbons (TPH), Former ILM Facility, Torrance, California

Sample ID	Sample Date	TPH[1] in µg/L			
		Crude/Waste Oil	Diesel-FFP	Kerosene/Jet Fuel	Z-Oil
P-20	12/27/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/18/96	ND(1,000)	1,600	ND(200)	ND(1,000)
	6/25/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	9/16/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/10/97	--	--	--	--
	3/4/99	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/4/99(D)[2]	ND(1,000)	ND(200)	ND(200)	ND(1,000)
P-21	12/26/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/18/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/25/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	9/17/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/10/97	--	--	--	--
P-22	12/20/95	ND(1,000)	ND(200)	ND(200)	1,000
	3/18/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/20/96	ND(1,000)	390	ND(200)	ND(1,000)
	9/12/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/9/97	--	--	--	--
	3/3/99	ND(1,000)	ND(200)	ND(200)	ND(1,000)
P-23	12/20/95	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	3/14/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/20/96	ND(1,000)	230	ND(200)	ND(1,000)
	9/11/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/8/97	ND(500)	ND(200)	ND(200)	ND(1,000)
P-24	12/20/95	ND(2,000)	6,200	ND(400)	ND(2,000)
	3/19/95	ND(5,000)	10,000	ND(1,000)	ND(5,000)
	6/24/96	ND(2,000)	4,100	ND(400)	ND(1,000)
	9/17/96	ND(2,000)	ND(200)	ND(400)	ND(2,000)
	9/17/96(D)	ND(2,000)	ND(200)	ND(400)	ND(2,000)
	7/9/97	ND(500)	ND(200)	ND(200)	ND(1,000)
	3/3/99	ND(1,000)	450	ND(200)	ND(1,000)
P-25	12/26/95	ND(1,000)	1,200	ND(200)	ND(1,000)
	3/19/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	6/26/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	9/18/96	ND(1,000)	ND(200)	ND(200)	ND(1,000)
	7/10/97	--	--	--	--
	7/10/97(D)	--	--	--	--

[1]Only detected analytes are reported in table; results of all analyses are reported in Appendices E and F.

[2]Duplicate sample for P-20 is identified as P-29 in Appendices E and F.

FFP	Fuel fingerprint
µg/L	Micrograms per liter
ND( )	Analyte not detected above the practical quantitation limit (in parentheses)
(D)	Duplicate sample
	Not sampled

BOE-C6-0234141

Table 10. Summary of Groundwater Analytical Results - Total Petroleum Hydrocarbons (TPH), BRC Property, Torrance, California

Sample ID	Sample Date	TPH[1] in µg/L			
		Crude/ Waste Oil	Diesel-FFP	Kerosene	Z-Oil
BL-1	3/4/99	ND(1,000)	560	ND(200)	ND(1,000)
	3/4/99[2]	ND(1,000)	450	ND(200)	ND(1,000)
BL-2	3/3/99	--	--	--	--
BL-3	3/3/99	--	--	--	--
BL-4	3/2/99	--	--	--	--
BL-5	3/4/99	ND(1,000)	610	ND(200)	ND(1,000)
BL-6	3/1/99	--	--	--	--
BL-7	3/2/99	--	--	--	--
BL-8	3/2/99	--	--	--	--

[1]Only detected analytes are reported in table; results of all analyses are reported in Appendices E and F.

[2]Duplicate sample for BL-1 is identified as B-17 in Appendices E and F.

FFP	Fuel fingerprint
µg/L	Micrograms per liter
ND( )	Analyte not detected above the practical quantitation limit (in parentheses)
--	Not sampled

BOE-C6-0234142

Table 11. Summary of Groundwater Analytical Results - Dissolved Metals, Former ILM Facility, Torrance, California

Sample ID	Sample Date	Dissolved Metals[1] (in µg/L)																		
		Arsenic	Selenium	Aluminum	Barium	Cadmium	Chromium	Cobalt	Iron	Lead	Molybdenum	Manganese	Nickel	Titanium	Zinc	Hexavalent Chromium	Magnesium	Copper	Mercury	Vanadium
P-1	1/24/95	4.8	ND(2)	ND(50)	ND(100)	ND(5)	1,100	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	22	1,100	46,000	ND(10)	--	ND(10)
	3/17/95	2	2.2	604	ND(100)	ND(5)	785	ND(10)	388	ND(5)	ND(10)	21	ND(50)	ND(10)	39	780	44,000	ND(10)	--	ND(10)
	12/27/95	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	1,450	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	ND(10)	1,280	51,000	ND(10)	--	ND(10)
	12/27/95(D)	ND(2)	ND(2)	ND(50)	ND(100)	10	1,350	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	ND(10)	1,120	51,000	ND(10)	--	ND(10)
	3/19/96	ND(2)	2.0	ND(50)	ND(100)	ND(10)	1,290	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	920	54,000	ND(10)	--	ND(10)
	6/26/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	1,290	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	1,260	52,000	ND(10)	--	ND(10)
	6/26/96(D)	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	1,260	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	1,100	51,000	ND(10)	--	ND(10)
	9/18/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	1,040	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	1,040	48,000	ND(10)	--	ND(10)
	7/10/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	1,270	--	--	--	--
	7/10/97(D)	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	1,270	--	--	--	--
	3/4/99	ND(2)	4.1	ND(50)	112	ND(5)	1,370	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	ND(10)	1,280	--	ND(10)	ND(0.2)	ND(10)
P-2	1/27/95	12	2	ND(50)	110	ND(5)	ND(10)	ND(10)	ND(50)	ND(5)	ND(10)	280	ND(50)	ND(10)	77	ND(10)	110,000	ND(10)	--	ND(10)
	3/17/95	9.2	2.2	53	199	ND(5)	ND(10)	ND(10)	1,310	6.3	ND(10)	2,150	ND(50)	ND(10)	58	ND(10)	114,000	ND(10)	--	ND(10)
	12/27/95	3.6	ND(2)	1,830	129	ND(10)	ND(5)	ND(10)	3,360	ND(5)	ND(10)	3,620	ND(50)	ND(10)	34	ND(10)	85,000	ND(10)	--	ND(10)
	3/19/96	3.8	ND(2)	13,900	ND(100)	ND(10)	12	ND(50)	41,600	ND(5)	ND(50)	2,650	69	ND(10)	346	ND(10)	21,000	ND(10)	--	ND(10)
	3/19/96(D)	6.2	ND(2)	12,800	138	ND(10)	8.3	ND(50)	51,600	ND(5)	ND(50)	3,690	98	ND(10)	820	ND(10)	27,000	ND(10)	--	ND(10)
	6/20/96	3.6	ND(2)	296	199	ND(10)	ND(5)	ND(50)	8,150	ND(5)	ND(50)	3,360	ND(50)	ND(10)	ND(10)	ND(10)	130,000	ND(10)	--	ND(10)
	6/20/96(D)	3.6	ND(2)	503	198	ND(10)	ND(5)	ND(50)	7,840	ND(5)	ND(50)	3,210	ND(50)	ND(10)	ND(10)	ND(10)	131,000	ND(10)	--	ND(10)
	9/17/96	ND(2)	ND(2)	97	165	ND(10)	ND(5)	ND(50)	1,810	ND(5)	ND(50)	1,840	ND(50)	ND(10)	ND(10)	ND(10)	133,000	ND(10)	--	ND(10)
	7/8/97	--	--	ND(50)	--	ND(10)	--	--	--	ND(5)	--	--	--	--	--	ND(10)	--	--	--	--
	3/2/99	2.2	ND(2)	ND(50)	161	ND(5)	ND(10)	ND(50)	1,550	ND(5)	ND(50)	--	ND(50)	ND(10)	129	2.5J	--	ND(10)	ND(0.2)	ND(10)
P-3	1/24/95	3.6	ND(2)	ND(50)	110	ND(5)	ND(10)	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	23	10	66,000	ND(10)	--	ND(10)
	3/17/95	2.2	2	175	113	ND(5)	ND(10)	ND(10)	187	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	142	ND(10)	60,000	ND(10)	--	ND(10)
	12/20/95	2.4	ND(2)	ND(50)	133	ND(10)	8.8	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	ND(10)	13	72,000	ND(10)	--	ND(10)
	3/14/96	2.2	ND(2)	ND(50)	136	ND(10)	10	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	10	76,000	ND(10)	--	ND(10)
	6/19/96	3.0	ND(2)	ND(50)	126	ND(10)	10	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	ND(10)	76,000	ND(10)	--	ND(10)
	9/11/96	3.7	ND(2)	ND(50)	133	ND(10)	14	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	12	77,000	ND(10)	--	ND(10)
	7/8/97	--	--	ND(50)	--	ND(10)	--	--	--	ND(5)	--	--	--	--	--	11	--	--	ND(0.2)	--
	3/2/99	3.0	ND(2)	ND(50)	111	ND(5)	12	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	22	31	--	25	ND(0.2)	ND(10)
P-4	1/26/95	2	ND(2)	ND(50)	110	ND(5)	99	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	13	15	NA	ND(10)	--	ND(10)
	3/17/95	ND(2)	2.8	ND(50)	130	ND(5)	1,570	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	334	1,800	71,700	ND(10)	--	ND(10)
	12/21/95	ND(2)	ND(2)	ND(50)	135	13	427	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	20	480	71,000	ND(10)	--	ND(10)
	3/18/96	2.2	ND(2)	ND(50)	127	ND(10)	385	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	280	68,000	ND(10)	--	ND(10)
	9/16/96	ND(2)	ND(2)	ND(50)	147	ND(10)	280	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	280	84,000	ND(10)	--	ND(10)
	7/9/97	--	--	1,450	--	--	--	--	--	ND(5)	--	--	--	--	--	140	--	--	ND(0.2)	--
P-5	1/26/95	12	ND(2)	ND(100)	130	ND(5)	ND(10)	ND(10)	6,240	ND(5)	ND(10)	1,370	ND(50)	ND(10)	ND(10)	ND(10)	NA	ND(10)	--	ND(10)
	3/17/95	5.6	ND(2)	314	ND(100)	ND(5)	ND(10)	ND(10)	4,580	7.4	ND(10)	623	ND(50)	ND(10)	27	ND(10)	38,400	ND(10)	--	ND(10)
	12/27/95	ND(2)	ND(2)	ND(50)	179	ND(10)	ND(5)	ND(10)	10,000	ND(5)	ND(10)	1,310	ND(50)	ND(10)	ND(10)	ND(10)	97,000	ND(10)	--	ND(10)
	3/19/96	27	ND(2)	ND(50)	192	ND(10)	ND(5)	ND(50)	11,700	ND(5)	ND(50)	1,350	ND(50)	ND(10)	ND(10)	ND(10)	91,000	ND(10)	--	ND(10)
	6/19/96	33	ND(2)	ND(50)	163	ND(10)	ND(5)	ND(50)	14,300	ND(5)	ND(50)	1,500	ND(50)	ND(10)	12	ND(10)	87,000	ND(10)	--	ND(10)
	9/17/96	29	ND(2)	ND(50)	196	ND(10)	ND(5)	ND(50)	13,400	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	ND(10)	101,000	ND(10)	--	ND(10)
	9/17/96(D)	31	ND(2)	ND(50)	181	ND(10)	ND(5)	ND(50)	12,700	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	ND(10)	106,000	ND(10)	--	ND(10)
	7/97	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

TABLE 11 P-1

BOE-C6-0234143

Table 11. Summary of Groundwater Analytical Results - Dissolved Metals, Former ILM Facility, Torrance, California

Sample ID	Sample Date	Dissolved Metals[1] (in µg/L)																		
		Arsenic	Selenium	Aluminum	Barium	Cadmium	Chromium	Cobalt	Iron	Lead	Molybdenum	Manganese	Nickel	Titanium	Zinc	Hexavalent Chromium	Magnesium	Copper	Mercury	Vanadium
P-6	3/16/95	ND(2)	2.4	ND(50)	ND(100)	ND(5)	ND(10)	ND(10)	ND(50)	ND(5)	ND(10)	57	ND(50)	ND(10)	ND(10)	10	66,400	ND(10)	--	ND(10)
	12/20/95	ND(2)	2.2	ND(50)	176	ND(10)	14	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	ND(10)	14	90,000	ND(10)	--	ND(10)
	3/18/96	ND(2)	2.0	ND(50)	193	ND(10)	11	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	ND(10)	91,000	ND(10)	--	ND(10)
	6/20/96	ND(2)	2.0	ND(50)	171	ND(10)	13	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	15	10	85,000	ND(10)	--	ND(10)
	9/12/96	ND(2)	ND(2)	ND(50)	144	ND(10)	14	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	15	69,000	ND(10)	--	ND(10)
	7/9/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	15	--	--	--	--
P-6B	3/3/99	2.3	ND(2)	ND(50)	268	ND(5)	ND(10)	ND(50)	53	ND(5)	ND(50)	--	ND(50)	ND(10)	12	4.9	--	ND(10)	ND(0.2)	ND(10)
P-7	3/17/95	2.2	ND(2)	733	ND(100)	ND(5)	ND(10)	ND(10)	806	ND(5)	ND(10)	104	ND(50)	29	20	ND(10)	41,000	ND(10)	--	ND(10)
	3/17/95(D)	ND(2)	ND(2)	154	ND(100)	ND(5)	ND(10)	ND(10)	104	ND(5)	ND(10)	126	ND(50)	ND(10)	22	ND(10)	40,000	22	--	ND(10)
	12/21/95	2.0	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(10)	ND(50)	ND(5)	ND(10)	77	ND(50)	ND(10)	14	ND(10)	34,000	ND(10)	--	ND(10)
	3/18/96	2.8	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	70	ND(50)	ND(10)	ND(10)	ND(10)	36,000	ND(10)	--	ND(10)
	6/24/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	47	ND(50)	ND(10)	ND(10)	ND(10)	36,000	ND(10)	--	ND(10)
	9/16/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	ND(10)	37,000	ND(10)	--	ND(10)
	7/9/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	ND(10)	--	--	--	--
	3/4/99	5.9	ND(2)	ND(50)	ND(100)	ND(5)	ND(10)	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	11	2.8	--	ND(10)	ND(0.2)	10
P-8	3/16/95	ND(2)	4.1	ND(50)	ND(100)	ND(5)	56	ND(10)	ND(50)	ND(5)	ND(10)	15	ND(50)	ND(10)	ND(10)	60	34,500	ND(10)	--	ND(10)
P-9	3/16/95	ND(2)	ND(2)	ND(50)	ND(100)	ND(5)	ND(10)	ND(10)	ND(50)	ND(5)	ND(10)	16	ND(50)	ND(10)	30	20	86,000	ND(10)	--	ND(10)
	12/20/95	2.2	ND(2)	ND(50)	ND(100)	ND(10)	12	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	ND(10)	17	67,000	ND(10)	--	ND(10)
	3/18/96	3.6	ND(2)	ND(50)	ND(100)	ND(10)	15	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	ND(10)	70,000	ND(10)	--	ND(10)
	6/26/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	16	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	16	64,000	ND(10)	--	ND(10)
	9/12/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	13	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	14	68,000	ND(10)	--	ND(10)
	7/9/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	16.0	--	--	--	--
P-9B	3/3/99	ND(2)	ND(2)	ND(50)	ND(100)	ND(5)	12	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	15	22	--	ND(10)	ND(0.2)	ND(10)
P-10	3/16/95	5.8	2.6	ND(50)	ND(100)	ND(5)	28	ND(10)	ND(50)	ND(5)	ND(10)	30	ND(50)	ND(10)	24	30	58,000	ND(10)	--	ND(10)
	12/19/95	2.6	2.6	ND(50)	ND(100)	ND(10)	28	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	ND(10)	30	62,000	ND(10)	--	ND(10)
	3/14/96	ND(2)	2.4	ND(50)	ND(100)	ND(10)	30	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	31	66,000	ND(10)	--	ND(10)
	6/18/96	2.6	2.0	ND(50)	ND(100)	ND(10)	29	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	25	66,000	ND(10)	--	ND(10)
	9/11/96	3.3	2.1	ND(50)	ND(100)	ND(10)	28	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	30	66,000	10	--	ND(10)
	7/8/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	35	--	--	--	--
	3/1/99	ND(2)	2.6	ND(50)	ND(100)	ND(5)	30	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	24	31J	--	29	ND(0.2)	ND(10)
P-11	12/27/95	ND(2)	ND(2)	ND(50)	101	ND(10)	13	ND(10)	ND(50)	ND(5)	ND(10)	19	ND(50)	ND(10)	ND(10)	18	139,000	ND(10)	--	ND(10)
	3/14/96	ND(2)	ND(2)	ND(50)	133	ND(10)	15	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	17	138,000	ND(10)	--	ND(10)
	6/19/96	ND(2)	2.0	ND(50)	100	ND(10)	23	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	20	118,000	ND(10)	--	ND(10)
	9/11/96	ND(2)	ND(2)	ND(50)	134	ND(10)	19	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	21	139,000	20	--	ND(10)
	7/8/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	26	--	--	ND(0.2)	--
P-12	12/21/95	6.2	2.0	ND(50)	112	ND(10)	18	21	ND(50)	ND(5)	ND(10)	81	ND(50)	ND(10)	12	21	63,000	ND(10)	--	ND(10)
	3/19/96	2.6	2.4	ND(50)	170	ND(10)	22	ND(50)	177	ND(5)	ND(50)	44	ND(50)	ND(10)	ND(10)	11	66,000	ND(10)	--	ND(10)
	6/26/96	2.7	2.4	ND(50)	160	ND(10)	25	ND(50)	260	9.5	ND(50)	38	ND(50)	ND(10)	ND(10)	23	60,000	ND(10)	--	ND(10)
	6/26/96(D)	2.8	2.5	ND(50)	162	ND(10)	25	ND(50)	236	ND(5)	ND(50)	35	ND(50)	ND(10)	ND(10)	25	60,000	ND(10)	--	ND(10)
	9/18/96	2.3	ND(2)	ND(50)	160	ND(10)	26	ND(10)	153	ND(5)	ND(50)	23	ND(50)	ND(10)	ND(10)	24	59,000	ND(10)	--	ND(10)
	7/10/97	--	--	ND(50)	--	20	--	--	--	ND(5)	--	--	--	--	--	17	--	--	0.20	--
	3/3/99	2.1	ND(2)	ND(50)	190	ND(5)	26	58	1,190	ND(5)	ND(50)	--	ND(50)	ND(10)	ND(50)	36	--	ND(10)	1.90	ND(10)

TABLE 11 P-6

BOE-C6-0234144

Table 11. Summary of Groundwater Analytical Results - Dissolved Metals, Former ILM Facility, Torrance, California

Sample ID	Sample Date	Dissolved Metals[1] (in µg/L)																		
		Arsenic	Selenium	Aluminum	Barium	Cadmium	Chromium	Cobalt	Iron	Lead	Molybdenum	Manganese	Nickel	Titanium	Zinc	Hexavalent Chromium	Magnesium	Copper	Mercury	Vanadium
P-13	12/21/95	2.6	7.8	ND(50)	ND(100)	ND(10)	15	ND(10)	ND(50)	ND(5)	11	ND(10)	ND(50)	19	ND(10)	ND(10)	22,000	ND(10)	--	ND(10)
	3/14/96	ND(2)	8.2	ND(50)	ND(100)	ND(10)	17	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	15	22,000	ND(10)	--	ND(10)
	6/19/96	2.0	8.6	ND(50)	ND(100)	ND(10)	14	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	10	24,000	ND(10)	--	ND(10)
	9/11/96	2.5	6.6	ND(50)	ND(100)	ND(10)	13	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	12	24,000	ND(10)	--	ND(10)
	7/8/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	17	--	--	ND(0.2)	--
P-14	12/21/95	2.4	2.0	ND(50)	ND(100)	ND(10)	2,820	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	ND(10)	2,600	34,000	ND(10)	--	ND(10)
	3/19/96	2.8	3.2	ND(50)	ND(100)	ND(10)	2,170	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	1,240	34,000	ND(10)	--	ND(10)
	6/26/96	ND(2)	3.0	ND(50)	ND(100)	ND(10)	1,860	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	12	1,360	32,000	20	--	ND(10)
	9/17/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	1,590	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(10)	ND(10)	ND(10)	1,640	32,000	ND(10)	--	ND(10)
	7/10/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	555	--	--	ND(0.2)	--
P-15	12/27/95	2.8	ND(2)	ND(50)	ND(100)	ND(10)	388	ND(10)	ND(50)	ND(5)	ND(10)	ND(10)	ND(50)	ND(10)	ND(10)	370	34,000	ND(10)	--	ND(10)
	3/19/96	3.0	ND(2)	ND(50)	ND(100)	ND(10)	218	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	120	30,000	ND(10)	--	ND(10)
	6/26/96	2.7	ND(2)	ND(50)	ND(100)	ND(10)	86	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	78	27,000	ND(10)	--	ND(10)
	9/18/96	2.1	ND(2)	ND(50)	ND(100)	ND(10)	73	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	72	25,000	ND(10)	--	ND(10)
	7/10/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	277	--	--	--	--
P-16A	12/26/95	4.8	2.6	ND(50)	ND(100)	ND(10)	26	ND(10)	ND(50)	ND(5)	ND(10)	28	ND(50)	ND(10)	11	23	59,000	ND(10)	--	ND(10)
	3/18/96	5.4	2.4	ND(50)	ND(100)	ND(10)	23	ND(50)	ND(50)	ND(5)	ND(50)	12	ND(50)	ND(10)	10	14	68,000	ND(10)	--	ND(10)
	3/18/96(D)	7.2	2.0	ND(50)	ND(100)	ND(10)	24	ND(50)	ND(50)	ND(5)	ND(50)	10	ND(50)	ND(10)	12	22	69,000	ND(10)	--	ND(10)
	6/25/96	5.4	3.6	ND(50)	ND(100)	ND(10)	60	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	15	54	52,000	ND(10)	--	ND(10)
	9/16/96	4.5	ND(2)	ND(50)	ND(100)	ND(10)	23	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	24	82,000	ND(10)	--	ND(10)
	7/9/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	21	--	--	--	--
	3/4/99	7.5	2.0	ND(50)	ND(100)	ND(5)	ND(10)	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	ND(10)	14	--	ND(10)	ND(0.2)	--
P-16B	12/19/95	ND(2)	2.8	ND(50)	158	ND(10)	ND(5)	ND(10)	ND(50)	ND(5)	ND(10)	94	ND(50)	ND(10)	498	ND(10)	35,000	ND(10)	--	ND(10)
	12/19/96(D)	ND(2)	2.8	ND(50)	157	ND(10)	ND(5)	ND(10)	ND(50)	ND(5)	ND(10)	94	ND(50)	ND(10)	497	ND(10)	36,000	14	--	ND(10)
	3/18/96	ND(2)	2.4	ND(50)	168	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	72	ND(50)	ND(10)	550	ND(10)	38,000	ND(10)	--	ND(10)
	6/24/96	ND(2)	5.8	ND(50)	492	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	22	ND(50)	ND(10)	18	ND(10)	98,000	ND(10)	--	ND(10)
P-16C	9/12/96	3.0	5.3	ND(50)	388	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	335	ND(50)	ND(10)	1,500	ND(10)	96,000	ND(10)	--	ND(10)
	7/9/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	ND(10)	--	--	--	--
	3/2/99	ND(2)	5.1	ND(50)	424	ND(5)	ND(10)	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	37	ND(5)UJ	--	ND(10)	ND(0.2)	ND(10)
P-17	12/21/95	2.0	ND(2)	ND(50)	ND(100)	ND(10)	1,030	ND(10)	ND(50)	ND(5)	ND(10)	53	ND(50)	ND(10)	13	902	62,000	ND(10)	--	ND(10)
	3/19/96	ND(2)	2.6	ND(50)	ND(100)	ND(10)	967	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	640	62,000	ND(10)	--	ND(10)
	9/18/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	1,060	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	1,140	55,000	ND(10)	--	ND(10)
	7/10/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	1,330	--	--	--	--
	3/4/99	ND(2)	ND(2)	ND(50)	ND(100)	ND(5)	30	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	ND(10)	40	--	ND(10)	ND(0.2)	ND(10)
P-18	12/26/95	3.4	4.2	926	ND(100)	ND(10)	19	ND(10)	268	ND(5)	ND(10)	77	ND(50)	ND(10)	32	10	63,000	ND(10)	--	ND(10)
	3/19/96	3.0	2.2	472	ND(100)	ND(10)	14	ND(50)	108	ND(5)	ND(50)	30	ND(50)	ND(10)	19	11	52,000	ND(10)	--	ND(10)
	9/12/96	2.9	3.3	ND(50)	ND(100)	ND(10)	10	ND(50)	ND(50)	ND(5)	ND(50)	40	ND(50)	ND(10)	ND(10)	ND(10)	54,000	ND(10)	--	ND(10)
	9/12/96(D)	3.3	3.3	ND(50)	ND(100)	18	10	ND(50)	ND(50)	ND(5)	ND(50)	38	ND(50)	ND(10)	ND(10)	ND(10)	54,000	ND(10)	--	ND(10)
	7/8/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	19	--	--	--	--
P-19	12/26/95	2.6	4.0	ND(50)	ND(100)	ND(10)	8.8	ND(10)	ND(50)	6.3	ND(10)	42	ND(50)	ND(10)	ND(10)	10	56,000	ND(10)	--	ND(10)
	3/19/96	ND(2)	3.8	ND(50)	ND(100)	ND(10)	13	ND(50)	ND(50)	ND(5)	ND(50)	13	ND(50)	ND(10)	ND(10)	ND(10)	57,000	ND(10)	--	ND(10)
	6/25/96	ND(2)	4.2	ND(50)	ND(100)	ND(10)	18	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	17	56,000	ND(10)	--	ND(10)
	9/17/96	ND(2)	2.0	ND(50)	ND(100)	ND(10)	16	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	16	55,000	ND(10)	--	ND(10)
	7/9/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	31	--	--	--	--

TABLE 11 P-13

BOE-C6-0234145

Table 11. Summary of Groundwater Analytical Results - Dissolved Metals, Former ILM Facility, Torrance, California

Sample ID	Sample Date	Dissolved Metals[1] (in µg/L)																		
		Arsenic	Selenium	Aluminum	Barium	Cadmium	Chromium	Cobalt	Iron	Lead	Molybdenum	Manganese	Nickel	Titanium	Zinc	Hexavalent Chromium	Magnesium	Copper	Mercury	Vanadium
P-20	12/27/95	2.6	ND(2)	ND(50)	ND(100)	ND(10)	26	ND(10)	ND(50)	ND(5)	ND(10)	14	ND(50)	ND(10)	ND(10)	26	76,000	ND(10)	--	ND(10)
	3/18/96	2.2	ND(2)	ND(50)	ND(100)	ND(10)	23	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	13	73,000	ND(10)	--	ND(10)
	6/25/96	2.4	ND(2)	ND(50)	ND(100)	ND(10)	27	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	18	23	50,000	ND(50)	--	ND(10)
	9/16/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	18	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	17	67,000	ND(10)	--	ND(10)
	7/10/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	19	--	--	--	--
	3/4/99	ND(2)	ND(2)	ND(50)	ND(100)	ND(5)	27	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	ND(10)	35	--	ND(10)	ND(0.2)	ND(10)
	3/4/99(D)[2]	ND(2)	ND(2)	ND(50)	ND(100)	ND(5)	28	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	ND(10)	33	--	ND(10)	ND(0.2)	ND(10)
P-21	12/26/95	2.4	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(10)	ND(50)	ND(5)	ND(50)	41	ND(50)	ND(10)	19	ND(10)	52,000	ND(10)	--	ND(10)
	3/18/96	4.6	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	100	ND(50)	ND(10)	ND(10)	ND(10)	52,000	ND(10)	--	ND(10)
	6/25/96	2.4	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	22	ND(50)	ND(10)	11	ND(10)	46,000	ND(10)	--	ND(10)
	9/17/96	2.3	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	25	ND(50)	ND(10)	ND(10)	ND(10)	49,000	ND(10)	--	ND(10)
	7/10/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	ND(10)	--	--	--	--
P-22	12/20/95	14	6.0	ND(50)	ND(100)	ND(10)	8.5	ND(10)	ND(50)	ND(5)	ND(10)	22	ND(50)	ND(10)	43	11	24,000	ND(10)	--	ND(10)
	3/18/96	7.6	6.0	ND(50)	ND(100)	ND(10)	11	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	11	25,000	ND(10)	--	ND(10)
	6/20/96	5.2	6.4	ND(50)	ND(100)	ND(10)	14	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	10	24,000	ND(10)	--	ND(10)
	9/12/96	4.5	5.8	ND(50)	ND(100)	ND(10)	12	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	12	27,000	ND(10)	--	ND(10)
	7/9/97	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	12	--	--	--	--
	3/3/99	3.8	2.3	ND(50)	178	ND(5)	10	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	ND(10)	18	--	ND(10)	ND(0.2)	ND(10)
P-23	12/20/95	2.8	ND(2)	ND(50)	ND(100)	ND(10)	11	ND(10)	ND(50)	ND(5)	ND(10)	13	ND(50)	ND(10)	24	16	93,000	ND(10)	--	ND(10)
	3/14/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	14	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	12	13	96,000	ND(10)	--	ND(10)
	6/20/96	2.6	ND(2)	ND(50)	ND(100)	ND(10)	14	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	10	97,000	ND(10)	--	ND(10)
	9/11/96	3.0	ND(2)	ND(50)	ND(100)	ND(10)	14	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	14	89,000	ND(10)	--	ND(10)
	7/8/97	--	--	ND(50)	--	ND(10)	--	--	--	ND(5)	--	--	--	--	--	14	--	--	ND(0.2)	--
P-24	12/20/95	2.0	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(10)	ND(50)	ND(5)	ND(10)	875	ND(50)	ND(10)	11	ND(10)	77,000	ND(10)	--	ND(10)
	3/19/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	1,080	ND(50)	ND(10)	ND(10)	ND(10)	85,000	ND(10)	--	ND(10)
	6/24/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	509	ND(50)	ND(10)	ND(10)	ND(10)	82,000	ND(10)	--	ND(10)
	9/17/96	2.3	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	922	ND(50)	ND(10)	ND(10)	ND(10)	81,000	ND(10)	--	ND(10)
	9/17/96(D)	2.3	ND(2)	ND(50)	ND(100)	ND(10)	ND(5)	ND(50)	ND(50)	ND(5)	ND(50)	844	ND(50)	ND(10)	ND(10)	ND(10)	89,000	ND(10)	--	ND(10)
	7/9/97	--	--	3,240	--	ND(10)	--	--	--	ND(5)	--	--	--	--	--	50	--	--	ND(0.2)	--
	3/3/99	3.6	ND(2)	ND(50)	120	ND(5)	ND(10)	ND(50)	ND(50)	ND(5)	ND(50)	--	ND(50)	ND(10)	16	5.6	--	ND(10)	ND(0.2)	ND(10)
P-25	12/26/95	2.4	ND(2)	ND(50)	ND(100)	ND(10)	518	ND(10)	ND(50)	ND(5)	ND(10)	28	ND(50)	ND(10)	ND(10)	480	58,000	ND(10)	--	ND(10)
	3/19/96	2.4	ND(2)	ND(50)	ND(100)	ND(10)	329	ND(50)	ND(50)	ND(5)	ND(50)	12	ND(50)	ND(10)	ND(10)	22	58,000	ND(10)	--	ND(10)
	6/26/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	464	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	480	58,000	ND(10)	--	ND(10)
	9/18/96	ND(2)	ND(2)	ND(50)	ND(100)	ND(10)	478	ND(50)	ND(50)	ND(5)	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	480	55,000	ND(10)	--	ND(10)
	7/10/97	--	--	218	--	--	--	--	--	ND(5)	--	--	--	--	--	281	--	--	--	--
	7/10/97(D)	--	--	ND(50)	--	--	--	--	--	ND(5)	--	--	--	--	--	323	--	--	--	--

[1]Only detected analytes are reported in table; results of all analyses are reported in Appendices E and F.
[2]Duplicate sample for P-20 is identified as P-29 in Appendices E and F.

TABLE 11 P-20

µg/L Micrograms per liter
ND( ) Analyte not detected above the practical quantitation limit (in parentheses)
(D) Duplicate sample
-- Not sampled

Data Validation Qualifers (for more information, see Appendix E)
J Not detected
Estimated, detected
UJ Estimated, not detected

BOE-C6-0234146

Table 12. Summary of Groundwater Analytical Results - Dissolved Metals, BRC Property, Torrance, California

Sample ID	Sample Date	Dissolved Metals[1] (in µg/L)															
		Arsenic	Selenium	Aluminum	Barium	Cadmium	Chromium	Cobalt	Iron	Lead	Molybdenum	Nickel	Titanium	Zinc	Hexavalent Chromium	Copper	Mercury
BL-1	3/4/99	ND(2)	ND(2)	ND(50)	ND(100)	ND(5)	ND(10)	ND(50)	ND(50)	ND(5)	ND(50)	ND(50)	ND(10)	ND(10)	4.1	ND(10)	ND(0.2)
	3/4/99[2]	ND(2)	ND(2)	ND(50)	ND(100)	ND(5)	ND(10)	ND(50)	50	ND(5)	ND(50)	ND(50)	ND(10)	ND(10)	4.8	ND(10)	ND(0.2)
BL-2	3/3/99	3.9	ND(2)	ND(50)	ND(100)	ND(5)	ND(10)	ND(50)	ND(50)	ND(5)	ND(50)	ND(50)	ND(10)	ND(50)	15	ND(10)	ND(0.2)
BL-3	3/3/99	ND(2)	ND(2)	ND(50)	270	ND(5)	ND(10)	ND(50)	ND(50)	ND(5)	ND(50)	ND(50)	ND(10)	ND(50)	11	ND(10)	ND(0.2)
BL-4	3/2/99	2.1	ND(2)	ND(50)	ND(100)	ND(5)	ND(10)	ND(50)	ND(50)	ND(5)	ND(50)	ND(50)	ND(10)	ND(10)	4.3	ND(10)	ND(0.2)
BL-5	3/4/99	ND(2)	2.6	ND(50)	ND(100)	ND(5)	ND(10)	ND(50)	ND(50)	ND(5)	ND(50)	ND(50)	ND(10)	16	5.5	ND(10)	ND(0.2)
BL-6	3/1/99	2.1	2.0	ND(50)	32	ND(5)	213	ND(50)	ND(50)	ND(5)	ND(50)	ND(50)	ND(10)	ND(50)	167	12U	ND(0.2)
BL-7	3/2/99	4.8	ND(2)	ND(50)	ND(100)	ND(5)	16	ND(50)	ND(50)	ND(5)	ND(50)	ND(50)	ND(10)	ND(10)	16	ND(10)	ND(0.2)
BL-8	3/2/99	2.4	ND(2)	ND(50)	122	ND(5)	11	ND(50)	ND(50)	ND(5)	ND(50)	ND(50)	ND(10)	ND(10)	14	22U	ND(0.2)

TABLE 12

[1]Only detected analytes are reported in table; results of all analyses are reported in Appendices E and F.

[2]Duplicate sample for BL-1 is identified as BL-17 in Appendices E and F.

µg/L Micrograms per liter
ND( ) Analyte not detected above the practical quantitation limit (in parentheses)
-- Not sampled

Data Validation Qualifers (for more information, see Appendix E)
U Not detected
J Estimated, detected
UJ Estimated, not detected

BOE-C6-0234147

Table 13. Summary of Groundwater Analytical Results - Total Metals, Former ILM Facility, Torrance, California

Sample ID	Sample Date	Total Metals[1] (in µg/L)																	
		Arsenic	Selenium	Aluminum	Barium	Cadmium	Chromium	Cobalt	Iron	Lead	Molybdenum	Manganese	Nickel	Titanium	Zinc	Copper	Vanadium	Mercury	Thallium
P-1	1/24/95	2.2	ND(2)	6,170	ND(100)	ND(5)	690	ND(10)	8,490	ND(5)	ND(10)	100	ND(50)	450	ND(50)	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/17/95	ND(2)	2.0	3,400	ND(100)	ND(5)	676	ND(10)	4,720	ND(5)	ND(10)	59	ND(50)	257	110	10.0	ND(50)	ND(0.2)	ND(5)
	12/27/95	2.0	ND(2)	310	ND(100)	ND(10)	1,420	ND(10)	384	ND(5)	ND(10)	11	ND(50)	14	ND(50)	ND(10)	ND(50)	ND(0.2)	ND(5)
	12/27/95(D)	2.2	ND(2)	1,980	ND(100)	ND(10)	1,250	ND(10)	2,490	ND(5)	ND(10)	35	ND(50)	361	ND(50)	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/19/96	2.6	ND(2)	2,790	ND(100)	ND(10)	1,180	ND(50)	4,370	ND(5)	ND(50)	64	ND(50)	213	138	ND(10)	ND(10)	ND(0.2)	ND(1)
	6/26/96	6.7	ND(2)	11,400	118	ND(10)	1,060	ND(50)	17,200	13	ND(50)	252	ND(50)	906	162	23	32	ND(0.2)	ND(1)
	6/26/96(D)	4.1	ND(2)	6,240	101	ND(10)	998	ND(50)	9,320	6.8	ND(50)	132	ND(50)	515	250	15	17	ND(0.2)	ND(1)
	9/18/96	3.7	ND(2)	4,400	ND(100)	ND(10)	1,050	ND(50)	6,380	ND(5)	ND(50)	95	ND(50)	339	87	ND(10)	11	0.7	ND(1)
	7/10/97	--	--	1,620	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	ND(1)
	7/10/97(D)	--	--	4,160	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	ND(1)
	3/4/99	4.0	3.9	8,270	164	ND(5)	1,280	ND(10)	10,600	12	ND(10)	--	ND(50)	559	53	ND(10)	21	5.3	ND(5.0)
P-2	1/27/95	ND(2)	ND(2)	16,800	180	ND(5)	55	10	23,200	ND(5)	ND(10)	430	ND(50)	1,130	190	17	ND(50)	ND(0.2)	ND(5)
	3/17/95	9.0	2.2	1,620	121	ND(5)	10	ND(10)	3,380	ND(5)	ND(10)	1,920	ND(50)	80	ND(50)	ND(10)	ND(50)	ND(0.2)	ND(5)
	12/27/95	6.8	ND(2)	5,810	179	172	14	ND(10)	7,900	38	14	3,590	ND(50)	153	1,470	143	ND(50)	ND(0.2)	ND(5)
	3/19/96	29	2.6	220,000	2,200	2,150	1,280	142	281,000	4,610	169	4,880	434	13,100	27,400	5,090	500	5.0	ND(1)
	3/19/96(D)	78	2.4	208,000	1,810	1,770	1,030	142	276,000	3,840	141	6,110	434	10,400	23,600	3,860	478	5.3	ND(1)
	6/20/96	6.8	ND(2)	5,220	212	68	25	ND(50)	12,900	245	ND(50)	2,800	ND(50)	211	2,030	75	16	0.42	ND(1)
	6/20/96(D)	8.8	ND(2)	7,170	223	76	34	ND(50)	14,600	153	ND(50)	2,670	ND(50)	293	2,610	94	21	0.64	ND(1)
	9/17/96	5.8	ND(2)	9,060	219	110	42	ND(50)	12,200	18	ND(50)	1,810	ND(50)	566	1,900	200	25	0.28	ND(1)
	7/8/97	--	--	2,360	--	32	--	--	--	103	--	--	--	--	--	--	--	--	--
	3/2/99	3.2	ND(2)	1,440	166	24	11	ND(10)	3,210	38	14	--	ND(50)	73U	388	29	ND(10)	ND(0.2)	ND(5.0)
P-3	1/24/95	9.2	ND(2)	11,400	160	ND(5)	32	ND(10)	14,400	5.3	ND(10)	130	ND(50)	710	81	14	ND(50)	0.36	ND(5)
	3/17/95	3.0	ND(2)	2,680	116	ND(5)	21	ND(10)	3,270	ND(5)	ND(10)	32	ND(50)	160	176	ND(10)	ND(50)	0.21	ND(5)
	12/20/95	11	ND(2)	3,000	131	ND(10)	17	ND(10)	3,140	ND(5)	ND(10)	75	ND(50)	118	52	ND(10)	ND(50)	3.0	ND(5)
	3/14/96	10	ND(2)	12,700	201	ND(10)	48	ND(50)	18,700	ND(5)	ND(50)	212	ND(50)	834	98	18	36	3.0	ND(5)
	6/19/96	5.8	ND(2)	1,960	141	ND(10)	16	ND(50)	1,930	ND(5)	ND(50)	108	ND(50)	78	ND(50)	ND(10)	ND(10)	2.0	1.1
	9/11/96	3.9	ND(2)	2,650	145	ND(10)	19	ND(50)	3,450	ND(5)	ND(50)	34	ND(50)	93	ND(50)	ND(10)	ND(10)	0.58	ND(1)
	7/8/97	--	--	1,770	--	ND(10)	--	--	--	ND(5)	--	--	--	--	--	--	--	0.31	--
	3/2/99	4.1	ND(2)	2,630	123	ND(5)	16	ND(10)	3,240	ND(5)	ND(10)	--	ND(50)	176	ND(50)	43	ND(10)	0.25	ND(5.0)
P-4	1/26/95	7.4	ND(2)	11,500	160	ND(5)	110	ND(10)	14,900	8.8	ND(10)	160	ND(50)	730	84	16	ND(50)	ND(0.2)	ND(5)
	3/17/95	ND(2)	2.4	530	122	ND(5)	731	ND(10)	777	ND(5)	ND(10)	ND(10)	ND(50)	11	73	ND(10)	ND(50)	ND(0.2)	ND(5)
	12/21/95	10	ND(2)	18,800	207	ND(10)	440	11	24,800	5.4	ND(10)	308	ND(50)	1,360	126	19	65	ND(0.2)	ND(5)
	3/18/96	25	ND(2)	24,000	258	ND(10)	383	ND(50)	34,800	33	ND(50)	520	ND(50)	1,620	179	42	68	0.36	ND(5)
	9/16/96	11	ND(2)	26,800	258	ND(10)	304	ND(50)	32,400	21	ND(50)	510	ND(50)	1,530	134	37	66	0.21	ND(1)
	7/9/97	--	--	317,000	--	--	--	--	--	311	--	--	--	--	--	--	--	1.5	--
P-5	1/26/95	38	4.6	67,200	400	ND(5)	110	39	91,400	24	ND(10)	2,260	71	3,680	310	86	210	ND(0.2)	ND(5)
	3/17/95	7.2	ND(2)	7,160	115	ND(5)	14	ND(10)	14,700	ND(5)	ND(10)	724	ND(50)	444	66	12	ND(50)	ND(0.2)	ND(5)
	12/27/95	37	ND(2)	18,000	270	ND(10)	22	10	32,700	9.1	ND(10)	1,560	ND(50)	1,240	87	21	77	ND(0.2)	ND(5)
	3/19/96	46	4.4	22,200	177	ND(10)	41	ND(50)	36,600	36	ND(10)	952	ND(50)	279	136	49	62	0.23	ND(1)
	6/25/96	38	ND(2)	11,500	182	ND(10)	25	ND(50)	27,500	8.6	ND(50)	1,370	ND(50)	687	94	35	36	ND(0.2)	ND(1)
	9/17/96	29	ND(2)	10,800	219	ND(10)	19	ND(50)	27,000	7.3	ND(50)	1,660	ND(50)	618	103	21	32	ND(0.2)	ND(1)
	9/17/96(D)	34	ND(2)	12,800	238	ND(10)	22	ND(50)	28,100	7.9	ND(50)	1,720	ND(50)	697	63	22	34	0.37	ND(1)
	7/97	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

TABLE 13 P-1

BOE-C6-0234148

Table 13. Summary of Groundwater Analytical Results - Total Metals, Former ILM Facility, Torrance, California

Sample ID	Sample Date	Total Metals[1] (in µg/L)																	
		Arsenic	Selenium	Aluminum	Barium	Cadmium	Chromium	Cobalt	Iron	Lead	Molybdenum	Manganese	Nickel	Titanium	Zinc	Copper	Vanadium	Mercury	Thallium
P-6	3/16/95	3.4	2.2	3,000	ND(100)	ND(5)	21	ND(10)	4,670	ND(5)	ND(10)	108	ND(50)	243	ND(50)	ND(10)	ND(50)	ND(0.2)	ND(5)
	12/20/95	12	ND(2)	18,900	257	ND(10)	59	17	26,800	ND(5)	ND(10)	494	ND(50)	1,520	110	21	67	ND(0.2)	ND(5)
	3/18/96	8.8	ND(2)	13,000	258	ND(10)	52	ND(50)	20,800	7.8	ND(50)	386	ND(50)	1,120	98	21	40	ND(0.2)	ND(5)
	6/20/96	4.6	2.2	11,200	215	ND(10)	45	ND(50)	17,500	10	ND(50)	423	ND(50)	919	166	21	35	ND(0.2)	1.6
	9/12/96	4.7	2.1	6,630	153	ND(10)	34	ND(50)	9,990	ND(5)	ND(50)	164	ND(50)	566	ND(50)	10	21	ND(0.2)	ND(1)
	7/9/97	--	--	4,850	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	ND(1)
P-6B	3/3/99	12	ND(2)	38,500	556	ND(5)	66	19	44,600	26	ND(10)	--	50	1,970	156	53	131	ND(0.2)	ND(5.0)
P-7	3/17/95	2.2	ND(2)	5,820	ND(100)	ND(5)	18	ND(10)	8,160	ND(5)	ND(10)	150	ND(50)	364	64	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/17/95(D)	ND(2)	ND(2)	2,590	ND(100)	ND(5)	13	ND(10)	3,700	ND(5)	ND(10)	126	ND(50)	160	57	ND(10)	ND(50)	ND(0.2)	ND(5)
	12/21/95	7.0	ND(2)	10,400	ND(100)	ND(10)	28	ND(10)	14,300	ND(5)	ND(10)	246	ND(50)	656	106	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/18/96	6.4	ND(2)	5,080	ND(100)	ND(10)	16	ND(50)	7,380	6.8	ND(50)	168	ND(50)	326	100	10	20	ND(0.2)	ND(5)
	6/24/96	2.6	ND(2)	2,800	ND(100)	ND(10)	10	ND(50)	4,450	ND(5)	ND(50)	90	ND(50)	197	ND(50)	ND(10)	14	ND(0.2)	ND(1)
	9/16/96	2.4	ND(2)	1,630	ND(100)	ND(10)	7	ND(50)	2,300	ND(5)	ND(50)	77	ND(50)	101	ND(50)	ND(10)	11	ND(0.2)	ND(1)
	7/9/97	--	--	5,920	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	--
	3/4/99	9.0	ND(2)	13,800	166	ND(5)	20	ND(10)	15,300	14	11	--	ND(50)	727	60	31	37	ND(0.2)	ND(5.0)
P-8	3/16/95	2.4	3.8	1,700	ND(100)	ND(5)	53	ND(10)	2,670	ND(5)	ND(10)	38	ND(50)	91	ND(50)	ND(10)	ND(50)	ND(0.2)	ND(5)
P-9	3/16/95	ND(2)	ND(2)	308	ND(100)	ND(5)	12	ND(10)	482	482	ND(10)	21	ND(50)	ND(10)	57	ND(10)	ND(50)	ND(0.2)	ND(5)
	12/20/95	8.4	ND(2)	3,580	ND(100)	ND(10)	19	ND(10)	3,570	ND(5)	ND(10)	114	ND(50)	136	52	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/18/96	12	ND(2)	15,800	131	ND(10)	58	ND(50)	23,900	8.1	ND(50)	256	ND(50)	1,080	110	16	48	ND(0.2)	ND(5)
	6/26/96	2.6	ND(2)	4,140	ND(100)	ND(10)	24	ND(50)	5,930	ND(5)	ND(50)	57	ND(50)	287	80	11	15	ND(0.2)	ND(1)
	9/12/96	16	ND(2)	20,400	202	ND(10)	56	ND(50)	25,800	29	ND(50)	450	ND(50)	1,250	186	38	59	0.30	1.2
	7/9/97	--	--	3,570	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	ND(1)
P-9B	3/3/99	2.3	ND(2)	4,600	100	ND(5)	32	ND(10)	6,530	ND(5)	ND(10)	--	ND(50)	295J	ND(50)	ND(10)	15	ND(0.2)	ND(5.0)
P-10	3/16/95	6.4	2.8	2,600	ND(100)	ND(5)	27	ND(10)	2,390	ND(5)	ND(10)	47	ND(50)	105	ND(50)	ND(10)	ND(50)	ND(0.2)	ND(5)
	12/19/95	9.4	2.8	1,120	ND(100)	ND(10)	26	ND(10)	1,000	ND(5)	ND(10)	153	ND(50)	ND(10)	51	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/14/96	3.6	2.0	3,750	ND(100)	ND(10)	32	ND(50)	4,680	ND(5)	ND(50)	80	ND(50)	192	62	ND(10)	13	ND(0.2)	ND(5)
	6/18/96	5.2	2.0	1,520	ND(100)	ND(10)	27	ND(50)	1,830	ND(5)	ND(50)	64	ND(50)	71	ND(50)	ND(10)	ND(10)	ND(0.2)	ND(1)
	9/11/96	3.8	2.1	2,100	ND(100)	ND(10)	29	ND(50)	2,580	ND(5)	ND(50)	44	ND(50)	77	ND(50)	ND(10)	ND(10)	ND(0.2)	ND(1)
	7/8/97	--	--	1,690	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	--
	3/1/99	ND(2)	2.8	196	76	ND(5)	26	ND(10)	190	ND(5)	ND(10)	--	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	ND(0.2)	ND(5.0)
P-11	12/27/95	6.8	ND(2)	16,200	170	ND(10)	62	ND(10)	18,600	5.9	ND(10)	199	ND(50)	1,090	57	11	85	ND(0.2)	ND(5)
	3/14/96	4.6	ND(2)	2,850	124	ND(10)	21	ND(50)	4,190	ND(5)	ND(50)	51	ND(50)	188	52	ND(10)	12	ND(0.2)	ND(5)
	6/19/96	4.0	2.0	1,690	ND(100)	ND(10)	21	ND(50)	1,490	ND(5)	ND(50)	60	ND(50)	54	ND(50)	ND(10)	ND(10)	ND(0.2)	ND(1)
	9/11/96	4.1	ND(2)	8,550	146	ND(10)	35	ND(50)	10,900	ND(5)	ND(50)	105	ND(50)	535	ND(50)	15	22	ND(0.2)	ND(1)
	7/8/97	--	--	2,180	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	ND(0.2)	--
P-12	12/21/95	17	2.2	47,200	323	ND(10)	109	42	59,600	7.1	ND(10)	626	ND(10)	2,480	230	38	159	0.31	ND(5)
	3/19/96	8.8	3.2	31,000	308	ND(10)	91	57	45,500	16	ND(50)	547	ND(50)	2,740	300	41	95	1.2	ND(1)
	6/26/96	5.9	2.3	14,300	208	ND(10)	54	ND(50)	21,100	10	ND(50)	249	ND(50)	950	78	21	46	1.5	ND(1)
	6/26/96(D)	6.3	2.1	18,800	237	ND(10)	63	ND(50)	26,800	10	ND(50)	312	ND(50)	1,220	98	25	54	1.6	ND(1)
	9/18/96	4.0	ND(2)	4,410	191	ND(10)	29	ND(50)	6,090	ND(5)	ND(50)	92	ND(50)	312	ND(50)	ND(10)	16	0.7	ND(1)
	7/10/97	--	--	852	--	ND(10)	--	--	--	ND(5)	--	--	--	--	--	--	--	0.53	--
	3/3/99	3.2	ND(2)	3,100	190	ND(5)	32	53	5,100	ND(5)	ND(10)	--	ND(50)	19	ND(50)	16	11	0.5	ND(5.0)
P-13	12/21/95	6.8	7.4	1,510	ND(100)	ND(10)	15	ND(10)	1,060	5.2	ND(10)	87	ND(50)	19	ND(50)	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/14/96	3.2	6.6	6,330	ND(100)	ND(10)	29	ND(50)	8,780	5.4	ND(50)	113	ND(50)	381	87	12	22	ND(0.2)	ND(5)
	6/19/96	3.0	7.8	2,140	ND(100)	ND(10)	18	ND(50)	2,890	ND(5)	ND(50)	53	ND(50)	125	ND(50)	ND(10)	ND(10)	ND(0.2)	ND(1)
	9/11/96	3.0	7.2	3,340	ND(100)	ND(10)	20	ND(50)	4,040	ND(5)	ND(50)	53	ND(50)	138	ND(50)	ND(10)	11	0.34	ND(1)
	7/8/97	--	--	6,660	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	ND(0.2)	--

TABLE 13 P-6

BOE-C6-0234149

Table 13. Summary of Groundwater Analytical Results - Total Metals, Former ILM Facility, Torrance, California

Sample ID	Sample Date	Total Metals[1] (in µg/L)																	
		Arsenic	Selenium	Aluminum	Barium	Cadmium	Chromium	Cobalt	Iron	Lead	Molybdenum	Manganese	Nickel	Titanium	Zinc	Copper	Vanadium	Mercury	Thallium
P-14	12/21/95	33	3.4	5,170	ND(100)	ND(10)	2,400	ND(10)	5,520	5.2	ND(10)	285	ND(50)	216	58	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/19/96	24	4.0	21,000	114	ND(10)	1,800	ND(50)	34,000	17	ND(50)	649	ND(50)	2,250	193	41	74	ND(0.2)	ND(1)
	6/26/96	11	3.4	9,060	ND(100)	ND(10)	1,520	ND(50)	12,900	9.1	ND(50)	245	ND(50)	564	108	19	28	ND(0.2)	ND(1)
	9/17/96	11	2.5	8,600	ND(100)	ND(10)	1,500	ND(50)	12,400	7.5	ND(50)	241	ND(50)	553	54	17	29	ND(0.2)	ND(1)
	7/10/97	--	--	1,700	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	ND(0.2)	--
P-15	12/27/95	5.6	ND(2)	3,820	ND(100)	ND(10)	372	ND(10)	5,290	ND(5)	ND(10)	72	ND(50)	279	ND(50)	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/19/96	5.4	2.0	5,780	ND(100)	ND(10)	223	ND(50)	7,490	ND(5)	ND(50)	109	ND(50)	1,580	175	ND(10)	21	ND(0.2)	ND(1)
	6/26/96	5.9	ND(2)	6,270	ND(100)	ND(10)	88	ND(50)	8,710	10	ND(50)	144	ND(50)	399	ND(50)	19	21	ND(0.2)	ND(1)
	9/18/96	4.9	ND(2)	4,070	ND(100)	ND(10)	73	ND(50)	4,980	10	ND(50)	107	ND(50)	257	66	ND(10)	13	ND(0.2)	ND(1)
	7/10/97	--	--	448	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	--
P-16A	12/26/95	12	2.4	17,700	ND(100)	ND(10)	70	ND(10)	24,100	7.1	ND(10)	240	ND(50)	979	89	13	72	ND(0.2)	ND(5)
	3/18/96	7.0	2.4	15,600	ND(100)	ND(10)	70	ND(50)	22,800	8.4	ND(50)	278	ND(50)	820	140	19	49	ND(0.2)	ND(5)
	3/18/96(D)	14	2.0	6,840	ND(100)	ND(10)	45	ND(50)	10,400	10	ND(50)	219	ND(50)	358	133	11	25	ND(0.2)	ND(5)
	6/25/96	7.0	3.0	12,600	ND(100)	ND(10)	90	ND(50)	19,800	6.1	ND(50)	254	ND(50)	659	93	16	ND(10)	ND(0.2)	ND(1)
	9/16/96	7.2	ND(2)	4,740	ND(100)	ND(10)	36	ND(50)	6,530	ND(5)	ND(50)	88	ND(50)	246	ND(50)	ND(10)	17	ND(0.2)	ND(1)
	7/9/97	--	--	1,580	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	ND(1)
	3/4/99	9.3	ND(2)	8,380	156	ND(5)	21	ND(10)	8,350	9.2	ND(10)	--	ND(50)	438	ND(50)	ND(10)	22	ND(0.2)	ND(5.0)
P-16B	12/19/95	ND(2)	3.0	87	144	ND(10)	ND(5)	ND(10)	147	ND(5)	11	87	ND(50)	ND(10)	504	ND(10)	ND(50)	ND(0.2)	ND(5)
	12/19/96(D)	2.0	2.8	85	143	ND(10)	ND(5)	ND(10)	165	ND(5)	ND(10)	86	ND(50)	ND(10)	510	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/18/96	ND(2)	3.2	300	170	ND(10)	ND(5)	ND(50)	280	ND(5)	ND(50)	88	ND(50)	14	561	ND(10)	ND(10)	ND(0.2)	ND(5)
	6/24/96	ND(2)	5.8	126	446	ND(10)	ND(5)	ND(50)	233	ND(5)	ND(50)	23	ND(50)	ND(10)	ND(50)	ND(10)	ND(10)	ND(0.2)	ND(1)
P-16C	9/12/96	3.2	5.6	381	391	ND(10)	ND(5)	ND(50)	405	ND(5)	ND(50)	332	ND(50)	19	1,370	ND(10)	ND(10)	ND(0.2)	ND(1)
	7/9/97	--	--	256	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	ND(1)
	3/2/99	2.6	4.3	3,680	451	ND(5)	ND(10)	ND(10)	4,000	ND(5)	ND(10)	--	ND(50)	209J	61	ND(10)	ND(10)	ND(0.2)	ND(5.0)
P-17	12/21/95	21	ND(2)	2,700	ND(100)	ND(10)	881	ND(10)	949	ND(5)	ND(10)	249	ND(50)	ND(10)	78	ND(10)	ND(50)	0.22	ND(5)
	3/19/96	10	2.0	18,300	116	ND(10)	770	ND(50)	28,600	12	ND(50)	388	ND(50)	382	138	24	58	ND(0.2)	ND(1)
	9/18/96	11	ND(2)	19,400	210	ND(10)	1,080	ND(50)	23,400	35	ND(50)	447	ND(50)	1,200	282	102	49	ND(0.2)	21
	7/10/97	--	--	340	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	ND(1)
	3/4/99	2.5	ND(2)	2,580	69	ND(5)	40	ND(10)	3,370	7.4	ND(10)	--	ND(50)	165	ND(50)	21	ND(10)	ND(0.2)	ND(5.0)
P-18	12/26/95	10	3.6	18,400	ND(100)	ND(10)	52	ND(10)	26,700	6.7	ND(10)	256	ND(50)	1,080	74	11	68	ND(0.2)	ND(5)
	3/19/96	12	2.0	10,800	ND(100)	ND(10)	50	ND(50)	17,700	11	ND(50)	209	ND(50)	612	75	16	33	ND(0.2)	ND(1)
	9/12/96	20	3.3	25,400	223	ND(10)	69	ND(50)	34,100	32	ND(50)	567	ND(50)	1,390	164	47	86	ND(0.2)	1.1
	9/12/96(D)	18	3.4	24,700	220	ND(10)	68	ND(50)	33,500	31	ND(50)	557	ND(50)	1,390	165	47	84	ND(0.2)	ND(1)
	7/8/97	--	--	4,550	--	--	--	--	--	7.6	--	--	--	--	--	--	--	--	ND(1)
P-19	12/26/95	15	3.8	25,300	111	ND(10)	72	11	36,500	8.9	ND(10)	347	ND(50)	1,540	87	14	91	ND(0.2)	ND(5)
	3/19/96	11	3.0	17,300	ND(100)	ND(10)	66	ND(50)	26,400	9.0	ND(50)	281	ND(50)	1,040	124	18	53	ND(0.2)	1.3
	6/25/96	29	3.0	7,860	ND(100)	ND(10)	35	ND(50)	12,100	ND(5)	ND(50)	147	ND(50)	467	85	10	27	ND(0.2)	ND(1)
	9/17/96	4.9	3.0	5,670	ND(100)	ND(10)	34	ND(50)	8,250	ND(5)	ND(50)	105	ND(50)	328	ND(50)	ND(10)	19	ND(0.2)	ND(1)
	7/9/97	--	--	1,220	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	--
P-20	12/27/95	6.2	ND(2)	4,110	ND(100)	ND(10)	42	ND(10)	5,120	ND(5)	ND(10)	104	ND(50)	290	ND(50)	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/18/96	4.6	ND(2)	5,830	ND(100)	ND(10)	36	ND(50)	8,700	6.6	ND(50)	170	ND(50)	416	65	10	22	ND(0.2)	ND(5)
	6/25/96	7.4	ND(2)	5,840	ND(100)	ND(10)	34	ND(50)	8,830	ND(5)	ND(50)	168	250	392	59	ND(10)	21	ND(0.2)	ND(1)
	9/16/96	5.7	ND(2)	3,990	ND(100)	ND(10)	25	ND(50)	5,360	ND(5)	ND(50)	124	ND(50)	262	ND(50)	ND(10)	13	ND(0.2)	ND(1)
	7/10/97	--	--	245	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	--
	3/4/99	4.4	ND(2)	4,060	102	ND(5)	39	19	5,700	5.2	ND(10)	--	ND(50)	290	ND(50)	23	12	ND(0.2)	ND(5.0)
	3/4/99(D)[2]	4.5	ND(2)	4,690	106	ND(5)	43	22	6,360	6.0	ND(10)	--	ND(50)	329	ND(50)	12	15	ND(0.2)	ND(5.0)

TABLE 13 P-14

BOE-C6-0234150

Table 13. Summary of Groundwater Analytical Results - Total Metals, Former ILM Facility, Torrance, California

Sample ID	Sample Date	Total Metals[1] (in µg/L)																	
		Arsenic	Selenium	Aluminum	Barium	Cadmium	Chromium	Cobalt	Iron	Lead	Molybdenum	Manganese	Nickel	Titanium	Zinc	Copper	Vanadium	Mercury	Thallium
P-21	12/26/95	8.4	ND(2)	12,500	125	ND(10)	36	ND(10)	16,300	13	ND(10)	188	ND(50)	857	79	ND(10)	60	ND(0.2)	ND(5)
	3/18/96	5.8	ND(2)	2,350	ND(100)	ND(10)	11	ND(50)	3,650	10	ND(50)	166	ND(50)	151	54	ND(10)	12	ND(0.2)	ND(5)
	6/25/96	ND(2)	ND(2)	5,540	ND(100)	ND(10)	24	ND(50)	8,610	ND(5)	ND(50)	393	ND(50)	352	60	11	22	ND(0.2)	ND(1)
	9/17/96	4.2	ND(2)	3,230	ND(100)	ND(10)	14	ND(50)	4,580	ND(5)	ND(50)	120	ND(50)	192	ND(50)	ND(10)	13	ND(0.2)	ND(1)
	7/10/97	--	--	281	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	--
P-22	12/20/95	19	6.4	3,120	ND(100)	ND(10)	11	ND(10)	2,520	5.2	ND(10)	228	ND(50)	64	171	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/18/96	5.0	5.2	7,810	ND(100)	ND(10)	23	ND(50)	7,970	10	ND(50)	460	ND(50)	349	103	ND(10)	24	ND(0.2)	ND(5)
	6/20/96	6.2	7.4	3,950	ND(100)	ND(10)	17	ND(50)	4,250	10	ND(50)	241	ND(50)	163	84	ND(10)	14	ND(0.2)	ND(1)
	9/12/96	6.0	6.3	5,370	ND(100)	ND(10)	21	ND(50)	5,440	ND(5)	ND(50)	184	ND(50)	236	ND(50)	ND(10)	14	ND(0.2)	ND(1)
	7/9/97	--	--	260	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	--
	3/3/99	4.2	2.3	2,200	184	ND(5)	25	ND(10)	2,420	ND(5)	ND(10)	--	ND(50)	139J	ND(50)	ND(10)	12	ND(0.2)	ND(5.0)
P-23	12/20/95	4.4	ND(2)	824	ND(100)	ND(10)	13	ND(10)	1,090	ND(5)	ND(10)	32	ND(50)	44	70	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/14/96	2.8	ND(2)	1,080	ND(100)	ND(10)	16	ND(50)	1,250	ND(5)	ND(50)	29	ND(50)	55	54	ND(10)	ND(10)	ND(0.2)	ND(5)
	6/20/96	3.4	ND(2)	1,220	ND(100)	ND(10)	16	ND(50)	1,820	ND(5)	ND(50)	39	ND(50)	82	ND(50)	ND(10)	ND(10)	ND(0.2)	ND(1)
	9/11/96	3.9	ND(2)	856	ND(100)	ND(10)	14	ND(50)	1,140	ND(5)	ND(50)	16	ND(50)	50	ND(50)	ND(10)	ND(10)	ND(0.2)	ND(1)
	7/8/97	--	--	583	--	ND(10)	--	--	--	ND(5)	--	--	--	--	--	--	--	ND(0.2)	--
P-24	12/20/95	9.6	ND(2)	9,720	ND(100)	ND(10)	38	11	14,400	ND(5)	ND(10)	995	ND(50)	621	106	ND(10)	ND(50)	ND(0.2)	ND(5)
	3/19/96	14	ND(2)	20,200	130	ND(10)	65	ND(50)	31,800	14	ND(50)	1,480	ND(50)	1,370	180	28	63	ND(0.2)	ND(1)
	6/24/96	5.6	ND(2)	6,610	ND(100)	ND(10)	18	ND(50)	10,700	ND(5)	ND(50)	771	ND(50)	416	ND(50)	ND(10)	21	ND(0.2)	ND(1)
	9/17/96	7.4	ND(2)	14,200	131	ND(10)	29	ND(50)	19,000	8.3	ND(50)	1,020	ND(50)	914	86	16	41	8.4	ND(1)
	9/17/96(D)	6.2	ND(2)	9,010	100	ND(10)	25	ND(50)	12,000	6.1	ND(50)	890	ND(50)	576	61	13	25	5.8	ND(1)
	7/9/97	--	--	898,000	--	109	--	--	--	143	--	--	--	--	--	--	--	20	--
	3/3/99	4.9	ND(2)	5,250	144	ND(5)	13	ND(10)	5,760	ND(5)	ND(10)	--	ND(50)	274J	ND(50)	ND(10)	15	ND(0.2)	ND(5.0)
P-25	12/26/95	13	ND(2)	22,400	119	ND(10)	490	12	30,600	12	ND(10)	360	ND(50)	1,680	98	17	78	ND(0.2)	ND(5)
	3/19/96	11	ND(2)	15,600	ND(100)	ND(10)	308	ND(50)	24,800	7.1	ND(50)	322	ND(50)	1,180	117	20	46	ND(0.2)	ND(1)
	6/26/96	8.6	ND(2)	12,100	ND(100)	ND(10)	453	ND(50)	18,300	10	ND(50)	230	ND(50)	810	119	27	32	ND(0.2)	ND(1)
	9/18/96	5.1	ND(2)	5,030	ND(100	ND(10)	488	ND(50)	7,530	ND(5)	ND(50)	101	ND(50)	373	ND(50)	ND(10)	15	ND(0.2)	ND(1)
	7/10/97	--	--	937	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	ND(1)
	7/10/97(D)	--	--	2,940	--	--	--	--	--	ND(5)	--	--	--	--	--	--	--	--	ND(1)

TABLE 13 P-21

[1]Only detected analytes are reported in table; results of all analyses are reported in Appendices E and F.

[2]Duplicate sample for P-20 is identified as P-29 in Appendices E and F.

µg/L Micrograms per liter

ND( ) Analyte not detected above the practical quantitation limit (in parentheses)

(D) Duplicate sample

-- Not sampled

Data Validation Qualifers (for more information, see Appendix E)

U Not detected

J Estimated, detected

UJ Estimated, not detected

BOE-C6-0234151

Table 14. Summary of Groundwater Analytical Results - Total Metals, BRC Property, Torrance, California

Sample ID	Sample Date	Total Metals[1] (in µg/L)																
		Arsenic	Selenium	Aluminum	Barium	Cadmium	Chromium	Cobalt	Iron	Lead	Molybdenum	Nickel	Titanium	Zinc	Copper	Vanadium	Mercury	Thallium
BL-1	3/4/99	110J	2.4	97800J	367J	ND(5)	195J	73J	154,000J	55J	12	123	4,920J	394J	110J	317J	0.29	ND(5.0)
	3/4/99[2]	166J	3.5	131000J	508J	ND(5)	280J	111J	229000J	87J	17	182	7510J	654J	146J	459J	0.46	ND(5.0)
BL-2	3/3/99	59	ND(2)	41,500	200	ND(5)	119	24	63,400	13	ND(10)	51	2,870	146	39	126	ND(0.2)	ND(5.0)
BL-3	3/3/99	20	ND(2)	24,400	328	ND(5)	92	10	37,400	8.9	ND(10)	ND(50)	1,360	86	ND(10)	75	ND(0.2)	ND(5.0)
BL-4	3/2/99	12	ND(2)	36,600	168	ND(5)	114	17	49,300	15	ND(10)	54	2,240	119	33	118	ND(0.2)	ND(5.0)
BL-5	3/4/99	12	3.4	18,000	110	ND(5)	84	ND(10)	28,900	10	ND(10)	ND(50)	946	122	30	55	ND(0.2)	ND(5.0)
BL-6	3/1/99	109	2.2	89,300	453	ND(5)	450	39	120,000	20	14	108	4,140	279	ND(10)	202	0.27	ND(5.0)
BL-7	3/2/99	86	ND(2)	62,300	203	ND(5)	255	31	106,000	23	11	99	3,740	256	29	188	ND(0.2)	ND(5.0)
BL-8	3/2/99	25	ND(2)	22,100	188	ND(5)	95	ND(10)	32,900	8.2	ND(10)	ND(50)	1,420	74	ND(10)	62	ND(0.2)	ND(5.0)

TABLE 14

[1]Only detected analytes are reported in table; results of all analyses are reported in Appendices E and F.

[2]Duplicate sample for BL-1 is identified as B-17 in Appendices E and F.

µg/L Micrograms per liter

ND( ) Analyte not detected above the practical quantitation limit (in parentheses)

-- Not sampled

BOE-C6-0234152