Contractor: O'Keefe
Drill Type: W750 (Buggy-Mounted)
Hole Size: 4 3/4"
Collar Elev.: 5346.63

Coordinates: 29696.23 , 46775.64
Casing Depth:
Bearing: VERT Inclination: VERT
Final Depth: 130'

Project: ~~West Anchor Hill~~ Ruby Ridge Exploration
State: SD
Date Started: 9-19-97
Date Completed: 9-19-97

Hole No.: R97-1060
Sheet 1 of 1
Property: GILT EDGE
Hole Surveyed: NO (Collar Only)

| DISTANCE (feet) | GRAPHIC LOGS: ALTERATION (1 Weak, 2 Moderate, 3 Strong) | TOTAL SULFIDES (vol %) | ROCK CODE | ORE CODE | DOWN HOLE LOCATION: DISTANCE DOWN HOLE (feet) | % SULFIDES | ROCK TYPE | DESCRIPTION: MINERALOGY, ALTERATION, TEXTURES, GRAIN SIZE, FRAGMENT SIZE | MINERALIZATION: DISTRIBUTION (Massive, Disseminated, Veinlill, Replacement) / TYPE | ASSAY Au | ASSAY Ag |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | 600 | 3 | 0-5 | 0 | Tap | (0-130 = Tert. Trach Porph) | (0-40 = OXIDE) | | |
| | | | " | | | " | | | 2-15% = yell/org Fe Ox | | |
| | | | " | | | " | | | | | |
| | | | " | | | " | | 0-40 = creamy white chips, mod Arg-Alt. | | | |
| | | | " | | 20-25 | " | | | | | |
| | | | " | | | " | | | | | |
| | | | " | | | " | | | | | |
| | | | " | | | " | | | | | |
| | | | " | 2 | | .4 | | | | | |
| | | | " | | 45-50 | .7 | | | (40-130 = mix) | | |
| | | | " | | | 1.0 | | | 0-5% org/brn Fe Ox | | |
| | | | " | | | .6 | | | | | |
| | | | " | | | .5 | | | | | |
| | | | " | | | .4 | | | Pyrite = 0.1-1.0% small ≤2mm cubes; massive | | |
| | | | " | | 70-75 | .4 | | | | | |
| | | | " | | | .5 | | | | | |
| | | | " | | | .3 | | | | | |
| | | | " | | | .3 | | | | | |
| | | | " | | | .4 | | | | | |
| | | | " | | 95-100 | .5 | | | | | |
| | | | " | | | .3 | | | TD @ 130' | | |
| | | | " | | | .5 | | (All Dry) | | | |
| | | | " | | | .9 | | | | | |
| | | | " | | | .6 | | | | | |
| | | | " | | 120-125 | .4 | | | | | |
| | | | " | | | .4 | | | | | |
| | | | | | 145-150 | | | | | | |
| | | | | | 170-175 | | | | | | |

DRILL CUTTING LOG

Logged by: