D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 8/1/14	Time: 5:00 Am
Shift: (First or Second)	
Monitor ID: Mini Rae 200	
Instrument Calibration Gases: Isobutylene 100PPM	
Background Instrument Reading: 0.0	

Unit Down

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	—	—		A	N	—	—	—
SDS Shredder	Running	Down ✓	94	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	124	0	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1793	7.4	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2667	62	0	A	N	—	—	—
Tank 51	Running ✓	Down	3317	1.4	0	A	N	—	—	—
Tank 55	Running ✓	Down	2984	0.9	0	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 8/2/14	Time: 5:00 Am
Shift: (First or Second)	
Monitor ID: MiniRae 2000	
Instrument Calibration Gases: Isobutylene 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	194	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	918	0.1	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1711	0.7	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2234	34	0	A	N	—	—	—
Tank 51	Running ✓	Down	3615	1.9	0	A	N	—	—	—
Tank 55	Running ✓	Down	2917	2.2	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Ted Compton
Date of Inspection: 8/3/14	Time: 5:00 AM
Shift: (First or Second)	
Monitor ID:	mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100PPM
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	174	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1111	0.1	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1233	2.7	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2776	0.6	0	A	N	—	—	—
Tank 51	Running ✓	Down	1924	1.4	0	A	N	—	—	—
Tank 55	Running ✓	Down	2105	1.5	0	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Aug 4, 14	Time: 5:00
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTYLENE	
Background Instrument Reading:	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	9999	1:4		A	N	—	—	—
ATDU / OWS	Running ✓	Down	9999	140	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2951	1.2	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	47.2	8.7	0	A	N	—	—	—
Tank 51	Running ✓	Down	1720	0/0		A	N	—	—	—
Tank 55	Running ✓	Down	9980	220	87.2	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Aug 5 14	Time: 500
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene	
Background Instrument Reading:	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	72.8	1.4		A	N	—	—	—
ATDU / OWS	Running	Down	9999	111.2	12.8	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	3429	.2	1.4	A	N	—	—	—
Distillation Unit	Running	Down	29.1	0 / 0		A	N	—	—	—
Tank 51	Running	Down	1728	0 / 1.3		A	N	—	—	—
Tank 55	Running	Down	1499	1.2 / 0		A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Aug 6, 14	Time: 5:00
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTENE	
Background Instrument Reading: 00	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	29.1	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	2758	0	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1750	1.4	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	920	3.2/0		A	N	—	—	—
Tank 51	Running ✓	Down	3000	1.8/0		A	N	—	—	—
Tank 55	Running ✓	Down	9999	19.1/2.4		A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Dimelko	
Date of Inspection: Aug 7, 14	Time: 5:00
Shift: (First or Second)	
Monitor ID: Mini Raz 2000	
Instrument Calibration Gases: ISOBUTYLENE 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	9557	10.1		A	N	—	—	—
ATDU / OWS	Running	Down	5239	0	3.4	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1229	0	0	A	N	—	—	—
Distillation Unit	Running	Down	158	.2	0	A	N	—	—	—
Tank 51	Running	Down	3561	3.4	0	A	N	—	—	—
Tank 55	Running	Down	7980	.01	0	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: M. Torres	
Date of Inspection: 8/8/14	Time: 5:00 am
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100ppm	
Background Instrument Reading:	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
						Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—	A	N	—	—	—
SDS Shredder	Running ✓	Down	61.0	0	A	N	—	—	—
ATDU / OWS	Running ✓	Down	876		A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1250		A	N	—	—	—
Distillation Unit	Running ✓	Down	26.5		A	N	—	—	—
Tank 51	Running ✓	Down	2100		A	N	—	—	—
Tank 55	Running ✓	Down	9497	11.0 | 1.6	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Darren Cudjoe	
Date of Inspection: 8/9/14	Time: 5:00 AM
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100ppm	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	—	—		A	N	—	—	—
SDS Shredder	Running	Down	177	0		A	N	—	—	—
ATDU / OWS	Running	Down	361	0.7	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	914	0.0	0	A	N	—	—	—
Distillation Unit	Running	Down	1334	1.1	0	A	N	—	—	—
Tank 51	Running	Down	1729	6.1	0	A	N	—	—	—
Tank 55	Running	Down	2114	1.4	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Darron Cudjoe	
Date of Inspection: 8/10/14	Time: 5:00 AM
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	199	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	201	0.7	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1390	2.1	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2115	0.6	0	A	N	—	—	—
Tank 51	Running ✓	Down	3116	9.4	0	A	N	—	—	—
Tank 55	Running ✓	Down	1924	24.0	0	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: 8-13-14	Time: 5:00
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTYLENE 100ppm	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
						Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0	A	N	—	—	—
SDS Shredder	Running ✓	Down	1692	9.8	A	N	—	—	—
ATDU / OWS	Running ✓	Down	1689	0/1332 0/0	A	Y	Aug 13	5:20	change
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2333	4122/1377 1.5/0	A	Y	Aug 13	5:20	change
Distillation Unit	Running ✓	Down	23	944 / 0	A	N	—	—	—
Tank 51	Running ✓	Down	203	1504 / 0	A	N	—	—	—
Tank 55	Running ✓	Down	1882	1106/161 / 0/0	A	Y	Aug 13	5:30	change

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: M. Tarr	
Date of Inspection: 8/11/14	Time: 5:00 am
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100 ppm	
Background Instrument Reading:	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	✓	✓	—
SDS Shredder	Running ✓	Down	—	0		A	N	✓	✓	—
ATDU / OWS	Running ✓	Down	200	116	0	A	N	✓	✓	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1000	4.0	0	A	N	✓	✓	—
Distillation Unit	Running ✓	Down	1650	0	0	A	N	✓	✓	—
Tank 51	Running ✓	Down	26.5	9.6	0	A	N	✓	✓	—
Tank 55	Running ✓	Down	5902	13.2	2	A	N	✓	✓	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Aug 14,14	Time: 5:00
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTYENE	
Background Instrument Reading: 100	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	2473	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1241	126	0	A	Y	Aug 14	5:00	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1995	1532	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	820	0	0	A	N	—	—	—
Tank 51	Running ✓	Down	1331	0 / 1837 / 0/0		A	N	—	—	—
Tank 55	Running ✓	Down	2619	0 / 0		A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 8/16/14	Time: 5:00 AM
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100PPM	
Background Instrument Reading:	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	147	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1796	0.7	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2214	0.0	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	1914	3.4	0	A	N	—	—	—
Tank 51	Running ✓	Down	1729	1.9	0	A	N	—	—	—
Tank 55	Running ✓	Down	3115	0.9	0	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: 8-17,14	Time: 500 Am
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTLYEME	
Background Instrument Reading: 10.0ppm	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
						Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE	Running ✓	Down	0	0	A	N	—	—	—
SDS Shredder	Running ✓	Down	200	0	A	N	—	—	—
ATDU / OWS	Running ✓	Down	4129	0 / 72.3	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	201	1.2 / 0	A	N	—	—	—
Distillation Unit	Running ✓	Down	374	2217 / 0	A	N	—	—	—
Tank 51	Running ✓	Down	173	514 / 0	A	N	—	—	—
Tank 55	Running ✓	Down	1235	1.0 / 0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 8/17/14	Time: 5:00 AM
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	201	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1145	0.9	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1729	0.0	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2136	0.6	0	A	N	—	—	—
Tank 51	Running ✓	Down	1924	4.5	0	A	N	—	—	—
Tank 55	Running ✓	Down	3007	31.7	0	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: 8-18-14	Time: 5:00 PM
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTYLENE 100ppm	
Background Instrument Reading: 1.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	278	0		A	N	—	—	—
ATDU / OWS	Running	Down	5661	1.3	74.8	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	320	3.6	0	A	N	—	—	—
Distillation Unit	Running	Down	714	2188	0	A	N	—	—	—
Tank 51	Running	Down	1100	600	0	A	N	—	—	—
Tank 55	Running	Down	2861	9.7	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 8/19/14	Time: 500AM
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	—	—		A	N	—	—	—
SDS Shredder	Running	Down	114	0		A	N	—	—	—
ATDU / OWS	Running	Down	2116	2.6	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1113	0.1	0	A	N	—	—	—
Distillation Unit	Running	Down	2445	0.0	0	A	N	—	—	—
Tank 51	Running	Down	1795	3.6	0	A	N	—	—	—
Tank 55	Running	Down	966	0.9	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 8/20/14	Time: 500AM
Shift: (First or Second)	
Monitor ID: Min. Rae 2000	
Instrument Calibration Gases: Isobutylene 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	211	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1175	4.7	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2166	16.9	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	914	2.4	0	A	N	—	—	—
Tank 51	Running ✓	Down	1914	0.0	0	A	N	—	—	—
Tank 55	Running ✓	Down	2997	0.5	0	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 8/21/14	Time: 500AM
Shift: (First or Second)	
Monitor ID: Min. Rae 2000	
Instrument Calibration Gases: Isobutylene 100ppm	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	18.7	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	966	0.4	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1111	0.9	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	1914	3.3	0	A	N	—	—	—
Tank 51	Running ✓	Down	2116	6.6	0	A	N	—	—	—
Tank 55	Running ✓	Down	918	10.1	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Ted Compton
Date of Inspection: 8/22/14	Time: 500AM
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene 100PPM
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Date	Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	199	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1138	0.9	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2116	1.1	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	3316	1.4	0	A	N	—	—	—
Tank 51	Running ✓	Down	918	5.7	0	A	N	—	—	—
Tank 55	Running ✓	Down	1715	20.6	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 8/23/14	Time: 500AM
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	144	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1111	2.6	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2161	0.0	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	1925	1.4	0	A	N	—	—	—
Tank 51	Running ✓	Down	413	0.7	0	A	N	—	—	—
Tank 55	Running ✓	Down	918	0.3	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 8/24/14	Time: 500PM
Shift: (First or Second)	
Monitor ID: M.n. Rae 2000	
Instrument Calibration Gases: Isobutylene 100 PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	156	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1921	0.9	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1312	0.1	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	3009	13.6	0	A	N	—	—	—
Tank 51	Running ✓	Down	1996	0.3	0	A	N	—	—	—
Tank 55	Running ✓	Down	1314	0.4	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 8/25/14	Time: 500 PM
Shift: (First or Second)	
Monitor ID: Min. Rae 2000	
Instrument Calibration Gases: Isobutylene 100 PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	179	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1921	0.7	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	3314	1.6	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2671	26.0	0	A	N	—	—	—
Tank 51	Running ✓	Down	3794	19.2	0	A	N	—	—	—
Tank 55	Running ✓	Down	2918	1.8	0	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smello	
Date of Inspection: Aug 26, 14	Time: 6.20
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTENE	
Background Instrument Reading:	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	1001	0		A	N	—	—	—
ATDU / OWS	Running	Down	301	520	350	A	Y	Aug 26 14	6:00	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1591	1.2	0	A	N	—	—	—
Distillation Unit	Running	Down	266	1455/1500	2651/1010	A	Y	A/141	—	—
Tank 51	Running	Down	10.6	151	0	A	N	—	—	—
Tank 55	Running	Down	2125	574/480	628/999	A	Y	Aug 4	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Aug 27, 14	Time: 6:00
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTLYENE 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Date	Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	–	–	–
SDS Shredder	Running	Down	1221	0		A	N	–	–	–
ATDU / OWS	Running	Down	283	487	345	A	Y	Aug 27,14	6:10pm	change Both
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1487	4.5	0	A	N	–	–	–
Distillation Unit	Running	Down	183	1403/1503	2113/1379	A	Y	8-27-14	6:20	change Both
Tank 51	Running	Down	7.9	723	0	A	N	–	–	–
Tank 55	Running	Down	1574	574/154	716/1589	A	Y	Aug 27,14	6:15	change Both

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Aug 28-11	Time: 500
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTYLENE	
Background Instrument Reading: 1.2	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	1508	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	400	520	400	A	Y	Aug 28	520	change both
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1420	5.2	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	215	1255/1408	2228/1541	A	Y	8-28-11	530	change both
Tank 51	Running ✓	Down	8	620	0	A	N	—	—	—
Tank 55	Running ✓	Down	2289	716	0	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: 8-29-14	Time: 5:00
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTLYENE	
Background Instrument Reading: 1.2	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	1328	0		A	N	—	—	—
ATDU / OWS	Running	Down	320	528	416	A	Y	8-29-14	5:20	change
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1620	0	0	A	N	—	—	—
Distillation Unit	Running	Down	112	1481/1300		A	Y	8-29-14	6:00	change
Tank 51	Running	Down	10.0	0		A	N	—	—	—
Tank 55	Running	Down	1672	1800/1528	151/760	A	Y	-	--	change

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 8/30/14	Time: 500PM
Shift: (First) or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100ppm	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	211	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1113	0.9	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	518	0.0	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2113	1.7	0	A	N	—	—	—
Tank 51	Running ✓	Down	1715	24.6	0	A	N	—	—	—
Tank 55	Running ✓	Down	1926	9.1	0	A	N	—	—	—

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: August 31 14	Time: 5:00
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTLENE	
Background Instrument Reading: 1.2	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	115.1	1.0		A	N	—	—	—
ATDU / OWS	Running	Down	3314	14.1	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	290	3.0	0	A	N	—	—	—
Distillation Unit	Running	Down	29.1	1540 / 0		A	N	—	—	—
Tank 51	Running	Down	117.6	0 / 0		A	N	—	—	—
Tank 55	Running	Down	875.1	241 / 4.1		A	N	—	—	—

Revised 2/10/09