EMERSON QUIET KOOL CORPORATION
400 Woodbine Avenue
Woodbridge, New Jersey 07095

Telephone: (201) 381-7000

APR 1 1985
Thompson
Duane Marine

HAND DELIVERED
April 1, 1985

April 1, 1985

Margaret Thompson
Law Clerk
Office of Regional Counsel
U.S. Environmental Protection Agency
Region II
26 Federal Plaza - Room #437
New York, New York 10278

Re: Duane Marine Salvage Corp. Facility
26 Washington Street, Perth Amboy, New Jersey

Dear Ms. Thompson:

In response to Douglas R. Blazey's letter directed to the President or General Counsel of the Emerson Quiet Kool Corporation dated March 22, 1985, and received on March 25, 1985, I am enclosing Material Safety Data Sheets which will support a Petition to Dismiss from the Administrative Order, Index No. II-CERCLA-50107 on the grounds that the substance sent to the Duane Marine Salvage Corp. facility by Emerson Quiet Kool Corporation on September 21, 1979 was not a hazardous substance under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA), 42 U.S.C. Section 9601 et seq.

Please review these enclosures and advise if we are to respond further.

Very truly yours,

Irwin M. Hersh
Executive Vice President, Manufacturing

IMH/kmd
Enclosures (Two, 2-page Data Sheets with covering letter)

cc: T. G. Petersen, President
Emerson Quiet Kool Corporation

335033

COLORA PRINTING INKS INC.

SPECIALISTS IN FLEXOGRAPHIC AND GRAVURE INKS

3401B Tremley Point Road
P.O. Box 4309
Linden, New Jersey 07036
TELEPHONE: (201) 862-1919
TELEGRAMS: COLORINKS, N.Y.

March 27, 1985

RECEIVED
MAR 29 1985
I. M. HEINSH

Emerson Quiet Kool
St. George & Woodbine Ave.
Woodbridge, N.J. 07095

Attn: Frank Wozniak

Reference: Aqua Pastel Red & Blue

Dear Frank:

As per our conversation of March 26, 1985, I am enclosing Material Safety Data Sheets on the Aqua Pastel Red 08591 and Aqua Pastel Blue 08872.

As you know Aqua Pastel is our tradename for water ink.

If you have any questions or need any further information, please don't hesitate to call.

Yours very truly,

James W. Snyder

James W. Snyder
Vice President

Enc.
JWS:rh

4
MAR 1985
RECEIVED
PURCHASING
DEPT.

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME: COLORA PRINTING INK CO	EMERGENCY TELEPHONE NO.: 201-862-1919
ADDRESS: 3401-B TREMLEY POINT RD. LINDEN N.J. 07036	
CHEMICAL NAME AND SYNONYMS:	TRADE NAME AND SYNONYMS: AQUA PASTEL 08591
CHEMICAL FAMILY: MIXTURE	FORMULA: PROPRIETARY

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS Pigment Red 200	20-30	N/A	BASE METAL		None
CATALYST Pigment White 6	10-15	N/A	ALLOYS		None
VEHICLE Acrylic Copolymer	40-50	N/A	METALLIC COATINGS		None
SOLVENTS Butoxy Ethanol	5-10	50 PPM	FILLER METAL PLUS COATING OR CORE FLUX		None
ADDITIVES			OTHERS		None
OTHERS WATER	40	N/A			

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
NOT A HAZARD BY OSHA STANDARDS		
PIGMENT RED 200 CONSIDERED A NUISANCE DUST IN DRY		
FORM.		

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	190	SPECIFIC GRAVITY (H_2O=1)	
VAPOR PRESSURE (mm Hg.)		PERCENT, VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____=1)	
SOLUBILITY IN WATER	YES		
APPEARANCE AND ODOR	RED MILD AMINE		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	125°F T.C.C	FLAMMABLE LIMITS	LEL	UEL
EXTINGUISHING MEDIA	WATER			
SPECIAL FIRE FIGHTING PROCEDURES	NONE			
UNUSUAL FIRE AND EXPLOSION HAZARDS	NONE			

OF OUR KNOWLEDGE THE INFORMATION CONTAINED IN THIS PUBLICATION IS ACCURATE; HOWEVER, WE DO NOT ASSUME ANY LIABILITY WHATSOEVER FOR THE COMPLETENESS OF SUCH INFORMATION. MOREOVER, THERE IS A NEED TO REDUCE HUMAN EXPOSURE TO MANY MATERIALS TO THE LOWEST PRACTICAL LIMITS DESIBLE LONG-TERM ADVERSE EFFECTS. TO THE EXTENT THAT ANY HAZARDS MAY HAVE BEEN MENTIONED IN THIS PUBLICATION, WE NEITHER SUGGEST NOR THAT SUCH HAZARDS ARE THE ONLY ONES WHICH EXIST. FINAL DETERMINATION OF THE SUITABILITY OF ANY INFORMATION OR PRODUCT FOR THE USE CON- LY ANY USER, THE MANNER OF THAT USE AND WHETHER THERE IS ANY INFRINGEMENT OF PATENTS IS THE SOLE RESPONSIBILITY OF THE USER. WE RECOMMEND C INTENDING TO RELY ON ANY RECOMMENDATION OR TO USE ANY EQUIPMENT, PROCESSING TECHNIQUE OR MATERIAL MENTIONED IN THIS PUBLICATION TEST HIMSELF AS TO SUCH SUITABILITY AND THAT HE CAN MEET ALL APPLICABLE SAFETY AND HEALTH STANDARDS. WE STRONGLY RECOMMEND THAT USERS

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

N/ESTABLISHED

EFFECTS OF OVEREXPOSURE

DIZZINESS

PROLONGED EXPOSURE MAY CAUSE SKIN IRRITATION

EMERGENCY AND FIRST AID PROCEDURES

SKIN CONTACT WASH WITH WATER

EYES WASH AT LEAST 15 MIN WITH WATER IF DISCOMFORT

PERSISTS CONTACT PHYSICIAN

SECTION VI - REACTIVITY DATA

STABILITY			CONDITIONS TO AVOID
	UNSTABLE		
	STABLE	✓	

INCOMPATIBILITY (Materials to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	MAY OCCUR		
	WILL NOT OCCUR	✓	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASH WITH WATER

WASTE DISPOSAL METHOD

AUTHORIZED LAND FILL

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

VENTILATION	LOCAL EXHAUST	SPECIAL
	MECHANICAL (General) YES	OTHER

PROTECTIVE GLOVES	EYE PROTECTION
RUBBER GLOVES	GOGGLES

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

AS WITH ALL INDUSTRIAL MATERIAL HANDLE IN SAFE MANNER.

STORE AT ROOM TEMP IN CLOSED CONTAINERS

OTHER PRECAUTIONS

NONE

GPO 836-180

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME: COLORA PRINTING INK CO	EMERGENCY TELEPHONE NO.: 201-862-1919
ADDRESS: 3401-B TRENTLEY POINT RD LINDEN N.J. 07036	
CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS: AQUA PASTEL BLUE
CHEMICAL FAMILY: MIXTURE	FORMULA: PROPRIETARY

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS: PIGMENT WHITE 6	30-40		BASE METAL		N/ABLE
PIGMENT BLACK 7	1-2	N/A			
CATALYST: VICTORIA BLUE 2580-56-5	10-15	N/A	ALLOYS		N/ABLE
VEHICLE: ACRYLIC CO POLYMER	40-50	N/A	METALLIC COATINGS		NONE
SOLVENTS: BUTOXY ETHANOL	5-10	50 PPM	FILLER METAL PLUS COATING OR CORE FLUX		NONE
ADDITIVES			OTHERS		NONE
OTHERS: WATER	40	N/A			

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
NOT A HAZARD BY CURRENT OSHA STANDARDS		
PIGMENT BLACK 7 CONSIDERED A NUISANCE DUST		
IN DRY FORM.		

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	180	SPECIFIC GRAVITY (H_2O=1)	
VAPOR PRESSURE (mm Hg.)		PERCENT, VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____ =1)	
SOLUBILITY IN WATER	YES		
APPEARANCE AND ODOR	BLUE MILD AMINE		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used): 120°F TCC	FLAMMABLE LIMITS	LEL	UEL
EXTINGUISHING MEDIA: WATER			
SPECIAL FIRE FIGHTING PROCEDURES: NONE			
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE			

OF OUR KNOWLEDGE THE INFORMATION CONTAINED IN THIS PUBLICATION IS ACCURATE; HOWEVER, WE DO NOT ASSUME ANY LIABILITY WHATSOEVER FOR THE COMPLETENESS OF SUCH INFORMATION. MOREOVER, THERE IS A NEED TO REDUCE HUMAN EXPOSURE TO MANY MATERIALS TO THE LOWEST PRACTICAL LIMITS SSIBLE LONG-TERM ADVERSE EFFECTS. TO THE EXTENT THAT ANY HAZARDS MAY HAVE BEEN MENTIONED IN THIS PUBLICATION, WE NEITHER SUGGEST NOR THAT SUCH HAZARDS ARE THE ONLY ONES WHICH EXIST. FINAL DETERMINATION OF THE SUITABILITY OF ANY INFORMATION OR PRODUCT FOR THE USE CON- Y ANY USER, THE MANNER OF THAT USE AND WHETHER THERE IS ANY INFRINGEMENT OF PATENTS IS THE SOLE RESPONSIBILITY OF THE USER. WE RECOMMEND C INTENDING TO RELY ON ANY RECOMMENDATION OR TO USE ANY EQUIPMENT, PROCESSING TECHNIQUE OR MATERIAL MENTIONED IN THIS PUBLICATION FY HIMSELF AS TO SUCH SUITABILITY AND THAT HE CAN MEET ALL APPLICABLE SAFETY AND HEALTH STANDARDS. WE STRONGLY RECOMMEND THAT USERS

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

N/ESTABLISHED

EFFECTS OF OVEREXPOSURE

DIZZINESS

PROLONGED EXPOSURE MAY CAUSE SKIN IRRITATION

EMERGENCY AND FIRST AID PROCEDURES

SKIN CONTACT WASH WITH WATER EYES WASH AT LEAST 15 MINUTES WITH WATER IF DISCOMFORT PERSISTS GET MEDICAL ATTENTION

SECTION VI - REACTIVITY DATA

STABILITY			CONDITIONS TO AVOID
	UNSTABLE		
	STABLE	✓	

INCOMPATIBILITY (Materials to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	MAY OCCUR		
	WILL NOT OCCUR	✓	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASH WITH WATER

WASTE DISPOSAL METHOD

AUTHORIZED LAND FILL

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

VENTILATION		
	LOCAL EXHAUST	SPECIAL
	MECHANICAL (General) YES	OTHER

PROTECTIVE GLOVES RUBBER GLOVES

EYE PROTECTION GOGGLES

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

AS WITH ALL INDUSTRIAL MATERIAL HANDLE IN SAFE MANNER

STORE AT ROOM TEMPERATURE IN CLOSED CONTAINERS

OTHER PRECAUTIONS

NONE