STATE OF WASHINGTON
DEPARTMENT OF CONSERVATION
AND DEVELOPMENT

WELL LOG

Date May 6, 1957 No. Appli. 4088 Cert. 2873-A

Record by well driller

Source driller's record

Location: State of WASHINGTON

County Pierce

~~xxx~~ Lots 17 to 34, Blk. 1

~~xxx~~ Wings Add. to Tacoma

~~xxxxxxxx~~ sec 18 T 20 N., R. 3 E.

Diagram of Section

Drilling Co. Robinson & Roberts

Address Tacoma, Wash.

Method of Drilling Date , 19

Owner City of Tacoma, Water Div.

Address Tacoma, Wash.

Land surface, datum ft. above / below

Correlation	Material	Thickness (feet)	Depth (feet)
	(Transcribe driller's terminology literally but paraphrase as necessary, in parentheses. If material water-bearing, so state and record static level if reported. Give depths in feet below land-surface datum unless otherwise indicated. Correlate with stratigraphic column, if feasible. Following log of materials, list all casings, perforations, screens, etc.)		
	Sand & gravel	11	11
	Connected sand & gravel	38	49
	Sandy, clay, some gravel	34	83
	Sand & gravel	4	87
	Sandy clay to dirty sand	32	119
	Hardpan	14	133
	Sand, streaks of gravel	7	140
	Coarse sand & gravel w/b	27	167
	PUMP TEST:		
	SWL: 85 ft.		
	DD: 122 ft.		
	Yield: 4920 g.p.m. & 6000 g.p.m.		
	Water Temp. 52°		
	Dim. 167.08'x36"		
	CASING: 36" diam. outer casing 3/8" steel from 0 to 133½'		

Turn up (over)

Sheet of sheets

20N 3E 18C

File number

USEPA SF
1468298

WELL LOG.—Continued

No...../.....-.....

CORRELATION	MATERIAL	THICKNESS (feet)	DEPTH (feet)
	Depth forward		
	30" diam. inner casing 3/8" steel from 0 to 140.67 ft.		
	For Shoe see drawing 1363-B, Plat V in file.		
	PERFORATIONS:		
	26 1/8" I.D. Diam. Johnson Woven Wire		
	Everdur well screen, slot opening 0.050" from 140.67 to 142.67 ft.		
	slot opening 0.200" from 142.67 to 167.09 ft.		