V-08-01305

SPRAGUE PROVIDES THE ATTACHED INSPECTION REPORT/ANALYSIS REPRESENTING THE SPECIFICATIONS OF THE PRODUCT AT THE SPRAGUE TERMINAL IN TANK ON THE DATE OF INSPECTION NOTED ON THE CERTIFICATE. THIS ANALYSIS IS PROVIDED TO THE CUSTOMER FOR THE PURPOSE OF ESTABLISHING THE INDEPENDENT [illegible] PRODUCT SPECIFICATION ON A COMPONENT [illegible] TANK AS NOTED ON THE CERTIFICATE. [illegible] TO BE USED FOR ANY OTHER PURPOSE. SPRAGUE DISCLAIMS ANY [illegible] THE PRODUCT AFTER DELIVERY BY SPRAGUE TO CUSTOMER. SPRAGUE [illegible] ANY WARRANTY OF [illegible] EXCEPT AS MAY BE SPECIFICALLY SET FORTH [illegible] TERMS OF SALE BETWEEN SPRAGUE AND A BUYER OF PRODUCT. SPRAGUE [illegible] LIABILITY FOR CLAIMS OR LOSSES THAT MAY ARISE FROM CUSTOMER'S USE OF THIS INSPECTION REPORT/ANALYSIS.

NMC Global Corporation
1100 Walnut Street, Roselle, NJ 07203. Tel: 908-620-3610 Fax: 908-620-3616
E-mail: nmcglobal@nmcigroup.com. Web page: www.nmcigroup.com

Ref: Sampling and lab analysis of #6 Fuel oil, from shore tank#15 after the discharging of barge Penn-300, at Sprague, Albany, NY on August 31, 2008.

File Number: 48941 Sample Number: 48941-6

CERTIFICATE OF ANALYSIS

Shore Tank#15

TEST	METHOD	UNITS	RESULT
		UPPER	
API Gravity	D-4052	° API @ 60 °F	12.0
Viscosity	D-445	CST @50 °C	219.1
	D-2161	SFS @ 122 °F	103.4
Sulfur	D-4294	Weight %	0.987
		MIDDLE	
API Gravity	D-4052	° API @ 60 °F	12.0
Viscosity	D-445	CST @50 °C	224.9
	D-2161	SFS @ 122 °F	106.2
Sulfur	D-4294	Weight %	1.00
		LOWER	
API Gravity	D-4052	° API @ 60 °F	12.0
Viscosity	D-445	CST @50 °C	220.4
	D-2161	SFS @ 122 °F	104.0
Sulfur	D-4294	Weight %	1.00
		SUCTION	
API Gravity	D-4052	° API @ 60 °F	12.0
Viscosity	D-445	CST @50 °C	229.6
	D-2161	SFS @ 122 °F	108.4
Sulfur	D-4294	Weight %	1.02
		COMPOSITE	
API Gravity	D-4052	° API @ 60 °F	12.0
Viscosity	D-445	CST @50 °C	224.9
	D-2161	SFS @ 122 °F	106.2
Sulfur	D-4294	Weight %	1.00
Pour Point	D-97	° F	48
Flash Point	D-93	° F	200
Water by Distillation	D-95	Volume %	0.30
Ash	D-482	Weight %	0.059
Nitrogen	D-5762	Weight %	0.37
Vanadium	D-5863	PPM	45
Sodium	D-5863	PPM	8
Heat of combustion	D-240	BTU/LAB	18,456
		BTU/GAL	151,581

H.Hossni
NMC Global Corporation Representative