D.1.12 SDS I Daily Visible Emissions Notations Per ...
(Stack SDS 04)

VISIBLE EMISSION NOTATIONS

Inspector: Alex Bautista		
Date of Inspection: Dec 1 2015		
Shift: 1st Shift or 2nd Shift	Time: 5:00AM	
Unit	Visual Inspection NORMAL or ABNORMAL	Comments
Visible Emission From Shaker	NOR	lite steam
Visible Emission From Discharge Conveyor System	NOR	–

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

D.1.12 SDS I Daily Visible Emission Notations Per Each Day

(Stack SDS 04)

VISIBLE EMISSION NOTATIONS

Inspector: M. PHILLIPS

Date of Inspection: 12-1-15

Shift: 1st Shift or 2nd Shift Time: 5 PM

Unit	Visual Inspection NORMAL or ABNORMAL	Comments
Visible Emission From Shaker	NORMAL	—
Visible Emission From Discharge Conveyor System	NORMAL	—

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

Inspector: Alex Bautista

Date of Inspection: 12/2/15

Shift: 1st Shift or 2nd Shift Time: 5 Am

Unit	Visual Inspection NORMAL or ABNORMAL	Comments
Visible Emission From Shaker	NOR	steam
Visible Emission From Discharge Conveyor System	NOR	

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

D.1.12 SDS I Daily Visible Emission Notations
(Stack SDS 04)

VISIBLE EMISSION NOTATIONS

Inspector: M. PHILLIPS

Date of Inspection: 12-2-15

Shift: 1st Shift or 2nd Shift Time: 5 PM

Unit	Visual Inspection NORMAL or ABNORMAL	Comments
Visible Emission From Shaker	NORMAL	—
Visible Emission From Discharge Conveyor System	NORMAL	—

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

D.1.12 SDS I Daily Visible Emissions

(Stack SDS 04)

VISIBLE EMISSION NOTATIONS

Inspector: Alex Bautista

Date of Inspection: 12/3/15

Time: 5AM

Shift: 1st Shift or 2nd Shift

Unit	Visual Inspection NORMAL or ABNORMAL	Comments
Visible Emission From Shaker	NOR	steam
Visible Emission From Discharge Conveyor System	NOR	

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

D.1.12 SDS I Daily Visible Emissions

(Stack SDS 04)

VISIBLE EMISSION NOTATIONS

Inspector: Paul Lark

Date of Inspection: 12-3-15

Time: 5:00 pm

Shift: 1st Shift or 2nd Shift

Unit	Visual Inspection NORMAL or ABNORMAL	Comments
Visible Emission From Shaker	nor	
Visible Emission From Discharge Conveyor System	abnor	paddles broke in metal bath

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.