:R Part 60 - Standards of Performance for Crude Oil and Natural Gas Facilities for which Construction, Modification or Reconstruction Commenced After September 18, 2015 - 60.5420a(b) Annual Report

ach pneumatic controller affected facility, an owner or operator must include the information specified in paragraphs (b)(5)(i) through (iii) of this section in all annual reports:

ısterisk (*) next to each field indicates that the corresponding field is required.

| | | | | | Pneumatic Controllers with a Natural Gas Bleed Rate Greater than 6 scfh | | |
|---|---|---|---|---|---|---|---|
| ity Record No. * ;elect from ıpdown list - need to scroll up ) | Pneumatic Controller Identification * (§60.5420a(b)(1)(ii), §60.5420a(b)(5)(i), and §60.5390a(b)(2) or §60.5390a(c)(2)) | Was the pneumatic controller constructed, modified or reconstructed during the reporting period? * (§60.5420a(b)(5)(i)) | Month of Installation, Reconstruction, or Modification* (§60.5420a(b)(5)(i) and §60.5390a(b)(2) or §60.5390a(c)(2)) | Year of Installation, Reconstruction, or Modification* (§60.5420a(b)(5)(i) and §60.5390a(b)(2) or §60.5390a(c)(2)) | Documentation that Use of a Pneumatic Controller with a Natural Gas Bleed Rate Greater than 6 Standard Cubic Feet per Hour is required * (§60.5420a(b)(5)(ii)) | Reasons Why * (§60.5420a(b)(5)(ii)) | Records of deviations where the pneumatic controller was not operated in compliance with requirements* (§60.5420a(b)(5)(iii) and §60.5420a(c)(4)(v)) |
| | e.g.: Controller 12A | e.g.: modified | e.g.: February | e.g.: 2017 | e.g.: Controller has a bleed rate of 8 scfh. | e.g.: safety bypass controller requires use of a high-bleed controller | e.g.: Controller was not tagged with month and year of installation. |
| | NA | | | | | | |